



# **RF TEST REPORT**

Applicant	Dspread Technology (Beijing) Inc
FCC ID	2AGQ6-D70
Product Type	Smart POS
Model	D70
Report No.	R2411A1678-R4
Issue Date	January 24, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15E (2023)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

## Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

1. Tes	st Laboratory	4
1.1.	Notes of the test report	4
1.2.	Test facility	4
1.3.	Testing Location	4
2. Ger	neral Description of Equipment under Test	5
2.1.	Applicant and Manufacturer Information	5
2.2.	General information	5
3. App	plied Standards	7
4. Tes	st Configuration	8
5. Tes	st Case Results	11
5.1.	Occupied Bandwidth	11
5.2.	Average Power Output	61
5.3.	Frequency Stability	73
5.4.	Power Spectral Density	77
5.5.	Unwanted Emission	118
5.6.	Conducted Emission	243
6. Mai	in Test Instruments	246
ANNEX	A: The EUT Appearance	247
ANNEX	B: Test Setup Photos	248

Number	Test Case	Clause in FCC rules	Verdict	
1	Average output power	15.407(a)	PASS	
2	Occupied bandwidth	15.407(e)	PASS	
3	Frequency stability	15.407(g)	PASS	
4	Power spectral density	15.407(a)	PASS	
5	Unwanted Emissions	15.407(b)	PASS	
6	Conducted Emissions	15.207	PASS	
Date of Testing: November 7, 2024 ~ December 4, 2024				
Date of Sample Received: November 7, 2024				
Note: PASS: The EUT complies with the essential requirements in the standard.				
FAIL: The EUT does not comply with the essential requirements in the standard.				

## Summary of measurement results

All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

## 1. Test Laboratory

#### 1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

#### 1.2. Test facility

#### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

#### **1.3. Testing Location**

Company:	Eurofins TA Technology (Shanghai) Co., Ltd.
Address:	Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	https://www.eurofins.com/electrical-and-electronics
E-mail:	Kain.Xu@cpt.eurofinscn.com

## 2. General Description of Equipment under Test

### 2.1. Applicant and Manufacturer Information

Applicant	Dspread Technology (Beijing) Inc	
Applicant address	Rm.407, B12C, #10 (Universal Business Park), Jiuxianqiao	
Applicant address	Road, Chaoyang District, Beijing, China,100015	
Manufacturer	Dspread Technology (Beijing) Inc	
Mapufaaturar addraaa	Rm.407, B12C, #10 (Universal Business Park), Jiuxianqiao	
Manufacturer address	Road, Chaoyang District, Beijing, China,100015	

#### 2.2. General information

EUT Description			
Model	D70		
Lab internal SN	R2411A1678/S01		
Hardware Version	1.1.0		
Software Version	1.1.0		
Power Supply	Battery / AC adapter		
Antenna Type	Internal Antenna		
Antenna Connector	A permanently attach Part 15.203 requirem	ned antenna (meet with the standard FCC nent)	
	U-NII-1	1.90 dBi	
Antonna Osin	U-NII-2A	2.01 dBi	
Antenna Gain	U-NII-2C	2.01 dBi	
	U-NII-3	2.76 dBi	
	U-NII-1: 5150MHz-52	250MHz	
Operating Frequency	U-NII-2A: 5250MHz -	5350MHz	
Range(s)	e(s) U-NII-2C: 5470MHz-5725MHz		
	U-NII-3: 5725MHz -5850MHz		
	802.11a: OFDM		
Modulation Type	Julation Type 802.11n (HT20/HT40): OFDM		
	802.11ac (VHT20/VHT40/VHT80): OFDM		
Max. Output Power	16.90 dBm		
Operating temperature range	-10 ° C to 50 ° C		
Operating voltage range	3.30 VDC to 4.35 VDC		
Testing temperature range	-30 ° C to 50° C		
Testing voltage range	3.30 VDC - 3.80 VDC - 4.35 VDC		
State voltage	3.80 VDC		
EUT Accessory			
Battery	Manufacturer: Guangdong Fenghua New Energy Co.,Ltd.		
Dattery	Model: F50109MA		

## 🛟 eurofins

RF Test Report	Report No.: R2411A1678-R4
	Manufacturer: ShenZhen FKY-QY Hardware&Electronics.,Ltd.
	Model: XC04W1000100

Note:

1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.

2. This device support automatically discontinue transmission, while the device is not transmitting any information, the device can automatically discontinue transmission and become standby mode for power saving. The device can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3. (a) Manufacturers implements security features in any digitally modulated devices capable of operating in any of the U-NII bands, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software prevents the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device.

Manufacturers uses means including, but not limited to the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment authorization.

(b) Manufacturers take steps to ensure that DFS functionality cannot be disabled by the operator of the U-NII device.



## 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15E (2023) Unlicensed National Information Infrastructure Devices

ANSI C63.10-2013

Reference standard:

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

## 4. Test Configuration

#### **Test Mode**

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Mode	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0



Wireless Technology and	Frequency Range
-------------------------	-----------------

Wireless	Technology	Bandwidth	Channel	Frequency
			36	5180MHz
		20 MH <del>-</del>	40	5200MHz
			44	5220MHz
	U-NII-1		48	5240MHz
			38	5190MHz
		40 10112	46	5230MHz
		80 MHz	42	5210MHz
			52	5260MHz
		20 MH-	56	5280MHz
		20 101112	60	5300MHz
	U-NII-2A		64	5320MHz
		40 MH <del>-</del>	54	5270MHz
			62	5310MHz
		80 MHz	58	5290MHz
			100	5500MHz
			104	5520MHz
			108	5540MHz
	U-NII-2C	20 MHz	112	5560MHz
Wi-Fi			116	5580MHz
			120	5600MHz
			124	5620MHz
			128	5640MHz
			132	5660MHz
			136	5680MHz
			140	5700MHz
			144	5720MHz
			102	5510MHz
			110	5550MHz
		40 MH <del>7</del>	118	5590MHz
		40 10112	126	5630MHz
			134	5670MHz
			142	5710MHz
		80 MHz	106	5530MHz
			122	5610MHz
			138	5690MHz
	NIII 2	20 MIH-	149	5745MHz
	0-111-0		153	5765MHz



RF Test Report		Report No.: R2411A1678-R4	
		157	5785MHz
		161	5805MHz
		165	5825MHz
	40 MHz	151	5755MHz
		159	5795MHz
	80 MHz	155	5775MHz
Does this device support TPC Function? $oxtimes$ Yes $\Box$ No			
Does this device support TDWR Band? ⊠Yes ⊡No			

## 5. Test Case Results

### 5.1. Occupied Bandwidth

#### Ambient condition

Temperature	Relative humidity	Pressure
15°C ~ 35°C	20% ~ 80%	86 kPa ~ 106 kPa

#### Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.

For U-NII-1/U-NII-2A/U-NII-2C, set RBW  $\approx$ 1% OCB kHz, VBW  $\geq$  3 × RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

For U-NII-3, Set RBW = 100 kHz, VBW  $\ge$  3 × RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

Use the 99 % power bandwidth function of the instrument

#### Test Setup



#### Limits

For U-NII-1/U-NII-2A/U-NII-2C No specific occupied bandwidth requirements in Part 15.407. For U-NII-3 Rule FCC Part §15.407(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

#### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 936 Hz.



## Test Results:

### U-NII-1

	Carrier	99%	Minimum 26 dB		
Mode	frequency	bandwidth	bandwidth	Conclusion	
	(MHz)	(MHz)	(MHz)		
802.11a	5180	16.614	20.433	PASS	
	5200	16.580	19.817	PASS	
	5240	16.555	20.160	PASS	
802.11n HT20	5180	17.608	20.196	PASS	
	5200	17.622	20.312	PASS	
	5240	17.658	20.382	PASS	
802.11n HT40	5190	36.083	40.814	PASS	
	5230	36.082	40.922	PASS	
802.11ac VHT20	5180	17.595	20.229	PASS	
	5200	17.607	20.309	PASS	
	5240	17.620	20.251	PASS	
802.11ac VHT40	5190	36.004	40.927	PASS	
	5230	35.961	40.597	PASS	
802.11ac VHT80	5210	75.340	80.815	PASS	



#### U-NII-2A

	Carrier	99%	Minimum 26 dB	
Mode	frequency	bandwidth	bandwidth	Conclusion
	(MHz)	(MHz)	(MHz)	
802.11a	5260	16.580	19.734	PASS
	5300	16.588	20.069	PASS
	5320	16.506	19.939	PASS
802.11n HT20	5260	17.652	20.260	PASS
	5300	17.639	20.275	PASS
	5320	17.643	20.234	PASS
802.11n HT40	5270	36.025	41.016	PASS
	5310	36.008	40.599	PASS
802.11ac VHT20	5260	17.637	20.525	PASS
	5300	17.637	20.411	PASS
	5320	17.587	20.363	PASS
802.11ac VHT40	5270	35.988	40.545	PASS
	5310	36.022	41.195	PASS
802.11ac VHT80	5290	75.359	80.931	PASS



	Carrier	99%	Minimum 26 dB	
Mode	frequency	bandwidth	bandwidth	Conclusion
	(MHz)	(MHz)	(MHz)	
802.11a	5500	16.564	20.373	PASS
	5600	16.590	19.948	PASS
	5700	16.532	20.025	PASS
	5720	16.610	Minimum 26 dB bandwidth (MHz) Co Co Co Co Co Co Co Co Co Co Co Co Co C	PASS
	5500	17.667	20.324	PASS
902 11p UT20	5600	17.629	20.881	PASS
802.110 H120	5700	17.643	20.468	PASS
	5720	17.616	20.373	PASS
	5510	36.029	40.478	PASS
902 11p UT40	5590	36.056	40.647	PASS
802.11n H140	5670	36.139	40.820	PASS
	5710	36.094	bandwidth (MHz) C   20.373 1   20.373 1   19.948 2   20.025 1   19.917 2   20.324 2   20.468 2   20.373 4   40.478 4   40.647 4   20.518 2   20.386 2   20.365 2   20.233 4   40.924 4   40.925 8   80.685 8   81.053 8	PASS
	5500	17.619	20.518	PASS
902 11aa \/UT20	5720 17.616   5510 36.029   5590 36.056   5670 36.139   5710 36.094   5500 17.619   5600 17.605   5700 17.586   5720 17.623   5510 35.943	20.386	PASS	
802.11ac VH120	5700	17.586	20.365	PASS
	5720	17.623	bandwidth (MHz) Cor (MHz)   20.373 F   19.948 F   20.025 F   19.948 F   20.025 F   20.324 F   20.324 F   20.324 F   20.468 F   20.373 F   40.478 F   40.647 F   40.647 F   20.318 F   20.365 F   20.365 F   20.365 F   20.333 F   40.924 F   40.924 F   40.935 F   80.685 F   81.053 F	PASS
	5510	35.943	41.313	PASS
802.11ac VHT40	5590	35.992	40.924	PASS
	5670	36.048	40.729	PASS
	5710	36.016	40.935	PASS
902 11co \/UT90	5610	75.184	80.685	PASS
802.11ac VH180	5690	75.436	81.053	PASS



Mode	Carrier frequency	99% bandwidth	Minimum 6 dB bandwidth	Limit (kHz)	Conclusion
	(MHz)	(MHz)	(MHz)	(K112)	
802.11a	5720	16.572	15.393	500	PASS
	5745	16.586	14.652	500	PASS
	5785	16.606	14.797	500	PASS
	5825	16.640	13.086	500	PASS
802.11n HT20	5720	17.663	14.423	500	PASS
	5745	17.609	16.921	500	PASS
	5785	17.644	13.581	500	PASS
	5825	17.650	15.110	500	PASS
802.11n HT40	5710	36.058	35.044	500	PASS
	5755	36.069	35.018	500	PASS
	5795	36.101	35.058	500	PASS
802.11ac VHT20	5720	17.634	13.861	500	PASS
	5745	17.632	15.333	500	PASS
	5785	17.622	13.787	500	PASS
	5825	17.652	15.279	500	PASS
802.11ac VHT40	5710	36.046	33.805	500	PASS
	5755	36.033	35.050	500	PASS
	5795	36.039	35.026	500	PASS
802.11ac VHT80	5690	75.328	75.125	500	PASS
	5775	75.423	75.116	500	PASS



Report No.: R2411A1678-R4

RF Test Report

99% bandwidth

#### U-NII-1

OBW 802.11a 5180MHz



#### OBW 802.11a 5200MHz





#### OBW 802.11a 5240MHz



#### OBW 802.11ac(VHT20) 5180MHz





#### OBW 802.11ac(VHT20) 5200MHz



#### OBW 802.11ac(VHT20) 5240MHz





#### OBW 802.11ac(VHT40) 5190MHz



#### OBW 802.11ac(VHT40) 5230MHz



#### OBW 802.11ac(VHT80) 5210MHz



#### OBW 802.11n(HT20) 5180MHz





#### OBW 802.11n(HT20) 5200MHz



#### OBW 802.11n(HT20) 5240MHz





#### OBW 802.11n(HT40) 5190MHz



#### OBW 802.11n(HT40) 5230MHz





Report No.: R2411A1678-R4

#### U-NII-2A

OBW 802.11a 5260MHz



#### OBW 802.11a 5300MHz





#### OBW 802.11a 5320MHz



#### OBW 802.11ac(VHT20) 5260MHz





#### OBW 802.11ac(VHT20) 5300MHz



#### OBW 802.11ac(VHT20) 5320MHz





#### OBW 802.11ac(VHT40) 5270MHz



#### OBW 802.11ac(VHT40) 5310MHz



#### OBW 802.11ac(VHT80) 5290MHz



#### OBW 802.11n(HT20) 5260MHz





#### OBW 802.11n(HT20) 5300MHz



#### OBW 802.11n(HT20) 5320MHz





#### OBW 802.11n(HT40) 5270MHz



#### OBW 802.11n(HT40) 5310MHz







#### U-NII-2C

OBW 802.11a 5500MHz



#### OBW 802.11a 5600MHz





#### OBW 802.11a 5700MHz



#### OBW 802.11a 5720MHz





#### OBW 802.11ac(VHT20) 5500MHz



#### OBW 802.11ac(VHT20) 5600MHz

![](_page_31_Figure_5.jpeg)

![](_page_32_Picture_1.jpeg)

#### OBW 802.11ac(VHT20) 5700MHz

![](_page_32_Figure_3.jpeg)

#### OBW 802.11ac(VHT20) 5720MHz

![](_page_32_Figure_5.jpeg)

![](_page_33_Picture_1.jpeg)

#### OBW 802.11ac(VHT40) 5510MHz

![](_page_33_Figure_3.jpeg)

#### OBW 802.11ac(VHT40) 5590MHz

![](_page_33_Figure_5.jpeg)

![](_page_34_Picture_1.jpeg)

#### OBW 802.11ac(VHT40) 5670MHz

![](_page_34_Figure_3.jpeg)

#### OBW 802.11ac(VHT40) 5710MHz

![](_page_34_Figure_5.jpeg)

![](_page_35_Picture_1.jpeg)

#### OBW 802.11ac(VHT80) 5610MHz

![](_page_35_Figure_3.jpeg)

#### OBW 802.11ac(VHT80) 5690MHz

![](_page_35_Figure_5.jpeg)

![](_page_36_Picture_1.jpeg)

#### OBW 802.11n(HT20) 5500MHz

![](_page_36_Figure_3.jpeg)

#### OBW 802.11n(HT20) 5600MHz

![](_page_36_Figure_5.jpeg)

![](_page_37_Picture_1.jpeg)

#### OBW 802.11n(HT20) 5700MHz

![](_page_37_Figure_3.jpeg)

#### OBW 802.11n(HT20) 5720MHz

![](_page_37_Figure_5.jpeg)

![](_page_38_Picture_1.jpeg)

#### OBW 802.11n(HT40) 5510MHz

![](_page_38_Figure_3.jpeg)

#### OBW 802.11n(HT40) 5590MHz

![](_page_38_Figure_5.jpeg)

![](_page_39_Picture_1.jpeg)

#### OBW 802.11n(HT40) 5670MHz

![](_page_39_Figure_3.jpeg)

#### OBW 802.11n(HT40) 5710MHz

![](_page_39_Figure_5.jpeg)