


**Plot 28: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-26
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n40 ANT 2
Channels	Low
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	2422
Relative permittivity (real part)	37.87
Conductivity (S/m)	1.75

Maximum location: X=10.00, Y=-48.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.069507
SAR 1g (W/Kg)	0.126875






Plot 29: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 1
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5180
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=13.00, Y=-6.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.064097
SAR 1g (W/Kg)	0.111951




Plot 30: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 1
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5180
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=32.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.031351
SAR 1g (W/Kg)	0.043173






Plot 31: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 2
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5180
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-57.00, Y=-65.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.080876
SAR 1g (W/Kg)	0.166942




**Plot 32: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 2
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5180
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-32.00, Y=-27.00

SAR Peak: 1.52 W/kg

SAR 10g (W/Kg)	0.247038
SAR 1g (W/Kg)	0.562990






Plot 33: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n40 ANT 1
Channels	Low
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5190
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-15.00, Y=-7.00

SAR Peak: 0.56 W/kg

SAR 10g (W/Kg)	0.107844
SAR 1g (W/Kg)	0.224463





Plot 34: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n40 ANT 1
Channels	Low
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5190
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-16.00, Y=-40.00

SAR Peak: 0.1/ W/kg

SAR 10g (W/Kg)	0.048774
SAR 1g (W/Kg)	0.063393






Plot 35: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n40 ANT 2
Channels	Low
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5190
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-57.00, Y=-65.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.086270
SAR 1g (W/Kg)	0.184574




Plot 36: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n40 ANT 2
Channels	Low
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5190
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-22.00, Y=-23.00

SAR Peak: 0.94 W/kg

SAR 10g (W/Kg)	0.174946
SAR 1g (W/Kg)	0.367441






Plot 37: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5320
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=9.00, Y=-16.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.063849
SAR 1g (W/Kg)	0.107301






Plot 38: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5320
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=1.00, Y=31.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.047590
SAR 1g (W/Kg)	0.067618




**Plot 39: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5320
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-39.00, Y=-56.00

SAR Peak: 0.93 W/kg

SAR 10g (W/Kg)	0.152590
SAR 1g (W/Kg)	0.354714




Plot 40: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5320
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-22.00, Y=-24.00

SAR Peak: 1.33 W/kg

SAR 10g (W/Kg)	0.214144
SAR 1g (W/Kg)	0.488852







**Plot 41: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n20 ANT 1
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5300
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=-17.00

SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.076698
SAR 1g (W/Kg)	0.125324

SURFACE SAR**VOLUME SAR****3D****Z Axis Scan**




Plot 42: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n20 ANT 1
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5300
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=32.00, Y=-17.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.061192
SAR 1g (W/Kg)	0.078834





Plot 43: DUT: 5G Smart phone; EUT Model: Glory G1


Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n20 ANT 2
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5300
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=-16.00


SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.076734
SAR 1g (W/Kg)	0.130857


SURFACE SAR




VOLUME SAR



3D



Z Axis Scan




Plot 44: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n20 ANT 2
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5300
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=23.00, Y=-34.00

SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.052390
SAR 1g (W/Kg)	0.067000






Plot 45: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=-16.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.069589
SAR 1g (W/Kg)	0.102984




Plot 46: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=23.00, Y=-32.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.048015
SAR 1g (W/Kg)	0.059161






Plot 47: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-72.00, Y=-72.00

SAR Peak: 0.24 W/kg

SAR 10g (W/Kg)	0.067110
SAR 1g (W/Kg)	0.106461




**Plot 48: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-40.00, Y=16.00

SAR Peak: 1.28 W/kg

SAR 10g (W/Kg)	0.203817
SAR 1g (W/Kg)	0.458461







**Plot 49: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n20 ANT 1
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=9.00, Y=-16.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.072040
SAR 1g (W/Kg)	0.105022

SURFACE SAR**VOLUME SAR****3D****Z Axis Scan**


**Plot 50: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n20 ANT 1
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=28.00, Y=2.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.056669
SAR 1g (W/Kg)	0.070267






Plot 51: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n20 ANT 2
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=-15.00

SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.078232
SAR 1g (W/Kg)	0.124125






Plot 52: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-30
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11n20 ANT 2
Channels	Mid
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5700
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=10.00, Y=-35.00

SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.047603
SAR 1g (W/Kg)	0.059618






Plot 53: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5825
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=11.00, Y=-14.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.084626
SAR 1g (W/Kg)	0.142250




**Plot 54: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 1
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5825
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=11.00, Y=-14.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.061192
SAR 1g (W/Kg)	0.078834




**Plot 55: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5825
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-72.00, Y=-72.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.063714
SAR 1g (W/Kg)	0.088461




**Plot 56: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ANT 2
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5825
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-33.00, Y=16.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.158225
SAR 1g (W/Kg)	0.332319







**Plot 57: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11ac20 ANT 1
Channels	Low
Signal	IEEE802.ac (Crest factor: 1.0)
Frequency (MHz)	5745
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=16.00, Y=-8.00

SAR Peak: 0.11W/kg

SAR 10g (W/Kg)	0.032670
SAR 1g (W/Kg)	0.066081

SURFACE SAR**3D****VOLUME SAR****Z Axis Scan**




Plot 58: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11ac20 ANT 1
Channels	Low
Signal	IEEE802.ac (Crest factor: 1.0)
Frequency (MHz)	5745
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=8.00, Y=-24.00

SAR Peak: 0.12 W/kg

SAR 10g (W/Kg)	0.025196
SAR 1g (W/Kg)	0.058291






Plot 59: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11ac20 ANT 2
Channels	Low
Signal	IEEE802.ac (Crest factor: 1.0)
Frequency (MHz)	5745
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-47.00, Y=-64.00

SAR Peak: 0.92 W/kg

SAR 10g (W/Kg)	0.122625
SAR 1g (W/Kg)	0.327597




Plot 60: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-25
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11ac20 ANT 2
Channels	Low
Signal	IEEE802.ac (Crest factor: 1.0)
Frequency (MHz)	5745
Relative permittivity (real part)	35.82
Conductivity (S/m)	4.61

Maximum location: X=-24.00, Y=-16.00

SAR Peak: 0.90W/kg

SAR 10g (W/Kg)	0.142201
SAR 1g (W/Kg)	0.323127




Plot 61: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-24
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 2 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1860
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=-50.00, Y=-51.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.161012
SAR 1g (W/Kg)	0.279374






Plot 62: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-24
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 2(RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1860
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=8.00, Y=-16.00

SAR Peak: 1.58 W/kg

SAR 10g (W/Kg)	0.379501
SAR 1g (W/Kg)	0.832739




**Plot 63: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-23
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 4 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1720
Relative permittivity (real part)	39.86
Conductivity (S/m)	1.33

Maximum location: X=-55.00, Y=-55.00

SAR Peak: 0.33 W/kg

SAR 10g (W/Kg)	0.129751
SAR 1g (W/Kg)	0.214533




Plot 64: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-10-23
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 4 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1720
Relative permittivity (real part)	39.86
Conductivity (S/m)	1.33

Maximum location: X=-16.00, Y=32.00

SAR Peak: 1.31 W/kg

SAR 10g (W/Kg)	0.445153
SAR 1g (W/Kg)	0.765763




**Plot 65: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-22
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 5 (RB 1)
Channels	Mid
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	836.5
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=-51.00, Y=-43.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.119981
SAR 1g (W/Kg)	0.157750




**Plot 66: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-10-22
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 5 (RB 1)
Channels	Mid
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	836.5
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=25.00, Y=-5.00

SAR Peak: 0.31 W/kg

SAR 10g (W/Kg)	0.140988
SAR 1g (W/Kg)	0.219464




Plot 67: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-26
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 7 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2510
Relative permittivity (real part)	38.00
Conductivity (S/m)	2.01

Maximum location: X=-47.00, Y=-55.00

SAR Peak: 0.67 W/kg

SAR 10g (W/Kg)	0.206395
SAR 1g (W/Kg)	0.402658




**Plot 68: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-26
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 7 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2510
Relative permittivity (real part)	38.00
Conductivity (S/m)	2.01

Maximum location: X=-21.00, Y=16.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.273174
SAR 1g (W/Kg)	0.535968




**Plot 69: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-27
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 38 (RB 1)
Channels	Mid
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2580
Relative permittivity (real part)	38.00
Conductivity (S/m)	2.01

Maximum location: X=-50.00, Y=-52.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.127116
SAR 1g (W/Kg)	0.261848




**Plot 70: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-27
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 38 (RB 1)
Channels	Mid
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2580
Relative permittivity (real part)	38.00
Conductivity (S/m)	2.01

Maximum location: X=-21.00, Y=16.00

SAR Peak: 0.59 W/kg

SAR 10g (W/Kg)	0.176066
SAR 1g (W/Kg)	0.345937





Plot 71: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-26
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 40 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=-56.00, Y=-62.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.045868
SAR 1g (W/Kg)	0.084757




**Plot 72: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-26
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 40 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=-17.00, Y=-16.00

SAR Peak: 1.07 W/kg

SAR 10g (W/Kg)	0.314554
SAR 1g (W/Kg)	0.633551




Plot 73: DUT: 5G Smart phone; EUT Model: Glory G1

Test Date	2021-09-26
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 41 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=-53.00, Y=-55.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.113128
SAR 1g (W/Kg)	0.222695




**Plot 74: DUT: 5G Smart phone; EUT Model: Glory G1**

Test Date	2021-09-26
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 41 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	41.99
Conductivity (S/m)	0.88

Maximum location: X=-23.00, Y=-13.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.186641
SAR 1g (W/Kg)	0.370852





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※

