

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Wireless Subwoofer with 5.8GHz function operating in 5730-5848MHz. The EUT is powered by AC 100-240V, 50/60Hz. For more detail information pls. refer to the user manual.

Modulation Type: GFSK

Antenna Type: Integral antenna

Antenna 1 Gain: 4.18dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

Antenna 2 Gain: 4.82dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: -5dBm (Tolerance: +/- 2dB)

The nominal conducted output power specified: -9.18dBm (Tolerance: +/- 2dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 91.0 dBμV/m at 3m in the frequency 5848MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -4.23 dBm

which is within the production variation.

The minimum peak radiated emission for the EUT is 89.7 dBμV/m at 3m in the frequency 5730MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -5.53 dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -5dBm+2dB= -3dBm = 0.50mW

The maximum ERP= -5dBm+2dB-2.15dB= -5.15dBm=0.31mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP exemption threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP exemption threshold is 3060mW for general population and uncontrolled exposure in the 5.8GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP exemption threshold, the compliance to the ERP exemption threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.