



The Photos of SAR test

No. I19Z61614-SEM02

For

Samsung Electronics Co., Ltd.

Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model Name: SM-A207M

with

Hardware Version: MP1.0

Software Version: A207MUBU0ASH1



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT


No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504


Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn




Picture - 1 Constituents of the sample




Picture 2 Left Hand Touch Cheek Position



Picture 3 Left Hand Tilt 15° Position




Picture 4 Right Hand Touch Cheek Position




Picture 5 Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm and 15mm between the EUT and the phantom bottom:




Picture 6 Front 10mm




Picture 7 Rear 10mm



Picture 8 Left 10mm




Picture 9 Right 10mm




Picture 10 Bottom 10mm



Picture 11 Top 10mm



Picture 11 Rear 15mm



Picture 12 Bottom 15mm