


9.6.5 Test Results


Band edge measurements

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	5.86	-47.78	≤-14.14	PASS
		High	2480	5.94	-47.05	≤-14.06	PASS
		Low	Hop_2402	5.25	-47.94	≤-14.75	PASS
		High	Hop_2480	4.90	-47.01	≤-15.1	PASS
2DH5	Ant1	Low	2402	10.08	-23.46	≤-9.92	PASS
		High	2480	1.61	-47.89	≤-18.39	PASS
		Low	Hop_2402	1.42	-47.79	≤-18.58	PASS
		High	Hop_2480	5.58	-46.97	≤-14.43	PASS
3DH5	Ant1	Low	2402	1.70	-46.99	≤-18.3	PASS
		High	2480	1.77	-48.15	≤-18.23	PASS
		Low	Hop_2402	5.57	-47.66	≤-14.43	PASS
		High	Hop_2480	0.56	-47.79	≤-19.44	PASS


DH5 Ant1 Low 2402




DH5 Ant1 High 2480




DH5 Ant1 Low Hop 2402




DH5_Ant1_High_Hop_2480




2DH5_Ant1_Low_2402




2DH5_Ant1_High_2480




2DH5 Ant1 Low Hop 2402




2DH5 Ant1 High Hop 2480




3DH5 Ant1 Low 2402




3DH5 Ant1_High_2480



3DH5 Ant1_Low_Hop_2402



3DH5 Ant1_High_Hop_2480




Conduceted Spurious Emission

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	5.23	5.23	---	PASS
			30~1000	5.23	-73.78	≤-14.77	PASS
			1000~26500	5.23	-50.88	≤-14.77	PASS
		2441	Reference	5.57	5.57	---	PASS
			30~1000	5.57	-72.07	≤-14.43	PASS
			1000~26500	5.57	-50.26	≤-14.43	PASS
		2480	Reference	5.37	5.37	---	PASS
			30~1000	5.37	-72.26	≤-14.63	PASS
			1000~26500	5.37	-48.51	≤-14.63	PASS
2DH5	Ant1	2402	Reference	9.82	9.82	---	PASS
			30~1000	9.82	-69.26	≤-10.18	PASS
			1000~26500	9.82	-50.36	≤-10.18	PASS
		2441	Reference	1.50	1.50	---	PASS
			30~1000	1.50	-77.63	≤-18.5	PASS
			1000~26500	1.50	-50.81	≤-18.5	PASS
		2480	Reference	1.15	1.15	---	PASS
			30~1000	1.15	-70.22	≤-18.85	PASS
			1000~26500	1.15	-50.24	≤-18.85	PASS
3DH5	Ant1	2402	Reference	1.22	1.22	---	PASS
			30~1000	1.22	-79.46	≤-18.78	PASS
			1000~26500	1.22	-51.14	≤-18.78	PASS
		2441	Reference	1.39	1.39	---	PASS
			30~1000	1.39	-78.72	≤-18.61	PASS
			1000~26500	1.39	-49.67	≤-18.61	PASS
		2480	Reference	1.40	1.40	---	PASS
			30~1000	1.40	-75.22	≤-18.6	PASS
			1000~26500	1.40	-50.73	≤-18.6	PASS

DH5_Ant1_2402_0~Reference




DH5_Ant1_2402_30~1000



DH5_Ant1_2402_1000~26500







DH5_Ant1_2480_0~Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500



2DH5 Ant1 2402_0~Reference



2DH5 Ant1 2402_30~1000




2DH5 Ant1 2402_1000~26500



2DH5 Ant1 2441 0~Reference




2DH5 Ant1 2441 30~1000




2DH5 Ant1 2441 1000~26500



2DH5 Ant1 2480 0~Reference



2DH5 Ant1 2480 30~1000




2DH5 Ant1 2480 1000~26500



3DH5 Ant1 2402_0~Reference




3DH5 Ant1 2402_30~1000



3DH5 Ant1 2402_1000~26500






3DH5_Ant1_2480_0~Reference



3DH5_Ant1_2480_30~1000



3DH5_Ant1_2480_1000~26500



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst result (GFSK) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Over (dB)	
		PK	AV	PK	AV	PK	AV
6950.625	V	53.17	38.49	74	54	20.83	15.51
8512.5	V	55.08	36.23	74	54	18.92	17.77
12678.75	V	60.95	44.87	74	54	13.05	9.13
6933.75	H	52.47	38.23	74	54	21.53	15.77
8670	H	55.09	36.69	74	54	18.91	17.31
12676.875	H	61.30	44.59	74	54	12.70	9.41

Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Over (dB)	
		PK	AV	PK	AV	PK	AV
7164.375	V	52.39	38.54	74	54	21.61	15.46
8441.25	V	54.98	36.43	74	54	19.02	17.57
12684.375	V	61.59	44.70	74	54	12.41	9.30
8441.25	H	55.37	42.06	74	54	18.63	11.94
12641.25	H	60.71	47.29	74	54	13.29	6.71
16706.25	H	59.35	45.74	74	54	14.65	8.26

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Over (dB)	
		PK	AV	PK	AV	PK	AV
8113.125	V	54.23	40.12	74	54	19.77	13.88
9965.625	V	59.89	42.43	74	54	14.11	11.57
14188.125	V	59.56	45.09	74	54	14.44	8.91
9885	H	60.60	46.63	74	54	13.40	7.37
12669.375	H	60.79	47.51	74	54	13.21	6.49
16635	H	59.17	45.14	74	54	14.83	8.86

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level = Reading Level + Correct Factor + Cable Loss.

(3) Correct Factor = Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
2389.46	V	43.75	74.00	30.25	peak
2389.46	V	37.48	54.00	16.52	AVG
2389.17	H	43.22	74.00	30.78	peak
2389.17	H	37.86	54.00	16.14	AVG

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
2483.58	V	43.59	74.00	30.41	peak
2483.58	V	37.97	54.00	16.03	AVG
2483.74	H	43.90	74.00	30.10	peak
2483.74	H	38.18	54.00	15.82	AVG

Test mode: GFSK Frequency: Hopping

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
2387.60	V	43.84	54.00	10.16	peak
2487.45	V	43.51	54.00	10.49	peak
2387.60	V	38.18	54.00	15.82	AVG
2487.45	V	38.10	54.00	15.90	AVG
2385.51	H	43.25	54.00	10.75	peak
2484.41	H	45.52	54.00	8.48	peak
2385.51	H	38.24	54.00	15.76	AVG
2484.41	H	37.82	54.00	16.18	AVG


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor +Cable Loss.


(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	BT		
	Channel 0: 2402MHz	GFSK	H



Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	BT		
	Channel 0: 2402MHz	GFSK	V



Test Model


Spurious Emission in Restricted Band 2483.5-2500MHz

BT

Channel 78: 2480MHz

GFSK

H



Test Model


Spurious Emission in Restricted Band 2483.5-2500MHz

BT

Channel 78: 2480MHz

GFSK

V




Test Model

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz
BT
Hopping

GFSK

H




Test Model

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz
BT
Hopping

GFSK


V



■ Spurious Emission below 1GHz (30MHz to 1GHz)


Bluetooth (GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	37.46	-18.16	19.30	PK	40.00	20.70	Vertical
2	56.2162	37.75	-16.92	20.83	PK	40.00	19.17	Vertical
3	239.729	40.98	-15.73	25.25	PK	46.00	20.75	Vertical
4	590.250	32.42	-6.97	25.45	PK	46.00	20.55	Vertical
5	620.350	33.60	-7.41	26.19	PK	46.00	19.81	Vertical
6	760.170	33.22	-6.81	26.41	PK	46.00	19.59	Vertical




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	40.14	-18.16	21.98	PK	40.00	18.02	Horizontal
2	239.729	40.70	-15.73	24.97	PK	46.00	21.03	Horizontal
3	299.929	37.22	-13.99	23.23	PK	46.00	22.77	Horizontal
4	599.96	30.93	-6.42	24.51	PK	46.00	21.49	Horizontal
5	703.853	31.91	-6.16	25.75	PK	46.00	20.25	Horizontal
6	805.805	31.74	-5.40	26.34	PK	46.00	19.66	Horizontal

Test mode: GFSK Frequency: Channel 39: 2441MHz




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	38.34	-18.16	20.18	PK	40.00	19.82	Vertical
2	56.2162	38.98	-16.92	22.06	PK	40.00	17.94	Vertical
3	239.729	41.79	-15.73	26.06	PK	46.00	19.94	Vertical
4	705.795	32.61	-6.14	26.47	PK	46.00	19.53	Vertical
5	825.225	32.17	-5.08	27.09	PK	46.00	18.91	Vertical
6	917.467	32.34	-3.09	29.25	PK	46.00	16.75	Vertical



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	39.52	-18.16	21.36	PK	40.00	18.64	Horizontal
2	70.7808	37.00	-18.90	18.10	PK	40.00	21.90	Horizontal
3	239.729	39.20	-15.73	23.47	PK	46.00	22.53	Horizontal
4	601.901	31.34	-6.49	24.85	PK	46.00	21.15	Horizontal
5	704.824	31.57	-6.14	25.43	PK	46.00	20.57	Horizontal
6	830.080	31.93	-4.94	26.99	PK	46.00	19.01	Horizontal

Test mode: GFSK Frequency: Channel 78: 2480MHz



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	37.78	-18.16	19.62	PK	40.00	20.38	Vertical
2	55.2452	38.00	-16.80	21.20	PK	40.00	18.80	Vertical
3	62.042	37.13	-17.72	19.41	PK	40.00	20.59	Vertical
4	239.729	41.82	-15.73	26.09	PK	46.00	19.91	Vertical
5	594.134	32.13	-6.75	25.38	PK	46.00	20.62	Vertical
6	838.818	31.09	-4.69	26.40	PK	46.00	19.60	Vertical



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.8549	39.91	-18.16	21.75	PK	40.00	18.25	Horizontal
2	239.729	39.95	-15.73	24.22	PK	46.00	21.78	Horizontal
3	299.929	36.95	-13.99	22.96	PK	46.00	23.04	Horizontal
4	600.930	31.36	-6.46	24.90	PK	46.00	21.10	Horizontal
5	715.505	31.79	-6.16	25.63	PK	46.00	20.37	Horizontal
6	841.731	31.94	-4.58	27.36	PK	46.00	18.64	Horizontal

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction 2#

Phase: **L1**

Temperature: 25.3

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 50 %

Mode: BT

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	39.40	10.69	50.09	66.00	-15.91	QP	
2		0.1500	23.23	10.69	33.92	56.00	-22.08	AVG	
3	*	0.1750	38.39	10.68	49.07	64.72	-15.65	QP	
4		0.1750	20.13	10.68	30.81	54.72	-23.91	AVG	
5		0.2850	30.67	10.69	41.36	60.67	-19.31	QP	
6		0.2850	16.91	10.69	27.60	50.67	-23.07	AVG	
7		0.5450	22.88	10.74	33.62	56.00	-22.38	QP	
8		0.5450	15.76	10.74	26.50	46.00	-19.50	AVG	
9		11.8550	19.35	10.67	30.02	60.00	-29.98	QP	
10		11.8550	8.15	10.67	18.82	50.00	-31.18	AVG	
11		21.3550	20.44	11.12	31.56	60.00	-28.44	QP	
12		21.3550	4.00	11.12	15.12	50.00	-34.88	AVG	



Site Conduction 2#

Phase: **N**

Temperature: 25.3

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 50 %

Mode: BT

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	40.03	10.69	50.72	66.00	-15.28	QP	
2		0.1500	20.14	10.69	30.83	56.00	-25.17	AVG	
3		0.1700	38.67	10.68	49.35	64.96	-15.61	QP	
4		0.1700	21.54	10.68	32.22	54.96	-22.74	AVG	
5		0.2100	35.99	10.66	46.65	63.21	-16.56	QP	
6		0.2100	16.55	10.66	27.21	53.21	-26.00	AVG	
7		0.2850	32.03	10.69	42.72	60.67	-17.95	QP	
8		0.2850	16.74	10.69	27.43	50.67	-23.24	AVG	
9		0.5450	27.16	10.74	37.90	56.00	-18.10	QP	
10		0.5450	15.50	10.74	26.24	46.00	-19.76	AVG	
11		14.6050	20.56	10.75	31.31	60.00	-28.69	QP	
12		14.6050	5.67	10.75	16.42	50.00	-33.58	AVG	

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.9.2 Result

PASS

- ☒ Antenna use a permanently attached antenna which is not replaceable.
- ☐ Not using a standard antenna jack or electrical connector for antenna replacement
- ☐ The antenna has to be professionally installed (please provide method of installation)

Note: Please refer to the attached document Internal Photos to show the antenna connector.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

--- End of Report ---