

On your side



TEST REPORT

FCC /IC SAR Exclusion Report for certification of DSX-M80

APPLICANT

Sony Corporation

REPORT NO.

HCT-SR-1906-FI003

DATE OF ISSUE

Jun 24, 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

『인정마크 로고』

TEST REPORT

(If needed)
FCC SAR Test for
certification

REPORT NO.
HCT-SR-1906-FI003

DATE OF ISSUE
Jun 24, 2019
Other ID

Applicant Sony Corporation
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Product Name FM/AM Bluetooth® MARINE AUDIO
Model Name DSX-M80
FCC ID AK8DSXM80
ISED ID 409B-DSXM80

Date of Test Jun 24, 2019

FCC Test Standard Used **47CFR §2.1093**
ISED Test Standard Used **RSS-102 Issue 5; Health Canada Safety Code 6**

Test Results PASS
This device has been excluded from SAR based on FCC and ISED Standard

Manufacturer Sony Corporation
Bluetooth 3.0. 2 402 – 2 480 MHz

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Technical Manager
Yun Jeang Heo

HCT CO., LTD.

Soo Chan Lee

SooChan Lee / CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	Jun 24, 2019	Initial Release

CONTENTS

REVISION HISTORY 3

CONTENTS..... 4

1. Test Regulations..... 5

2. Test Location 5

 2.1 Test Laboratory 5

3. Information of the EUT..... 5

 3.1 General Information of the EUT..... 5

4. FCC 6

5. ISED 7

1. Test Regulations

The results in this report apply only to sample tested.

The tests were performed according to the following regulations:

Test Standard	FCC: 47CFR §2.1093 ISED : RSS102 Issue 5
Phenomena	Calculation
Application Port	SAR
Test Method	FCC KDB 447498 D01 v06 Per RSS102 Issue 5

2. Test Location

2.1 Test Laboratory

Company Name	HCT Co., Ltd.
Address	74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Telephone	031-645-6300
Fax	031-645-6401

3. Information of the EUT

3.1 General Information of the EUT

Model Name	DSX-M80
Product Name	FM/AM Bluetooth® MARINE AUDIO
Manufacturer	Sony Corporation
Manufacturer's Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

4. FCC

4.1 SAR Test Exclusions Applied _Bluetooth 3.0

According to the FCC KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Distance (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0 \text{ For 1g SAR, 7.5 for 10g SAR}$$

where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range: 2 402 MHz ~ 2 480 MHz

SAR Consideration Min. test separation distance: 5 mm

Maximum Output Power: 1.25 mW

The Highest RF channel frequency: 2 480 MHz

For SAR Exclusion

Mode	Frequency	Maximum Allowed Power	Separation Distance	≤ 3.0 for 1g SAR
	[MHz]	[mW]	[mm]	
Bluetooth 3.0	2 480	1.	5	0.3

Based on the maximum output power of Bluetooth 3.0 and antenna to use separation distance, Bluetooth 3.0 SAR was not required.

5. ISED

5.1 SAR Test Exclusions Applied _Bluetooth 3.0

Per RSS102 Issue 5, 2.5.1 Exemption Limits for Routine Evaluation

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

For SAR Exclusion: 4mW

Calculation Result::

Tx frequency range: 2 402 MHz ~ 2 480 MHz

SAR Consideration Min. test separation distance: 5 mm

Maximum Output Power: 1.25 mW

The Highest RF channel frequency: 2 480 MHz

The SAR exemption from RSS102: Issue 5 was also exempted by the above exclusion conditions.