



# FCC Test Report

**Test report**  
**On Behalf of**  
**Shenzhen Yunlink Technology Co., Ltd**  
**For**  
**Access Point**  
**Model No.: HWAP-AX880, AX880, AX-HQ880**  
**FCC ID: 2ADUG-HWAP-AX880**

**Prepared For :** Shenzhen Yunlink Technology Co., Ltd  
B3 Building, An'le Industrial Zone, Hangcheng Road, gushu, xixiang town, Baoan,  
Shenzhen Guangdong Province, China

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,  
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**Date of Test:** Jun. 05, 2023 ~ Jun. 14, 2023

**Date of Report:** Jun. 14, 2023

**Report Number:** HK2306052297-1E



## Test Result Certification

**Applicant's name** .....: Shenzhen Yunlink Technology Co., Ltd  
**Address** .....: B3 Building, An'le Industrial Zone, Hangcheng Road, gushu, xixiang town, Baoan, Shenzhen Guangdong Province, China

**Manufacture's Name**.....: Shenzhen Yunlink Technology Co., Ltd  
**Address** .....: B3 Building, An'le Industrial Zone, Hangcheng Road, gushu, xixiang town, Baoan, Shenzhen Guangdong Province, China

### Product description

**Trade Mark:** N/A  
**Product name**.....: Access Point  
**Model and/or type reference** : HWAP-AX880, AX880, AX-HQ880  
**Standards** .....: FCC Rules and Regulations Part 15 Subpart C Section 15.247  
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** .....:  
**Date (s) of performance of tests** .....: Jun. 05, 2023 ~ Jun. 14, 2023  
**Date of Issue**.....: Jun. 14, 2023  
**Test Result**.....: Pass

Testing Engineer :

(Gary Qian)

Technical Manager :

(Eden Hu)

Authorized Signatory :

(Jason Zhou)



## Table of Contents

<b>1. Test Result Summary .....</b>	<b>5</b>
1.1. Test Procedures and Results.....	5
1.2. Information of the Test Laboratory .....	5
1.3. Measurement Uncertainty .....	6
<b>2. EUT Description .....</b>	<b>7</b>
2.1. General Description of EUT .....	7
2.2. Carrier Frequency of Channels.....	8
2.3. Operation of EUT During Testing .....	8
2.4. Description of Test Setup.....	9
<b>3. General Information.....</b>	<b>10</b>
3.1. Test Environment and Mode .....	10
3.2. Description of Support Units .....	11
<b>4. Test Results and Measurement Data .....</b>	<b>12</b>
4.1. Conducted Emission.....	12
4.2. Maximum Conducted Output Power .....	16
4.3. Emission Bandwidth .....	19
4.4. Power Spectral Density .....	48
4.5. Conducted Band Edge and Spurious Emission Measurement .....	79
4.6. Radiated Spurious Emission Measurement .....	129
4.7. Antenna Requirement .....	165
<b>5. Photograph of Test .....</b>	<b>166</b>
<b>6. Photos of the EUT .....</b>	<b>168</b>



**\*\* Modified History \*\***

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	Jun. 14, 2023	Jason Zhou





## 1. Test Result Summary

### 1.1. Test Procedures and Results

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247(b)(4)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247(b)(3)	PASS
6dB Emission Bandwidth	§15.247(a)(2)	PASS
Power Spectral Density	§15.247(e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 1.2. Information of the Test Laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.  
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,  
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**Testing Laboratory Authorization:**

A2LA Accreditation Code is 4781.01.  
FCC Designation Number is CN1229.  
Canada IC CAB identifier is CN0045.  
CNAS Registration Number is L9589.



### 1.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 0.37\text{dB}$
2	RF power, conducted	$\pm 3.35\text{dB}$
3	Spurious emissions, conducted	$\pm 2.20\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.90\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^{\circ}\text{C}$
7	Humidity	$\pm 1.0\%$



## 2. EUT Description

### 2.1. General Description of EUT

Equipment:	Access Point
Model Name:	HWAP-AX880
Serial Model:	AX880, AX-HQ880
Model Difference:	All model's the function, software and electric circuit are the same, only with a product model named different. Test sample model: HWAP-AX880.
Trade Mark:	N/A
FCC ID:	2ADUG-HWAP-AX880
Antenna Type:	External Antenna
Antenna Gain:	Antenna 1:6.54dBi Antenna 2:6.54dBi Antenna 3:6.54dBi Antenna 4:6.54dBi MIMO: 12.56dBi
Operation frequency:	802.11b/g/n/ax20: 2412~2462MHz 802.11n/ax40: 2422~2452MHz
Number of Channels:	802.11b/g/n/ax20: 11CH 802.11n/ax40: 7CH
Modulation Type:	CCK/OFDM/DBPSK/DAPSK
Power Source:	DC 48V from Adapter
Power Rating:	DC 48V from Adapter
Hardware Version	V5.6
Software Version:	V5.6
Note: The EUT incorporates a MIMO function. Physically, it provides two completed transmitters and receivers(4T4R), two transmit signals are completely correlated, then, Direction gain=GANT + Array Gain(Array Gain=10 log(4) dB for power spectral density; Array Gain=0 for power measurement)	



## 2.2. Carrier Frequency of Channels

Channel List for 802.11b/ 802.11g/ 802.11n (HT20)/ 802.11ax (HT20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n (HT40) / 802.11ax (HT40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
--	--	04	2427	07	2442	--	--
--	--	05	2432	08	2447	--	--
03	2422	06	2437	09	2452		

### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

## 2.3. Operation of EUT During Testing

### Operating Mode

**The mode is used: Transmitting mode for 802.11b/802.11g/802.11n(HT20)/802.11ax (HT20)**

Low Channel: 2412MHz  
Middle Channel: 2437MHz  
High Channel: 2462MHz

**The mode is used: Transmitting mode for 802.11n (HT40)/802.11ax (HT40)**


Low Channel: 2422MHz  
Middle Channel: 2437MHz  
High Channel: 2452MHz





## 2.4. Description of Test Setup

Operation of EUT during testing:



### Laptop information

Model: TP00096A

Input: DC 20V, 2.25A/3.25A

### Adapter information

Model: GRT-POE20-480050A

Input: AC100-240V~50-60Hz 0.8A max

Output: 48V 500mA

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.



### 3. General Information

#### 3.1. Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations (The value of duty cycle is 98.46%)
<p>The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.</p>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

**Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.**

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)/ax (HT20)	6.5Mbps
802.11n(HT40)/ax (HT40)	13.5Mbps

#### Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

2. According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20)/ax (H20), 13.5Mbps for 802.11n(HT40)/ax (HT40). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.



### 3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



## 4. Test Results and Measurement Data

### 4.1. Conducted Emission

#### 4.1.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<div><p>Reference Plane</p><p>40cm</p><p>E.U.T</p><p>AC power</p><p>80cm</p><p>LISN</p><p>Filter</p><p>AC power</p><p>EMI Receiver</p><p>Test table/Insulation plane</p><p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div>														
Test Mode:	Charging + transmitting with modulation														
Test Procedure:	<div><div>1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</div></div>														
Test Result:	PASS														





#### 4.1.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Receiver	R&S	ESR-7	HKE-005	Feb. 17, 2023	Feb. 16, 2024
LISN	R&S	ENV216	HKE-002	Feb. 17, 2023	Feb. 16, 2024
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



#### 4.1.3 Test data

Test Specification: Line



#### Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1545	61.36	20.03	65.75	4.39	41.33	PK	L
2	0.4830	54.98	20.04	56.29	1.31	34.94	PK	L
3	1.6845	49.70	20.13	56.00	6.30	29.57	PK	L
4	2.0580	48.65	20.15	56.00	7.35	28.50	PK	L
5	5.2395	49.34	20.26	60.00	10.66	29.08	PK	L
6	22.2765	55.62	20.16	60.00	4.38	35.46	PK	L

#### Final Data List

NO.	Freq. [MHz]	Correction factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	0.4825	20.04	52.72	56.30	3.58	32.68	45.54	46.30	0.76	25.50	L
2	0.1548	20.03	54.67	65.74	11.07	34.64	34.08	55.74	21.66	14.05	L
3	1.6830	20.13	48.36	56.00	7.64	28.23	45.41	46.00	0.59	25.28	L
4	2.0568	20.15	47.37	56.00	8.63	27.22	43.82	46.00	2.18	23.67	L
5	22.0650	20.16	52.65	60.00	7.35	32.49	46.93	50.00	3.07	26.77	L


Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



Test Specification: Neutral



## Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1770	55.32	20.05	64.63	9.31	35.27	PK	N
2	0.4830	55.19	20.04	56.29	1.10	35.15	PK	N
3	1.6845	49.25	20.13	56.00	6.75	29.12	PK	N
4	2.0580	49.68	20.15	56.00	6.32	29.53	PK	N
5	4.6770	48.24	20.26	56.00	7.76	27.98	PK	N
6	23.1990	54.63	20.20	60.00	5.37	34.43	PK	N

## Final Data List

NO.	Freq. [MHz]	Correction factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	0.1767	20.05	50.72	64.64	13.92	30.67	32.67	54.64	21.97	12.62	N
2	0.4808	20.04	53.11	56.32	3.21	33.07	45.82	46.32	0.50	25.78	N
3	1.6825	20.13	48.32	56.00	7.68	28.19	45.37	46.00	0.63	25.24	N
4	2.0566	20.15	47.41	56.00	8.59	27.26	43.83	46.00	2.17	23.68	N
5	4.6735	20.26	46.30	56.00	9.70	26.04	42.55	46.00	3.45	22.29	N
6	23.1798	20.19	49.20	60.00	10.80	29.01	45.91	50.00	4.09	25.72	N

Remark: Margin = Limit – Level


Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



## 4.2. Maximum Conducted Output Power

### 4.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test Setup:	 <p>The diagram illustrates the test setup. On the left is a green box labeled 'Power meter'. A line connects it to a small white box, which is then connected to a yellow box labeled 'EUT' (Equipment Under Test). Below the green box is the text 'Power meter' and below the yellow box is the text 'EUT'.</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"><li>1. The testing follows the Measurement Procedure of FCC KDB 558074 D01 15.247 Meas Guidance v05r02.</li><li>2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li><li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>4. Measure the Peak output power and record the results in the test report.</li></ol>
Test Result:	PASS

### 4.2.2. Test Instruments

RF Test Room					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Power meter	Agilent	E4419B	HKE-085	Feb. 17, 2023	Feb. 16, 2024
Power Sensor	Agilent	E9300A	HKE-086	Feb. 17, 2023	Feb. 16, 2024
RF cable	Times	1-40G	HKE-034	Feb. 17, 2023	Feb. 16, 2024
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 17, 2023	Feb. 16, 2024

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).





## 4.2.3. Test Data

Mode	Test channel	Frequency (MHz)	Reading Conducted Output Power (dBm)				Cable loss	Maximum Conducted Output Power (dBm)				Limit (dBm)	Result
			Antenna port 1	Antenna port 2	Antenna port 3	Antenna port 4		Antenna port 1	Antenna port 2	Antenna port 3	Antenna port 4		
802.11b	CH01	2412	16.79	15.97	16.46	14.43	1	17.79	16.97	17.46	15.43	30	PASS
802.11b	CH06	2437	14.75	14.81	15.32	16.32	1	15.75	15.81	16.32	17.32	30	PASS
802.11b	CH11	2462	15.27	16.99	14.70	15.61	1	16.27	17.99	15.70	16.61	30	PASS
802.11g	CH01	2412	15.30	15.37	14.88	14.78	1	16.30	16.37	15.88	15.78	30	PASS
802.11g	CH06	2437	15.47	15.46	15.10	15.05	1	16.47	16.46	16.10	16.05	30	PASS
802.11g	CH11	2462	15.62	15.63	15.31	15.20	1	16.62	16.63	16.31	16.20	30	PASS
802.11n(HT 20)	CH01	2412	16.41	15.47	14.92	14.90	1	17.41	16.47	15.92	15.90	30	PASS
802.11n(HT 20)	CH06	2437	15.40	15.60	15.15	15.15	1	16.40	16.60	16.15	16.15	30	PASS
802.11n(HT 20)	CH11	2462	15.67	16.72	15.26	15.23	1	16.67	17.72	16.26	16.23	30	PASS
802.11n(HT 40)	CH03	2422	15.82	15.76	15.44	15.38	1	16.82	16.76	16.44	16.38	30	PASS
802.11n(HT 40)	CH06	2437	15.87	15.82	15.55	15.51	1	16.87	16.82	16.55	16.51	30	PASS
802.11n(HT 40)	CH09	2452	16.11	16.07	15.51	15.55	1	17.11	17.07	16.51	16.55	30	PASS
802.11ax(HT 20)	CH01	2412	16.30	14.31	15.81	15.71	1	17.30	15.31	16.81	16.71	30	PASS
802.11ax(HT 20)	CH06	2437	16.44	16.42	16.05	16.09	1	17.44	17.42	17.05	17.09	30	PASS
802.11ax(HT 20)	CH11	2462	14.62	15.64	16.23	16.25	1	15.62	16.64	17.23	17.25	30	PASS
802.11ax(HT 40)	CH03	2422	16.59	16.43	16.09	16.17	1	17.59	17.43	17.09	17.17	30	PASS
802.11ax(HT 40)	CH06	2437	15.62	16.51	16.17	16.27	1	16.62	17.51	17.17	17.27	30	PASS
802.11ax(HT 40)	CH09	2452	16.72	16.21	16.16	16.27	1	17.72	17.21	17.16	17.27	30	PASS
Note: Maximum Conducted Output Power(dBm)= Reading Conducted Output Power(dBm)+ Cable loss													




Mode	Test channel	Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Result
			Antenna port 1	Antenna port 2	Antenna port 3	Antenna port 4	MIMO		
802.11n(HT20)	CH01	2412	17.41	16.47	15.92	15.90	22.49	30	PASS
802.11n(HT20)	CH06	2437	16.40	16.60	16.15	16.15	22.35	30	PASS
802.11n(HT20)	CH11	2462	16.67	17.72	16.26	16.23	22.78	30	PASS
802.11n(HT40)	CH03	2422	16.82	16.76	16.44	16.38	22.62	30	PASS
802.11n(HT40)	CH06	2437	16.87	16.82	16.55	16.51	22.71	30	PASS
802.11n(HT40)	CH09	2452	17.11	17.07	16.51	16.55	22.84	30	PASS
802.11ax(HT20)	CH01	2412	17.30	15.31	16.81	16.71	22.61	30	PASS
802.11ax(HT20)	CH06	2437	17.44	17.42	17.05	17.09	23.27	30	PASS
802.11ax(HT20)	CH11	2462	15.62	16.64	17.23	17.25	22.75	30	PASS
802.11ax(HT40)	CH03	2422	17.59	17.43	17.09	17.17	23.35	30	PASS
802.11ax(HT40)	CH06	2437	16.62	17.51	17.17	17.27	23.18	30	PASS
802.11ax(HT40)	CH09	2452	17.72	17.21	17.16	17.27	23.37	30	PASS

Note: This product supports antenna 1, antenna 2, antenna 3 and antenna 4 launch, but only support 802.11 n /802.11ax for MIMO mode, not support 802.11 b and 802.11 g for MIMO mode.



### 4.3. Emission Bandwidth

#### 4.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05r02
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer                      EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"><li>1. The testing follows FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02.</li><li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.</li><li>4. Measure and record the results in the test report.</li></ol>
Test Result:	PASS

#### 4.3.2. Test Instruments

RF Test Room					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-048	Feb. 17, 2023	Feb. 16, 2024
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Feb. 17, 2023	Feb. 16, 2024
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 17, 2023	Feb. 16, 2024

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



#### 4.3.3. Test data

##### For antenna port 1

Test channel	6dB Emission Bandwidth (MHz)					
	802.11b	802.11g	802.11n (HT20)	802.11n (HT40)	802.11ax (HT20)	802.11ax (HT40)
Lowest	7.60	16.32	17.56	36.32	18.72	37.84
Middle	7.08	16.32	17.60	36.32	18.88	37.60
Highest	8.52	16.32	17.32	36.40	18.80	38.00
Limit:	>500KHz					
Test Result:	PASS					


Test plots as follows:





## 802.11b Modulation

## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11g Modulation


Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11n (HT20) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11n (HT40) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11ax (HT20) Modulation

### Lowest channel



### Middle channel



### Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11ax (HT40) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**For antenna port 2**

Test channel	6dB Emission Bandwidth (MHz)					
	802.11b	802.11g	802.11n (HT20)	802.11n (HT40)	802.11ax (HT20)	802.11ax (HT40)
Lowest	8.04	16.32	17.56	36.08	18.92	37.52
Middle	7.12	16.32	17.60	36.00	18.88	37.68
Highest	7.56	16.28	17.60	36.08	18.72	37.76
Limit:	>500KHz					
Test Result:	PASS					

**Test plots as follows:**




## 802.11b Modulation

## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11g Modulation


### Lowest channel



### Middle channel



### Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



## 802.11n (HT20) Modulation

## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11n (HT40) Modulation


### Lowest channel



### Middle channel



### Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11ax (HT20) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11ax (HT40) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



For antenna port 3

Test channel	6dB Emission Bandwidth (MHz)					
	802.11b	802.11g	802.11n (HT20)	802.11n (HT40)	802.11ax (HT20)	802.11ax (HT40)
Lowest	7.56	16.32	17.56	35.92	18.80	37.84
Middle	7.04	16.32	17.28	36.00	18.84	37.76
Highest	7.56	16.32	17.56	36.32	19.00	37.84
Limit:	>500KHz					
Test Result:	PASS					

Test plots as follows:



802.11b Modulation

Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11g Modulation


### Lowest channel



### Middle channel



### Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






## 802.11n (HT20) Modulation

## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11n (HT40) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




## 802.11ax (HT20) Modulation


## Lowest channel



## Middle channel



## Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China