ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

Applicant:	Immedia Semiconductor LLC. 100 Riverpark Drive, Suite 125 North Reading, MA 01864, United States of America
Manufacturer:	Immedia Semiconductor LLC. 100 Riverpark Drive, Suite 125 North Reading, MA 01864, United States of America
Product Name:	Camera
Brand Name:	blink
Model No.:	BCM00700U
Model Difference:	N/A
Report Number:	TERF2310002706E2
FCC ID	2AF77-H2311821
IC:	20741-H2311821
Date of EUT Received:	October 30, 2023
Date of Test:	October 31, 2023～December 08, 2023
Issue Date:	December 13, 2023

Approved By _____
Jay Lin

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Central RF Lab The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT comply with FCC rule part §15.247, ISED RSS-247.

The results of this report relate only to the sample identified in this report.

Revision History

Report Number	Revision	Description	Issue Date	Revised By	Remark
TERF2310002706E2	00	Original	December 13, 2023	Violetta Tang	

Note:

1、The remark "*" indicates modification of the report upon requests from certification body.

Table of Contents

1 GENERAL INFORMATION

1.1 Product Description

Product Name:	Camera
Brand Name:	blink
Model No.:	BCM00700U
Model Difference:	N/A
Hardware Version:	PVT
Firmware Version:	N/A
EUT Series No.:	TE_SP_2023103001
Power Supply:	5V
Test Software (Name/Version)	Tera Term V4.106

1.2 RF Specification

Radio Technology:	BLE
Frequency Range:	2402 – 2480MHz
Channel number:	40 channels
Modulation type:	GFSK
Transmit Power:	BLE 1M: 4.39 dBm

1.3 Antenna Designation

Antenna Type	Supplier	Antenna Part No.	Freq. (MHz)	Peak Antenna Gain (dBi)
Monopole	Immedia Semiconductor LLC	BCM00700U	2400~2500	3.4

Note: Antenna information is provided by the applicant.

1.4 Test Methodology of Applied Standards

FCC Part 15, Subpart C §15.247
FCC KDB 558074 D01 15.247 Meas Guidance v05r02
RSS-247 issue 3 Aug. 2023
RSS-Gen, Issue 5 April 2018
ANSI C63.10:2013

1.5 Test Facility

Laboratory	Test Site Address	Test Site Name	FCC Designation number	IC CAB identifier
SGS Taiwan Ltd. Central RF Lab. (TAF code 3702)	No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan.	SAC 1	TW0027	TW3702
		SAC 2		
		SAC 3		
		Conduction 1		
		Conducted 1		
		Conducted 2		
		Conducted 3		
		Conducted 4		
		Conducted 5		
		Conducted 6		
	No.2, Keji 1st Rd., Guishan District, Taoyuan City, Taiwan 333	Conduction C	TW0028	
		SAC C		
		SAC D		
		SAC G		
		Conducted A		
		Conducted B		
		Conducted C		
		Conducted D		
		Conducted E		
		Conducted F		
		Conducted G		

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

1.6 Special Accessories

There are no special accessories used while test was conducted.

1.7 Equipment Modifications

There was no modification incorporated into the EUT.

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on a table which is 0.8 m above ground plane. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz. The CISPR Quasi-Peak and Average detector mode is employed. The two LISNs provide 50uH/50 ohm of coupling impedance for the measuring instrument. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

2.3.2 Conducted Test (RF)

The active antenna port of the unlicensed wireless device is connected to the spectrum analyzer with attenuator to protect the instrumentation. If a second antenna port is available, it is tested at one operating frequency, with other port(s) appropriately terminated, to verify it has similar output characteristics as the fully tested port.

2.3.3 Radiated Emissions

The EUT is a placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.

2.4 Measurement Results Explanation Example

2.4.1 Radiated Emission Test Sites For Measurements From 9 kHz To 30 MHz

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-anechoic chamber, the measurements correspond to those obtained at an open-field test site.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

2.4.2 For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuation factor between EUT conducted port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly EUT RF output level.

2.5 Test Configuration

Conduction Setup	Conducted Setup
	

Radiated Setup


2.6 Control Unit(s)

1st

AC Power-Line Conducted Emission Test Site: Conduction C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Notebook	Lenovo	L480	P0002332	N/A	N/A
USB Cable	DONGGUAN YUQIU ELECTRONIC CO., LTD	1310252-00200-01	N/A	N/A	N/A
Adapter	Dongguan Aohai Technology Co.,Lte.	A726-050150U-US1	N/A	N/A	N/A
USB Cable	DONGGUAN YUQIU ELECTRONIC CO., LTD	1310252-00100-01	N/A	N/A	N/A

2nd

AC Power-Line Conducted Emission Test Site: Conduction C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Adapter	Dongguan Aohai Technology Co.,Ltd	BAH0410U	N/A	N/A	N/A

Conducted Emission Test Site: Conducted D					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Notebook	Lenovo	T14	P0003332	N/A	N/A

1st

Radiated Emission Test Site: SAC C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Notebook	Lenovo	L480	P0002332	N/A	N/A
USB Cable	DONGGUAN YUQIU ELECTRONIC CO., LTD	1310252-00200-01	N/A	N/A	N/A
USB Cable	DONGGUAN YUQIU ELECTRONIC CO., LTD	1310252-00100-01	N/A	N/A	N/A
Adapter	Dongguan Aohai Technology Co.,Lte.	A726-050150U-US1	N/A	N/A	N/A

2nd

Radiated Emission Test Site: SAC C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Adapter	Dongguan Aohai Technology Co.,Ltd	BAH0410U	N/A	N/A	N/A

3 SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description Of Test	Result
§15.207(a)	RSS-Gen §8.8	AC Power Line Conducted Emission	Compliant
§15.247(b) (3)	RSS-247 §5.4 d	Peak Output Power	Compliant
§15.247(a)(2)	RSS-247 §5.2 a RSS-Gen §6.7	Emission Bandwidth	Compliant
§15.247(d) §15.205 §15.209	RSS-247 §5.5 RSS-Gen §8.9 RSS-Gen §8.10	Radiated & Conducted Band Edge and Spurious Emission	Compliant
§15.247(e)	RSS-247 §5.2 b	Peak Power Density	Compliant
§15.203	N/A	Antenna Requirement	Compliant
§15.205	RSS-Gen § 8.10	Restricted Bands	Compliant

4 DESCRIPTION OF TEST MODES

4.1 Operating Frequencies

2400~2483.5 MHz							
ITEM	Freq. (MHz)	ITEM	Freq. (MHz)	ITEM	Freq. (MHz)	ITEM	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

4.2 The Worst Test Modes and Channel Details

1. The EUT has been tested under operating condition.
2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.
3. The field strength of radiation emission was measured as the EUT positioned in different orthogonal planes (E1/E2/H) based on actual usage of the EUT to pre-scan the emissions for determining the worst case scenario.
4. Investigation has been done on all the possible configurations for searching the worst case.

CONDUCTED TEST				
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
Bluetooth LE	0 to 39	0,19,39	GFSK	1

TRANSMIT RADIATED EMISSION TEST (BELOW 1 GHz)				
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
Bluetooth LE	0 to 39	19	GFSK	1
TRANSMIT RADIATED EMISSION TEST (ABOVE 1 GHz)				
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
Bluetooth LE	0 to 39	0,19,39	GFSK	1

5 MEASUREMENT UNCERTAINTY

Test Items	Uncertainty		
AC Power Line Conducted Emission	+/-	2.32	dB
Output Power measurement	+/-	1	dB
Emission Bandwidth	+/-	1.53	Hz
Undesignable radiated emission measurement	+/-	1.68	dB
Peak Power Density	+/-	2.16	dB
Temperature	+/-	0.7	°C
Humidity	+/-	3	%
DC / AC Power Source	+/-	1	%

Radiated Spurious Emission Measurement Uncertainty				
Polarization: Vertical	**+/-**	**2.8**	**dB**	9kHz~30MHz
	+/-	**4.82**	**dB**	30MHz - 1000MHz
	+/-	**4.37**	**dB**	1GHz - 18GHz
	+/-	**4.21**	**dB**	18GHz - 40GHz
Polarization: Horizontal	**+/-**	**2.8**	**dB**	9kHz~30MHz
	+/-	**4.54**	**dB**	30MHz - 1000MHz
	+/-	**4.37**	**dB**	1GHz - 18GHz
	+/-	**4.21**	**dB**	18GHz - 40GHz

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

6 MEASUREMENT EQUIPMENT USED

6.1 Emission from AC power line

AC Power-Line Conducted Emission Test Site: Conduction C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
LISN	SCHWARZBECK Mess-Elektronik	NSLK8127	973	04/20/2023	04/19/2024
EMI Test Receiver	R&S	ESCI	101342	04/24/2023	04/23/2024
Coaxial Cable	EC Lab	RF-HY-CAB-250	RF-HY-CAB-250-01	03/27/2023	03/26/2024
Pulse Limiter	EC Lab	VTSD 9561F-N	485	03/27/2023	03/26/2024
Test Software	audix	e3	E3 20923 SGS Ver.9 (C)	N.C.R	N.C.R

6.2 Conducted Measurement

Conducted Emission Test Site: Conducted D					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	KEYSIGHT	N9010B	MY59071573	05/23/2023	05/22/2024
Power Meter	Anritsu	ML2496A	2138002	08/31/2023	08/30/2024
Power Sensor	Anritsu	MA2411B	1911390	08/31/2023	08/30/2024
Power Sensor	Anritsu	MA2411B	1911398	08/31/2023	08/30/2024
Test Software	SGS Taiwan	Radio Test Software	Ver.21	N.C.R	N.C.R
Attenuator	Woken	WATT-218FS-10	RF18	11/16/2022	11/15/2023
Attenuator	Woken	WATT-218FS-10	RF19	11/16/2022	11/15/2023
DC Block	PASTERNACK	PE8210	RF155	11/16/2022	11/15/2023

6.3 Radiated Measurement

Radiated Emission Test Site: SAC C					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Broadband Antenna	SCHWARZBECK	VULB 9168	9168-300	11/11/2022	11/10/2023
Horn Antenna	Schwarzbeck	BBHA9170	184	12/30/2022	12/29/2023
Horn Antenna	Schwarzbeck	BBHA9120D	1187	01/12/2023	01/11/2024
Loop Antenna	ETS.LINDGREN	6502	148045	10/13/2023	10/12/2024
3m Site NSA	SGS	966 chamber C	N/A	03/02/2023	03/01/2024
Spectrum Analyzer	KEYSIGHT	N9010A	MY57120200	03/29/2023	03/28/2024
Test Software	audix	e3	E3 20923 SGS Ver.9 (C)	N.C.R	N.C.R
Pre-Amplifier	EMC Instruments	EMC330	980096	11/16/2022	11/15/2023
Pre-Amplifier	EMC Instruments	EMC118A45SE	980789	11/16/2022	11/15/2023
Pre-Amplifier	EMC Instruments	EMC18405SEE	980881	10/25/2023	10/24/2024
Attenuator	Woken	WATT-218FS-10	RF16	11/16/2022	11/15/2023
Coaxial Cable	Huber Suhner	EMC106-SM-SM-9100	150704	11/16/2022	11/15/2023
Coaxial Cable	Huber Suhner	SUCOFLEX 104	MY17388/4	11/16/2022	11/15/2023
Coaxial Cable	Huber Suhner	RG 214/U	W22.03	11/16/2022	11/15/2023

NOTE: *N.C.R refers to Not Calibrated Required.*

7 CONDUCTED EMISSION TEST

7.1 Standard Applicable:

Frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

7.2 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10:2013.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

7.3 Test Setup



7.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all phases of power being supplied by given UE are completed

7.5 Measurement Result:

Note: Refer to next page for measurement data and plots.

Note2: The * reveals the worst-case results that closest to the limit.

AC POWER LINE CONDUCTED EMISSION TEST DATA

1st

Report Number	:TERF2310002706E2	Test Site	:Conduction C
Test Mode	:BLE	Test Date	:2023-11-02
Power	:120V/60Hz	Temp./Humi.	:20.3℃/63%
Probe	:L1	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV	dBµV	dB
0.155	Peak	40.70	10.65	51.35	65.72	-14.37
0.168	Peak	38.59	10.65	49.24	65.08	-15.85
0.211	Peak	32.21	10.65	42.86	63.18	-20.32
0.225	Peak	31.60	10.65	42.25	62.61	-20.37
0.243	Peak	28.42	10.64	39.06	61.98	-22.92
0.652	Peak	27.81	10.64	38.45	56.00	-17.55

Report Number	:TERF2310002706E2	Test Site	:Conduction C
Test Mode	:BLE	Test Date	:2023-11-02
Power	:120V/60Hz	Temp./Humi.	:20.3℃/63%
Probe	:N	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV	dBµV	dB
0.159	Peak	40.37	10.66	51.03	65.51	-14.47
0.168	Peak	38.30	10.66	48.96	65.08	-16.13
0.192	Peak	35.71	10.65	46.36	63.95	-17.60
0.222	Peak	31.95	10.64	42.59	62.76	-20.17
0.229	Peak	29.77	10.64	40.41	62.47	-22.07
0.652	Peak	28.31	10.63	38.94	56.00	-17.06

2nd

Report Number	:TERF2310002706E2	Test Site	:Conduction C
Test Mode	:BLE	Test Date	:2023-12-08
Power	:120V/60Hz	Temp./Humi.	:20.3℃/63%
Probe	:L1	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV	dBµV	dB
0.218	Peak	20.06	10.65	30.71	62.90	-32.19
0.518	Peak	17.54	10.62	28.16	56.00	-27.84
0.841	Peak	13.45	10.67	24.12	56.00	-31.88
1.884	Peak	12.03	10.76	22.80	56.00	-33.20
2.349	Peak	13.87	10.80	24.67	56.00	-31.33
4.633	Peak	12.02	10.94	22.96	56.00	-33.04

Report Number	:TERF2310002706E2	Test Site	:Conduction C
Test Mode	:BLE	Test Date	:2023-12-08
Power	:120V/60Hz	Temp./Humi.	:20.3℃/63%
Probe	:N	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV	dBµV	dB
0.235	Peak	19.22	10.64	29.86	62.26	-32.40
0.272	Peak	16.56	10.63	27.19	61.06	-33.87
0.518	Peak	14.43	10.61	25.04	56.00	-30.96
2.329	Peak	10.75	10.78	21.52	56.00	-34.48
3.442	Peak	7.73	10.85	18.58	56.00	-37.42
6.079	Peak	8.73	10.94	19.67	60.00	-40.33

8 PEAK OUTPUT POWER MEASUREMENT

8.1 Standard Applicable:

8.1.1 Duty Cycle

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

8.1.2 FCC

For systems using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1Watt.

If the transmitting antenna of directional gain greater than 6dBi are used the peak output power form the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi.

In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of Antenna exceeds 6dBi.

8.1.3 ISED

For systems using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1Watt and the e.i.r.p. shall not exceed 4 W.

8.2 Test Setup

8.2.1 Duty Cycle



8.2.2 Output Power



8.3 Measurement Procedure:

8.3.1 Duty Cycle

1. Place the EUT on the table and set it in transmitting mode.
2. Set span = Zero
3. RBW = 8MHz, VBW = 8MHz,
4. Detector = Peak

8.3.2 Output Power

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
4. Record the max. Reading as observed from Power Meter.
5. Repeat above procedures until all test default channel measured was complete.

8.4 Duty Factor:

	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
BLE 1M	85.63	0.67	0.47	1.00

BLE_1M_LowCH00-2402



8.5 Output Power:

8.5.1 Peak & Avg

BLE 1M mode:

CH	Frequency (MHz)	Power set	Peak Output Power (dBm)	Required Limit (dBm)
Low	2402	default	4.27	30
Mid	2440	default	**4.39**	30
High	2480	default	4.17	30
CH	**Frequency (MHz)**	**Power set**	**Avg. Output Power (dBm)**	**Required Limit (dBm)**
Low	2402	default	4.04	30
Mid	2440	default	4.15	30
High	2480	default	3.95	30

**Note:*

1.Measured by power meter, cable loss 10.8 dB + Duty cycle factor has been offseted to the power meter for Avg. power and cable loss has been offseted for Peak power measurement.

8.5.2 EIRP

EIRP BLE 1M mode

CH	Frequency (MHz)	Power set	Avg. Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit
Low	2402	default	4.04	3.40	7.44	4W= 36 dBm
Mid	2440	default	4.15	3.40	7.55	4W= 36 dBm
High	2480	default	3.95	3.40	7.35	4W= 36 dBm

* ***Note:*** EIRP = Average Power + Gain

9 EMISSION BANDWIDTH MEASUREMENT

9.1 Standard Applicable

The minimum 6 dB bandwidth shall be at least 500 kHz .

9.2 Test Setup



9.3 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

9.3.1 6dB BW measurements

1. The testing follows the Measurement Procedure of the KDB 558074 D01.
2. Set the spectrum analyzer as
   RBW= 100 kHz ,
   VBW = 3 X RBW,
   Span= 2 to 5 times of the OBW,
   Sweep=auto, Detector = Peak, and Max hold.
3. Mark the upper and lower frequencies of -6dB.
4. Repeat above procedures until all test default channel is completed.

9.3.2 99% BW measurements

1. The testing follows the Measurement Procedure of the RSS-Gen section 6.7.
2. Set the spectrum analyzer as
   RBW= 1 % to 5% of 99%,
   VBW ≥ 3 X RBW,
   Span= large enough to capture all products of the modulation process
   Sweep=auto, Detector = Peak, and Max hold.
3. Mark the upper and lower frequencies of 99%.
4. Repeat above procedures until all test default channel is completed.

9.4 Measurement Result:

9.4.1 6dB BW measurements

BLE 1M mode

Frequency (MHz)	6dB BW (MHz)	Required BW (MHz)	Result
2402	0.6633	≧ 0.5	PASS
2440	0.6527	≧ 0.5	PASS
2480	0.6628	≧ 0.5	PASS

OBW_BLE 1M_LowCH00-2402MHz

OBW_BLE 1M_HighCH39-2480MHz

OBW_BLE 1M_MidCH19-2440MHz



9.4.2 99% Bandwidth

BLE 1M mode

Frequency (MHz)	99%Bandwidth (MHz)
2402	1.0449
2440	1.0468
2480	1.0457

IC OBW_BLE 1M_LowCH00-2402MHz

IC OBW_BLE 1M_HighCH39-2480MHz



IC OBW_BLE 1M_MidCH19-2440MHz



10 CONDUCTED BAND EDGES AND SPURIOUS EMISSION MEASUREMENT

10.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) & RSS-Gen §8.10, must also comply with the radiated emission limits specified in §15.209(a) & RSS-Gen §8.9.

10.2 Test Setup



10.3 Measurement Procedure

10.3.1 Reference Level of Emission Limit:

1. Set analyzer center frequency to DTS channel center frequency.
2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW = 100kHz & VBW = 300 kHz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.

10.3.2 Conducted Band Edge:

1. To connect Antenna Port of EUT to Spectrum.
2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
4. Set start to edge frequency, and stop frequency of spectrum analyzer so as to encompass the spectrum to be examined.
5. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz, Detector = Peak, Sweep = auto
6. Set DL as the limit = reading on marker of reference level measurement – 20dBm
7. Mark the highest readings of the emissions outside of 2400MHz~2483.5MHz.
8. Repeat above procedures until all default test channel (low and high) was complete.

10.3.3 Conducted Spurious Emission:

1. To connect Antenna Port of EUT to Spectrum.
2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
3. Set RBW = 100 kHz & VBW=300 kHz, Detector =Peak, Sweep = Auto
4. Allow trace to fully stabilize.
5. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
6. Repeat above procedures until all default test channel measured were complete.

10.4 Measurement Result

BLE 1M_Reference Level of Limit

Frequency (MHz)	RF Power Density (dBm)	Reference Level of Limit = PSD - 20dB (dBm)
2402	4.13	-15.87
2440	4.33	-15.67
2480	4.06	-15.94

Note:
1.cable loss as 10.8 dB that offsets in the spectrum
2.Refer to next page for plots.

Reference Level_BLE 1M_LowCH00-2402MHz



Band Edge_BLE 1M_LowCH00-2402MHz



Reference Level_BLE 1M_MidCH19-2440MHz



Band Edge_BLE 1M_HighCH39-2480MHz



Reference Level_BLE 1M_HighCH39-2480MHz

Spurious Emission_BLE 1M_LowCH00-2402MHz



Spurious Emission_BLE 1M_MidCH19-2440MHz



Spurious Emission_BLE 1M_HighCH39-2480MHz



11 RADIATED BANDEDGE AND SPURIOUS EMISSION MEASUREMENT

11.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands must also comply with the §15.209 and RSS-Gen §8.9 Table 5 and 6 limit as below.

And according to §15.33(a) (1) & RSS-Gen §6.13.2.a for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

Frequency (MHz)	Field strength (microvolts/meter)	Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note: The lower limit shall apply at the transition frequencies.

11.2 Test Setup

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz.



(B) Radiated Emission Test Set-Up, Frequency From 30MHz to 1000MHz.



(C) Radiated Emission Test Set-Up, Frequency Above 1GHz.



11.3 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
2. The EUT was placed on a turn table with 0.8m for frequency< 1GHz and 1.5m for frequency> 1GHz above ground plane.
3. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
4. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
5. Set the spectrum analyzer as RBW=100 kHz and VBW=300 kHz for Peak Detector (PK) at frequency between 30MHz and 1 GHz.
6. Use receiver mode as RBW=120 kHz for Quasi-peak (QP) at frequency between 30MHz and 1 GHz.

7. Set the spectrum analyzer as RBW=1 MHz, VBW=3 MHz for Maximum Emission Measurements at frequency above 1 GHz.
8. Set the spectrum analyzer as RBW=1 MHz, VBW=10 Hz (Duty cycle > 98%) or VBW ≥ 1/T (Duty cycle < 98%) for Average Emission Measurements at frequency above 1 GHz.
9. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
10. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
11. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
12. Repeat above procedures until all default test channel measured were complete.

11.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where *FS = Field Strength* *CL = Cable Attenuation Factor (Cable Loss)*
RA = Reading Amplitude *AG = Amplifier Gain*
AF = Antenna Factor

*The limit of the emission level is expressed in dBuV/m, which converts 20*log(uV/m)*

Actual FS(dBμV/m) = SPA. Reading level(dBμV) + Factor(dB)

Factor(dB) = Antenna Factor(dBμV/m) + Cable Loss(dB) – Pre_Amplifier Gain(dB)

11.5 Test Results of Radiated Spurious Emissions from 9 kHz to 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit per 15.31(o) & RSS-GEN §6.13.2 was not reported.

11.6 Measurement Result:

11.6.1 Radiated Band Edge Measurement Result

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2402 MHz	Temp./Humi.	:19.0℃/64%
Test Mode	:Bandedge	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2363.600	Average	40.40	-2.10	38.30	54.00	-15.70
2363.600	Peak	52.86	-2.10	50.76	74.00	-23.24
2390.000	Average	40.46	-2.15	38.31	54.00	-15.69
2390.000	Peak	50.62	-2.15	48.47	74.00	-25.53

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2402 MHz	Temp./Humi.	:19.0℃/64%
Test Mode	:Bandedge	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2329.700	Average	40.32	-1.96	38.36	54.00	-15.64
2329.700	Peak	52.99	-1.96	51.03	74.00	-22.97
2390.000	Average	40.22	-2.15	38.07	54.00	-15.93
2390.000	Peak	50.97	-2.15	48.81	74.00	-25.19

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2480 MHz	Temp./Humi.	:19.0℃/64%
Test Mode	:Bandedge	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.500	Average	41.37	-2.06	39.31	54.00	-14.69
2483.500	Peak	54.36	-2.06	52.30	74.00	-21.70
2483.850	Average	41.45	-2.06	39.39	54.00	-14.61
2483.850	Peak	54.77	-2.06	52.71	74.00	-21.29

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2480 MHz	Temp./Humi.	:19.0℃/64%
Test Mode	:Bandedge	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2483.500	Average	41.48	-2.06	39.42	54.00	-14.58
2483.500	Peak	55.21	-2.06	53.15	74.00	-20.85
2483.850	Average	41.57	-2.06	39.52	54.00	-14.48
2483.850	Peak	56.03	-2.06	53.97	74.00	-20.03

11.6.2 Radiated Spurious Emission

1st

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2440 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
52.310	Peak	46.84	-13.31	33.53	40.00	-6.47
74.620	Peak	48.13	-16.76	31.37	40.00	-8.63
96.930	Peak	48.75	-18.41	30.34	43.50	-13.16
273.470	Peak	44.41	-13.47	30.94	46.00	-15.06
524.700	Peak	36.25	-6.90	29.35	46.00	-16.65
725.490	Peak	35.32	-3.06	32.26	46.00	-13.74

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2440 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
87.230	Peak	48.04	-19.65	28.39	40.00	-11.61
96.930	Peak	48.34	-18.41	29.92	43.50	-13.58
174.530	Peak	41.22	-14.22	27.00	43.50	-16.50
245.340	Peak	48.03	-14.35	33.68	46.00	-12.32
725.490	Peak	35.94	-3.06	32.88	46.00	-13.12
774.960	Peak	35.46	-1.33	34.13	46.00	-11.87

2nd

Report Number	:TERF2310002706E2	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-12-08
Test Frequency	:2440 MHz	Temp./Humi.	:20.2℃/70%
Test Mode	:Tx	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
33.880	Peak	52.11	-17.51	34.60	40.00	-5.40
62.010	Peak	52.01	-17.52	34.49	40.00	-5.51
68.800	Peak	43.23	-18.58	24.65	40.00	-15.35
163.860	Peak	35.35	-16.56	18.79	43.50	-24.71
218.180	Peak	38.38	-19.58	18.80	46.00	-27.20
744.890	Peak	37.52	-5.23	32.29	46.00	-13.71

Report Number	:TERF2310002706E2	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-12-08
Test Frequency	:2440 MHz	Temp./Humi.	:20.2℃/70%
Test Mode	:Tx	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
33.880	Peak	47.12	-17.51	29.61	40.00	-10.39
122.150	Peak	37.05	-18.28	18.77	43.50	-24.73
218.180	Peak	41.68	-19.58	22.10	46.00	-23.90
399.570	Peak	34.97	-12.71	22.26	46.00	-23.74
735.190	Peak	40.47	-5.88	34.59	46.00	-11.41
743.920	Peak	43.21	-5.26	37.95	46.00	-8.05

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2402 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4804.000	Average	40.75	3.31	44.06	54.00	-9.94
4804.000	Peak	44.13	3.31	47.44	74.00	-26.56
7206.000	Average	25.35	9.14	34.49	54.00	-19.51
7206.000	Peak	36.97	9.14	46.11	74.00	-27.89

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2402 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4804.000	Average	37.72	3.31	41.03	54.00	-12.97
4804.000	Peak	42.14	3.31	45.45	74.00	-28.55
7206.000	Average	26.04	9.14	35.18	54.00	-18.82
7206.000	Peak	35.61	9.14	44.75	74.00	-29.25

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2440 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4880.000	Average	38.10	3.28	41.38	54.00	-12.62
4880.000	Peak	42.32	3.28	45.60	74.00	-28.40
7320.000	Average	25.50	10.24	35.74	54.00	-18.26
7320.000	Peak	35.43	10.24	45.67	74.00	-28.33

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2440 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4880.000	Average	34.26	3.28	37.54	54.00	-16.46
4880.000	Peak	41.00	3.28	44.28	74.00	-29.72
7320.000	Average	26.08	10.24	36.32	54.00	-17.68
7320.000	Peak	36.60	10.24	46.84	74.00	-27.16

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2480 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Vertical
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4960.000	Average	38.72	3.42	42.14	54.00	-11.86
4960.000	Peak	43.05	3.42	46.47	74.00	-27.53
7440.000	Average	25.20	10.20	35.40	54.00	-18.60
7440.000	Peak	35.46	10.20	45.66	74.00	-28.34

Report Number	:TERF2310002706	Test Site	:SAC C
Operation Mode	:BLE 1M	Test Date	:2023-10-31
Test Frequency	:2480 MHz	Temp./Humi.	:20.9℃/61%
Test Mode	:Tx	Antenna Pol.	:Horizontal
EUT Pol	:H Plane	Engineer	:Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4960.000	Average	37.08	3.42	40.50	54.00	-13.50
4960.000	Peak	42.03	3.42	45.46	74.00	-28.54
7440.000	Average	26.91	10.20	37.11	54.00	-16.89
7440.000	Peak	36.29	10.20	46.49	74.00	-27.51

12 POWER SPECTRAL DENSITY

12.1 Standard Applicable:

Per Part 15.247 (e) & RSS-247 section 5.2 b

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

12.2 Test Setup



12.3 Measurement Procedure:

1. Set analyzer center frequency to DTS channel center frequency.
2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW = 3 kHz. & the VBW = 10 kHz
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.

12.4 Measurement Result:

BLE 1M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	4.10	8	PASS
2440	4.30	8	PASS
2480	4.02	8	PASS

**Note:*

1.cable loss as 10.8 dB that offsets in the spectrum

PSD_BLE 1M_LowCH00-2402MHz



PSD_BLE 1M_HighCH39-2480MHz



PSD_BLE 1M_MidCH19-2440MHz



13 ANTENNA REQUIREMENT

13.1 Standard Applicable:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

13.2 Antenna Connected Construction:

The antenna complies with this requirement and no consideration of replacement. Please see EUT photo for details.

~ End of Report ~