


63.5*32.1±0.2mm, 4R

文字转曲（供应商来料效果）

注：S/N码由工厂打印至33*7mm空白标贴(7210500094)
空白标贴后黏贴至指定条码框上，MAC码由工厂直接打印在标贴上。
MAC条码由“XXXXXXXXXXXX”生成，
文本打印为“XX-XX-XX-XX-XX-XX”。



卷装供货：
边距&跳距=3mm

普联技术有限公司 TP-LINK TECHNOLOGIES CO., LTD.					
名 称	EAP245(EU/US) 3.0_产品规格标贴	颜 色	logo	白色	
版 本	A2		底色	TP底壳灰	
材 质	80g艾利铜版纸+雾膜		文字	白色	
模 具	海浪改-206		其它	白色	
机型版本号	EAP 245(EU/US) 3.0	审 核	结构工程师		
设 计	梁敏		硬件工程师		
完成日期	2018-05-09		产品工程师		
记 录 与上一版的区别			平面负责人		



Omada

EAP245

AC1750 Wireless MU-MIMO

Gigabit Ceiling Mount Access Point

Model: EAP245

Power: 48V $\approx$ 0.5A Passive PoE

PoE: 36-57V $\approx$ 0.36A 802.3af

Default Access: <http://tplinkeap.net>

Username: admin Password: admin

MADE IN CHINA

FC

EAC

RoHS

5734

CE

CE

FCC ID: TE7EAP245V3

for indoor use only

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Building 24 (floors 1, 3, 4, 5), and 28 (floors 1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

TP-Link Technologies Co., Ltd.