



EMC TEST REPORT

Applicant Huawei Technologies Co., Ltd.
FCC ID QISCRS-B19S
Product Smart Band
Model CRS-B19S
Report No. R1904H0083-E1
Issue Date May 13, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2018)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Liu

Guangchang Fan

Performed by: Wei Liu/ Manager

Approved by: Guangchang Fan/ Director

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report.....	4
1.2	Test facility.....	4
1.3	Testing Location.....	5
2	General Description of Equipment under Test.....	6
2.1	Client Information.....	6
2.2	General information.....	6
2.3	Applied Standards.....	7
2.4	Test Mode.....	8
3	Test Case Results	9
3.1	Radiated Emission	9
3.2	Conducted Emission	16
4	Main Test Instrument.....	19



Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Test Date: April 25, 2019 ~May 7, 2019			

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2 General Description of Equipment under Test

2.1 Client Information

Applicant	Huawei Technologies Co., Ltd.
Applicant address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.China.
Manufacturer	Huawei Technologies Co., Ltd.
Manufacturer address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.China.

2.2 General information

EUT Description			
Device Type:	Portable Device		
Model:	CRS-B19S		
SN:	7460FA595096		
HW Version:	EB1CRIUSM		
SW Version:	1.0.0.1		
Antenna Type:	Internal Antenna		
Frequency:	Band	Tx (MHz)	Rx (MHz)
	Bluetooth:	2402 ~ 2480	2402 ~ 2480
Modulation:	Bluetooth v4.2 LE: GFSK		
EUT Accessory			
Battery	Manufacturer: Tianjin lishen battery joint-stock.,LTD. Model: HB351329ECW		
USB Cable	Manufacturer: Huawei Technologies Co., Ltd. Description : 5V 1A		
Charge dock	Manufacturer: Huawei Technologies Co., Ltd. Name: AF33-1 Description : 5V 1A		
Auxiliary test equipment			
PC	PC Manufacturer: Microsoft Corporation Model: L20170076		
Note: The information of the EUT is declared by the manufacturer.			



2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2018)

ANSI C63.4 (2014)

2.4 Test Mode

Test Mode for RE	
Mode 1:	USB power (EUT with PC) +Idle
Mode 2:	USB Copy power(EUT with PC) + work via phone monitor
Mode 3:	EUT+Idle
Mode 4:	EUT+work

During the test, the preliminary test was performed in all modes, mode 2 is selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Test Mode for CE	
Mode 1:	USB power(EUT with PC) +Idle
Mode 2:	USB power(EUT with PC) +work via phone monitor

During the test, the preliminary test was performed in all modes, mode 2 is selected as the worst condition. The test data of the worst-case condition was recorded in this report.

3 Test Case Results

3.1 Radiated Emission

Ambient condition

Temperature	Relative humidity	Pressure
24°C~26°C	45%~50%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=1MHz / VBW=3MHz/ Sweep=AUTO


(b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.


During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC;

Test Setup

Below 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits

Frequency (MHz)	Field Strength (dBμV/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
30MHz~200MHz	4.02 dB
200MHz~1000MHz	3.28 dB
1GHz~18GHz	3.70 dB
18GHz~26.5GHz	5.78 dB
26.5GHz~40GHz	5.82 dB


Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier, the Emissions in the frequency band 18GHz- 40GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software.

For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

RE 30M-1GHz QP




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
31.375416	18.3	100.0	V	84.0	-3.1	21.7	40.0
58.518431	15.0	120.0	V	339.0	-8.1	25.0	40.0
247.776750	27.1	120.0	H	338.0	-10.9	18.9	46.0
258.711000	29.6	100.0	H	162.0	-10.9	16.4	46.0
384.010000	34.6	100.0	H	182.0	-5.9	11.4	46.0
470.856250	17.6	125.0	V	0.0	-6.2	28.4	46.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Note: The signal beyond the limit is carrier.

Radiated Emission from 1GHz to 3GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1038.750000	35.4	200.0	H	171.0	-11.0	38.6	74.0
1434.500000	36.7	200.0	V	83.0	-8.5	37.3	74.0
1714.500000	37.3	200.0	V	246.0	-7.7	36.7	74.0
1981.250000	38.0	100.0	H	151.0	-6.5	36.0	74.0
2251.000000	38.4	100.0	H	110.0	-5.5	35.6	74.0
2724.750000	52.4	200.0	V	260.0	-3.5	21.6	74.0

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1062.500000	22.7	200.0	H	333.0	-10.8	31.3	54.0
1425.750000	24.0	100.0	V	264.0	-8.6	30.0	54.0
1574.750000	24.5	200.0	H	0.0	-8.1	29.5	54.0
2044.000000	25.8	200.0	H	225.0	-6.3	28.2	54.0
2220.750000	25.3	200.0	H	144.0	-5.6	28.7	54.0
2840.500000	27.4	200.0	H	117.0	-3.1	26.6	54.0




Radiated Emission from 3GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
3181.875000	40.4	200.0	H	330.0	-1.6	33.6	74.0
3978.750000	42.1	200.0	H	0.0	1.3	31.9	74.0
5154.375000	44.9	200.0	V	70.0	4.1	29.1	74.0
6870.000000	48.5	200.0	H	0.0	7.7	25.5	74.0
9121.875000	51.8	200.0	H	233.0	13.5	22.2	74.0
13329.375000	52.9	200.0	H	148.0	14.5	21.1	74.0


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
3170.625000	28.1	200.0	H	120.0	-1.7	25.9	54.0
4010.625000	30.3	200.0	H	0.0	1.4	23.7	54.0
5186.250000	32.7	200.0	H	34.0	4.3	21.3	54.0
6840.000000	36.1	100.0	V	260.0	7.6	17.9	54.0
9082.500000	39.3	100.0	V	287.0	13.3	14.7	54.0
13293.750000	40.5	100.0	V	274.0	14.5	13.5	54.0

RE 18-26.5GHz PK+AV



Radiated Emission from 18GHz to 26.5GHz

RE 26.5-40GHz PK+AV



Radiated Emission from 26.5GHz to 40GHz

3.2 Conducted Emission

Ambient condition


Temperature	Relative humidity	Pressure
24°C ~26°C	50%~55%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC;

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50


*: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 2.57$ dB.


Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.16	---	35.16	55.40	20.24	1000.0	9.000	L1	ON	19.13
0.19	49.03	---	64.11	15.08	1000.0	9.000	L1	ON	19.17
0.37	30.49	---	58.54	28.05	1000.0	9.000	L1	ON	19.20
0.79	---	20.89	46.00	25.11	1000.0	9.000	L1	ON	19.24
0.99	---	21.01	46.00	24.99	1000.0	9.000	L1	ON	19.24
1.19	26.27	---	56.00	29.73	1000.0	9.000	L1	ON	19.23
3.17	27.71	---	56.00	28.29	1000.0	9.000	L1	ON	19.08
3.17	---	25.95	46.00	20.05	1000.0	9.000	L1	ON	19.08
6.81	---	23.93	50.00	26.07	1000.0	9.000	L1	ON	19.15
12.18	28.75	---	60.00	31.25	1000.0	9.000	L1	ON	19.41
15.78	34.59	---	60.00	25.41	1000.0	9.000	L1	ON	19.42
15.93	---	23.54	50.00	26.46	1000.0	9.000	L1	ON	19.44

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.16	---	35.69	55.63	19.94	1000.0	9.000	N	ON	19.11
0.19	48.11	---	64.11	16.00	1000.0	9.000	N	ON	19.18
0.36	29.03	---	58.64	29.61	1000.0	9.000	N	ON	19.19
0.80	---	20.07	46.00	25.93	1000.0	9.000	N	ON	19.24
0.99	---	21.86	46.00	24.14	1000.0	9.000	N	ON	19.24
1.19	28.84	---	56.00	27.16	1000.0	9.000	N	ON	19.23
3.18	---	27.41	46.00	18.59	1000.0	9.000	N	ON	19.08
4.63	22.06	---	56.00	33.94	1000.0	9.000	N	ON	19.10
6.86	---	22.67	50.00	27.33	1000.0	9.000	N	ON	19.15
12.36	26.67	---	60.00	33.33	1000.0	9.000	N	ON	19.40
15.92	33.54	---	60.00	26.46	1000.0	9.000	N	ON	19.38
16.70	---	24.63	50.00	25.37	1000.0	9.000	N	ON	19.47

Conducted Emission from 150 KHz to 30 MHz

4 Main Test Instrument

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV40	15195-01-00	2018-05-20	2019-05-19
EMI Test Receiver	R&S	ESCI	100948	2018-05-20	2019-05-19
Trilog Antenna	SCHWARZBECK	VULB 9163	9163-201	2017-11-18	2019-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Standard Gain Horn	ETS-Lindgren	3160-09	00102643	2018-06-20	2019-06-19
EMI Test Receiver	R&S	ESR	101667	2018-05-20	2019-05-19
LISN	R&S	ENV216	101171	2016-12-16	2019-12-15
Bore Sight Antenna mast	ETS	2171B	00058752	/	/
Test software	EMC32	R&S	9.26.0	/	/

*****END OF REPORT *****