

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Report Template Version: V04

Report Template Revision Date: 2018-07-06

Telephone: +86-755-26648640 Fax: +86-755-26648637

Website: <u>www.cqa-cert.com</u>

# **Test Report**

**Report No.:** CQASZ20210500031EX-02

Applicant: SHENZHEN POWEROAK NEWENER CO., LTD

Room 701-3, Building B, CADRE Building, Tongsha Road, Nanshan

Address of Applicant:

District, Shenzhen City, Guangdong Province, P.R.China

Manufacturer: SHENZHEN POWEROAK NEWENER CO., LTD

Address of Room 701-3, Building B, CADRE Building, Tongsha Road, Nanshan

Manufacturer: District, Shenzhen City, Guangdong Province, P.R.China

**Equipment Under Test (EUT):** 

**Product:** Portable Power Station

All Model No.: EP500

Test Model No.: EP500

Brand Name: /

FCC ID: 2AYT3-EP500

Standards: 47 CFR FCC Part 15 Subpart C 15.247

**Date of Test:** May 25, 2021 – Jun. 10, 2021

Date of Issue: Jun. 10, 2021

Test Result: PASS\*

Tested By:

(Lewis Zhou)

Reviewed By:

(Timo Lei)

Sheek Luc

(Sheek Luo)

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.





# 1 Version

# **Revision History Of Report**

Report No.	Version	Description	Issue Date
CQASZ20210500031EX-02	Rev.01	Initial report	Jun. 10, 2021



# 2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

N/A: Not Applicable



# 3 Contents

			Page
1	VE	ERSION	
2		EST SUMMARY	
		ONTENTS	
3			
4	GI	ENERAL INFORMATION	5
	4.1	CLIENT INFORMATION	
	4.2	GENERAL DESCRIPTION OF EUT	
	4.3	ADDITIONAL INSTRUCTIONS.	
	4.4	TEST ENVIRONMENT	
	4.5 4.6	DESCRIPTION OF SUPPORT UNITS	
	4.7	TEST LOCATION	
	4.8	TEST FACILITY	
	4.9	ABNORMALITIES FROM STANDARD CONDITIONS.	
	4.10	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	4.11	EQUIPMENT LIST	11
5	TE	EST RESULTS AND MEASUREMENT DATA	12
	5.1	Antenna Requirement	
	5.2	CONDUCTED EMISSIONS	13
	5.3	CONDUCTED PEAK OUTPUT POWER	
	5.4	20DB OCCUPY BANDWIDTH	
	5.5	CARRIER FREQUENCIES SEPARATION	
	5.6 5.7	HOPPING CHANNEL NUMBER	
	5.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS.	
	5.9	SPURIOUS RF CONDUCTED EMISSIONS	
	5.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	5.11	RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	61
		11.1 Radiated Emission below 1GHz	
		11.2 Transmitter Emission above 1GHz	
6		HOTOGRAPHS - EUT TEST SETUP	
7	PH	HOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	69



Report No.: CQASZ20210500031EX-02

# 4 General Information

### 4.1 Client Information

Applicant:	SHENZHEN POWEROAK NEWENER CO., LTD
Address of Applicant:	Room 701-3, Building B, CADRE Building, Tongsha Road, Nanshan District, Shenzhen City, Guangdong Province, P.R.China
Manufacturer:	SHENZHEN POWEROAK NEWENER CO., LTD
Address of Manufacturer:	Room 701-3, Building B, CADRE Building, Tongsha Road, Nanshan District, Shenzhen City, Guangdong Province, P.R.China

# 4.2 General Description of EUT

Product Name:	Portable Power Station
Test Model No.:	EP500
Trade Mark:	/
Hardware Version:	V1.0
Software Version:	
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	BT-V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Antenna Type:	Chip antenna
Antenna Gain	0dBi
Power Supply:	DC 51.2V from battery 5120Wh 100Ah  Input: 100-120VAC 50/60Hz 15A max DC55-145VDC 20AMAX  Output: AC*4: 100-120VAC 50/60Hz, 2000W Total     Aviation Sockets*1: 12VDC, 30A     USB-A*1: 5VDC, 2A,     USB-A*1: 5VDC, 1A,     USB-A*2: 5VDC, 2A, 9VDC, 2A, 12VDC 1.5A     USB-C*1: 5V-15VDC 3A 20VDC 5A     Cigarette lighter*1: 12VDC, 10A     DC 5521*2: 12VDC, 10A     Wireless Charging*2: 5/7.5/10/15W Total

Note: 1. This report is only for BT

2. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



Report No.: CQASZ20210500031EX-02

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: CQASZ20210500031EX-02

# 4.3 Additional Instructions

EUT Test Software Settings:				
Mode:	☐ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *!*!3646633!*!*			
EUT Power level:	Class2 (Power level is built-in set para selected)	Class2 (Power level is built-in set parameters and cannot be changed and selected)		
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.				
Mode	Channel	Frequency(MHz)		
	CH0	2402		
DH1/DH3/DH5	CH39	2441		
	CH78	2480		
	CH0	2402		
2DH1/2DH3/2DH5	CH39	2441		
	CH78	2480		



Report No.: CQASZ20210500031EX-02

### **4.4** Test Environment

Operating Environment	Operating Environment:		
Temperature:	25.0 °C		
Humidity:	53 % RH		
Atmospheric Pressure:	995mbar		
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		

# 4.5 Description of Support Units

The EUT has been tested with associated equipment below.

The Let The Seen tested With description against Selevi.					
Description	Manufacturer	Model No.	Remark	FCC certification	
/	/	/	1	1	





### 4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10 <sup>-8</sup>	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

<sup>(1)</sup>This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Report No.: CQASZ20210500031EX-02

### 4.7 Test Location

#### Shenzhen Huaxia Testing Technology Co., Ltd,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

### 4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L5785)

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 4742.01)

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

#### • FCC Registration No.: 522263

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

#### 4.9 Abnormalities from Standard Conditions

None.

#### 4.10 Other Information Requested by the Customer

None.





# 4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/10/25	2021/10/24
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/25	2021/10/24
EXA spectrum alalyzer	Keysight	N9010A	CQA-106	2020/9/26	2021/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29- 20P	CQA-036	2020/10/25	2021/10/24
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2020/10/21	2020/10/20
Bilog Antenna	R&S	HL562	CQA-011	2020/9/26	2021/9/25
Horn Antenna	R&S	HF906	CQA-012	2020/9/26	2021/9/25
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2020/9/25	2021/9/24
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2020/9/26	2021/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2020/9/26	2021/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/26	2021/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/26	2021/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/26	2021/9/25
EMI Test Receiver	R&S	ESR7	CQA-005	2020/10/25	2021/10/24
LISN	R&S	ENV216	CQA-003	2020/10/23	2021/10/22
Coaxial cable	CQA	N/A	CQA-C009	2020/9/26	2021/9/25

#### Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.





### 5 Test results and Measurement Data

### 5.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is chip antenna. The best case gain of the antenna is 0 dBi.





# **5.2** Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	: 150kHz to 30MHz					
Limit:	Fraguency range (MHz)	Limit (dBuV)				
	Frequency range (MHz)	Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	5-30	60	50			
	* Decreases with the logarithn					
Test Procedure:	<ol> <li>* Decreases with the logarithm of the frequency.</li> <li>The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50µH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>In order to find the maximum emission, the relative positions of</li> </ol>					
Test Setup:	ANSI C63.10: 2013 on con	iducted measurement.				
rest octup.	Shielding Room  EUT  AC Mains	AE  LISN2 AC MAN  Ground Reference Plane	Test Receiver			




Report No.: CQASZ20210500031EX-02

Exploratory Test Mode:	: Non-hopping transmitting mode with all kind of modulation and all kind of		
	data type at the lowest, middle, high channel.		
Final Test Mode:	Through Pre-scan, find the DH5 of data type at the mid channel is the worst case.		
	Only the worst case is recorded in the report.		
Test Voltage:	AC120V/60Hz		
Test Results:	Pass		

#### **Measurement Data**


#### Live Line:



#### Remark:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
- 3. If the Peak value under Average limit, the Average value is not recorded in the report.

#### **Neutral Line:**




	Mk.	Freq.	Level	Factor	ment	Limit	Over			
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1		0.1620	55.29	-0.13	55.16	65.36	-10.20	QP		
2	*	0.1620	45.53	-0.13	45.40	55.36	-9.96	AVG		
3		0.2340	49.10	-0.12	48.98	62.30	-13.32	QP		
4		0.2420	37.71	-0.11	37.60	52.02	-14.42	AVG		
5		0.7260	24.64	-0.06	24.58	46.00	-21.42	AVG		
6		0.7340	40.64	-0.06	40.58	56.00	-15.42	QP		
7		1.5020	36.95	-0.19	36.76	56.00	-19.24	QP		
8		1.5420	22.95	-0.19	22.76	46.00	-23.24	AVG		
9		2.9300	36.58	-0.18	36.40	56.00	-19.60	QP		
10		3.1700	24.41	-0.18	24.23	46.00	-21.77	AVG		
11		7.1020	37.21	-0.28	36.93	60.00	-23.07	QP		
12		7.2620	24.23	-0.28	23.95	50.00	-26.05	AVG		

#### Remark:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
- 3. If the Peak value under Average limit, the Average value is not recorded in the report.



### **5.3** Conducted Peak Output Power






Report No.: CQASZ20210500031EX-02

### **Measurement Data**


GFSK mode							
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	4.865	30.00	Pass				
Middle	6.037	30.00	Pass				
Highest	4.655	30.00	Pass				
	π/4DQPSK m	ode					
Test channel	Test channel Peak Output Power (dBm)		Result				
Lowest	3.907	30.00	Pass				
Middle	5.339	30.00	Pass				
Highest	3.929	30.00	Pass				
	8DPSK mode						
Test channel	Test channel Peak Output Power (dBm)		Result				
Lowest	4.079	30.00	Pass				
Middle	5.434	30.00	Pass				
Highest 4.109		30.00	Pass				





















### 5.4 20dB Occupy Bandwidth




#### **Measurement Data**

Toot showned	20dB Occupy Bandwidth (MHz)				
Test channel	GFSK	π/4DQPSK	8DPSK		
Lowest	1.029	1.295	1.294		
Middle	1.028	1.317	1.312		
Highest	1.038	1.310	1.296		





### Test plot as follows:















# 5.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)						
Test Method:	ANSI C63.10:2013						
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane						
	Remark: Offset=Cable loss+ attenuation factor.						
Limit:	2/3 of the 20dB bandwidth						
	Remark: the transmission power is less than 0.125W.						
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type						
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.						
Test Results:	Pass						




Modulation	Channel	Channel Separation (MHz)	Limit(MHz)	Result
	CH00			Pass
	CH01	1.001		
GFSK	CH39		25KHz or 2/3*20dB	
OI OIL	CH40	1.318	bandwidth	
	CH77	4.000	.003	
	CH78	1.003		
	CH00		25KHz or 2/3*20dB bandwidth	B Pass
pi/4DQPSK	CH01	0.996		
	CH39	1.318		
	CH40			
	CH77			
	CH78	0.688	0.688	
	CH00			D
8DPSK	CH01	0.996		
	CH39	1.005	25KHz or 2/3*20dB	
	CH40		bandwidth	Pass
	CH77	1.007		
	CH78			




Test plot as follows:














Report No.: CQASZ20210500031EX-02

### **5.6** Hopping Channel Number




#### **Measurement Data**

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15




#### Test plot as follows:







### 5.7 Dwell Time







#### **Measurement Data**

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time[ms]	Limit (second)
GFSK	DH1	LCH	0.3794	121.408	≤0.4
GFSK	DH1	MCH	0.3826	122.432	≤0.4
GFSK	DH1	НСН	0.3809	121.888	≤0.4
GFSK	DH3	LCH	1.639	262.240	≤0.4
GFSK	DH3	MCH	1.638	262.080	≤0.4
GFSK	DH3	нсн	1.639	262.240	≤0.4
GFSK	DH5	LCH	2.889	308.160	≤0.4
GFSK	DH5	MCH	2.884	307.627	≤0.4
GFSK	DH5	НСН	2.888	308.053	≤0.4
π/4DQPSK	2DH1	LCH	0.3890	124.480	≤0.4
π/4DQPSK	2DH1	MCH	0.3909	125.088	≤0.4
π/4DQPSK	2DH1	НСН	0.3889	124.448	≤0.4
π/4DQPSK	2DH3	LCH	1.644	263.040	≤0.4
π/4DQPSK	2DH3	MCH	1.643	262.880	≤0.4
π/4DQPSK	2DH3	нсн	1.641	262.560	≤0.4
π/4DQPSK	2DH5	LCH	2.888	308.053	≤0.4
π/4DQPSK	2DH5	MCH	2.889	308.160	≤0.4
π/4DQPSK	2DH5	нсн	2.888	308.053	≤0.4
8DPSK	3DH1	LCH	0.3888	124.416	≤0.4
8DPSK	3DH1	MCH	0.3932	125.824	≤0.4
8DPSK	3DH1	НСН	0.3900	124.800	≤0.4
8DPSK	3DH3	LCH	1.234	197.440	≤0.4
8DPSK	3DH3	MCH	1.640	262.400	≤0.4
8DPSK	3DH3	НСН	1.639	262.240	≤0.4
8DPSK	3DH5	LCH	2.893	308.587	≤0.4
8DPSK	3DH5	MCH	2.890	308.267	≤0.4
8DPSK	3DH5	НСН	2.891	308.373	≤0.4

### Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)\*(1600/ (2\*79))\*31.6

DH3/2DH3/3DH3 Dwell time = Burst Width (ms)\*(1600/ (4\*79))\*31.6

DH5/2DH5/3DH5 Dwell time = Burst Width (ms)\*(1600/ (6\*79))\*31.6

















































# 5.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table
	Ground Reference Plane
	Remark: Offset=cable loss+ attenuation factor.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of π/4DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.  Only the worst case is recorded in the report.
Test Results:	Pass
Test Results:	Pass




#### Test plot as follows:
























# **5.9** Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark: Offset=cable loss+ attenuation factor.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass



























Report No.: CQASZ20210500031EX-02

#### Remark

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: CQASZ20210500031EX-02

### 5.10 Other requirements Frequency Hopping Spread Spectrum System

#### Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

#### Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence: 29 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

#### Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.



Report No.: CQASZ20210500031EX-02

#### Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.




Report No.: CQASZ20210500031EX-02

# 5.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2013						
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)						
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark	
	0.009MHz-0.090MH	z	Peak	10kHz	z 30kHz	Peak	
	0.009MHz-0.090MH	z	Average	10kHz	z 30kHz	Average	
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	0.110MHz-0.490MH	z	Peak	10kHz	z 30kHz	Peak	
	0.110MHz-0.490MH	z	Average	10kHz	z 30kHz	Average	
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	30MHz-1GHz		Peak	100 kH	lz 300kHz	Peak	
	Above 1GHz		Peak	1MHz	3MHz	Peak	
	Above 1GHZ		Peak	1MHz	10Hz	Average	
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measuremen distance (m)	- 11
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300	
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30	
	1.705MHz-30MHz		30	-	-	30	
	30MHz-88MHz		100	40.0	Quasi-peak	3	
	88MHz-216MHz		150	43.5	Quasi-peak	3	
	216MHz-960MHz		200	46.0	Quasi-peak	3	
	960MHz-1GHz		500	54.0	Quasi-peak	3	
	Above 1GHz	500	54.0	Average	3		
	Note: 15.35(b), Unless emissions is 20dE applicable to the peak emission lev	3 ab equi	ove the maxim	num perm est. This p	itted average	emission limit	



Report No.: CQASZ20210500031EX-02



Antenna Tower

Artenna Fower

Ground Reference Plane

Test Receiver

Test Receiver

Controller




Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz

#### Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

Note: For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.




	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
	<ul> <li>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> </ul>
	i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the GFSK modulation is the worst case.
	Pretest the EUT at GFSK Transmitting mode, middle-channel mode is worse
	Case
	Only the GFSK-mid channel mode is recorded in the report.
Test Results:	Pass



Report No.: CQASZ20210500031EX-02

#### 5.11.1 Radiated Emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



No.	Mk.	Freq.	Reading Level	Correct	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.0000	41.20	-7.51	33.69	40.00	-6.31	QP			
2	į	48.8429	51.68	-16.39	35.29	40.00	-4.71	QP			
3	*	67,2022	54.36	-17.95	36.41	40.00	-3.59	QP			
4		152.6639	51.83	-15.13	36.70	43.50	-6.80	QP			
5		234.1682	55.09	-16.56	38.53	46.00	-7.47	QP			
6		813.1114	32.54	6.31	38.85	46.00	-7.15	QP			

#### Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Factor = Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.



Report No.: CQASZ20210500031EX-02



#### Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor = Antenna Factor + Cable Factor - Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.



# 5.11.2 Transmitter Emission above 1GHz

Worse case	mode:	GFSK(DH	5)	Test chann	el:	Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
2390	61.16	-9.2	51.96	74	-26.49	Peak	н
2400	60.62	-9.39	51.23	74	-22.34	Peak	Н
4804	57.72	-4.33	53.39	74	-25.21	Peak	Н
7206	48.42	1.01	49.43	74	-18.55	Peak	Н
2390	60.50	-9.2	51.30	74	-29.06	Peak	V
2400	60.43	-9.39	51.04	74	-22.20	Peak	V
4804	57.60	-4.33	53.27	74	-24.25	Peak	V
7206	47.33	1.01	48.34	74	-19.90	Peak	V

Worse case	mode:	GFSK(DH	5)	Test chann	el:	Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
4882	58.76	-4.11	54.65	74	-24.22	peak	Н
7323	61.27	1.51	62.78	74	-24.46	peak	Н
4882	57.81	-4.11	53.70	74	-27.26	peak	<b>V</b>
7323	50.43	1.51	51.94	74	-19.74	peak	V

Worse case	mode:	GFSK(DH5	5)	Test chann	el:	Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
2483.5	60.32	-9.29	51.03	74	-25.05	Peak	н
4960	60.14	-4.04	56.10	74	-23.55	Peak	Н
7440	58.76	1.57	60.33	74	-20.32	Peak	Н
2483.5	49.06	-9.29	39.77	74	-18.99	Peak	V
4960	60.27	-4.04	56.23	74	-27.68	Peak	V
7440	61.85	1.57	63.42	74	-23.25	Peak	V



Report No.: CQASZ20210500031EX-02

Worse case	mode:	π/4DQPSk	( (2DH5)	Test chann	el:	Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
2390	60.30	-9.2	51.10	74	-22.29	Peak	н
2400	61.99	-9.39	52.60	74	-24.61	Peak	Н
4804	59.57	-4.33	55.24	74	-23.63	Peak	Н
7206	48.21	1.01	49.22	74	-19.27	Peak	Н
2390	58.33	-9.2	49.13	74	-26.99	Peak	V
2400	61.64	-9.39	52.25	74	-22.99	Peak	V
4804	58.73	-4.33	54.40	74	-24.78	Peak	V
7206	47.27	1.01	48.28	74	-19.70	Peak	V

Worse case	mode:	π/4DQPSk	(2DH5)	Test chann	el:	Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
4882	59.48	-4.11	55.37	74	-23.69	peak	Н
7323	60.66	1.51	62.17	74	-21.90	peak	Н
4882	59.41	-4.11	55.30	74	-23.58	peak	V
7323	50.39	1.51	51.90	74	-20.01	peak	V

Worse case	mode:	π/4DQPSk	(2DH5)	Test chann	el:	Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V
2483.5	60.47	-9.29	51.18	74	-23.41	Peak	Н
4960	59.67	-4.04	55.63	74	-23.01	Peak	Н
7440	58.69	1.57	60.26	74	-23.91	Peak	Н
2483.5	49.38	-9.29	40.09	74	-20.83	Peak	V
4960	59.09	-4.04	55.05	74	-28.86	Peak	V
7440	62.31	1.57	63.88	74	-21.73	Peak	V

#### Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
  - Final Test Level =Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.





# 6 Photographs - EUT Test Setup

Please refer to test setup file



# 7 Photographs - EUT Constructional Details

Please refer to the report No.: CQASZ20210500031EX-03

THE END