

## TEST REPORT

**Product** : Smart Sleep Light  
**Trade mark** : N/A  
**Model/Type reference** : TEW201  
**Serial Number** : N/A  
**Report Number** : EED32K00287203  
**FCC ID** : 2ADIOTEW201  
**Date of Issue** : Nov. 09, 2018  
**Test Standards** : 47 CFR Part 15 Subpart C  
**Test result** : PASS

Prepared for:

**Shenzhen Medica Technology Development Co., Ltd.**  
**2F Building A, Tongfang Information Harbor, No.11, East Langshan Road,**  
**Nanshan District, Shenzhen, P.R. China**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Tested by:

Tom-chen

Tom chen (Test Project)

Reviewed by:

Kevin Yang

Kevin yang (Reviewer)

Date:

Nov. 09, 2018

Compiled by:

Max liang

Max liang (Project Engineer)

Approved by:

Sheek Luo

Sheek Luo (Lab supervisor)



Check No.:3096353610

## 2 Version

Version No.	Date	Description
00	Nov. 09, 2018	Original

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013/ KDB 558074 D01v04	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013/ KDB 558074 D01v04	PASS
<b>Power Spectral Density</b>	47 CFR Part 15 Subpart C Section 15.247 (e)	ANSI C63.10-2013/ KDB 558074 D01v04	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013/ KDB 558074 D01v04	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013/ KDB 558074 D01v04	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
<b>Restricted bands around fundamental frequency (Radiated Emission)</b>	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

The tested sample(s) and the sample information are provided by the client.


## 4 Content

<b>1 COVER PAGE</b>	<b>1</b>
<b>2 VERSION</b>	<b>2</b>
<b>3 TEST SUMMARY</b>	<b>3</b>
<b>4 CONTENT</b>	<b>4</b>
<b>5 TEST REQUIREMENT</b>	<b>5</b>
5.1 TEST SETUP	5
5.1.1 For Conducted test setup	5
5.1.2 For Radiated Emissions test setup	5
5.1.3 For Conducted Emissions test setup	6
5.2 TEST ENVIRONMENT	6
5.3 TEST CONDITION	6
<b>6 GENERAL INFORMATION</b>	<b>7</b>
6.1 CLIENT INFORMATION	7
6.2 GENERAL DESCRIPTION OF EUT	7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	7
6.4 DESCRIPTION OF SUPPORT UNITS	7
6.5 TEST LOCATION	8
6.6 DEVIATION FROM STANDARDS	8
6.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
6.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
6.9 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, $K=2$ )	8
<b>7 EQUIPMENT LIST</b>	<b>9</b>
<b>8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION</b>	<b>11</b>
Appendix A): Conducted Peak Output Power	12
Appendix B): 6dB Occupied Bandwidth	16
Appendix C): Band-edge for RF Conducted Emissions	20
Appendix D): RF Conducted Spurious Emissions	23
Appendix E): Power Spectral Density	32
Appendix F): Antenna Requirement	36
Appendix G): AC Power Line Conducted Emission	37
Appendix H): Restricted bands around fundamental frequency (Radiated)	40
Appendix I): Radiated Spurious Emissions	54
<b>PHOTOGRAPHS OF TEST SETUP</b>	<b>62</b>
<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	<b>64</b>

## 5 Test Requirement

### 5.1 Test setup

#### 5.1.1 For Conducted test setup



#### 5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz



### 5.1.3 For Conducted Emissions test setup

#### Conducted Emissions setup



## 5.2 Test Environment

Operating Environment:	
Temperature:	22°C
Humidity:	58% RH
Atmospheric Pressure:	1010mbar

## 5.3 Test Condition

Test channel:

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11b/g/n(HT20)	2412MHz ~2462MHz	Channel 1	Channel 6	Channel11
		2412MHz	2437MHz	2462MHz
TX mode:	The EUT transmitted the continuous signal at the specific channel(s).			

Test mode:

Pre-scan under all rate at lowest channel 1

Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power(dBm)	16.12	16.74	16.88	16.96				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power(dBm)	16.06	16.01	15.87	15.41	15.30	15.21	15.00	14.98
Mode	802.11n (HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power(dBm)	15.36	15.22	15.14	15.01	14.97	14.87	14.33	14.21

Through Pre-scan, 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).

## 6 General Information

### 6.1 Client Information

Applicant:	Shenzhen Medica Technology Development Co., Ltd.
Address of Applicant:	2F Building A, Tongfang Information Harbor, No.11, East Langshan Road, Nanshan District, Shenzhen, P.R. China
Manufacturer:	Shenzhen Medica Technology Development Co., Ltd.
Address of Manufacturer:	2F Building A, Tongfang Information Harbor, No.11, East Langshan Road, Nanshan District, Shenzhen, P.R. China
Factory:	E-safe Technology Limited
Address of Factory:	Room 210, Block B, Baoyuan huafeng Economic Building, Xixiang Avenue, Bao'an District, Shenzhen, Guangdong, China

### 6.2 General Description of EUT

Product Name:	Smart Sleep Light
Model No.(EUT):	TEW201
Trade mark:	N/A
EUT Supports Radios application:	BT: 4.0 BT Dual mode, 2402MHz to 2480MHz WiFi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Power Supply:	Model: NLB100120W1A5S95 Input: 100-240V~50/60Hz, 0.35A Max Output: 12V---1A
Sample Received Date:	Oct. 25, 2018
Sample tested Date:	Oct. 25, 2018 to Nov. 09, 2018

### 6.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channel
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM,QPSK,BPSK)
Test Power Grade:	N/A
Test Software of EUT:	N/A
Firmware version:	V0.51(manufacturer declare)
Hardware version:	V1.0(manufacturer declare)
Antenna Type:	PCB Antenna
Antenna Gain:	2.5dBi
Test Voltage:	AC 120V, 60Hz

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

### 6.4 Description of Support Units

The EUT has been tested independently.

## 6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax: +86 (0) 755 3368 3385

No tests were sub-contracted.

CNAS-Lab Code: L1910

A2LA-Lab Cert. No. 3061.01

FCC Designation No.: CN1164

## 6.6 Deviation from Standards

None.

## 6.7 Abnormalities from Standard Conditions

None.

## 6.8 Other Information Requested by the Customer

None.

## 6.9 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	$7.9 \times 10^{-8}$
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%



## 7 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Signal Generator	Keysight	E8257D	MY53401106	03-13-2018	03-12-2019
Spectrum Analyzer	Keysight	N9010A	MY54510339	03-13-2018	03-12-2019
Signal Generator	Keysight	N5182B	MY53051549	03-13-2018	03-12-2019
High-pass filter	Sinoscite	FL3CX03WG1 8NM12-0398-002	---	01-10-2018	01-09-2019
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	---	01-10-2018	01-09-2019
DC Power	Keysight	E3642A	MY54426035	03-13-2018	03-12-2019
PC-1	Lenovo	R4960d	---	03-13-2018	03-12-2019
BT&WI-FI Automatic control	R&S	OSP120	101374	03-13-2018	03-12-2019
RF control unit	JS Tonscend	JS0806-2	15860006	03-13-2018	03-12-2019
RF control unit	JS Tonscend	JS0806-1	15860004	03-13-2018	03-12-2019
RF control unit	JS Tonscend	JS0806-4	158060007	03-13-2018	03-12-2019
BT&WI-FI Automatic test software	JS Tonscend	JS1120-2	---	03-13-2018	03-12-2019

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	05-25-2018	05-24-2019
Temperature/ Humidity Indicator	Defu	TH128	/	07-02-2018	07-01-2019
Communication test set	Agilent	E5515C	GB47050 534	03-16-2018	03-15-2019
Communication test set	R&S	CMW500	152394	03-16-2018	03-15-2019
LISN	R&S	ENV216	100098	05-10-2018	05-10-2019
LISN	schwarzbeck	NNLK8121	8121-529	05-10-2018	05-10-2019
Voltage Probe	R&S	ESH2-Z3 0299.7810.5 6	100042	06-13-2017	06-11-2020
Current Probe	R&S	EZ-17 816.2063.03	100106	05-30-2018	05-29-2019
ISN	TESEQ	ISN T800	30297	02-06-2018	02-05-2019

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	06-04-2016	06-03-2019
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-401	04-26-2018	04-25-2019
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	07-30-2018	07-29-2019
Microwave Preamplifier	Agilent	8449B	3008A02425	08-21-2018	08-20-2019
Microwave Preamplifier	Tonscend	EMC051845 SE	980380	01-19-2018	01-18-2019
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1869	04-25-2018	04-23-2021
Double ridge horn antenna	A.H.SYSTEM S	SAS-574	6042	06-05-2018	06-04-2021
Pre-amplifier	A.H.SYSTEM S	PAP-1840-60	6041	06-05-2018	06-04-2021
Loop Antenna	ETS	6502	00071730	06-22-2017	06-21-2019
Spectrum Analyzer	R&S	FSP40	100416	05-11-2018	05-10-2019
Receiver	R&S	ESCI	100435	05-25-2018	05-24-2019
Multi device Controller	maturo	NCD/070/1071112	---	01-10-2018	01-09-2019
LISN	schwarzbeck	NNBM8125	81251547	05-11-2018	05-10-2019
LISN	schwarzbeck	NNBM8125	81251548	05-11-2018	05-10-2019
Signal Generator	Agilent	E4438C	MY45095744	03-13-2018	03-12-2019
Signal Generator	Keysight	E8257D	MY53401106	03-13-2018	03-12-2019
Temperature/Humidity Indicator	TAYLOR	1451	1905	05-02-2018	05-01-2019
Communication test set	Agilent	E5515C	GB47050534	03-16-2018	03-15-2019
Cable line	Fulai(7M)	SF106	5219/6A	01-10-2018	01-09-2019
Cable line	Fulai(6M)	SF106	5220/6A	01-10-2018	01-09-2019
Cable line	Fulai(3M)	SF106	5216/6A	01-10-2018	01-09-2019
Cable line	Fulai(3M)	SF106	5217/6A	01-10-2018	01-09-2019
Communication test set	R&S	CMW500	104466	02-05-2018	02-04-2019
High-pass filter	Sinoscite	FL3CX03WG18NM12-0398-002	---	01-10-2018	01-09-2019
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	---	01-10-2018	01-09-2019
band rejection filter	Sinoscite	FL5CX01CA09CL12-0395-001	---	01-10-2018	01-09-2019
band rejection filter	Sinoscite	FL5CX01CA08CL12-0393-001	---	01-10-2018	01-09-2019
band rejection filter	Sinoscite	FL5CX02CA04CL12-0396-002	---	01-10-2018	01-09-2019
band rejection filter	Sinoscite	FL5CX02CA03CL12-0394-001	---	01-10-2018	01-09-2019

## 8 Radio Technical Requirements Specification

### Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

### Test Results List:


Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix A)
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)

## Appendix A): Conducted Peak Output Power




**Result Table**


Mode	Channel	Conducted Peak Output Power [dBm]	Verdict
11B	LCH	16.96	PASS
11B	MCH	17.04	PASS
11B	HCH	17.62	PASS
11G	LCH	16.06	PASS
11G	MCH	16.26	PASS
11G	HCH	15.9	PASS
11N20SISO	LCH	15.36	PASS
11N20SISO	MCH	15.4	PASS
11N20SISO	HCH	14.83	PASS

## Test Graph





11G/LCH	 <p>Keynote Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.412000000 GHz</p> <p>Ref Offset: 19.06 dB</p> <p>Ref: 20.00 dBm</p> <p>Center: 2.412 GHz</p> <p>#Res BW: 1 MHz</p> <p>#VBW: 3 MHz</p> <p>Span: 40 MHz</p> <p>Sweep: 1 ms</p> <p>Channel Power: 16.06 dBm / 20 MHz</p> <p>Power Spectral Density: -56.95 dBm / Hz</p>
11G/MCH	 <p>Keynote Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset: 19.02 dB</p> <p>Ref: 20.00 dBm</p> <p>Center: 2.437 GHz</p> <p>#Res BW: 1 MHz</p> <p>#VBW: 3 MHz</p> <p>Span: 40 MHz</p> <p>Sweep: 1 ms</p> <p>Channel Power: 16.26 dBm / 20 MHz</p> <p>Power Spectral Density: -56.75 dBm / Hz</p>
11G/HCH	 <p>Keynote Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset: 19.06 dB</p> <p>Ref: 20.00 dBm</p> <p>Center: 2.462 GHz</p> <p>#Res BW: 1 MHz</p> <p>#VBW: 3 MHz</p> <p>Span: 40 MHz</p> <p>Sweep: 1 ms</p> <p>Channel Power: 15.90 dBm / 20 MHz</p> <p>Power Spectral Density: -57.12 dBm / Hz</p>

11N20SISO/LCH	 <p>KeySight Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 19.06 dB Ref 20.00 dBm</p> <p>Center 2.412 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power 15.36 dBm / 20 MHz</p> <p>Power Spectral Density -57.65 dBm / Hz</p>
11N20SISO/MCH	 <p>KeySight Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 19.02 dB Ref 20.00 dBm</p> <p>Center 2.437 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power 15.40 dBm / 20 MHz</p> <p>Power Spectral Density -57.61 dBm / Hz</p>
11N20SISO/HCH	 <p>KeySight Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.462000000 GHz</p> <p>Ref Offset 19.06 dB Ref 20.00 dBm</p> <p>Center 2.462 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power 14.83 dBm / 20 MHz</p> <p>Power Spectral Density -58.18 dBm / Hz</p>

## Appendix B): 6dB Occupied Bandwidth




**Result Table**

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	8.076	10.587	PASS
11B	MCH	8.056	10.614	PASS
11B	HCH	10.02	14.368	PASS
11G	LCH	16.32	16.337	PASS
11G	MCH	16.31	16.334	PASS
11G	HCH	16.31	16.345	PASS
11N20SISO	LCH	16.55	17.478	PASS
11N20SISO	MCH	16.64	17.477	PASS
11N20SISO	HCH	16.54	17.488	PASS




## Test Graph





11G/LCH	
11G/MCH	
11G/HCH	




11N20SISO/LCH	
11N20SISO/MCH	
11N20SISO/HCH	


## Appendix C): Band-edge for RF Conducted Emissions

Result Table


Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	5.287	-49.300	-24.71	PASS
11B	HCH	6.023	-48.959	-23.98	PASS
11G	LCH	-2.981	-48.331	-32.98	PASS
11G	HCH	-2.955	-48.723	-32.96	PASS
11N20SISO	LCH	-3.694	-50.117	-33.69	PASS
11N20SISO	HCH	-3.812	-48.930	-33.81	PASS

Test Graph





11N20SISO/HCH






## Appendix D): RF Conducted Spurious Emissions


**Result Table**


Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
11B	LCH	5.885	<Limit	PASS
11B	MCH	5.782	<Limit	PASS
11B	HCH	6.371	<Limit	PASS
11G	LCH	-2.754	<Limit	PASS
11G	MCH	-2.66	<Limit	PASS
11G	HCH	-3.4	<Limit	PASS
11N20SISO	LCH	-3.231	<Limit	PASS
11N20SISO	MCH	-3.374	<Limit	PASS
11N20SISO	HCH	-3.866	<Limit	PASS


**Test Graph**





























## Appendix E): Power Spectral Density


Result Table


Mode	Channel	Power Spectral Density[dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B	LCH	-8.213	8	PASS
11B	MCH	-9.334	8	PASS
11B	HCH	-8.087	8	PASS
11G	LCH	-17.158	8	PASS
11G	MCH	-17.142	8	PASS
11G	HCH	-17.383	8	PASS
11N20SISO	LCH	-18.089	8	PASS
11N20SISO	MCH	-18.134	8	PASS
11N20SISO	HCH	-18.556	8	PASS



## Test Graph





11N20SISO/LCH	 <p>Key: Keysight Spectrum Analyzer - Sweep SA Center Freq 2.41200000 GHz Ref Offset 19.08 dB Ref 10.00 dBm Mkr1 2.405 099 GHz -18.089 dBm Span 24.83 MHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 2.618 s (1001 pts)</p>
11N20SISO/MCH	 <p>Key: Keysight Spectrum Analyzer - Sweep SA Center Freq 2.43700000 GHz Ref Offset 19.02 dB Ref 10.00 dBm Mkr1 2.430 111 GHz -18.134 dBm Span 24.96 MHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 2.632 s (1001 pts)</p>
11N20SISO/HCH	 <p>Key: Keysight Spectrum Analyzer - Sweep SA Center Freq 2.46200000 GHz Ref Offset 19.06 dB Ref 10.00 dBm Mkr1 2.455 103 GHz -18.556 dBm Span 24.81 MHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 2.616 s (1001 pts)</p>



## Appendix F): Antenna Requirement

### 15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 2.5dBi.





## Appendix G): AC Power Line Conducted Emission

Test Procedure:	<p>Test frequency range :150KHz-30MHz</p> <ol style="list-style-type: none"> <li>1)The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3)The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.</li> </ol>															
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dB<math>\mu</math>V)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> <p>* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. NOTE : The lower limit is applicable at the transition frequency</p>		Frequency range (MHz)	Limit (dB $\mu$ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dB $\mu$ V)															
	Quasi-peak	Average														
0.15-0.5	66 to 56*	56 to 46*														
0.5-5	56	46														
5-30	60	50														


### Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:


80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5660	42.40	39.65	29.53	9.84	52.24	49.49	39.37	56.00	46.00	-6.51	-6.63	P	
2	1.0900	35.83	32.11	21.50	9.81	45.64	41.92	31.31	56.00	46.00	-14.08	-14.69	P	
3	1.8260	36.89	33.58	23.25	9.74	46.63	43.32	32.99	56.00	46.00	-12.68	-13.01	P	
4	4.1540	40.10	37.64	23.32	9.72	49.82	47.36	33.04	56.00	46.00	-8.64	-12.96	P	
5	5.8340	35.55	32.69	22.34	9.72	45.27	42.41	32.06	60.00	50.00	-17.59	-17.94	P	
6	19.4100	34.02	31.48	17.19	10.17	44.19	41.65	27.36	60.00	50.00	-18.35	-22.64	P	

Neutral line:

80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5620	36.51	33.21	23.68	9.83	46.34	43.04	33.51	56.00	46.00	-12.96	-12.49	P	
2	1.0940	29.96	26.54	18.50	9.81	39.77	36.35	28.31	56.00	46.00	-19.65	-17.69	P	
3	2.5540	26.06	23.84	17.35	9.72	35.78	33.56	27.07	56.00	46.00	-22.44	-18.93	P	
4	5.1140	29.95	26.58	17.30	9.72	39.67	36.30	27.02	60.00	50.00	-23.70	-22.98	P	
5	8.0140	29.59	26.33	18.12	9.81	39.40	36.14	27.93	60.00	50.00	-23.86	-22.07	P	
6	23.8060	33.55	30.21	11.90	10.18	43.73	40.39	22.08	60.00	50.00	-19.61	-27.92	P	

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

## Appendix H): Restricted bands around fundamental frequency (Radiated)


Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	<p><b>Below 1GHz test procedure as below:</b></p> <ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> </ol> <p><b>Above 1GHz test procedure as below:</b></p> <ol style="list-style-type: none"> <li>Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).</li> <li>Test the EUT in the lowest channel , the Highest channel</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol>				
Limit:	Frequency	Limit (dBμV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	



**Test plot as follows:**

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2480
Remark:	PK		


**Test Graph**



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	46.46	55.46	74.00	18.54	Pass	H	Peak
2	2411.9024	32.28	13.35	-36.61	85.70	94.72	74.00	-20.72	Pass	H	Peak

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2480
Remark:	PK		


**Test Graph**



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	46.95	55.95	74.00	18.05	Pass	V	Peak
2	2413.1977	32.28	13.36	-36.61	83.00	92.03	74.00	-18.03	Pass	V	Peak

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.71	43.71	54.00	10.29	Pass	H	Average
2	2412.4781	32.28	13.36	-36.61	79.22	88.25	54.00	-34.25	Pass	H	Average

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.85	43.85	54.00	10.15	Pass	V	Average
2	2412.4781	32.28	13.36	-36.61	77.14	86.17	54.00	-32.17	Pass	V	Average

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2461.9449	32.35	13.48	-36.70	85.20	94.33	74.00	-20.33	Pass	H	Peak
2	2483.5000	32.38	13.38	-36.80	45.70	54.66	74.00	19.34	Pass	H	Peak

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2463.3242	32.35	13.47	-36.70	82.57	91.69	74.00	-17.69	Pass	V	Peak
2	2483.5000	32.38	13.38	-36.80	45.62	54.58	74.00	19.42	Pass	V	Peak

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.5257	32.35	13.47	-36.69	79.81	88.94	54.00	-34.94	Pass	H	Average
2	2483.5000	32.38	13.38	-36.80	34.53	43.49	54.00	10.51	Pass	H	Average

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:			

Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.5982	32.35	13.47	-36.69	77.57	86.70	54.00	-32.70	Pass	V	Average
2	2483.5000	32.38	13.38	-36.80	34.49	43.45	54.00	10.55	Pass	V	Average



Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	45.26	54.26	74.00	19.74	Pass	H	Peak
2	2416.7960	32.28	13.38	-36.61	81.38	90.43	74.00	-16.43	Pass	H	Peak

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	45.68	54.68	74.00	19.32	Pass	V	Peak
2	2417.5156	32.28	13.38	-36.61	78.11	87.16	74.00	-13.16	Pass	V	Peak

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.63	43.63	54.00	10.37	Pass	H	Average
2	2412.1902	32.28	13.36	-36.61	69.57	78.60	54.00	-24.60	Pass	H	Average

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.63	43.63	54.00	10.37	Pass	V	Average
2	2412.0463	32.28	13.36	-36.61	66.45	75.48	54.00	-21.48	Pass	V	Average

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2467.7522	32.35	13.45	-36.71	82.58	91.67	74.00	-17.67	Pass	H	Peak
2	2483.5000	32.38	13.38	-36.80	45.75	54.71	74.00	19.29	Pass	H	Peak

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2467.1715	32.35	13.45	-36.71	78.42	87.51	74.00	-13.51	Pass	V	Peak
2	2483.5000	32.38	13.38	-36.80	45.71	54.67	74.00	19.33	Pass	V	Peak

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.3805	32.35	13.47	-36.69	71.75	80.88	54.00	-26.88	Pass	H	Average
2	2483.5000	32.38	13.38	-36.80	34.70	43.66	54.00	10.34	Pass	H	Average

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	AV		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.3079	32.35	13.47	-36.69	67.23	76.36	54.00	-22.36	Pass	V	Average
2	2483.5000	32.38	13.38	-36.80	34.49	43.45	54.00	10.55	Pass	V	Average



Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2412
Remark:	PK	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	45.99	54.99	74.00	19.01	Pass	H	Peak
2	2414.6370	32.28	13.37	-36.61	81.93	90.97	74.00	-16.97	Pass	H	Peak

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2412
Remark:	PK	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	46.10	55.10	74.00	18.90	Pass	V	Peak
2	2414.4931	32.28	13.37	-36.61	77.80	86.84	74.00	-12.84	Pass	V	Peak

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel:2412
Remark:	AV	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.68	43.68	54.00	10.32	Pass	H	Average
2	2412.0463	32.28	13.36	-36.61	69.06	78.09	54.00	-24.09	Pass	H	Average

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2412
Remark:	AV	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	32.25	13.37	-36.62	34.63	43.63	54.00	10.37	Pass	V	Average
2	2412.0463	32.28	13.36	-36.61	65.77	74.80	54.00	-20.80	Pass	V	Average

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2462
Remark:	PK	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2468.5507	32.36	13.44	-36.72	82.84	91.92	74.00	-17.92	Pass	H	Peak
2	2483.5000	32.38	13.38	-36.80	46.10	55.06	74.00	18.94	Pass	H	Peak

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2462
Remark:	PK	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2468.5507	32.36	13.44	-36.72	78.38	87.46	74.00	-13.46	Pass	V	Peak
2	2483.5000	32.38	13.38	-36.80	45.14	54.10	74.00	19.90	Pass	V	Peak

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2462
Remark:	AV	


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.2353	32.35	13.47	-36.69	69.53	78.66	54.00	-24.66	Pass	H	Average
2	2483.5000	32.38	13.38	-36.80	41.20	50.16	54.00	3.84	Pass	H	Average

Mode:	802.11 n(HT20)(6.5Mbps) Transmitting	Channel: 2462
Remark:	AV	

### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2462.1627	32.35	13.47	-36.69	66.87	76.00	54.00	-22.00	Pass	V	Average
2	2483.5000	32.38	13.38	-36.80	41.25	50.21	54.00	3.79	Pass	V	Average



Note:

1) Through Pre-scan transmitting mode with all kind of modulation and data rate, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20), and then Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

## Appendix I): Radiated Spurious Emissions

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Test Procedure:

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter)..

h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.


j. Repeat above procedures until all frequencies measured was complete.

Limit:


Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## Radiated Spurious Emissions test Data: Radiated Emission below 1GHz



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	96.0636	10.37	1.13	-32.07	53.08	32.51	43.50	10.99	Pass	Horizontal
2	147.2847	7.45	1.43	-32.00	56.46	33.34	43.50	10.16	Pass	Horizontal
3	347.9978	14.26	2.22	-31.86	55.10	39.72	46.00	6.28	Pass	Horizontal
4	480.0280	16.68	2.61	-31.90	54.78	42.17	46.00	3.83	Pass	Horizontal
5	597.4097	18.95	2.94	-31.97	41.77	31.69	46.00	14.31	Pass	Horizontal
6	840.1280	21.38	3.50	-31.89	39.89	32.88	46.00	13.12	Pass	Horizontal



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	96.0636	10.37	1.13	-32.07	47.73	27.16	43.50	16.34	Pass	Vertical
2	131.9572	7.60	1.34	-32.01	56.99	33.92	43.50	9.58	Pass	Vertical
3	324.0364	13.73	2.14	-31.81	48.86	32.92	46.00	13.08	Pass	Vertical
4	351.1991	14.33	2.23	-31.87	50.10	34.79	46.00	11.21	Pass	Vertical
5	480.0280	16.68	2.61	-31.90	45.05	32.44	46.00	13.56	Pass	Vertical
6	599.1559	18.98	2.95	-31.98	41.01	30.96	46.00	15.04	Pass	Vertical



**Transmitter Emission above 1GHz**

Mode: 802.11 b(11Mbps) Transmitting								Channel: 2412MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1196.4393	28.10	2.66	-37.65	49.05	42.16	74.00	31.84	Pass	H	Peak
2	3215.4966	33.29	4.59	-36.74	46.05	47.19	74.00	26.81	Pass	H	Peak
3	4824.0000	34.50	4.61	-36.11	47.60	50.60	74.00	23.40	Pass	H	Peak
4	6172.9673	35.83	5.24	-36.25	44.01	48.83	74.00	25.17	Pass	H	Peak
5	7236.0000	36.34	5.79	-36.44	42.36	48.05	74.00	25.95	Pass	H	Peak
6	9648.0000	37.66	6.72	-36.92	42.45	49.91	74.00	24.09	Pass	H	Peak
7	1196.8394	28.10	2.66	-37.65	51.75	44.86	74.00	29.14	Pass	V	Peak
8	3021.4521	33.21	4.89	-36.79	46.32	47.63	74.00	26.37	Pass	V	Peak
9	4824.0000	34.50	4.61	-36.11	46.35	49.35	74.00	24.65	Pass	V	Peak
10	6025.7276	35.81	5.27	-36.28	43.56	48.36	74.00	25.64	Pass	V	Peak
11	7236.0000	36.34	5.79	-36.44	42.48	48.17	74.00	25.83	Pass	V	Peak
12	9648.0000	37.66	6.72	-36.92	43.48	50.94	74.00	23.06	Pass	V	Peak

Mode: 802.11 b(11Mbps) Transmitting								Channel: 2437MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1196.4393	28.10	2.66	-37.65	48.59	41.70	74.00	32.30	Pass	H	Peak
2	2965.9932	33.15	4.45	-36.78	45.83	46.65	74.00	27.35	Pass	H	Peak
3	4874.0000	34.50	4.78	-36.09	42.96	46.15	74.00	27.85	Pass	H	Peak
4	7311.0000	36.41	5.85	-36.31	40.82	46.77	74.00	27.23	Pass	H	Peak
5	8129.9880	36.45	6.32	-36.48	43.55	49.84	74.00	24.16	Pass	H	Peak
6	9748.0000	37.70	6.77	-36.79	43.08	50.76	74.00	23.24	Pass	H	Peak
7	1195.6391	28.10	2.66	-37.65	53.09	46.20	74.00	27.80	Pass	V	Peak
8	2967.1934	33.15	4.45	-36.78	45.83	46.65	74.00	27.35	Pass	V	Peak
9	4874.0000	34.50	4.78	-36.09	44.34	47.53	74.00	26.47	Pass	V	Peak
10	6263.6514	35.85	5.38	-36.27	43.40	48.36	74.00	25.64	Pass	V	Peak
11	7311.0000	36.41	5.85	-36.31	40.30	46.25	74.00	27.75	Pass	V	Peak
12	9748.0000	37.70	6.77	-36.79	42.87	50.55	74.00	23.45	Pass	V	Peak

Mode: 802.11 b(11Mbps) Transmitting								Channel: 2462MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1232.0464	28.13	2.67	-37.55	49.54	42.79	74.00	31.21	Pass	H	Peak
2	3007.8008	33.20	4.91	-36.73	45.95	47.33	74.00	26.67	Pass	H	Peak
3	4924.0000	34.50	4.85	-36.17	43.25	46.43	74.00	27.57	Pass	H	Peak
4	6524.0024	35.91	5.41	-36.17	44.93	50.08	74.00	23.92	Pass	H	Peak
5	7386.0000	36.49	5.85	-36.34	42.28	48.28	74.00	25.72	Pass	H	Peak
6	9848.0000	37.74	6.83	-36.93	43.18	50.82	74.00	23.18	Pass	H	Peak
7	1199.2398	28.10	2.66	-37.64	53.68	46.80	74.00	27.20	Pass	V	Peak
8	3389.0639	33.36	4.55	-36.66	47.17	48.42	74.00	25.58	Pass	V	Peak
9	4924.0000	34.50	4.85	-36.17	43.06	46.24	74.00	27.76	Pass	V	Peak
10	6315.3315	35.86	5.46	-36.20	44.13	49.25	74.00	24.75	Pass	V	Peak
11	7386.0000	36.49	5.85	-36.34	42.59	48.59	74.00	25.41	Pass	V	Peak
12	9848.0000	37.74	6.83	-36.93	42.64	50.28	74.00	23.72	Pass	V	Peak

Mode: 802.11 g(6Mbps) Transmitting								Channel: 2412MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1894.1788	31.00	3.42	-36.79	47.67	45.30	74.00	28.70	Pass	H	Peak
2	3003.9004	33.20	4.92	-36.72	45.56	46.96	74.00	27.04	Pass	H	Peak
3	4824.0000	34.50	4.61	-36.11	42.47	45.47	74.00	28.53	Pass	H	Peak
4	5779.0279	35.45	4.96	-36.07	43.43	47.77	74.00	26.23	Pass	H	Peak
5	7236.0000	36.34	5.79	-36.44	41.58	47.27	74.00	26.73	Pass	H	Peak
6	9648.0000	37.66	6.72	-36.92	43.18	50.64	74.00	23.36	Pass	H	Peak
7	1196.4393	28.10	2.66	-37.65	50.27	43.38	74.00	30.62	Pass	V	Peak
8	2989.9980	33.18	4.52	-36.73	44.76	45.73	74.00	28.27	Pass	V	Peak
9	4824.0000	34.50	4.61	-36.11	38.91	41.91	74.00	32.09	Pass	V	Peak
10	5719.5470	35.35	4.99	-36.12	41.87	46.09	74.00	27.91	Pass	V	Peak
11	7236.0000	36.34	5.79	-36.44	39.51	45.20	74.00	28.80	Pass	V	Peak
12	9648.0000	37.66	6.72	-36.92	43.27	50.73	74.00	23.27	Pass	V	Peak

Mode: 802.11 g(6Mbps) Transmitting								Channel: 2437MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1854.1708	30.74	3.38	-36.93	46.86	44.05	74.00	29.95	Pass	H	Peak
2	3469.9970	33.39	4.45	-36.58	44.78	46.04	74.00	27.96	Pass	H	Peak
3	4874.0000	34.50	4.78	-36.09	42.62	45.81	74.00	28.19	Pass	H	Peak
4	6500.6001	35.90	5.47	-36.22	43.81	48.96	74.00	25.04	Pass	H	Peak
5	7311.0000	36.41	5.85	-36.31	41.30	47.25	74.00	26.75	Pass	H	Peak
6	9748.0000	37.70	6.77	-36.79	42.83	50.51	74.00	23.49	Pass	H	Peak
7	1195.6391	28.10	2.66	-37.65	54.41	47.52	74.00	26.48	Pass	V	Peak
8	3330.5581	33.33	4.54	-36.74	46.31	47.44	74.00	26.56	Pass	V	Peak
9	4874.0000	34.50	4.78	-36.09	41.68	44.87	74.00	29.13	Pass	V	Peak
10	5974.0474	35.76	5.33	-36.23	44.01	48.87	74.00	25.13	Pass	V	Peak
11	7311.0000	36.41	5.85	-36.31	42.12	48.07	74.00	25.93	Pass	V	Peak
12	9748.0000	37.70	6.77	-36.79	43.28	50.96	74.00	23.04	Pass	V	Peak

Mode: 802.11 g(6Mbps) Transmitting								Channel: 2462MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1393.6787	28.29	2.89	-37.21	49.29	43.26	74.00	30.74	Pass	H	Peak
2	3218.4218	33.29	4.58	-36.74	47.16	48.29	74.00	25.71	Pass	H	Peak
3	4924.0000	34.50	4.85	-36.17	42.66	45.84	74.00	28.16	Pass	H	Peak
4	6394.3144	35.88	5.33	-36.32	45.27	50.16	74.00	23.84	Pass	H	Peak
5	7386.0000	36.49	5.85	-36.34	41.89	47.89	74.00	26.11	Pass	H	Peak
6	9848.0000	37.74	6.83	-36.93	43.33	50.97	74.00	23.03	Pass	H	Peak
7	1796.5593	30.36	3.31	-36.81	48.32	45.18	74.00	28.82	Pass	V	Peak
8	3189.1689	33.28	4.63	-36.75	45.51	46.67	74.00	27.33	Pass	V	Peak
9	4924.0000	34.50	4.85	-36.17	41.86	45.04	74.00	28.96	Pass	V	Peak
10	6138.8389	35.83	5.25	-36.22	44.27	49.13	74.00	24.87	Pass	V	Peak
11	7386.0000	36.49	5.85	-36.34	41.32	47.32	74.00	26.68	Pass	V	Peak
12	9848.0000	37.74	6.83	-36.93	43.00	50.64	74.00	23.36	Pass	V	Peak

Mode: 802.11 n(HT20)(6.5Mbps) Transmitting								Channel: 2412MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1396.0792	28.30	2.89	-37.21	50.18	44.16	74.00	29.84	Pass	H	Peak
2	3352.9853	33.34	4.52	-36.70	46.16	47.32	74.00	26.68	Pass	H	Peak
3	4824.0000	34.50	4.61	-36.11	42.41	45.41	74.00	28.59	Pass	H	Peak
4	5952.5953	35.72	5.32	-36.15	43.27	48.16	74.00	25.84	Pass	H	Peak
5	7236.0000	36.34	5.79	-36.44	42.18	47.87	74.00	26.13	Pass	H	Peak
6	9648.0000	37.66	6.72	-36.92	43.52	50.98	74.00	23.02	Pass	H	Peak
7	1393.6787	28.29	2.89	-37.21	55.44	49.41	74.00	24.59	Pass	V	Peak
8	2903.1806	33.05	4.38	-36.64	47.33	48.12	74.00	25.88	Pass	V	Peak
9	4824.0000	34.50	4.61	-36.11	42.00	45.00	74.00	29.00	Pass	V	Peak
10	5946.7447	35.71	5.30	-36.15	43.20	48.06	74.00	25.94	Pass	V	Peak
11	7236.0000	36.34	5.79	-36.44	42.56	48.25	74.00	25.75	Pass	V	Peak
12	9648.0000	37.66	6.72	-36.92	43.17	50.63	74.00	23.37	Pass	V	Peak

Mode: 802.11 n(HT20)(6.5Mbps) Transmitting								Channel: 2437MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1916.9834	31.15	3.42	-36.80	47.51	45.28	74.00	28.72	Pass	H	Peak
2	3536.3036	33.43	4.45	-36.48	45.28	46.68	74.00	27.32	Pass	H	Peak
3	4874.0000	34.50	4.78	-36.09	42.27	45.46	74.00	28.54	Pass	H	Peak
4	6441.1191	35.89	5.48	-36.27	44.10	49.20	74.00	24.80	Pass	H	Peak
5	7311.0000	36.41	5.85	-36.31	42.56	48.51	74.00	25.49	Pass	H	Peak
6	9748.0000	37.70	6.77	-36.79	42.88	50.56	74.00	23.44	Pass	H	Peak
7	1596.5193	29.04	3.07	-37.00	47.73	42.84	74.00	31.16	Pass	V	Peak
8	2902.7806	33.04	4.38	-36.63	46.04	46.83	74.00	27.17	Pass	V	Peak
9	4874.0000	34.50	4.78	-36.09	40.18	43.37	74.00	30.63	Pass	V	Peak
10	6249.0249	35.85	5.35	-36.29	42.82	47.73	74.00	26.27	Pass	V	Peak
11	7311.0000	36.41	5.85	-36.31	41.59	47.54	74.00	26.46	Pass	V	Peak
12	9748.0000	37.70	6.77	-36.79	42.88	50.56	74.00	23.44	Pass	V	Peak



Mode: 802.11 n(HT20)(6.5Mbps) Transmitting								Channel: 2462MHz			
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1198.8398	28.10	2.66	-37.64	50.06	43.18	74.00	30.82	Pass	H	Peak
2	3091.6592	33.24	4.74	-36.83	46.75	47.90	74.00	26.10	Pass	H	Peak
3	4924.0000	34.50	4.85	-36.17	42.31	45.49	74.00	28.51	Pass	H	Peak
4	5980.8731	35.77	5.33	-36.25	44.35	49.20	74.00	24.80	Pass	H	Peak
5	7386.0000	36.49	5.85	-36.34	42.09	48.09	74.00	25.91	Pass	H	Peak
6	9848.0000	37.74	6.83	-36.93	42.80	50.44	74.00	23.56	Pass	H	Peak
7	1197.6395	28.10	2.66	-37.65	53.46	46.57	74.00	27.43	Pass	V	Peak
8	4298.8299	34.22	4.40	-36.13	45.35	47.84	74.00	26.16	Pass	V	Peak
9	4924.0000	34.50	4.85	-36.17	42.04	45.22	74.00	28.78	Pass	V	Peak
10	6391.3891	35.88	5.34	-36.31	44.68	49.59	74.00	24.41	Pass	V	Peak
11	7386.0000	36.49	5.85	-36.34	41.92	47.92	74.00	26.08	Pass	V	Peak
12	9848.0000	37.74	6.83	-36.93	42.98	50.62	74.00	23.38	Pass	V	Peak

**Note:**

1) Through Pre-scan transmitting mode and charge+transmitter mode with all kind of modulation and data rate, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20), and then Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

3) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

## PHOTOGRAPHS OF TEST SETUP

Test model No.: TEW201



**Radiated spurious emission Test Setup-1(Below 30MHz)**



**Radiated spurious emission Test Setup-2(30MHz-1GHz)**



**Radiated spurious emission Test Setup-3(Above 1GHz)**



**Conducted Emissions Test Setup**



## PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No.EED32K00287201 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.