

Report on the Radio Testing
For
Telecom Design S.A.
on
Modem for ITU Region 2
Report no. TRA-030878-47-00A
6th July 2016

RF916 6.0

Report Number: TRA-030878-47-00A
Issue: A

REPORT ON THE RADIO TESTING OF A
Telecom Design S.A.
Modem for ITU Region 2
WITH RESPECT TO SPECIFICATION
FCC 47CFR 15.247

TEST DATE: 14th April - 13th May 2016

Written by: D Winstanley

A Longley
D Winstanley
Radio Test Engineers

Approved by:

J Charters
Department Manager - Radio

Date: 6th July 2016

Disclaimers:

- [1] THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE
- [2] THE RESULTS CONTAINED IN THIS DOCUMENT RELATE ONLY TO THE ITEM(S) TESTED

RF916 6.0

1 Revision Record

| <i>Issue Number</i> | <i>Issue Date</i> | <i>Revision History</i> |
|---------------------|-------------------|-------------------------|
| A | 6th July 2016 | Original |
| | | |

2 Summary

| | |
|-----------------------------|--|
| TEST REPORT NUMBER: | TRA-030878-47-00A |
| WORKS ORDER NUMBER | TRA-030878-00 |
| PURPOSE OF TEST: | USA: Testing of radio frequency equipment per the relevant authorization procedure of chapter 47 of CFR (code of federal regulations) Part 2, subpart J. |
| TEST SPECIFICATION(S): | 47CFR15.247 |
| EQUIPMENT UNDER TEST (EUT): | Modem for ITU Region 2 |
| FCC IDENTIFIER: | 2AGMK-TD1508 |
| EUT SERIAL NUMBER: | 76214, 7622B, 761DC, 761FB |
| MANUFACTURER/AGENT: | Telecom Design S.A. |
| ADDRESS: | 2 bis rue Nully de Harcourt 33610 CANEJAN FRANCE |
| CLIENT CONTACT: | Michel Stempin ☎ +33(0)557356386 ✉ mstempin@telecomdesign.fr |
| ORDER NUMBER: | Not Applicable |
| TEST DATE: | 14th April - 13th May 2016 |
| TESTED BY: | A Longley D Winstanley Element |

2.1 Test Summary

| Test Method and Description | Requirement Clause | Applicable to this equipment | Result / Note |
|---|----------------------------------|-------------------------------------|---------------|
| | m 47CFR15 | | |
| Radiated spurious emissions (restricted bands of operation and cabinet radiation) | 15.205 | <input checked="" type="checkbox"/> | Pass |
| AC power line conducted emissions | 15.207 | <input checked="" type="checkbox"/> | Pass |
| Carrier frequency separation | 15.247(a)(1) | <input checked="" type="checkbox"/> | Pass |
| Number of hopping channels | 15.247(a)(1) (i), (ii) and (iii) | <input checked="" type="checkbox"/> | Pass |
| Average time of occupancy | 15.247(a)(1) (i), (ii) and (iii) | <input checked="" type="checkbox"/> | Pass |
| Maximum peak conducted output power | 15.247 (a)(1), (b)(1) and (b)(2) | <input checked="" type="checkbox"/> | Pass |
| 20dB emission bandwidth | 15.247(a)(1) (i) and (ii) | <input checked="" type="checkbox"/> | Pass |
| Out-of-band emissions | 15.247(d) | <input checked="" type="checkbox"/> | Pass |
| Unintentional Radiated Spurious Emissions | 15.105 | <input checked="" type="checkbox"/> | Pass |

Notes:

The results contained in this report relate only to the items tested, in the condition at time of test, and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only. Any modifications made are identified in Section 8 of this report.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 5.2 of this test report (Deviations from Test Standards).

3 Contents

| | | |
|-------|---|----|
| 1 | Revision Record..... | 3 |
| 2 | Summary..... | 4 |
| 2.1 | Test Summary..... | 5 |
| 3 | Contents..... | 6 |
| 4 | Introduction | 8 |
| 5 | Test Specifications..... | 9 |
| 5.1 | Normative References | 9 |
| 5.2 | Deviations from Test Standards | 9 |
| 6 | Glossary of Terms..... | 10 |
| 7 | Equipment Under Test | 11 |
| 7.1 | EUT Identification..... | 11 |
| 7.2 | System Equipment..... | 11 |
| 7.3 | EUT Mode of Operation | 11 |
| 7.3.1 | Transmission..... | 11 |
| 7.3.2 | Reception..... | 11 |
| 7.4 | EUT Radio Parameters | 12 |
| 7.4.1 | General | 12 |
| 7.4.2 | Antennas..... | 12 |
| 7.4.3 | Product specific declarations..... | 13 |
| 7.5 | EUT Description | 13 |
| 8 | Modifications | 14 |
| 9 | EUT Test Setup | 15 |
| 9.1 | Block Diagram..... | 15 |
| 9.2 | General Set-up Photograph | 16 |
| 10 | General Technical Parameters..... | 17 |
| 10.1 | Normal Conditions..... | 17 |
| 10.2 | Varying Test Conditions | 17 |
| 11 | Radiated emissions..... | 18 |
| 11.1 | Definitions | 18 |
| 11.2 | Test Parameters..... | 18 |
| 11.3 | Test Limit..... | 18 |
| 11.4 | Test Method | 19 |
| 11.5 | Test Set-up Photograph | 20 |
| 11.6 | Test Equipment..... | 21 |
| 11.7 | Test Results | 22 |
| 12 | AC power-line conducted emissions | 26 |
| 12.1 | Definition | 26 |
| 12.2 | Test Parameters..... | 26 |
| 12.3 | Test Method | 27 |
| 12.4 | Test Set-up Photograph | 27 |
| 12.5 | Test Equipment..... | 27 |
| 12.6 | Test Results | 28 |
| 13 | Carrier frequency separation..... | 29 |
| 13.1 | Definition | 29 |
| 13.2 | Test Parameters..... | 29 |
| 13.3 | Test Limit..... | 29 |
| 13.4 | Test Method | 30 |
| 13.5 | Test Equipment..... | 30 |
| 13.6 | Test Results | 30 |
| 14 | Number of hopping frequencies | 31 |
| 14.1 | Definition | 31 |
| 14.2 | Test Parameters..... | 31 |
| 14.3 | Test Limit..... | 31 |
| 14.4 | Test Method | 32 |
| 14.5 | Test Equipment..... | 32 |
| 14.6 | Test Results | 32 |
| 15 | Average channel occupancy | 36 |
| 15.1 | Definition | 36 |
| 15.2 | Test Parameters..... | 36 |
| 15.3 | Test Limit..... | 36 |
| 15.4 | Test Method | 37 |
| 15.5 | Test Equipment..... | 37 |
| 15.6 | Test Results | 37 |

| | | |
|------|---|----|
| 16 | Maximum peak conducted output power..... | 39 |
| 16.1 | Definition | 39 |
| 16.2 | Test Parameters..... | 39 |
| 16.3 | Test Limit..... | 39 |
| 16.4 | Test Method | 40 |
| 16.5 | Test Equipment..... | 40 |
| 16.6 | Test Results | 40 |
| 17 | Occupied Bandwidth | 41 |
| 17.1 | Definition | 41 |
| 17.2 | Test Parameters..... | 41 |
| 17.3 | Test Limit..... | 41 |
| 17.4 | Test Method | 42 |
| 17.5 | Test Equipment..... | 42 |
| 17.6 | Test Results | 42 |
| 18 | Out-of-band and conducted spurious emissions | 44 |
| 18.1 | Definition | 44 |
| 18.2 | Test Parameters..... | 44 |
| 18.3 | Test Limits..... | 44 |
| 18.4 | Test Method | 45 |
| 18.5 | Test Equipment..... | 45 |
| 18.6 | Test Results | 45 |
| 19 | Radiated emissions – unintentional radiation / receiver emissions | 49 |
| 19.1 | Definitions | 49 |
| 19.2 | Test Parameters..... | 49 |
| 19.3 | Test Limit..... | 49 |
| 19.4 | Test Method | 50 |
| 19.5 | Test Set-up Photograph | 50 |
| 19.6 | Test Equipment..... | 50 |
| 19.7 | Test Results | 51 |
| 20 | Measurement Uncertainty | 53 |

4 Introduction

This report TRA-030878-47-00A presents the results of the Radio testing on a Telecom Design S.A.Modem for ITU Region 2 to specification 47CFR15 Radio Frequency Devices and RSS-247 Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment.

The testing was carried out for Telecom Design S.A.by Element, at the address(es) detailed below.

| | | | |
|--------------------------|---|-------------------------------------|---|
| <input type="checkbox"/> | Element Hull Unit E South Orbital Trading Park Hedon Road Hull HU9 1NJ UK | <input checked="" type="checkbox"/> | Element Skelmersdale Unit 1 Pendle Place Skemersdale West Lancashire WN8 9PN UK |
|--------------------------|---|-------------------------------------|---|

This report details the configuration of the equipment, the test methods used and any relevant modifications where appropriate.

All test and measurement equipment under the control of the laboratory and requiring calibration is subject to an established programme and procedures to control and maintain measurement standards. The quality management system meets the principles of ISO 9001, and has quality control procedures for monitoring the validity of tests undertaken. Records and sufficient detail are retained to establish an audit trail of calibration records relating to its test results for a defined period. Under control of the established calibration programme, key quantities or values of the test & measurement instrumentation are within specification and comply with the relevant traceable internationally recognised and appropriate standard specifications, which are UKAS calibrated as such where these properties have a significant effect on results. Participation in inter-laboratory comparisons and proficiency testing ensures satisfactory correlation of results conform to Elements own procedures, as well as statistical techniques for analysis of test data providing the appropriate confidence in measurements.

Throughout this report EUT denotes equipment under test.

FCC Site Listing:

Element is accredited for the above sites under the US-EU MRA, Designation number UK0009.

IC Registration Number(s):

| | |
|--------------------|-------|
| Element Hull | 3483A |
| Element North West | 3930B |

The test site requirements of ANSI C63.4-2014 are met up to 1GHz.

The test site SVSWR requirements of CISPR 16-1-4:2010 are met over the frequency range 1 GHz to 18 GHz.

5 Test Specifications

5.1 Normative References

- FCC 47 CFR Ch. I – Part 15 – Radio Frequency Devices.
- ANSI C63.10-2013 – American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
- ANSI C63.4-2014 – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- Compliance of Radio Apparatus.

5.2 Deviations from Test Standards

There were no deviations from the test standard.

6 Glossary of Terms

| | |
|---------------|--|
| § | denotes a section reference from the standard, not this document |
| AC | Alternating Current |
| ANSI | American National Standards Institute |
| BW | bandwidth |
| C | Celsius |
| CFR | Code of Federal Regulations |
| CW | Continuous Wave |
| dB | decibel |
| dBm | dB relative to 1 milliwatt |
| DC | Direct Current |
| DSSS | Direct Sequence Spread Spectrum |
| EIRP | Equivalent Isotropically Radiated Power |
| ERP | Effective Radiated Power |
| EUT | Equipment Under Test |
| FCC | Federal Communications Commission |
| FHSS | Frequency Hopping Spread Spectrum |
| Hz | hertz |
| IC | Industry Canada |
| ITU | International Telecommunication Union |
| LBT | Listen Before Talk |
| m | metre |
| max | maximum |
| MIMO | Multiple Input and Multiple Output |
| min | minimum |
| MRA | Mutual Recognition Agreement |
| N/A | Not Applicable |
| PCB | Printed Circuit Board |
| PDF | Portable Document Format |
| Pt-mpt | Point-to-multipoint |
| Pt-pt | Point-to-point |
| RF | Radio Frequency |
| RH | Relative Humidity |
| RMS | Root Mean Square |
| Rx | receiver |
| s | second |
| SVSWR | Site Voltage Standing Wave Ratio |
| Tx | transmitter |
| UKAS | United Kingdom Accreditation Service |
| V | volt |
| W | watt |
| Ω | ohm |

7 Equipment Under Test

7.1 EUT Identification

- Name: Modem for ITU Region 2
- Serial Number: 76214, 7622B, 761DC, 761FB
- Model Number: TD1508
- Software Revision: SOFT1963
- Build Level / Revision Number: Production

7.2 System Equipment

Equipment listed below forms part of the overall test setup and is required for equipment functionality and/or monitoring during testing. The compliance levels achieved in this report relate only to the EUT and not items given in the following list.

Not Applicable – No support/monitoring equipment required.

7.3 EUT Mode of Operation

7.3.1 Transmission

The mode of operation for Tx tests was as follows...

The EUT was programmed using command sequences sent via terminal program. Operating modes consisted of

CW – Fixed Frequency
Modulated Carrier - Fixed Frequency
Hopping over all channels
Hopping over a limited range of channels.

7.3.2 Reception

The mode of operation for Rx tests was as follows...

Permanent RX mode – Fixed Frequency

7.4 EUT Radio Parameters

7.4.1 General

| | |
|---------------------------------------|------------------------------|
| Frequency of operation: | 902.2 MHz – 904.6 MHz |
| Modulation type(s): | FHSS |
| Occupied channel bandwidth(s): | 21.7 kHz |
| Channel spacing: | 25 kHz |
| ITU emission designator(s): | Not Stated |
| Declared output power(s): | +25 dBm |
| Nominal Supply Voltage: | 3.3 Vdc (regulated from USB) |

7.4.2 Antennas

| | |
|------------------------------|-----------------------------|
| Type: | Dipole |
| Frequency range: | 868 MHz |
| Impedance: | 50 Ohm |
| SWR: | ≤ 2.0 @ 868 MHz |
| Gain: | 2.0 ± 0.7 dBi @ 868 MHz |
| Polarisation: | Linear |
| Beam width: | Not Applicable |
| Connector type: | SMA Male |
| Environmental limits: | - 40 °C ~ + 65 °C |
| Mounting: | Screw on |

7.4.3 Product specific declarations

| | |
|---|------------|
| Multiple antenna configuration(s), e.g. MIMO: | N/A |
| Fixed pt-pt operations (yes/no): | No |
| Installation manual advice on pt-pt operational restrictions (yes/no): | No |
| Fixed pt-mpt operations (yes/no): | No |
| Simultaneous tx (yes/no): | No |

7.5 EUT Description

The EUT is a FHSS radio module operating in the 902 - 928 MHz band. The EUT is designed to utilise the Sigfox network.


8 Modifications

No modifications were performed during this assessment.

9 EUT Test Setup


9.1 Block Diagram

The following diagram shows basic EUT interconnections with cable type and cable lengths identified:



9.2 General Set-up Photograph

The following photograph shows basic EUT set-up:



10 General Technical Parameters

10.1 Normal Conditions

The E U T was tested under the normal environmental conditions of the test laboratory, except where otherwise stated. The normal power source applied was approx. 3.3 V dc from the adaptor from the mains.

10.2 Varying Test Conditions

There are no specific frequency stability requirements for the type of device. The results contained in this report demonstrate that the occupied bandwidth is contained within the authorised band and the manufacturer has declared sufficient frequency stability (refer to section 7.4).

Variation of supply voltage is required to ensure stability of the declared output power. During carrier power testing the following variations were made:

| | Category | Nominal | Variation |
|-------------------------------------|-----------------|-----------------|------------------|
| <input type="checkbox"/> | Mains | 110 V ac +/-2 % | 85 % and 115 % |
| <input type="checkbox"/> | Battery | N/A | 85 % and 115 % |
| <input checked="" type="checkbox"/> | Other | 3.3 Vdc | 85 % and 115 % |

11 Radiated emissions

11.1 Definitions

Spurious emissions

Emissions on a frequency or frequencies, which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

Restricted bands

A frequency band in which intentional radiators are permitted to radiate only spurious emissions but not fundamental signals.

11.2 Test Parameters

| | |
|--------------------------------------|--|
| Test Location: | Element Skelmersdale |
| Test Chamber: | Chamber 1 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 6.5 and 6.6 |
| EUT Channels / Frequencies Measured: | 902.2 MHz / 904.6 MHz |
| EUT Channel Bandwidths: | 25 kHz |
| Deviations From Standard: | None |
| Measurement BW: | 30 MHz to 1 GHz: 120 kHz Above 1 GHz: 1 MHz |
| Measurement Detector: | Up to 1 GHz: quasi-peak Above 1 GHz: RMS average and Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 22 °C | +15 °C to +35 °C (as declared) |
| Humidity: 48 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: 3.3 V dc | 3.3 V dc |

11.3 Test Limit

Unwanted emissions that fall within the restricted frequency bands shall comply with the limits specified:

General Field Strength Limits for License-Exempt Transmitters at Frequencies above 30 MHz

| Frequency (MHz) | Field Strength ($\mu\text{V/m}$ at 3 m) |
|----------------------------|---|
| 30 to 88 | 100 |
| 88 to 216 | 150 |
| 216 to 960 | 200 |
| Above 960 | 500 |

11.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure i, the emissions from the EUT were measured on a spectrum analyzer / EMI receiver.

Radiated electromagnetic emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked, using a peak detector and where applicable worst-case determined for function, operation, orientation, etc. for both vertical and horizontal polarisations. Pre-scan plots are shown with a peak detector and 100 kHz RBW.

If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.10 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed, (see EUT setup photographs for more detail).

Emissions between 30 MHz and 1 GHz are measured using calibrated broadband antennas. Emissions above 1 GHz are characterized using standard gain horn antennas. Pre-amplifiers and filters are used where required. Care is taken to ensure that test receiver resolution bandwidth, video bandwidth and detector type(s) meet the regulatory requirements.

For both horizontal and vertical polarizations, the EUT is then rotated through 360 degrees in azimuth until the highest emission is detected. At the previously determined azimuth the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected, this maximum value is recorded.

Power values measured on the test receiver / analyzer are converted to field strength, FS, in dBμV/m at the regulatory distance, using:


$$FS = PR + CL + AF - PA + DC - CF$$

Where,

PR is the power recorded on the receiver / spectrum analyzer in dBμV;
 CL is the cable loss in dB;
 AF is the test antenna factor in dB/m;
 PA is the pre-amplifier gain in dB (where used);
 DC is the duty correction factor in dB (where used, e.g. harmonics of pulsed fundamental);
 CF is the distance factor in dB (where measurement distance different to limit distance);


This field strength value is then compared with the regulatory limit.

Figure i Test Setup



11.5 Test Set-up Photograph







11.6 Test Equipment


| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU26 | R&S | Spectrum Analyser | REF909 | 26/04/2017 | 12 |
| 3115 | EMCO | 1-18GHz Horn | L138 | 13/04/2018 | 24 |
| 8449B | Agilent | Pre Amp | U457 | 18/08/2016 | 12 |
| ESVS10 | R&S | Receiver | L352 | 07/08/2016 | 12 |
| CBL6112B | Chase | Bilog | U093 | 17/06/2017 | 24 |

11.7 Test Results

30MHz-1GHz ESVS10 + UH93 (Pre+Zoom)





Date: 15.APR.2016 13:03:55




Date: 15.APR.2016 13:06:34

| <i>High Power; Channel: 902.2 MHz</i> | | | | | | | | | | |
|---------------------------------------|------------------------|---------------------------------------|--------------------------------|--------------------------------------|----------------------------------|---|--|--|--------------------------------------|-------------------------|
| <i>Detector</i> | <i>Freq. (MHz)</i> | <i>Meas'd Emission (dBμV)</i> | <i>Cable Loss (dB)</i> | <i>Antenna Factor (dB/m)</i> | <i>Pre-amp Gain (dB)</i> | <i>Duty Cycle Corr'n (dB)</i> | <i>Distance Extrap'n Factor (dB)</i> | <i>Field Strength (dBμV/m)</i> | <i>Field Strength (μV/m)</i> | <i>Limit (μV/m)</i> |
| Pk | 2706.60 | 53.51 | 4.10 | 29.10 | 35.52 | 0.00 | 0.00 | 51.19 | 362.66 | 5012 |
| Av | 2706.60 | 48.47 | 4.10 | 29.10 | 35.52 | 0.00 | 0.00 | 46.15 | 203.00 | 500 |
| Pk | 3608.80 | 51.38 | 4.80 | 31.20 | 35.50 | 0.00 | 0.00 | 51.88 | 392.64 | 5012 |
| Av | 3608.80 | 46.06 | 4.80 | 31.20 | 35.50 | 0.00 | 0.00 | 46.56 | 212.81 | 500 |
| Pk | 5413.20 | 48.48 | 7.00 | 33.90 | 35.25 | 0.00 | 0.00 | 54.13 | 508.74 | 5012 |
| Av | 5413.20 | 41.42 | 7.00 | 33.90 | 35.25 | 0.00 | 0.00 | 47.07 | 225.68 | 500 |

30MHz-1GHz ESVS10 + UH93 (Pre+Zoom)



Date: 15.APR.2016 13:29:16



Date: 15.APR.2016 13:31:39

| <i>High Power; Channel: 904.6 MHz</i> | | | | | | | | | | |
|---------------------------------------|------------------------|---------------------------------------|--------------------------------|--------------------------------------|----------------------------------|---|--|--|--------------------------------------|-------------------------|
| <i>Detector</i> | <i>Freq. (MHz)</i> | <i>Meas'd Emission (dBμV)</i> | <i>Cable Loss (dB)</i> | <i>Antenna Factor (dB/m)</i> | <i>Pre-amp Gain (dB)</i> | <i>Duty Cycle Corr'n (dB)</i> | <i>Distance Extrap'n Factor (dB)</i> | <i>Field Strength (dBμV/m)</i> | <i>Field Strength (μV/m)</i> | <i>Limit (μV/m)</i> |
| Pk | 2713.80 | 55.16 | 4.10 | 29.10 | 35.52 | 0.00 | 0.00 | 52.84 | 438.53 | 5012 |
| Av | 2713.80 | 51.55 | 4.10 | 29.10 | 35.52 | 0.00 | 0.00 | 49.23 | 289.40 | 500 |
| Pk | 3618.40 | 52.06 | 4.90 | 31.20 | 35.50 | 0.00 | 0.00 | 52.66 | 429.54 | 5012 |
| Av | 3618.40 | 46.56 | 4.90 | 31.20 | 35.50 | 0.00 | 0.00 | 47.16 | 228.03 | 500 |
| Pk | 5427.60 | 48.74 | 7.00 | 34.00 | 35.26 | 0.00 | 0.00 | 54.48 | 529.66 | 5012 |
| Av | 5427.60 | 41.46 | 7.00 | 34.00 | 35.26 | 0.00 | 0.00 | 47.20 | 229.09 | 500 |

12 AC power-line conducted emissions

12.1 Definition

Line-to-ground radio-noise voltage that is conducted from all of the EUT current-carrying power input terminals that are directly (or indirectly via separate transformers or power supplies) connected to a public power network.

12.2 Test Parameters

| | |
|---------------------------|--------------------------------|
| Test Location: | Element Skelmersdale |
| Test Chamber: | UH404 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 6.2 |
| Deviations From Standard: | None |
| Measurement BW: | 10 kHz |
| Measurement Detectors: | Quasi-Peak and Average, RMS |

Environmental Conditions (Normal Environment)

| | |
|--------------------|---|
| Temperature: 22 °C | +15 °C to +35 °C (as declared) |
| Humidity: 28 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: 3.3 Vdc | 3.3Vdc (regulated from a linear 110 Vac Supply) |

Test Limit

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in Table 3.

Table 3 – AC Power Line Conducted Emission Limits

| <i>Frequency (MHz)</i> | <i>Conducted limit (dBμV)</i> | |
|----------------------------|-----------------------------------|------------------|
| | <i>Quasi-Peak</i> | <i>Average**</i> |
| 0.15 to 0.5 | 66 to 56 | 56 to 46 |
| 0.5 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

*The level decreases linearly with the logarithm of the frequency.

**A linear average detector is required.


12.3 Test Method

With the EUT setup in a screened room, as per section 9 of this report and connected as per Figure ii, the power line emissions were measured on a spectrum analyzer / EMI receiver.


AC power line conducted emissions from the EUT are checked first by preview scans with peak and average detectors covering both live and neutral lines. A spectrum analyzer is used to determine if any periodic emissions are present.

Formal measurements using the correct detector(s) and bandwidth are made on frequencies identified from the preview scans. Final measurements were performed with EUT set at its maximum duty in transmit and receive modes.

Figure ii Test Setup



12.4 Test Set-up Photograph




12.5 Test Equipment

| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| ESHS10 | R&S | Receiver | U187 | 29/10/2016 | 12 |
| ESH3-Z5.831.5 | R&S | Lisn | U195 | 04/06/2016 | 12 |

12.6 Test Results

Conducted emissions on Mains 9kHz-30MHz ESHS10 + UH195



| Frequency (MHz) | QuasiPeak (dBμV) | Meas. Time (ms) | Bandwidth (kHz) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 0.165000 | 27.2 | 2000.0 | 10.000 | GND | N | 0.1 | 38.0 | 65.2 |
| 0.200000 | 15.5 | 2000.0 | 10.000 | GND | N | 0.1 | 48.1 | 63.6 |
| 0.305000 | 11.5 | 2000.0 | 10.000 | GND | L1 | 0.1 | 48.6 | 60.1 |
| 0.430000 | 14.1 | 2000.0 | 10.000 | GND | L1 | 0.1 | 43.1 | 57.3 |
| 0.440000 | 14.4 | 2000.0 | 10.000 | GND | L1 | 0.1 | 42.7 | 57.1 |
| 0.470000 | 11.8 | 2000.0 | 10.000 | GND | L1 | 0.1 | 44.7 | 56.5 |
| 0.525000 | 6.7 | 2000.0 | 10.000 | GND | L1 | 0.1 | 49.3 | 56.0 |

| Frequency (MHz) | Average (dBμV) | Meas. Time (ms) | Bandwidth (kHz) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|----------------|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 0.150000 | 9.0 | 2000.0 | 10.000 | GND | L1 | 0.1 | 47.0 | 56.0 |
| 0.180000 | 11.8 | 2000.0 | 10.000 | GND | L1 | 0.1 | 42.7 | 54.5 |
| 0.220000 | 6.9 | 2000.0 | 10.000 | GND | L1 | 0.1 | 45.9 | 52.8 |
| 0.305000 | 10.1 | 2000.0 | 10.000 | GND | L1 | 0.1 | 40.0 | 50.1 |
| 0.335000 | 6.6 | 2000.0 | 10.000 | GND | L1 | 0.1 | 42.7 | 49.3 |
| 24.015000 | 8.3 | 2000.0 | 10.000 | GND | N | 1.6 | 41.7 | 50.0 |

13 Carrier frequency separation

13.1 Definition

The carrier frequency separation is the frequency separation between two adjacent hopping frequencies.

13.2 Test Parameters

| | |
|--------------------------------------|---|
| Test Location: | Element Hull |
| Test Chamber: | Radio Lab |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 7.8.2 |
| EUT Channels / Frequencies Measured: | All; 902 MHz – 928 MHz |
| EUT 20dB Bandwidth: | 21.7 kHz |
| EUT Test Modulations: | Internal pattern generation – hopping enabled |
| Deviations From Standard: | None |
| Measurement BW: | 1 kHz |
| Measurement Detector: | Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 24 °C | +15 °C to +35 °C (as declared) |
| Humidity: 42 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: +3.3Vdc | +3.3Vdc (as declared) |

13.3 Test Limit


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the band 2400 to 2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

13.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure iii, the emissions of the EUT were measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each nominal bandwidth.

Figure iii Test Setup




13.5 Test Equipment

| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |

13.6 Test Results

| $F1_c$ (MHz) | $F2_c$ (MHz) | Channel Separation, $F2_c - F1_c$ (kHz) | Result |
|-----------------|-----------------|---|--------|
| 902.1715144 | 902.1965 | 25 kHz | PASS |



Date: 14.APR.2016 10:14:14

14 Number of hopping frequencies

14.1 Definition

The total number of hopping frequencies (the centre frequencies defined within the hopping sequence of a FHSS equipment) which are randomly sequenced in order to spread the transmission.

14.2 Test Parameters

| | |
|--------------------------------------|---|
| Test Location: | Element Hull |
| Test Chamber: | Lab 4 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 7.8.3 |
| EUT Channels / Frequencies Measured: | All; 902 - 928 MHz |
| EUT 20dB Bandwidth: | 21.7 kHz |
| EUT Test Modulations: | Internal pattern generation – hopping enabled |
| Deviations From Standard: | None |
| Measurement BW: | 1kHz |
| Measurement Detector: | Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 24 °C | +15 °C to +35 °C (as declared) |
| Humidity: 42 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: +3.3Vdc | +3.3Vdc (as declared) |

14.3 Test Limit


- For frequency hopping systems in the band 902 to 928 MHz: if the -20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels;
If the -20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels;
- Frequency hopping systems operating in the band 2400 to 2483.5 MHz shall use at least 15 hopping channels;
- Frequency hopping systems operating in the band 5725 to 5850 MHz shall use at least 75 hopping channels.

14.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure iv, the emissions of the EUT were measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each nominal bandwidth. The Measurement of hopping channels was split over several plots.

Figure iv Test Setup




14.5 Test Equipment


| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |

14.6 Test Results


| <i>Lowest channel, F_{CL} (MHz)</i> | <i>Highest channel, F_{CH} (MHz)</i> | <i>Number of channels observed</i> | <i>Result</i> |
|--|---|--|---------------|
| 902.2 | 904.6 | 54 | PASS |




Date: 14.APR.2016 11:51:40




Date: 14.APR.2016 11:55:37




Date: 14.APR.2016 11:58:20




Date: 14.APR.2016 12:00:35




Date: 14.APR.2016 12:04:17




Date: 14.APR.2016 12:08:18



Date: 14.APR.2016 12:12:10



Date: 14.APR.2016 12:15:47



Date: 14.APR.2016 12:18:08

15 Average channel occupancy

15.1 Definition

The channel occupancy is the total of the transmitter 'on' times, during an observation period, on a particular hopping frequency.

15.2 Test Parameters

| | |
|--------------------------------------|---|
| Test Location: | Element Hull |
| Test Chamber: | Lab 4 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 7.8.4 |
| EUT Channels / Frequencies Measured: | 902 MHz |
| EUT 20dB bandwidth: | 21.7 kHz |
| EUT Number of hopping channels: | 54 |
| EUT Test Modulations: | Internal pattern generation – hopping enabled |
| Deviations From Standard: | None |
| Measurement BW: | 10 kHz |
| Measurement Detector: | Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 24 °C | +15 °C to +35 °C (as declared) |
| Humidity: 42 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: +3.3Vdc | +3.3Vdc (as declared) |

15.3 Test Limit


- For frequency hopping systems in the band 902 to 928 MHz: if the -20 dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20 second period; If the -20 dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10 second period;
- Frequency hopping systems operating in the band 2400 to 2483.5 MHz: The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed;
- Frequency hopping systems operating in the band 5725 to 5850 MHz: The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

15.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure v, the emissions of the EUT were measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. A number of hops were observed to confirm consistency of the dwell time / observe the worst case. All modulation schemes, data rates and power settings were used to observe the worst-case configuration.

Figure v Test Setup




15.5 Test Equipment


| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |

15.6 Test Results

| <i>Individual occupancy time (ms)</i> | <i>Observation period (s)</i> | <i>Number of hops observed</i> | <i>Average time of occupancy (s)</i> | <i>Result</i> |
|---------------------------------------|-------------------------------|--------------------------------|--------------------------------------|---------------|
| 352.56 | 20 | 1 | 0.35256 | PASS |



Date: 14.APR.2016 12:32:32



Date: 14.APR.2016 12:38:34

16 Maximum peak conducted output power

16.1 Definition

The maximum peak conducted output power is defined as the maximum power level measured with a peak detector using a filter with width and shape of which is sufficient to accept the signal bandwidth.

16.2 Test Parameters

| | |
|---|---|
| Test Location: | Element Hull |
| Test Chamber: | Lab 4 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 7.8.5 |
| EUT Channels / Frequencies Measured: | 902.2 MHz / 903.4 MHz / 904.6 MHz – hopping disabled. |
| EUT Channel Bandwidths: | 25 kHz |
| Deviations From Standard: | None |
| Measurement BW: | 100 kHz |
| Spectrum Analyzer Video BW: | 300 kHz |
| Measurement Detector: | Peak |
| Voltage Extreme Environment Test Range: | Mains Power = 85 % and 115 % of Nominal (FCC only requirement); Battery Power = new battery. |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 22 °C | +15 °C to +35 °C (as declared) |
| Humidity: 45 % RH | 20 % RH to 75 % RH (as declared) |

16.3 Test Limit


- For frequency hopping systems operating in the band 902 to 928 MHz, the maximum peak conducted output power shall not exceed 1 W, and the e.i.r.p. shall not exceed 4 W, if the hopset uses 50 or more hopping channels; the maximum peak conducted output power shall not exceed 0.25 W, and the e.i.r.p. shall not exceed 1 W, if the hopset uses less than 50 hopping channels.
- For frequency hopping systems operating in the band 2400 to 2483.5 MHz and employing at least 75 hopping channels, the maximum peak conducted output power shall not exceed 1 W; for all other frequency hopping systems in the band, the maximum peak conducted output power shall not exceed 0.125 W. The e.i.r.p. shall not exceed 4 W.
- For frequency hopping systems operating in the band 5725 to 5850 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.
- Point-to-point systems in the bands 2400-2483.5 MHz and 5725 to 5850 MHz are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers.

16.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure vi, the resolution bandwidth of the spectrum analyser was increased above the EUT occupied bandwidth and the peak emission data noted.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Figure vi Test Setup



16.5 Test Equipment

| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |

16.6 Test Results

| Channel Frequency (MHz) | Analyzer Level (dBm) | Cable loss (dB) | Attenuator loss (dB) | Maximum peak conducted output power (dBm) | Maximum peak conducted output power (mW) | Antenna gain (dBi) | E.I.R.P. (mW) | Result |
|-------------------------|----------------------|-----------------|----------------------|---|--|--------------------|---------------|--------|
| 902.2 | 14.77 | 0.45 | 10 | 25.22 | 332.66 | 2.7 | 619.44 | PASS |
| 903.4 | 14.88 | 0.45 | 10 | 25.33 | 341.19 | 2.7 | 635.33 | PASS |
| 904.6 | 14.75 | 0.45 | 10 | 25.20 | 331.13 | 2.7 | 616.60 | PASS |

17 Occupied Bandwidth

17.1 Definition

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal.

17.2 Test Parameters

| | |
|--------------------------------------|---|
| Test Location: | Element Hull |
| Test Chamber: | Lab 4 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 6.9 |
| EUT Channels / Frequencies Measured: | Low / Mid / High – hopping stopped. |
| EUT Channel Bandwidths: | 902.2 MHz / 903.4 MHz / 904.6 MHz – hopping disabled. |
| EUT Test Modulations: | FHSS |
| Deviations From Standard: | None |
| Measurement BW: | 300 Hz |
| (requirement: 1 % to 5 % OBW) | |
| Spectrum Analyzer Video BW: | 1 kHz |
| (requirement at least 3x RBW) | |
| Measurement Span: | 30 kHz |
| (requirement 2 to 5 times OBW) | |
| Measurement Detector: | Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 24 °C | +15 °C to +35 °C (as declared) |
| Humidity: 42 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: +5Vdc | +5Vdc (as declared) |

17.3 Test Limit


- For frequency hopping systems in the band 902 to 928 MHz: The maximum allowed -20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the band 5725 to 5850 MHz: The maximum -20 dB bandwidth of the hopping channel shall be 1 MHz

17.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure vii, the bandwidth of the EUT was measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Figure vii Test Setup




17.5 Test Equipment


| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |

17.6 Test Results


| Channel Frequency (MHz) | F_L (MHz) | F_H (MHz) | 20dB Bandwidth (kHz) | Result |
|-------------------------|-------------|-------------|----------------------|--------|
| 902.2 | 902.2003125 | 902.2219952 | 21.682692 | PASS |
| 903.4 | 903.3753846 | 903.3969712 | 21.586539 | PASS |
| 904.6 | 904.6502404 | 904.6719712 | 21.730769 | PASS |



Date: 14.APR.2016 10:56:36



Date: 14.APR.2016 11:13:48



Date: 14.APR.2016 11:06:47

18 Out-of-band and conducted spurious emissions

18.1 Definition

Out-of-band emission.

Emission on a frequency or frequencies immediately outside the necessary bandwidth that results from the modulation process but excluding spurious emissions.

Spurious emission.

Emission on a frequency or frequencies that are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products, and frequency conversion products, but exclude out-of-band emissions.

18.2 Test Parameters

| | |
|--|--------------------------------|
| Test Location: | Element Skelmersdale |
| Test Chamber: | Radio Lab |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 7.8.8 |
| EUT Channels / Frequencies Measured: | Low / Mid / High |
| EUT Channel Bandwidths: | 25 kHz |
| Deviations From Standard: | None |
| Measurement BW: | 100 kHz |
| Spectrum Analyzer Video BW: (requirement at least 3x RBW) | 300 kHz |
| Measurement Detector: | Peak |
| Measurement Range: | 30 MHz to 26.5 GHz |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 24 °C | +15 °C to +35 °C (as declared) |
| Humidity: 44 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: +3.3Vdc | +3.3Vdc (as declared) |

18.3 Test Limits


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in FCC 47CFR15.209(a) / RSS-Gen is not required.

18.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure viii, the emissions from the EUT were measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst case configuration in each bandwidth.


Figure viii Test Setup




18.5 Test Equipment

| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU46 | R&S | Spectrum Analyser | REF910 | 28/05/2016 | 12 |


18.6 Test Results




Date: 27.APR.2016 10:15:59




Date: 27.APR.2016 10:19:17



Date: 27.APR.2016 10:17:56



Date: 14.APR.2016 14:28:44



Date: 14.APR.2016 14:31:18

19 Radiated emissions – unintentional radiation / receiver emissions

19.1 Definitions

Receiver spurious emissions

The radio frequency signals generated within the receiver, which may cause interference to other equipment. This includes the period during which the equipment is scanning or switching channels.

Unintentional radiator

A device that generates RF energy which is not intended to be radiated for reception by a radio receiver.

19.2 Test Parameters

| | |
|--------------------------------------|--|
| Test Location: | Element Skelmersdale |
| Test Chamber: | Chamber 1 |
| Test Standard and Clause: | ANSI C63.10-2013, Clause 6.5 and 6.6 |
| EUT Channels / Frequencies Measured: | 902.2 MHz / 904.6 MHz |
| EUT Channel Bandwidths: | 25 kHz |
| Deviations From Standard: | None |
| Measurement BW: | 30 MHz to 1 GHz: 120 kHz Above 1 GHz: 1 MHz |
| Measurement Detector: | Up to 1 GHz: quasi-peak Above 1 GHz: Peak |

Environmental Conditions (Normal Environment)

| | |
|--------------------|----------------------------------|
| Temperature: 22 °C | +15 °C to +35 °C (as declared) |
| Humidity: 48 % RH | 20 % RH to 75 % RH (as declared) |
| Supply: 3.3 V dc | 3.3 V dc |

19.3 Test Limit

Note:

Only radio communication receivers operating in stand-alone mode within the band 30 to 960 MHz, as well as scanner receivers, are subject to requirements, as described above. All other receivers are exempted from any certification, testing, labelling and reporting requirements.

However, all receivers in all frequency bands shall comply with the limits set forth in FCC 47CFR15B / IC RSS-Gen even in cases where testing, reporting and/or certification are not required.

Receiver Radiated Limits

| <i>Frequency (MHz)</i> | <i>Field Strength (μV/m at 3 m)</i> |
|----------------------------|--|
| 30 to 88 | 100 |
| 88 to 216 | 150 |
| 216 to 960 | 200 |
| Above 960 | 500 |


19.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure viii, the emissions from the EUT were measured on a spectrum analyzer / EMI receiver. The EUT was rotated in three orthogonal planes and the measurement antenna height scanned (below 1 GHz, from 1 to 4 m; above 1 GHz as necessary) in order to maximise emissions.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration at each frequency.

Pre-scan plots are shown with a peak detector and 100 kHz RBW.

Figure viii Test Setup





19.5 Test Set-up Photograph




19.6 Test Equipment

| Equipment Type | Manufacturer | Equipment Description | Element No | Due For Calibration | Calibration Period |
|----------------|--------------|-----------------------|------------|---------------------|--------------------|
| FSU26 | R&S | Spectrum Analyser | REF909 | 26/04/2017 | 12 |
| 3115 | EMCO | 1-18GHz Horn | L138 | 13/04/2018 | 24 |
| 8449B | Agilent | Pre Amp | U457 | 18/08/2016 | 12 |
| ESVS10 | R&S | Receiver | L352 | 07/08/2016 | 12 |
| CBL6112B | Chase | Bilog | U093 | 17/06/2017 | 24 |

19.7 Test Results





Date: 15.APR.2016 13:39:29




Date: 15.APR.2016 13:37:07

High Power; Channel: 902.2 MHz

| Detector | Freq. (MHz) | Measured Emission (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Pre-amp Gain (dB) | Field Strength (dBuV/m) | Extrap'n Factor (dB) | Field Strength (uV/m) | Limit (uV/m) |
|----------|-------------|----------------------------|-----------------|-----------------------|-------------------|-------------------------|----------------------|-----------------------|--------------|
| Pk | 3618.86 | 52.22 | 4.90 | 31.20 | 35.50 | 0.00 | -9.54 | 43.28 | 145.84 |
| Av | 3618.86 | 51.05 | 4.90 | 31.20 | 35.50 | 0.00 | -9.54 | 42.11 | 127.46 |



Date: 15.APR.2016 13:51:29



Date: 15.APR.2016 13:49:41

| High Power; Channel: high MHz | | | | | | | | | |
|-------------------------------|-------------|----------------------------|-----------------|-----------------------|-------------------|-------------------------|----------------------|-----------------------|--------------|
| Detector | Freq. (MHz) | Measured Emission (dBμV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Pre-amp Gain (dB) | Field Strength (dBμV/m) | Extrap'n Factor (dB) | Field Strength (μV/m) | Limit (μV/m) |
| Pk | 3682.45 | 54.58 | 4.90 | 31.40 | 35.49 | 0.00 | -9.54 | 45.85 | 196.06 |
| Av | 3682.45 | 50.50 | 4.90 | 31.40 | 35.49 | 0.00 | -9.54 | 41.77 | 122.57 |

20 Measurement Uncertainty

Calculated Measurement Uncertainties

All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95 % confidence:

[1] Radiated spurious emissions

Uncertainty in test result (30 MHz to 1 GHz) = **4.6 dB**

Uncertainty in test result (1 GHz to 18 GHz) = **4.7 dB**

[2] AC power line conducted emissions

Uncertainty in test result = **3.4 dB**

[3] Occupied bandwidth

Uncertainty in test result = **15.5 %**

[4] Conducted carrier power

Uncertainty in test result (Power Meter) = **1.08 dB**

[5] Conducted / radiated RF power out-of-band

Uncertainty in test result – up to 8.1 GHz = **3.31 dB**

Uncertainty in test result – 8.1 GHz to 15.3 GHz = **4.43 dB**

Uncertainty in test result (30 MHz to 1 GHz) = **4.6 dB**

Uncertainty in test result (1 GHz to 18 GHz) = **4.7 dB**

[6] Frequency separation

Uncertainty in test result (Spectrum Analyser) = **3.6 kHz**

[7] Accumulated channel occupancy time

Uncertainty in test result = **7.98 %**