

1 Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard

: CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 v06, section 7
RSS-102 Issue 5 March 2015, section 2.5.2

➤ FCC requirements

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to KDB 447498 v06Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

From the peak RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain (Max. 2.2 dBi for BLE, Max -0.27 dBi for Wi-Fi), the RF power density can be calculated as below:

$$S_{(mW/cm^2)} = PG/4\pi R^2$$

Prüfbericht - Nr.:
Test Report No.

Seite 2 von 3

Page 2 of 3

a) EUT RF Exposure Evaluation standalone operations

| Test Mode | Measured Conducted Power | | Antenna Gain (dBi) | Measured e.i.r.p | | $S_{(mW/cm^2)} = \frac{PG}{4\pi R^2}$ | Limit (mW/cm ²) |
|--------------|--------------------------|--------|--------------------|------------------|--------|---------------------------------------|-----------------------------|
| | (dBm) | (mW) | | (dBm) | (mW) | | |
| Wi-Fi 2.4GHz | 14.93 | 31.117 | -0.27 | 14.66 | 29.242 | 0.006 | 1.0 |
| BLE* | 8.19 | 6.592 | 2.2 | 10.39 | 10.940 | 0.002 | 1.0 |

*Note: this device contains a single module FCC ID: SH6MDBT50Q

b) EUT RF Exposure Evaluation simultaneous transmission operations

| Simultaneous transmission mode | The sum of the ratios | Result |
|--------------------------------|-------------------------|--------|
| BLE + Wi-Fi | $0.006/1 + 0.002/1 < 1$ | Pass |

- **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 2.5.2.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

- RF exposure evaluation exempted power for BLE: 2.67 W
- RF exposure evaluation exempted power for 2.4GHz Wi-Fi: 2.68 W

a) EUT RF Exposure Evaluation standalone operations:

| Test Mode | Measured conducted Power | | Antenna Gain (dBi) | Measured e.i.r.p (mW) | |
|--------------|--------------------------|--------|--------------------|-----------------------|--------|
| | (dBm) | (mW) | | (dBm) | (mW) |
| Wi-Fi 2.4GHz | 14.93 | 31.117 | -0.27 | 14.66 | 29.242 |
| BLE | 7.16 | 5.200 | 2.2 | 9.36 | 8.630 |

b) EUT RF Exposure Evaluation simultaneous transmission operations

| Simultaneous transmission mode | The sum of the ratios | Result |
|--------------------------------|---------------------------------|--------|
| BLE + DTSSs | $0.0086/2.67 + 0.0292/2.68 < 1$ | Pass |

The e.i.r.p. for BLE, DTSSs and FHSs are less than the RF exposure evaluation exempted power. So RF exposure evaluation is not required.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”