





Report No.:BCTC2411135403-1E







13. Number Of Hopping Frequency

13.1 Block Diagram Of Test Setup

EUT	SPECTRUM		
	ANALYZER		

13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure


- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

13.4 Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass


No.: BCTC/RF-EMC-005 Page: 66 of 83 / / / Edition: BX








Report No.:BCTC2411135403-1E







14. Dwell Time

14.1 Block Diagram Of Test Setup

	i -			
EUT		SPECTRUM		
		ANALYZER		

14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set spectrum analyzer span = 0. Centred on a hopping channel;
- 3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).


14.4 Test Result


Condition	Mode	Fre- quency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.378	118.692	314	31600	400	Pass
NVNT	1-DH3	2441	1.633	259.647	159	31600	400	Pass
NVNT	1-DH5	2441	2.882	8.646	3	31600	400	Pass
NVNT	2-DH1	2441	0.385	121.66	316	31600	400	Pass
NVNT	2-DH3	2441	1.636	258.488	158	31600	400	Pass
NVNT	2-DH5	2441	2.885	308.695	107	31600	400	Pass
NVNT	3-DH1	2441	0.386	0.386	1	31600	400	Pass
NVNT	3-DH3	2441	1.636	260.124	159	31600	400	Pass
NVNT	3-DH5	2441	2.886	317.46	110	31600	400	Pass

Note: Total Dwell Time (ms) = Pulse Time (ms)*Burst Count


No.: BCTC/RF-EMC-005 Page: 69 of 83 / / / Edition Bi2































#VBW 3.0 MHz

Span 0 Hz Sweep 31.60 s (10001 pts)













Center 2.441000000 GHz Res BW 1.0 MHz



#VBW 3.0 MHz

Span 0 Hz Sweep 31.60 s (10001 pts)







15. Antenna Requirement


15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

No.: BCTC/RF-EMC-005

The EUT antenna is Internal antenna, fulfill the requirement of this section.





16. EUT Photographs

EUT Photo 1



EUT Photo 2



NOTE: Appendix-Photographs Of EUT Constructional Details.

No.: BCTC/RF-EMC-005 Page: 80 of 83 / / Edition B:2




17. EUT Test Setup Photographs

Conducted Emissions Photo



Radiated Measurement Photos





No.: BCTC/RF-EMC-005 Page: 81 of 83 / / / Edition B2













STATEMENT

- 1. The equipment lists are traceable to the national reference standards.
- 2. The test report can not be partially copied unless prior written approval is issued from our lab.
- 3. The test report is invalid without the "special seal for inspection and testing".
- 4. The test report is invalid without the signature of the approver.
- 5. The test process and test result is only related to the Unit Under Test.
- 6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
- 7. The quality system of our laboratory is in accordance with ISO/IEC17025.
- 8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

Consultation E-mail: bctc@bctc-lab.com.cn.

Complaint/Advice E-mail: advice@bctc-lab.com.cn

**** END ****

No.: BCTC/RF-EMC-005 Page: 83 of 83 / / / Edition: B.2