



Project No.: TM-2303000028P
Report No.: TMWK2303000591KS

FCC ID: KA2M30A01

Page 1 / 20
Rev.: 01

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for

**AX3000 Dual-Band Wi-Fi 6 Router (Single pack),
AX3000 Dual-Band Wi-Fi 6 Mesh System (multi-pack)**

Model Name.: M30

Prepared for:

**D-Link Corporation
14420 Myford Road Suite 100 Irvine California United States 92606**

Prepared by

**Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan.
Issue Date: July 24, 2023**

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2303000591KS

Page 2 / 20

Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 20, 2023	Initial Issue	ALL	Allison Chen
01	July 24, 2023	See the following Note Rev.(01)	P.6	Allison Chen

Note:

Rev.(01)

1. Modify HW/SW version.



Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION.....	6
3.1	DUT DESCRIPTION.....	6
3.2	WIRELESS TECHNOLOGIES.....	7
4	MAXIMUM PERMISSIBLE EXPOSURE	12
4.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
4.2	MPE CALCULATION METHOD	13
4.3	MPE EXEMPTION.....	14
4.4	MULTIPLE RF SOURCES.....	15
5	MPE EXEMPTION OPTION B.....	16
6	SIMULTANEOUS TRANSMISSION ANALYSIS.....	19
6.1	SUM OF THE WIFI 2.4GHZ & WIFI 5GHZ.....	19
7	FACILITIES	20



Report No.: TMWK2303000591KS

Page 4 / 20
Rev.: 01

1 Attestation of Test Results

Applicant Name	D-Link Corporation
Model Name	M30
Applicable Standards	FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1307 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures
Receive EUT Date:	March 25, 2023
Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.	
Approved & Released By: 	
Sky Zhou Asst. Section Manager Compliance Certification Services Inc.	



Report No.: TMWK2303000591KS

Page 5 / 20

Rev.: 01

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Report No.: TMWK2303000591KS

Page 6 / 20
Rev.: 01

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	AX3000 Dual-Band Wi-Fi 6 Router (Single pack), AX3000 Dual-Band Wi-Fi 6 Mesh System (multi-pack)
Trade Name	D-Link
Model No.	M30
Model Discrepancy	N/A
Hardware Version	A1
Software Version	1.00
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	☐ Bluetooth: 2402MHz-2480MHz ☒ 802.11b/g/n HT20/ax (HE20): 2412MHz ~ 2462 MHz ☒ 802.11n HT40/ax (HE40): 2422MHz ~ 2452MHz ☒ 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11ac VHT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11ax HE20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700 MHz / 5745MHz ~ 5825MHz ☒ 802.11n HT40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT 40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ax HE40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT80: 5210MHz / 5290MHz / 5530MHz ~ 5610MHz / 5775MHz ☒ 802.11ax HE80: 5210MHz / 5290MHz / 5530MHz ~ 5610MHz / 5775MHz ☒ 802.11ac VHT160: 5250 MHz / 5570 MHz ☒ 802.11ax HE160: 5250 MHz / 5570 MHz ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)

Antenna Specification

Type: Short Dipole Antenna

(1) WIFI 2.4GHz:

2G-1 (Chain 0): WIESON / ARY196-0030-014-00

2G-2 (Chain 1): WIESON / ARY196-0030-015-00

Frequency	2G-1 (Chain 0) Gain (dBi)	2G-2 (Chain 1) Gain (dBi)	Total Gain (dBi)
2412-2462MHz	2.44	1.94	5.20

(2) WIFI 5GHz:

5G-0: WIESON / ARY196-0030-016-00 (TX/RX)

5G-1: WIESON / ARY196-0030-018-00 (TX/RX)

5G-2: WIESON / ARY196-0030-017-00 (RX)

Band	5G-0 (Chain 0) Gain (dBi)	5G-1 (Chain 1) Gain (dBi)	5G-2 Gain (dBi)	Total Gain [Note 1] (dBi)
Band I (U-NII 1) 5150-5250MHz	2.51	2.42	2.12	5.48
Band II (U-NII 2a) 5250-5350 MHz	2.51	2.42	2.20	5.48
Band III (U-NII 2c) 5470-5725 MHz	2.51	2.40	2.32	5.47
Band IV (U-NII 3) 5725-5850MHz	2.69	2.47	2.40	5.59

[Note 1]: Since port 2 is RX don't count DG.

Antenna Gain:

2.4GHz: Chain 0 2.44 dBi (Numeric gain: 1.75)
2.4GHz: Chain 1 1.94 dBi (Numeric gain: 1.56)
2.4GHz: Power Directional 5.20 dBi (Numeric gain: 3.31) Worst

Antenna Gain:

5GHz(Band 1) Chain 0 2.51 dBi (Numeric gain: 1.78)
5GHz(Band 1) Chain 1 2.42 dBi (Numeric gain: 1.75)
5GHz(Band 1) Power Directional 5.48 dBi (Numeric gain: 3.53) Worst
5GHz(Band 2) Chain 0 2.51 dBi (Numeric gain: 1.78) Worst
5GHz(Band 2) Chain 1 2.42 dBi (Numeric gain: 1.75) Worst
5GHz(Band 2) Power Directional 5.48 dBi (Numeric gain: 3.53) Worst
5GHz(Band 3) Chain 0 2.51 dBi (Numeric gain: 1.78) Worst
5GHz(Band 3) Chain 1 2.40 dBi (Numeric gain: 1.74) Worst
5GHz(Band 3) Power Directional 5.47 dBi (Numeric gain: 3.52) Worst
5GHz(Band 4) Chain 0 2.69 dBi (Numeric gain: 1.86)
5GHz(Band 4) Chain 1 2.47 dBi (Numeric gain: 1.77)
5GHz(Band 4) Power Directional 5.59 dBi (Numeric gain: 3.62) Worst

Maximum
tune up
power

2.4GHz (Non-Beamforming)

IEEE 802.11b (Chain 0)	23.50 dBm
IEEE 802.11b (Chain 1)	22.00 dBm
IEEE 802.11g (Chain 0)	23.00 dBm
IEEE 802.11g (Chain 1)	23.00 dBm
IEEE 802.11n HT 20 (MIMO)	25.00 dBm
IEEE 802.11n HT 40 (MIMO)	24.50 dBm
IEEE 802.11ax HE 20 (MIMO)	25.00 dBm
IEEE 802.11ax HE 40 (MIMO)	24.50 dBm

5GHz U-NII 1 (Non-Beamforming)

IEEE 802.11a Chain 0(SISO)	22.50 dBm
IEEE 802.11a Chain 1(SISO)	23.00 dBm
IEEE 802.11n HT 20(MIMO)	26.50 dBm
IEEE 802.11n HT 40(MIMO)	26.50 dBm
IEEE 802.11ac VHT 20(MIMO)	26.50 dBm
IEEE 802.11ac VHT 40(MIMO)	26.50 dBm
IEEE 802.11ac VHT 80(MIMO)	18.00 dBm
IEEE 802.11ax HE 20(MIMO)	26.50 dBm
IEEE 802.11ax HE 40(MIMO)	26.50 dBm
IEEE 802.11ax HE 80(MIMO)	18.00 dBm

5GHz U-NII 2a (Non-Beamforming)

IEEE 802.11a Chain 0(SISO)	22.50 dBm
IEEE 802.11a Chain 1(SISO)	21.50 dBm
IEEE 802.11n HT 20(MIMO)	22.50 dBm
IEEE 802.11n HT 40(MIMO)	24.00 dBm
IEEE 802.11ac VHT 20(MIMO)	22.50 dBm
IEEE 802.11ac VHT 40(MIMO)	24.00 dBm
IEEE 802.11ac VHT 80(MIMO)	18.00 dBm
IEEE 802.11ac VHT 160(MIMO)	16.00 dBm
IEEE 802.11ax HE 20(MIMO)	22.50 dBm
IEEE 802.11ax HE 40(MIMO)	24.00 dBm
IEEE 802.11ax HE 80(MIMO)	18.00 dBm
IEEE 802.11ax HE 160(MIMO)	16.00 dBm

Maximum
tune up
power

5GHz U-NII 2c (Non-Beamforming)

IEEE 802.11a_Chain 0(SISO)	22.00 dBm
IEEE 802.11a_Chain 1(SISO)	21.50 dBm
IEEE 802.11n HT 20(MIMO)	22.50 dBm
IEEE 802.11n HT 40(MIMO)	24.50 dBm
IEEE 802.11ac VHT 20(MIMO)	22.50 dBm
IEEE 802.11ac VHT 40(MIMO)	24.50 dBm
IEEE 802.11ac VHT 80(MIMO)	24.00 dBm
IEEE 802.11ac VHT 160(MIMO)	17.00 dBm
IEEE 802.11ax HE 20(MIMO)	22.50 dBm
IEEE 802.11ax HE 40(MIMO)	24.50 dBm
IEEE 802.11ax HE 60(MIMO)	24.00 dBm
IEEE 802.11ax HE 80(MIMO)	17.00 dBm

5GHz U-NII 3 (Non-Beamforming)

IEEE 802.11a_Chain 0(SISO)	23.00 dBm
IEEE 802.11a_Chain 1(SISO)	23.00 dBm
IEEE 802.11n HT 20(MIMO)	27.00 dBm
IEEE 802.11n HT 40(MIMO)	26.00 dBm
IEEE 802.11ac VHT 20(MIMO)	27.00 dBm
IEEE 802.11ac VHT 40(MIMO)	26.00 dBm
IEEE 802.11ac VHT 80(MIMO)	23.50 dBm
IEEE 802.11ax HE 20(MIMO)	27.00 dBm
IEEE 802.11ax HE 40(MIMO)	26.00 dBm
IEEE 802.11ax HE 80(MIMO)	23.50 dBm

2.4GHz (Beamforming)

IEEE 802.11n HT 20 (MIMO)	21.50 dBm
IEEE 802.11n HT 40 (MIMO)	21.50 dBm
IEEE 802.11ax HE 20 (MIMO)	21.50 dBm
IEEE 802.11ax HE 40 (MIMO)	21.50 dBm

5GHz U-NII 1 (Beamforming)

IEEE 802.11n HT 20(MIMO)	23.00 dBm
IEEE 802.11n HT 40(MIMO)	23.50 dBm
IEEE 802.11ac VHT 20(MIMO)	23.00 dBm
IEEE 802.11ac VHT 40(MIMO)	23.50 dBm
IEEE 802.11ac VHT 80(MIMO)	15.00 dBm
IEEE 802.11ax HE 20(MIMO)	23.50 dBm
IEEE 802.11ax HE 40(MIMO)	23.50 dBm
IEEE 802.11ax HE 80(MIMO)	15.00 dBm

Maximum
tune up
power

5GHz U-NII 2a (Beamforming)

IEEE 802.11n HT 20(MIMO)	19.50 dBm
IEEE 802.11n HT 40(MIMO)	21.00 dBm
IEEE 802.11ac VHT 20(MIMO)	19.50 dBm
IEEE 802.11ac VHT 40(MIMO)	21.00 dBm
IEEE 802.11ac VHT 80(MIMO)	14.50 dBm
IEEE 802.11ac VHT 160(MIMO)	13.00 dBm
IEEE 802.11ax HE 20(MIMO)	19.50 dBm
IEEE 802.11ax HE 40(MIMO)	21.00 dBm
IEEE 802.11ax HE 80(MIMO)	14.50 dBm
IEEE 802.11ax HE 160(MIMO)	13.00 dBm

5GHz U-NII 2c (Beamforming)

IEEE 802.11n HT 20(MIMO)	19.50 dBm
IEEE 802.11n HT 40(MIMO)	21.50 dBm
IEEE 802.11ac VHT 20(MIMO)	19.50 dBm
IEEE 802.11ac VHT 40(MIMO)	21.50 dBm
IEEE 802.11ac VHT 80(MIMO)	20.50 dBm
IEEE 802.11ac VHT 160(MIMO)	13.50 dBm
IEEE 802.11ax HE 20(MIMO)	19.50 dBm
IEEE 802.11ax HE 40(MIMO)	21.50 dBm
IEEE 802.11ax HE 80(MIMO)	20.50 dBm
IEEE 802.11ax HE 160(MIMO)	13.50 dBm

5GHz U-NII 3 (Beamforming)

IEEE 802.11n HT 20(MIMO)	23.50 dBm
IEEE 802.11n HT 40(MIMO)	23.00 dBm
IEEE 802.11ac VHT 20(MIMO)	23.50 dBm
IEEE 802.11ac VHT 40(MIMO)	23.00 dBm
IEEE 802.11ac VHT 80(MIMO)	20.00 dBm
IEEE 802.11ax HE 20(MIMO)	23.50 dBm
IEEE 802.11ax HE 40(MIMO)	23.00 dBm
IEEE 802.11ax HE 80(MIMO)	20.00 dBm

Notes:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- The tune up power referred the AVG power of the test report TMWK2303000589KR and TMWK2303000590KR for RF Exposure assessment purpose.

4 Maximum Permissible Exposure

4.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

4.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Report No.: TMWK2303000591KS

4.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	

4.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



5 MPE Exemption Option B

1. Non-Beamforming: WIFI 2.4GHz (DTS)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11b_Chain 0(SISO)	2437.00	0.2	23.5	2.44	25.94	23.79	239.332	3060	Complies
IEEE 802.11b_Chain 1(SISO)	2462.00	0.2	22.0	1.94	23.94	21.79	151.008	3060	Complies
IEEE 802.11g_Chain 0(SISO)	2437.00	0.2	23.0	2.44	25.44	23.29	213.304	3060	Complies
IEEE 802.11g_Chain 1(SISO)	2437.00	0.2	23.0	1.94	24.94	22.79	190.108	3060	Complies
IEEE 802.11n HT 20(MIMO)	2437.00	0.2	25.0	5.20	30.20	28.05	638.263	3060	Complies
IEEE 802.11n HT 40(MIMO)	2437.00	0.2	24.5	5.20	29.70	27.55	568.853	3060	Complies
IEEE 802.11ax HE 20(MIMO)	2437.00	0.2	25.0	5.20	30.20	28.05	638.263	3060	Complies
IEEE 802.11ax HE 40(MIMO)	2437.00	0.2	24.5	5.20	29.70	27.55	568.853	3060	Complies

WIFI 5.2GHz (U-NII 1)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11a_Chain 0(SISO)	5240.00	0.2	22.5	2.51	25.01	22.86	193.197	3060	Complies
IEEE 802.11a_Chain 1(SISO)	5240.00	0.2	23.0	2.42	25.42	23.27	212.324	3060	Complies
IEEE 802.11n HT 20(MIMO)	5240.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11n HT 40(MIMO)	5230.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5240.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5230.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5210.00	0.2	18.0	5.48	23.48	21.33	135.831	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5240.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5230.00	0.2	26.5	5.48	31.98	29.83	961.612	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5210.00	0.2	18.0	5.48	23.48	21.33	135.831	3060	Complies

WIFI 5.3GHz (U-NII 2A)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11a_Chain 0(SISO)	5320.00	0.2	22.5	2.51	25.01	22.86	193.197	3060	Complies
IEEE 802.11a_Chain 1(SISO)	5320.00	0.2	21.5	2.42	23.92	21.77	150.314	3060	Complies
IEEE 802.11n HT 20(MIMO)	5320.00	0.2	22.5	5.48	27.98	25.83	382.825	3060	Complies
IEEE 802.11n HT 40(MIMO)	5270.00	0.2	24.0	5.48	29.48	27.33	540.754	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5320.00	0.2	22.5	5.48	27.98	25.83	382.825	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5270.00	0.2	24.0	5.48	29.48	27.33	540.754	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5290.00	0.2	18.0	5.48	23.48	21.33	135.831	3060	Complies
IEEE 802.11ac VHT 160(MIMO)	5250.00	0.2	16.0	5.48	21.48	19.33	85.704	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5320.00	0.2	22.5	5.48	27.98	25.83	382.825	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5270.00	0.2	24.0	5.48	29.48	27.33	540.754	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5290.00	0.2	18.0	5.48	23.48	21.33	135.831	3060	Complies
IEEE 802.11ax HE 160(MIMO)	5250.00	0.2	16.0	5.48	21.48	19.33	85.704	3060	Complies

WIFI 5.5GHz (U-NII 2C)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11a_Chain 0(SISO)	5700.00	0.2	22.0	2.51	24.51	22.36	172.187	3060	Complies
IEEE 802.11a_Chain 1(SISO)	5580.00	0.2	21.5	2.40	23.90	21.75	149.624	3060	Complies
IEEE 802.11n HT 20(MIMO)	5700.00	0.2	22.5	5.47	27.97	25.82	381.944	3060	Complies
IEEE 802.11n HT 40(MIMO)	5550.00	0.2	24.5	5.47	29.97	27.82	605.341	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5700.00	0.2	22.5	5.47	27.97	25.82	381.944	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5550.00	0.2	24.5	5.47	29.97	27.82	605.341	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5610.00	0.2	24.0	5.47	29.47	27.32	539.511	3060	Complies
IEEE 802.11ac VHT 160(MIMO)	5570.00	0.2	17.0	5.47	22.47	20.32	107.647	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5700.00	0.2	22.5	5.47	27.97	25.82	381.944	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5550.00	0.2	24.5	5.47	29.97	27.82	605.341	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5610.00	0.2	24.0	5.47	29.47	27.32	539.511	3060	Complies
IEEE 802.11ax HE 160(MIMO)	5570.00	0.2	17.0	5.47	22.47	20.32	107.647	3060	Complies

**WIFI 5.8GHz (U-NII 3)**

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11a_Chain 0(SISO)	5825.00	0.2	23.0	2.69	25.69	23.54	225.944	3060	Complies
IEEE 802.11a_Chain 1(SISO)	5825.00	0.2	23.0	2.47	25.47	23.32	214.783	3060	Complies
IEEE 802.11n HT 20(MIMO)	5825.00	0.2	27.0	5.59	32.59	30.44	1106.624	3060	Complies
IEEE 802.11n HT 40(MIMO)	5795.00	0.2	26.0	5.59	31.59	29.44	879.023	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5825.00	0.2	27.0	5.59	32.59	30.44	1106.624	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5795.00	0.2	26.0	5.59	31.59	29.44	879.023	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5775.00	0.2	23.5	5.59	29.09	26.94	494.311	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5825.00	0.2	27.0	5.59	32.59	30.44	1106.624	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5795.00	0.2	26.0	5.59	31.59	29.44	879.023	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5775.00	0.2	23.5	5.59	29.09	26.94	494.311	3060	Complies

2. Beamforming:**WIFI 2.4GHz (DTS)**

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11n HT 20(MIMO)	2437.00	0.2	21.5	5.20	26.70	24.55	285.102	3060	Complies
IEEE 802.11n HT 40(MIMO)	2437.00	0.2	21.5	5.20	26.70	24.55	285.102	3060	Complies
IEEE 802.11ax HE 20(MIMO)	2437.00	0.2	21.5	5.20	26.70	24.55	285.102	3060	Complies
IEEE 802.11ax HE 40(MIMO)	2437.00	0.2	21.5	5.20	26.70	24.55	285.102	3060	Complies

WIFI 5.2GHz (U-NII 1)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11n HT 20(MIMO)	5240.00	0.2	23.0	5.48	28.48	26.33	429.536	3060	Complies
IEEE 802.11n HT 40(MIMO)	5230.00	0.2	23.5	5.48	28.98	26.83	481.948	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5240.00	0.2	23.0	5.48	28.48	26.33	429.536	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5230.00	0.2	23.5	5.48	28.98	26.83	481.948	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5210.00	0.2	15.0	5.48	20.48	18.33	68.077	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5240.00	0.2	23.5	5.48	28.98	26.83	481.948	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5230.00	0.2	23.5	5.48	28.98	26.83	481.948	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5210.00	0.2	15.0	5.48	20.48	18.33	68.077	3060	Complies

WIFI 5.3GHz (U-NII 2A)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11n HT 20(MIMO)	5320.00	0.2	19.5	5.48	24.98	22.83	191.867	3060	Complies
IEEE 802.11n HT 40(MIMO)	5270.00	0.2	21.0	5.48	26.48	24.33	271.019	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5320.00	0.2	19.5	5.48	24.98	22.83	191.867	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5270.00	0.2	21.0	5.48	26.48	24.33	271.019	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5290.00	0.2	14.5	5.48	19.98	17.83	60.674	3060	Complies
IEEE 802.11ac VHT 160(MIMO)	5250.00	0.2	13.0	5.48	18.48	16.33	42.954	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5320.00	0.2	19.5	5.48	24.98	22.83	191.867	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5270.00	0.2	21.0	5.48	26.48	24.33	271.019	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5290.00	0.2	14.5	5.48	19.98	17.83	60.674	3060	Complies
IEEE 802.11ax HE 160(MIMO)	5250.00	0.2	13.0	5.48	18.48	16.33	42.954	3060	Complies



Report No.: TMWK2303000591KS

Page 18 / 20

Rev.: 01

WIFI 5.5GHz (U-NII 2C)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11n HT 20(MIMO)	5700.00	0.2	19.5	5.47	24.97	22.82	191.426	3060	Complies
IEEE 802.11n HT 40(MIMO)	5550.00	0.2	21.5	5.47	26.97	24.82	303.389	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5700.00	0.2	19.5	5.47	24.97	22.82	191.426	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5550.00	0.2	21.5	5.47	26.97	24.82	303.389	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5610.00	0.2	20.5	5.47	25.97	23.82	240.991	3060	Complies
IEEE 802.11ac VHT 160(MIMO)	5570.00	0.2	13.5	5.47	18.97	16.82	48.084	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5700.00	0.2	19.5	5.47	24.97	22.82	191.426	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5550.00	0.2	21.5	5.47	26.97	24.82	303.389	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5610.00	0.2	20.5	5.47	25.97	23.82	240.991	3060	Complies
IEEE 802.11ax HE 160(MIMO)	5570.00	0.2	13.5	5.47	18.97	16.82	48.084	3060	Complies

WIFI 5.8GHz (U-NII 3)

Mode	Frequency (MHz)	R(m)	Max Tune-up power(dBm)	G(dBi)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11n HT 20(MIMO)	5825.00	0.2	23.5	5.59	29.09	26.94	494.311	3060	Complies
IEEE 802.11n HT 40(MIMO)	5795.00	0.2	23.0	5.59	28.59	26.44	440.555	3060	Complies
IEEE 802.11ac VHT 20(MIMO)	5825.00	0.2	23.5	5.59	29.09	26.94	494.311	3060	Complies
IEEE 802.11ac VHT 40(MIMO)	5795.00	0.2	23.0	5.59	28.59	26.44	440.555	3060	Complies
IEEE 802.11ac VHT 80(MIMO)	5775.00	0.2	20.0	5.59	25.59	23.44	220.800	3060	Complies
IEEE 802.11ax HE 20(MIMO)	5825.00	0.2	23.5	5.59	29.09	26.94	494.311	3060	Complies
IEEE 802.11ax HE 40(MIMO)	5795.00	0.2	23.0	5.59	28.59	26.44	440.555	3060	Complies
IEEE 802.11ax HE 80(MIMO)	5775.00	0.2	20.0	5.59	25.59	23.44	220.800	3060	Complies

6 Simultaneous Transmission Exempt

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations	
	1	DTS	+ NII

6.1 Sum of the WIFI 2.4GHz & WIFI 5GHz

WIFI 2.4GHz + WIFI 5GHz

Mode	Frequency (MHz)	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WiFi 2.4GHz	2437.00	638.263	3060	0.570	≤1
WiFi 5GHz	5825.00	1106.624	3060		



Report No.: TMWK2303000591KS

Page 20 / 20

Rev.: 01

7 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

☐ No. 12, Ln. 116, Wugong 3rd Rd., Wugu Dist., New Taipei City, Taiwan.

END OF REPORT