************ INFORMATION FOR CERTIFICATION (1) **********

APPLICANT:

Name Address Grantee Code: Applicant Rep.	 Sharp Corporation, CS Promotion Group, Quality Assurance Center 22-22 Nagaike-Cho, Abeno-Ku Osaka 545-8522, Japan <u>APY</u> K. Fukushima 	
CONTACT PERSON:		
Name Address Applicant Rep. Telephone No.	: <u>Sharp Electronics Corporation</u> : <u>Sharp Plaza, Mahwah, New Jersey 07430</u> : <u>Steve Petruska, Product Safety Dept.</u> : <u>201-529-9689</u>	
MEASUREMENT SITE:		
Name	: Japan Quality Assurance Organization Kita-Kansai Testing Center	
Address	: <u>7-1 Ishimaru 1-Chome</u> <u>Minoh-shi, Osaka 562-0027, Japan</u>	
MANUFACTURER:		
Name Address	 Sharp Appliances (Thailand) Ltd. 64 Moo 5, Tambol Bangsamuk Amphur Bangpakong Chachoengsao Province, Thailand 	
FCC IDENTIFICATION	: <u>APYDMR0167</u>	
EQUIPMENT		
Model Name Brand Importer	: <u>Microwave Oven Model R-403KK-T</u> : <u>Sharp Electronics Corp.</u> : <u>Sharp Electronics Corp.</u>	

********** INFORMATION FOR CERTIFICATION (2) **********

- (1) Type(s) of emission: Not Applicable
- (2) Frequency range: 2450 MHz
- (3) Range of operating power and description of means provided for variation of operating power:

<u>RF output power 1100 W</u> (Average power output is controlled by ON/OFF switching cycles.)

(4) Max. power rating as described in the applicable rules:

<u>1100 W</u>

(5) The voltage and current to magnetron:

Magnetron Cat. No. 2M253J(L) : 3.8 kV peak, 349 mA

(6) Function of each electro tube, semiconductor or other active circuit device:

Fixed Magnetron, Type 2M253J(L) as power generator

- (7) Complete circuit diagram: Attached
- (8) Instruction book: Attached
- (9) Tune up procedure over the power range or at specific operating power levels: <u>Not adjustable</u>
- (10) A description of all circuitry and devices provided for determining and stabilizing frequency:

Fixed by magnetron and oven design

(11) A description of any circuit or devices employed for suppression of spurious radiation, for limiting modulation, and for limiting the operating power:

Suppression obtained by shielding design

(12) Identification plate or label: <u>Illustration attached</u> Location of identification plate or label: <u>Photo. Attached</u>

*********** INFORMATION FOR CERTIFICATION (3) **********

DESCRIPTION OF THE MICROWAVE OVEN

Unit Body Dimensions	:	<u>549 mm wide, 314 mm high, 444 mm deep</u>
Door Dimensions	:	<u>450 mm wide, 293 mm high</u> (Viewing Area: 300 mm wide, 153 mm high)
Oven Cavity Dimensions	:	393mm wide, 261 mm high, 426 mm deep
Feed Type and Location	:	Supplied by waveguide located side of oven
Door Seal Type	:	Choke and Capacitive Seals
Magnetron Type	:	2M253J(L) mfd by Toshiba