

Page 1 of 19

Report No.: KS2407S2782E

	TEST REPORT
Report No	KS2407S2782E
FCC ID	2AGOFRC492A
Applicant:	HCS (Suzhou) Limited
Address:	19F-20F, Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, P.R.China
Manufacturer:	HCS (Suzhou) Limited
Address	19F-20F, Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, P.R.China
Product Name	Remote Control
Model/Type reference:	RC4921401/01BRP, RC4921402/01BRP, RC492XXXX/XXRP, RC492XXXX/XXBRP ('X'=0-9, 'B' means packed with battery)
Standard:	47 CFR Part 15, Subpart B
Date of Receipt:	July 12, 2024
Date of Test Date	July 12, 2024 to July 17, 2024
Date of issue:	August 2, 2024
Test result	Pass
Conclusion	The submitted sample was found to COMPLY with the standards above.
Prepared by: ( Printed name + Signature)	Chad Lin Chaol Lin
Approved by:	
(Printed name + Signature)	Sky Dong Sky day
Testing Laboratory Name:	KSIGN(Guangdong) Testing Co., Ltd.
Address:	West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China
A CONTRACTOR	

TRF No. EMC\_R1



## TABLE OF CONTENTS

### Page

1. TEST SUMMARY	3
1.1. Test Standards	3
1.2. Report Version	3
1.3. Test Description	4
1.4. Test Facility	5
1.5. Measurement Uncertainty	5
2. GENERAL INFORMATION	6
	~
	6
2.2. Accessory Equipment Information	6
2.3. Description of Test Modes	6
2.4. Measurement Instruments List	7
3. Emission Test Results (EMI)	8
3.1. Radiated emissions (Below 1GHz)	8
3.2. Radiated emissions (Above 1GHz)	11
4. EUT TEST PHOTOS	14
5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL	15

## TRF No. EMC\_R1



## **1. TEST SUMMARY**

## 1.1. Test Standards

The tests were performed according to following standards:

47 CFR Part 15, Subpart B: Unintentional Radiators

ANSI C63.4 (2014) +A1 (2017): American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

## 1.2. Report Version

Revised No.	Date of issue	Description		
01	August 2, 2024	Original		
87				
	862			

## TRF No. EMC\_R1



## **1.3. Test Description**

Test Item	Standard	Requirement	Result	
Radiated emissions (Below 1GHz)	47 CFR Part 15, Subpart B	15.109, Class B	Pass	
Radiated emissions (Above 1GHz)	47 CFR Part 15, Subpart B	15.109, Class B	Pass	
Conducted Emission at AC power line	7 CFR Part 15, Subpart B	15.107, Class B	N/A	

N/A:According to the EUT functions of EUT, this test is not applicable.

### TRF No. EMC\_R1



## 1.4. Test Facility

### KSIGN(Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified, or accredited by the following organizations:

### CNAS-Lab Code: L 13261

KSIGN(Guangdong) Testing Co., Ltd. has been assessed and proved to be in Compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

## A2LA-Lab Cert. No.: 5457.01

KSIGN(Guangdong) Testing Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the

identified field of testing

### ISED# : 25693 CAB identifier.: CN0096

KSIGN(Guangdong) Testing Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

### FCC-Registration No.: 294912 Designation Number: CN1328

KSIGN(Guangdong) Testing Co., Ltd. EMC Laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

## 1.5. Measurement Uncertainty

Test Items	Measurement Uncertainty	
RE (30-1000MHz)	± 5.7dB	
RE (1-18GHz)	± 4.68dB	
Conducted Emission (150k-30MHz)	± 3.34dB	

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %. Otherwise required by the applicant or Product Regulations.Decision Rule in this report did not consider the uncertainty.

### TRF No. EMC\_R1

## 2. GENERAL INFORMATION

## 2.1. General Description Of EUT

Test Sample Number:	1-1 (Normal Sample)
Product Name:	Remote Control
Model / Type reference:	RC4921401/01BRP, RC4921402/01BRP, RC492XXXX/XXRP, RC492XXXX/XXBRP ('X'=0-9, 'B' means packed with battery)
Model difference:	The differences between product models are the appearance and whether to carry batteries for sale. Different model names are available to meet market demands. Other power supply methods, internal structures, circuits and key components are the same, and do not affect safety and electromagnetic compatibility performance. According to the above information, all tests were performed on RC4921401/01BRP.
Ratings:	DC 3V
Highest Internal Frequency:	Above 1GHz
Classification of Equipment:	Class B

## 2.2. Accessory Equipment Information

Title	Manufacturer	Model No.	Technical Parameters	Provided by
GP Alkaline Battery	1	GN15A	1.5V	Applicant

## 2.3. Description of Test Modes

No.	Title	Description of Mode	
Test Mode1	Normal Work	N/A	

## TRF No. EMC\_R1

## 2.4. Measurement Instruments List

Radiated emissions (Below 1GHz) Radiated emissions (Above 1GHz)					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Until	
Color Signal Generator	Philips	PM5418	672926	2025-01-21	
Log Periodic Antenna	Schwarzbeck	VULB 9163	1230	2025-01-29	
Pre-Amplifier	Schwarzbeck	BBV 9745	9745#129	2025-01-21	
Broadcast Television Signal Generator	R&S	SFE100	141038	2025-01-21	
Analog Signal Generator	Agilent	8648A	3847M00445	2025-01-21	
EMI Test Receiver	R&S	ESR	102525	2025-01-21	
Loop Antenna	Beijin ZHINAN	ZN30900C	18050	2025-01-29	
Horn Antenna	Schwarzbeck	BBHA 9120 D	2023	2025-01-22	
Pre-Amplifier	EMCI	EMC051835SE	980662	2025-01-21	
Spectrum Analyzer	Keysight	N9020A	MY46471971	2025-01-21	

## TRF No. EMC\_R1



## 3. Emission Test Results (EMI)

## 3.1. Radiated emissions (Below 1GHz)

Test Requirement:	15.109, Class B				
. N	Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:				
	Frequency of emission Field strength		Field strength @10m		
Test Limit:	(	(uV/m)	(dBuV/ m)	(uV/m)	(dBuV/m)
	30 - 88	100	40	30	29.5
	88 – 216	150	43.5	45	33.1
	216 – 960 🤍	200	46	60	35.6
	Above 960	500	54	150	43.5
Test Method:	ANSI C63.4-2014		75		
Procedure:	An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor				

## 3.1.1. E.U.T. Operation:

Operating Environment:		
Temperature:	23 °C	
Humidity:	50.3 %	
Atmospheric Pressure:	102 kPa	
Final test mode:	Test Mode1	

## 3.1.2. Test Setup Diagram:



## TRF No. EMC\_R1



## Page 9 of 19

Report No.: KS2407S2782E

## 3.1.3. Test Data:





### TRF No. EMC\_R1



## Page 10 of 19

Report No.: KS2407S2782E

Test Mode1 / Polarization: Vertical



#### TRF No. EMC\_R1



## 3.2. Radiated emissions (Above 1GHz)

Test Requirement:	15.109, Class B			
	Frequency of emission (MHz)	Field strength @3m		
Test Limit:		Average (uV/m)	Average(dB uV/m)	Peak (dBuV/m)
	Above 1GHz	500	54	74
Test Method:	ANSI C63.4-2014	3~		
Procedure:	An initial pre-scan was performed in the chamber using the spectrum analy- in peak detection mode. For below 1GHz test, Quasi-peak measurements v conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. For above 1GHz test, Avera measurements were conducted based on the peak sweep graph. The EUT measured by Horn antenna with 2 orthogonal polarities.			

## 3.2.1. E.U.T. Operation:

Operating Environment:	
Temperature:	23 °C
Humidity:	50.3 %
Atmospheric Pressure:	102 kPa
Final test mode:	Test Mode1

## 3.2.2. Test Setup Diagram:



## TRF No. EMC\_R1



## Page 12 of 19

Report No.: KS2407S2782E

## 3.2.3. Test Data:





### TRF No. EMC\_R1



## Page 13 of 19

Report No.: KS2407S2782E

#### Test Mode1 / Polarization: Vertical



Not: The maximum operating frequency of the product is 2400MHz.

#### TRF No. EMC\_R1



Page 14 of 19

Report No.: KS2407S2782E

## 4. EUT TEST PHOTOS



## TRF No. EMC\_R1



Page 15 of 19

## 5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL



## TRF No. EMC\_R1



## Page 16 of 19

Report No.: KS2407S2782E



### TRF No. EMC\_R1



Page 17 of 19



### TRF No. EMC\_R1



Page 18 of 19

Report No.: KS2407S2782E



--THE END--

## TRF No. EMC\_R1



# **Important Notice**

- 1. The results are valid only for the samples submitted.
- 2. The report is invalid without the "APPROVED Seal" and the "Riding Seam Seal".
- 3. This report is invalid without the signature of the main inspector, reviewer, or approver.
- 4. The testing report cannot be partially copied without the written consent of our laboratory.
- 5. If the report is not stamped with the "CMA" logo, it indicates that the report does not have any social certification effect in China.
- 6. Product information, customer information, and sample sources are all provided by the client, and we are not responsible for their authenticity.
- 7. The inspection basis or inspection items marked with "\*" are not within the scope of CNAS, CMA and A2LA accreditation in this laboratory.
- 8. Reports that are transferred, copied, stolen, impersonated, altered, or tampered with in any media form without authorization are invalid.
- 9. If you have any objections to this report, you can appeal to our unit within 15 days after receiving the report. Failure to do so will not be accepted.
- 10. For situations where compliance decision needs to be made based on test result, such as when there are no relevant decision rules required by the regulations, standards, or technical specifications used, or when there are no relevant customer requirements, the report issued by our laboratory refer to ILAC-G8:09-2019 and CNAS-GL015:2022 using simple acceptance decision rules.

		077777777777777777777776570 <b>6</b> 7777			
I aboratory:	KSIGN(	Guanadona	Testing	Co I	8
Laboratory	1101011	Guungaong	rooting	00., 1	-

- td.
- First Floor West Side, Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu Village, Shatou Community, Shajing Street, Bao'an District, Address: Shenzhen City, Guangdong Province, P. R. China. 518104
  - Tel.: +(86) 0755-29852678
  - Fax.: +(86) 0755-29852397
  - E-mail: info@gdksign.cn
  - Web: www.gdksign.com

## TRF No. EMC R1