

# MPE REPORT

## FCC

APPLICANT

**Safetrust Inc**

MODEL NAME

**SA520**

FCC ID

**2ANI5SA520**

REPORT NUMBER

**HA220420-SFT-002-R25**

# TEST REPORT

**Date of Issue**  
August 17, 2022

**Test Site**  
Hyundai C-Tech, Inc. dba HCT America, Inc.  
1726 Ringwood Ave, San Jose, CA 95131, USA

<b>Applicant</b>	Safetrust Inc
<b>Applicant Address</b>	8116 Mill Creek Rd, Fremont, CA 94539, U.S.A.
<b>FCC ID</b>	2ANI5SA520
<b>Model Name</b>	SA520
<b>EUT Type</b>	IoT Sensor
<b>FCC Classification</b>	Digital Transmission System (DTS) Unlicensed National Information Infrastructure (NII)
<b>FCC Rule Part(s)</b>	Part 1 (§1.1310), Part 2 (§2.1091)
<b>Test Procedure</b>	KDB 447498 D01 v06

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was in accordance with the procedures specified in §2.947. The results in this report apply only to the product which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Hyundai C-Tech, Inc. dba HCT America, Inc. certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**



Yongsoo Park

Test Engineer

**Reviewed By**



Sunwoo Kim

Technical Manager

## REVISION HISTORY

*The revision history for this document is shown in table.*

TEST REPORT NO.	DATE	DESCRIPTION
HA220420-SFT-002-R25	August 17, 2022	Initial Issue

## TABLE OF CONTENTS

1. EUT DESCRIPTION .....	4
2. INTRODUCTION.....	5
2.1. LIMIT .....	5
2.2. MAXIMUM PERMISSIBLE EXPOSURE PREDICTION.....	5
3. RESULT .....	6
3.1. MPE Calculation .....	6
3.2. SUMMARY OF RESULTS .....	7

## 1. EUT DESCRIPTION

<b>Model</b>	SA520	
<b>EUT Type</b>	IoT Sensor	
<b>RF Specification</b>	WIFI 5 GHz (U-NII 3) : 802.11a/n(HT20/40)/ ac(VHT20/40/80) Bluetooth LE MCU (1Mbps) Bluetooth LE MESH (1Mbps) RFID (LF/HF)	
<b>Transmitter Chain</b>	WIFI 5 GHz : SISO Bluetooth LE : SISO (BLE MCU and BLE MESH transmit simultaneously)	
<b>Antenna Specification</b>	WIFI 5 GHz	6.2 dBi (Peak Gain)
	BLE 1M (MCU)	2.0 dBi (Peak Gain)
	BLE 1M (MESH)	2.0 dBi (Peak Gain)
<b>Operating Environment</b>	Indoor and outdoor	
<b>Operating Temperature</b>	-20 °C ~ 50 °C	

### Note(s) :

According to the comparative measurement data in the Evaluation Report, all measurement data from the reference FCC ID below were reused for this report.

FCC ID : 2ANI5SA530

## 2. INTRODUCTION

### 2.1. LIMIT

The limit for Maximum Permissible Exposure (MPE), specified in FCC Rule Part §1.1310 listed in the table below, shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation specified in §1.1310 (b)

Frequency Range (MHz)	E- Field Strength (V/m)	H- Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
<b>(A) Limits for Occupational / Controlled Exposure</b>				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842 / f	4.89 / f	*900 / f <sup>2</sup>	6
30 – 300	61.4	0.163	1.0	6
300 – 1,500	-	-	f / 300	6
1,500 – 100,000	-	-	5	6
<b>(B) Limits for General Population / Uncontrolled Exposure</b>				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824 / f	2.19 / f	*180 / f <sup>2</sup>	30
30 – 300	27.5	0.073	0.2	30
300 – 1,500	-	-	f / 1500	30
1,500 – 100,000	-	-	1.0	30

f = frequency in MHz, \* = Plane-wave equivalent power density

### 2.2. MAXIMUM PERMISSIBLE EXPOSURE PREDICTION

Prediction of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S : Power density (mW/cm<sup>2</sup>)

P : Output power to antenna (mW)

G : Antenna gain in linear scale

R : Distance between the center of radiator and observation point (cm)

### 3. RESULT

#### 3.1. MPE Calculation

Bluetooth LE (MCU)				
Frequency (MHz)	2402 - 2480	MHz		
MPE Limit (mW/cm <sup>2</sup> )	1	mW/cm <sup>2</sup>		
Distance (R)	20	Cm		
Output Power (P)	1	dBm	1.26	mW
Antenna Gain (G)	2	dBi	1.58	-
Power density (S) at distance 20 cm	0.000397	mW/cm <sup>2</sup>	at 20 cm separation distance	

Bluetooth LE (MESH)				
Frequency (MHz)	2402 - 2480	MHz		
MPE Limit (mW/cm <sup>2</sup> )	1	mW/cm <sup>2</sup>		
Distance (R)	20	Cm		
Output Power (P)	1	dBm	1.26	mW
Antenna Gain (G)	2	dBi	1.58	-
Power density (S) at distance 20 cm	0.000397	mW/cm <sup>2</sup>	at 20 cm separation distance	

WIFI 5 GHz (U-NII 3)				
Frequency (MHz)	5745 - 5825	MHz		
MPE Limit (mW/cm <sup>2</sup> )	1	mW/cm <sup>2</sup>		
Distance (R)	20	Cm		
Output Power (P)	10	dBm	10.00	mW
Antenna Gain (G)	6.2	dBi	4.17	-
Power density (S) at distance 20 cm	0.008293	mW/cm <sup>2</sup>	at 20 cm separation distance	

**Note :**

1. Output power (P) e.i.r.p is included tune-up tolerance.

### 3.2. SUMMARY OF RESULTS

Mode	Frequency Range (MHz)	Ant Gain (dBi)	MPE Calculation (mW/cm <sup>2</sup> )	MPE Ratio (PD/MPE Limit)
Bluetooth LE MCU	2402 – 2480	2.0	0.000397	0.000397
Bluetooth LE MESH	2402 – 2480	2.0	0.000397	0.000397
WIFI 5 GHz (U-NII 3)	5745 – 5825	6.2	0.008293	0.008293

Both BLE (MCU) and BLE (MESH) transmit simultaneously, but not with WIFI 5 GHz, which is used for firmware update. Therefore, the worst-case RF exposure is at WIFI 5 GHz single transmitting mode.

#### Sample Calculation

MPE (WIFI 5GHz) at 20cm distance =  $0.008293/1.0 < 1.0$



***END OF TEST REPORT***