

## RF Exposure Requirements

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Chuangyiyuan(Shenzhen)keji Co., Ltd.  
Address of applicant: Room312,Baoli Building, Jixiangnan Street, Longgang District,Shenzhen, Guangdong, China

Manufacturer: Chuangyiyuan(Shenzhen)keji Co., Ltd.  
Address of manufacturer: Room312,Baoli Building, Jixiangnan Street, Longgang District,Shenzhen, Guangdong, China

#### General Description of EUT

Product Name: Bluetooth Speaker  
Trade Name: /  
Model No.: BTS07  
Adding Model(s): BTS06,BTS07,BTS09,BTS-X,Q9,A01L,A03,W13,W15,B62,S16, BT90, BT280, Q50, C6, W11, W12,X3, G2, GT-112,S10, X25, X26, XM-21,S08U, M2,CL-671,S300 , 350T ,350TS  
Rated Voltage: DC 3.7V from Battery  
Power Adapter Model: /  
Serial number: /  
FCC ID: 2BBQ8-BTS07

| Technical Characteristics of EUT |              |
|----------------------------------|--------------|
| Bluetooth Version:               | V5.0 BLE     |
| Frequency Range:                 | 2402-2480MHz |
| RF Output Power:                 | -1.14dBm     |
| Data Rate:                       | 1Mbps        |
| Modulation:                      | GFSK         |
| Quantity of Channels:            | 40           |
| Channel Separation:              | 2MHz         |
| Type of Antenna:                 | PCB          |
| Antenna Gain:                    | 1.7dBi       |

## 1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

## 1.3 Calculation Method

### Bluetooth

Tx frequency range: 2402~2480MHz

Min. test separation distance: 5mm

Maximum Tune-up Conducted Output Power: -1dBm

RF channel transmit frequency: 2440MHz

Result: 0.2482

Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.