

## Variant RF Exposure Report

**Report No.:** SA171206E01B R1

**FCC ID:** NKRM18Q2

**Test Model:** M18Q2FG-1, M14Q2FG-1

**Series Model:** M18Q2F, M14Q2F, M18Q2, M14Q2, M18Q2G, M14Q2G, M18Q2FG, M14Q2FG

**Received Date:** Mar. 26, 2018

**Date of Evaluation:** Apr. 23, 2018

**Issued Date:** Jul. 05, 2018

**Applicant:** Wistron NeWeb Corporation

**Address:** 20 Park Ave. II, Hsinchu Science Park, Hsichu 308, Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1     Certificate of Conformity .....</b>	<b>4</b>
<b>2     RF Exposure .....</b>	<b>5</b>
2.1   Limits For Maximum Permissible Exposure (MPE) .....	5
2.2   MPE Calculation Formula .....	5
2.3   Classification .....	5
2.4   Antenna Gain .....	6
2.5   Calculation Result Of Maximum Conducted Power .....	6

### Release Control Record

Issue No.	Description	Date Issued
SA171206E01B	Original Release	Apr. 30, 2018
SA171206E01B R1	Revise Maximum Conducted Power and Antenna gain	Jul. 05, 2018

## 1 Certificate of Conformity

**Product:** LGA Module

**Brand:** Wistron NeWeb Corporation

**Test Model:** M18Q2FG-1, M14Q2FG-1

**Series Model:** M18Q2F, M14Q2F, M18Q2, M14Q2, M18Q2G, M14Q2G, M18Q2FG, M14Q2FG

**Sample Status:** Engineering Sample

**Applicant:** Wistron NeWeb Corporation

**Date of Evaluation:** Apr. 23, 2018

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

This report is issued as a supplementary report to Sporton report no. FA622601. The differences compared with original report are changing FW and HW (Refer to Hardware Change Notes letter); therefore the re-calculation in this report.

**Prepared by :**



**Date:**

Jul. 05, 2018

Gina Liu / Specialist

**Approved by :**



**Date:**

Jul. 05, 2018

Dylan Chiou / Project Engineer

## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

## 2.4 Antenna Gain

Base on 47 CFR Section 2.1091, the analysis concludes that this product when transmitting in standalone within a host device, is compliant with the FCC RF exposure requirements in mobile exposure condition, provided the conducted power and antenna gain do not exceed the limits for each given frequency band per WWAN technology as follow table:

Antenna Type	Frequency Band (MHz)	Maximum Allowable Antenna Gain (dBi)
Dipole	WCDMA Band 2	7.5
	WCDMA Band 5	8.0
	LTE Band 2	7.5
	LTE Band 4	5.0
	LTE Band 5	8.0
	LTE Band 12	8.0

## 2.5 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Maximum Allowable Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WCDMA Band 2	25.5	7.5	20	0.397	1.000
WCDMA Band 5	25.5	8.0	20	0.446	0.551
LTE Band 2	24.5	7.5	20	0.315	1.000
LTE Band 4	25.0	5.0	20	0.199	1.000
LTE Band 5	25.0	8.0	20	0.397	0.550
LTE Band 12	25.0	8.0	20	0.397	0.466

### Note:

1. By design, maximum LTE RF power of smaller supported bandwidth does not exceed the RF power of largest supported bandwidth; the information is included in "tune-up procedure" exhibit.
2. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.

--- END ---