


TEST REPORT

Application No.: SZCR2103020011AT
Applicant: Jwipc Technology Co., Ltd.
Address of Applicant: 13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China
Manufacturer: Jwipc Technology Co., Ltd.
Address of Manufacturer: 13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China
Factory: Dongguan Scd Technology Co., Ltd.
Address of Factory: No.1 The 2nd Street, Huihuang Industrial Zone, Xiekeng Village, Qingxi Town, Dongguan, 523000 Guangdong, China
Equipment Under Test (EUT):
EUT Name: Android Box
Model No.: D039, DEY21 ♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: NONE
FCC ID: 2AYLND039
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-03-24
Date of Test: 2021-04-15 to 2021-05-08
Date of Issue: 2021-05-10

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-05-10		Original

Authorized for issue by:				
		Harry Wu		
		Harry Wu/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass

Declaration of EUT Family Grouping:

Model No.: D039, DEY21

Only the model D039 was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	7
4.4 TEST LOCATION.....	8
4.5 TEST FACILITY.....	8
4.6 DEVIATION FROM STANDARDS.....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	13
6.1 ANTENNA REQUIREMENT	13
6.1.1 <i>Test Requirement:</i>	13
6.1.2 <i>Conclusion</i>	13
7 RADIO SPECTRUM MATTER TEST RESULTS	14
7.1 CONDUCTED PEAK OUTPUT POWER.....	14
7.1.1 <i>E.U.T. Operation</i>	14
7.1.2 <i>Test Mode Description</i>	14
7.1.3 <i>Test Setup Diagram</i>	15
7.1.4 <i>Measurement Procedure and Data</i>	15
7.2 MINIMUM 6DB BANDWIDTH.....	16
7.2.1 <i>E.U.T. Operation</i>	16
7.2.2 <i>Test Mode Description</i>	16
7.2.3 <i>Test Setup Diagram</i>	16
7.2.4 <i>Measurement Procedure and Data</i>	16
7.3 POWER SPECTRUM DENSITY.....	17
7.3.1 <i>E.U.T. Operation</i>	17
7.3.2 <i>Test Mode Description</i>	17
7.3.3 <i>Test Setup Diagram</i>	17
7.3.4 <i>Measurement Procedure and Data</i>	17
7.4 CONDUCTED BAND EDGES MEASUREMENT.....	18
7.4.1 <i>E.U.T. Operation</i>	18
7.4.2 <i>Test Mode Description</i>	18
7.4.3 <i>Test Setup Diagram</i>	18
7.4.4 <i>Measurement Procedure and Data</i>	19
7.5 CONDUCTED SPURIOUS EMISSIONS.....	20
7.5.1 <i>E.U.T. Operation</i>	20
7.5.2 <i>Test Mode Description</i>	20
7.5.3 <i>Test Setup Diagram</i>	20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, China Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.5.4	Measurement Procedure and Data.....	21
7.6	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	22
7.6.1	E.U.T. Operation	22
7.6.2	Test Mode Description	22
7.6.3	Test Setup Diagram	23
7.6.4	Measurement Procedure and Data.....	23
7.7	RADIATED SPURIOUS EMISSIONS	48
7.7.1	E.U.T. Operation	48
7.7.2	Test Mode Description	48
7.7.3	Test Setup Diagram	49
7.7.4	Measurement Procedure and Data.....	50
8	EMISSION TEST RESULTS	75
8.1	CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz).....	75
8.1.1	E.U.T. Operation	75
8.1.2	Test Mode Description	75
8.1.3	Test Setup Diagram	76
8.1.4	Measurement Procedure and Data.....	76
9	TEST SETUP PHOTO	81
10	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	81
11	APPENDIX.....	82



4 General Information

4.1 Details of E.U.T.

Power supply:	<p>Input: DC 12.0V, 3A from AC/DC Adapter Model1:KPL-040F-VI Manufacturer: Channel Well Technology Input:AC100-240V, 50/60Hz, 1.7A Output:DC12.0V, 3.33A</p> <p>Model2:WA-36A12R Manufacturer: Asian Power Devices Inc. Input:AC100-240V, 50/60Hz, 0.9A Output:DC12.0V, 3.0A</p> <p>Remote Control: DC 3.0V (2 x “AAA” Batteries)</p>
Test Voltage:	AC 120V, 60Hz
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK); 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11
Channel Spacing:	5MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	Antenna 1&2: 4.32dBi Directional Gain: 7.33dBi
Remark:	Two AC/DC adapters were tested. The test data of two AC/DC adapters for Conducted Emissions at AC Power Line (150kHz-30MHz) and Radiated Spurious Emissions below 1GHz were recorded in the report. For other tests, only the worst case(Adapter: KPL-040F-VI) were recorded in the report.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions	$\pm 4.5\text{dB}$
<p>Remark:</p> <p>The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results</p> <ul style="list-style-type: none"> – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. 	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2019-06-13	2022-06-12
EMI Test Receiver	Rohde&Schwarz	ESCI	SEM004-02	2021-03-24	2022-03-23
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2020-07-10	2021-07-09
LISN	Rohde&Schwarz	ENV216	SEM007-01	2020-09-23	2021-09-22
LISN	ETS-LINDGREN	3816/2	SEM007-02	2021-03-24	2022-03-25

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07



Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF906	SHEM009-2	2020-07-27	2022-07-26
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2021-03-24	2022-03-23

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2021-03-27	2024-03-26
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2020-11-02	2021-11-01
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2019-08-08	2022-08-07
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2021-04-08	2022-04-07
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2020-08-14	2023-08-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2020-07-10	2021-07-09

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF906	SHEM009-2	2020-07-27	2022-07-26
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2020-11-14	2023-11-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, CSTC Standards Technical Services Co., Ltd. Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
---------------	-----	-----	-----------	------------	------------

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2020-09-15	2021-09-14
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2020-09-15	2021-09-14
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2021-03-30	2022-03-29



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antennas dipole Antennas. The best case gain of the antennas are 4.32dBi.

Antenna location: Refer to External photos.



7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 18.4 °C Humidity: 48.1 % RH Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥ 500 kHz

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 18.4 °C


Humidity: 48.1 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 18.4 °C Humidity: 48.1 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 18.4 °C Humidity: 48.1 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 18.4 °C


Humidity: 48.1 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 52.3 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Antenna 1 & 2 were tested for Modulation: 802.11b/g. Only the worst case(Antenna 1) was recorded in the report.
Antenna 1, 2 & 1+2, were tested for Modulation: 802.11n(HT20). Only the worst case(Antenna 1+2) was recorded in the report.

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2387.307	4.34	28.51	40.42	60.09	52.52	74.00	-21.48 peak
2	2390.000	4.34	28.52	40.42	59.63	52.07	74.00	-21.93 peak
3 *	2412.000	4.38	28.56	40.43	104.32	96.83	74.00	22.83 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11b; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	4.34	28.52	40.42	49.01	41.45	54.00	-12.55	Average
2	2390.000	4.34	28.52	40.42	49.01	41.45	54.00	-12.55	Average
3 *	2412.000	4.38	28.56	40.43	100.63	93.14	54.00	39.14	Average



Test Mode: 02; Polarity: Vertical; Modulation: 802.11b; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2386.944	4.34	28.51	40.42	64.71	57.14	74.00	-16.86 Peak
2	2390.000	4.34	28.52	40.42	63.70	56.14	74.00	-17.86 Peak
3 *	2412.000	4.38	28.56	40.43	113.80	106.31	74.00	32.31 Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2387.186	4.34	28.51	40.42	57.05	49.48	54.00	-4.52 Average
2	2390.000	4.34	28.52	40.42	56.36	48.80	54.00	-5.20 Average
3 *	2412.000	4.38	28.56	40.43	111.04	103.55	54.00	49.55 Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	104.44	97.08	74.00	23.08	peak
2 2483.500	4.49	28.67	40.47	59.42	52.11	74.00	-21.89	peak
3 2483.890	4.49	28.67	40.47	60.85	53.54	74.00	-20.46	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1 *	2462.000	4.46	28.64	40.46	101.01	93.65	54.00	39.65 Average
2	2483.500	4.49	28.67	40.47	50.79	43.48	54.00	-10.52 Average
3	2483.589	4.49	28.67	40.47	50.52	43.21	54.00	-10.79 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	114.32	106.96	74.00	32.96	Peak
2 2483.500	4.49	28.67	40.47	65.27	57.96	74.00	-16.04	Peak
3 2483.820	4.49	28.67	40.47	64.80	57.49	74.00	-16.51	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	110.87	103.51	54.00	49.51	Average
2 2483.500	4.49	28.67	40.47	58.07	50.76	54.00	-3.24	Average
3 2483.539	4.49	28.67	40.47	57.76	50.45	54.00	-3.55	Average



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.605	4.34	28.52	40.42	62.04	54.48	74.00	-19.52 peak
2	2390.000	4.34	28.52	40.42	61.29	53.73	74.00	-20.27 peak
3 *	2412.000	4.38	28.56	40.43	104.67	97.18	74.00	23.18 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.968	4.34	28.52	40.42	49.14	41.58	54.00	-12.42 Average
2	2390.000	4.34	28.52	40.42	49.14	41.58	54.00	-12.42 Average
3 *	2412.000	4.38	28.56	40.43	94.71	87.22	54.00	33.22 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.968	4.34	28.52	40.42	70.83	63.27	74.00	-10.73 Peak
2	2390.000	4.34	28.52	40.42	70.83	63.27	74.00	-10.73 Peak
3 *	2412.000	4.38	28.56	40.43	111.92	104.43	74.00	30.43 Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	4.34	28.52	40.42	57.62	50.06	54.00	-3.94	Average
2	2390.000	4.34	28.52	40.42	57.33	49.77	54.00	-4.23	Average
3 *	2412.000	4.38	28.56	40.43	103.08	95.59	54.00	41.59	Average



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	4.46	28.64	40.46	103.76	96.40	74.00	22.40 peak
2	2483.500	4.49	28.67	40.47	59.34	52.03	74.00	-21.97 peak
3	2484.994	4.50	28.68	40.47	60.53	53.24	74.00	-20.76 peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	4.46	28.64	40.46	93.83	86.47	54.00	32.47 Average
2	2483.500	4.49	28.67	40.47	48.15	40.84	54.00	-13.16 Average
3	2483.790	4.49	28.67	40.47	48.14	40.83	54.00	-13.17 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	110.75	103.39	74.00	29.39	Peak
2 2483.500	4.49	28.67	40.47	66.13	58.82	74.00	-15.18	Peak
3 2484.994	4.50	28.68	40.47	66.10	58.81	74.00	-15.19	Peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11g; Bandwidth: 20MHz; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	101.09	93.73	54.00	39.73	Average
2 2483.500	4.49	28.67	40.47	53.84	46.53	54.00	-7.47	Average
3 2483.890	4.49	28.67	40.47	53.61	46.30	54.00	-7.70	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.726	4.34	28.52	40.42	62.62	55.06	74.00	-18.94 peak
2	2390.000	4.34	28.52	40.42	62.19	54.63	74.00	-19.37 peak
3 *	2412.000	4.38	28.56	40.43	106.53	99.04	74.00	25.04 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11n; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.968	4.34	28.52	40.42	48.94	41.38	54.00	-12.62 Average
2	2390.000	4.34	28.52	40.42	48.94	41.38	54.00	-12.62 Average
3 *	2412.000	4.38	28.56	40.43	96.97	89.48	54.00	35.48 Average



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	4.34	28.52	40.42	74.06	66.50	74.00	-7.50	Peak
2	2390.000	4.34	28.52	40.42	74.06	66.50	74.00	-7.50	Peak
3 *	2412.000	4.38	28.56	40.43	114.68	107.19	74.00	33.19	Peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.242	4.34	28.52	40.42	57.72	50.16	54.00	-3.84 Average
2	2390.000	4.34	28.52	40.42	57.42	49.86	54.00	-4.14 Average
3 *	2412.000	4.38	28.56	40.43	105.37	97.88	54.00	43.88 Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	105.08	97.72	74.00	23.72	peak
2 2483.500	4.49	28.67	40.47	58.43	51.12	74.00	-22.88	peak
3 2484.693	4.50	28.68	40.47	59.74	52.45	74.00	-21.55	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	94.76	87.40	54.00	33.40	Average
2 2483.500	4.49	28.67	40.47	47.33	40.02	54.00	-13.98	Average
3 2483.840	4.49	28.67	40.47	47.69	40.38	54.00	-13.62	Average



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	40.46	113.97	106.61	74.00	32.61	Peak
2 2483.500	4.49	28.67	40.47	67.03	59.72	74.00	-14.28	Peak
3 2484.392	4.50	28.67	40.47	67.63	60.33	74.00	-13.67	Peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	4.46	28.64	40.46	104.39	97.03	54.00	43.03 Average
2 2483.500	4.49	28.67	40.47	53.82	46.51	54.00	-7.49 Average
3 2483.940	4.49	28.67	40.47	53.48	46.17	54.00	-7.83 Average



7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3
Above 1000	500	3

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 52.3 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



Below 30MHz

30MHz-1GHz



Above 1GHz



7.7.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Antenna 1 & 2 were tested for Modulation: 802.11b/g. Only the worst case(Antenna 1) was recorded in the report.

Antenna 1, 2 & 1+2, were tested for Modulation: 802.11n(HT20). Only the worst case(Antenna 1+2) was recorded in the report.

Model1:KPL-040F-VI;Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Condition: 10m HORIZONTAL

Job No. : 20011AT


Test Mode: 02

: 2.4G

	Ant Freq	Preamp Factor	Cable Loss	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.071	18.65	32.50	0.88	28.45	15.48	29.50	-14.02 QP
2	38.212	20.00	32.50	0.92	27.54	15.96	29.50	-13.54 QP
3	138.874	19.55	32.43	1.44	27.65	16.21	33.00	-16.79 QP
4	517.248	24.27	32.30	2.89	27.65	22.51	35.60	-13.09 QP
5 pp	625.078	26.25	32.30	3.12	33.65	30.72	35.60	-4.88 QP
6	952.094	29.86	31.12	3.56	27.45	29.75	35.60	-5.85 QP



Model1:KPL-040F-VI;Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Condition: 10m VERTICAL

Job No. : 20011AT

Test Mode: 02

: 2.4G

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	82.071	14.29	32.46	1.18	33.45	16.46	29.50	-13.04	QP
2	pp 106.759	16.02	32.45	1.29	41.20	26.06	33.00	-6.94	QP
3	128.113	18.08	32.43	1.38	33.44	20.47	33.00	-12.53	QP
4	222.950	16.21	32.40	1.79	31.56	17.16	35.60	-18.44	QP
5	318.817	20.24	32.38	2.18	30.62	20.66	35.60	-14.94	QP
6	625.078	26.25	32.30	3.12	27.45	24.52	35.60	-11.08	QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: $\mu\text{V}/\text{m}$;

L_{10} : Level @ 10m distance. Unit: $\mu\text{V}/\text{m}$;

D_3 : 3m distance. Unit: m


D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m ($\mu\text{V}/\text{m}$)	Level @ 3m ($\mu\text{V}/\text{m}$)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
82.07	16.46	6.65	22.18	26.92	40.00	-13.08	V
106.76	26.06	20.09	66.97	36.52	43.50	-6.98	V
128.11	20.47	10.56	35.19	30.93	43.50	-12.57	V
222.95	17.16	7.21	24.04	27.62	46.00	-18.38	V
318.82	20.66	10.79	35.96	31.12	46.00	-14.88	V
625.08	24.52	16.83	56.09	34.98	46.00	-11.02	V
31.07	15.48	5.94	19.81	25.94	40.00	-14.06	H
38.21	15.96	6.28	20.94	26.42	40.00	-13.58	H
138.87	16.21	6.46	21.55	26.67	43.50	-16.83	H
517.25	22.51	13.35	44.50	32.97	46.00	-13.03	H
625.08	30.72	34.36	114.52	41.18	46.00	-4.82	H
952.09	29.75	30.73	102.42	40.21	46.00	-5.79	H



Model2:WA-36A12R;Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Condition: 10m HORIZONTAL

Job No. : 20011AT


Test Mode: 02

: 2.4G WA-36A12R

	Ant	Preamp	Cable	Read	Limit	Over		
Freq	Factor	Factor	Loss	Level	Line	Limit	Remark	
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.071	18.65	32.50	0.88	30.10	17.13	29.50	-12.37 QP
2	138.874	19.55	32.43	1.44	29.40	17.96	33.00	-15.04 QP
3	331.355	20.50	32.37	2.25	24.01	14.39	35.60	-21.21 QP
4	625.078	26.25	32.30	3.12	30.40	27.47	35.60	-8.13 QP
5	719.200	27.48	32.26	3.32	29.40	27.94	35.60	-7.66 QP
6 pp	952.094	29.86	31.12	3.56	27.40	29.70	35.60	-5.90 QP



Model2:WA-36A12R;Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Condition: 10m VERTICAL

Job No. : 20011AT

Test Mode: 02

: 2.4G WA-36A12R

	Ant	Preamp	Cable	Read	Limit	Over		
Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	39.299	20.00	32.50	0.93	28.40	16.83	29.50	-12.67 QP
2	59.025	19.39	32.49	1.04	30.10	18.04	29.50	-11.46 QP
3	106.759	16.02	32.45	1.29	38.40	23.26	33.00	-9.74 QP
4	128.113	18.08	32.43	1.38	30.39	17.42	33.00	-15.58 QP
5	374.623	21.34	32.32	2.35	29.40	20.77	35.60	-14.83 QP
6 pp	955.438	29.88	31.09	3.57	24.60	26.96	35.60	-8.64 QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;


D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
31.07	17.13	7.19	23.95	27.59	40.00	-12.41	H
138.87	17.96	7.91	26.36	28.42	43.50	-15.08	H
331.36	14.39	5.24	17.47	24.85	46.00	-21.15	H
625.08	27.47	23.63	78.77	37.93	46.00	-8.07	H
719.20	27.94	24.95	83.15	38.40	46.00	-7.60	H
952.09	29.70	30.55	101.83	40.16	46.00	-5.84	H
39.30	16.83	6.94	23.14	27.29	40.00	-12.71	V
59.03	18.04	7.98	26.60	28.50	40.00	-11.50	V
106.76	23.26	14.55	48.52	33.72	43.50	-9.78	V
128.11	17.42	7.43	24.77	27.88	43.50	-15.62	V
374.62	20.77	10.93	36.42	31.23	46.00	-14.77	V
955.44	26.96	22.28	74.28	37.42	46.00	-8.58	V

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.73	42.25	74.00	-31.75	peak
2	4405.090	6.67	33.44	41.79	48.12	46.44	74.00	-27.56	peak
3	4824.000	7.12	34.00	42.16	48.93	47.89	74.00	-26.11	peak
4	6303.890	8.27	35.41	42.18	48.99	50.49	74.00	-23.51	peak
5	7236.000	8.77	36.09	41.48	46.92	50.30	74.00	-23.70	peak
6	9648.000	10.79	37.69	37.69	41.86	52.65	74.00	-21.35	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1213.677	2.79	24.65	39.77	51.11	38.78	74.00	-35.22	peak
2	4354.454	6.63	33.35	41.74	48.29	46.53	74.00	-27.47	peak
3	4824.000	7.12	34.00	42.16	47.57	46.53	74.00	-27.47	peak
4	6231.427	8.27	35.34	42.23	49.10	50.48	74.00	-23.52	peak
5	7236.000	8.77	36.09	41.48	47.09	50.47	74.00	-23.53	peak
6	9648.000	10.79	37.69	37.69	41.97	52.76	74.00	-21.24	peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11b; Bandwidth: 20MHz; Channel: middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.78	42.30	74.00	-31.70	peak
2	4456.315	6.72	33.53	41.84	49.41	47.82	74.00	-26.18	peak
3	4874.000	7.17	34.05	42.20	47.50	46.52	74.00	-27.48	peak
4	6036.421	8.26	35.14	42.37	50.04	51.07	74.00	-22.93	peak
5	7311.000	8.84	36.15	41.41	48.11	51.69	74.00	-22.31	peak
6	9748.000	10.76	37.75	37.52	42.46	53.45	74.00	-20.55	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	49.52	38.04	74.00	-35.96	peak
2	4254.921	6.53	33.17	41.65	49.34	47.39	74.00	-26.61	peak
3	4874.000	7.17	34.05	42.20	48.62	47.64	74.00	-26.36	peak
4	6914.763	8.50	35.85	41.76	47.87	50.46	74.00	-23.54	peak
5	7311.000	8.84	36.15	41.41	47.71	51.29	74.00	-22.71	peak
6	9748.000	10.76	37.75	37.52	41.76	52.75	74.00	-21.25	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.57	42.09	74.00	-31.91	peak
2	4242.641	6.52	33.15	41.64	49.18	47.21	74.00	-26.79	peak
3	4924.000	7.22	34.11	42.24	47.11	46.20	74.00	-27.80	peak
4	6756.708	8.42	35.76	41.86	48.90	51.22	74.00	-22.78	peak
5	7386.000	8.91	36.21	41.34	47.81	51.59	74.00	-22.41	peak
6	9848.000	10.73	37.81	37.35	41.40	52.59	74.00	-21.41	peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11b; Bandwidth: 20MHz; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	49.86	38.38	74.00	-35.62	peak
2	4417.841	6.68	33.46	41.80	49.29	47.63	74.00	-26.37	peak
3	4924.000	7.22	34.11	42.24	49.69	48.78	74.00	-25.22	peak
4	6974.982	8.53	35.89	41.72	48.29	50.99	74.00	-23.01	peak
5	7386.000	8.91	36.21	41.34	47.62	51.40	74.00	-22.60	peak
6	9848.000	10.73	37.81	37.35	42.30	53.49	74.00	-20.51	peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	54.18	42.70	74.00	-31.30	peak
2	4242.641	6.52	33.15	41.64	49.75	47.78	74.00	-26.22	peak
3	4824.000	7.12	34.00	42.16	48.16	47.12	74.00	-26.88	peak
4	6914.763	8.50	35.85	41.76	48.47	51.06	74.00	-22.94	peak
5	7236.000	8.77	36.09	41.48	47.02	50.40	74.00	-23.60	peak
6	9648.000	10.79	37.69	37.69	42.51	53.30	74.00	-20.70	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1217.190	2.80	24.67	39.77	51.72	39.42	74.00	-34.58 peak
2 4392.376	6.66	33.42	41.78	48.35	46.65	74.00	-27.35 peak
3 4824.000	7.12	34.00	42.16	48.56	47.52	74.00	-26.48 peak
4 6159.797	8.27	35.26	42.28	49.82	51.07	74.00	-22.93 peak
5 7236.000	8.77	36.09	41.48	47.59	50.97	74.00	-23.03 peak
6 9648.000	10.79	37.69	37.69	42.47	53.26	74.00	-20.74 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.36	41.88	74.00	-32.12	peak
2	4098.010	6.38	32.88	41.50	49.23	46.99	74.00	-27.01	peak
3	4874.000	7.17	34.05	42.20	47.94	46.96	74.00	-27.04	peak
4	6698.373	8.39	35.72	41.90	48.15	50.36	74.00	-23.64	peak
5	7311.000	8.84	36.15	41.41	47.46	51.04	74.00	-22.96	peak
6	9748.000	10.76	37.75	37.52	42.29	53.28	74.00	-20.72	peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11g; Bandwidth: 20MHz; Channel: middle




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	50.46	38.98	74.00	-35.02	peak
2	4417.841	6.68	33.46	41.80	48.49	46.83	74.00	-27.17	peak
3	4874.000	7.17	34.05	42.20	48.25	47.27	74.00	-26.73	peak
4	6974.982	8.53	35.89	41.72	48.25	50.95	74.00	-23.05	peak
5	7311.000	8.84	36.15	41.41	47.37	50.95	74.00	-23.05	peak
6	9748.000	10.76	37.75	37.52	42.33	53.32	74.00	-20.68	peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11g; Bandwidth: 20MHz; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.85	42.37	74.00	-31.63	peak
2	4405.090	6.67	33.44	41.79	49.36	47.68	74.00	-26.32	peak
3	4924.000	7.22	34.11	42.24	47.28	46.37	74.00	-27.63	peak
4	6488.754	8.28	35.59	42.04	50.53	52.36	74.00	-21.64	peak
5	7386.000	8.91	36.21	41.34	48.03	51.81	74.00	-22.19	peak
6	9848.000	10.73	37.81	37.35	41.98	53.17	74.00	-20.83	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	50.93	39.45	74.00	-34.55	peak
2	4405.090	6.67	33.44	41.79	49.04	47.36	74.00	-26.64	peak
3	4924.000	7.22	34.11	42.24	48.66	47.75	74.00	-26.25	peak
4	6795.879	8.44	35.78	41.83	48.75	51.14	74.00	-22.86	peak
5	7386.000	8.91	36.21	41.34	47.72	51.50	74.00	-22.50	peak
6	9848.000	10.73	37.81	37.35	42.00	53.19	74.00	-20.81	peak

Test Mode: 02; Polarity: Horizontal; Modulation: 802.11n; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	52.97	41.49	74.00	-32.51	peak
2	4392.376	6.66	33.42	41.78	48.95	47.25	74.00	-26.75	peak
3	4824.000	7.12	34.00	42.16	48.09	47.05	74.00	-26.95	peak
4	6974.982	8.53	35.89	41.72	47.74	50.44	74.00	-23.56	peak
5	7236.000	8.77	36.09	41.48	47.60	50.98	74.00	-23.02	peak
6	9648.000	10.79	37.69	37.69	42.46	53.25	74.00	-20.75	peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1220.714	2.80	24.68	39.77	49.80	37.51	74.00 -36.49 peak
2	4443.453	6.71	33.50	41.82	48.12	46.51	74.00 -27.49 peak
3	4824.000	7.12	34.00	42.16	47.26	46.22	74.00 -27.78 peak
4	6737.207	8.41	35.75	41.87	48.28	50.57	74.00 -23.43 peak
5	7236.000	8.77	36.09	41.48	46.88	50.26	74.00 -23.74 peak
6	9648.000	10.79	37.69	37.69	42.18	52.97	74.00 -21.03 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11n; Bandwidth: 20MHz; Channel: middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	3.07	25.33	39.88	53.70	42.22	74.00	-31.78	peak
2	4430.628	6.70	33.48	41.81	48.31	46.68	74.00	-27.32	peak
3	4874.000	7.17	34.05	42.20	47.20	46.22	74.00	-27.78	peak
4	6358.789	8.27	35.46	42.14	49.22	50.81	74.00	-23.19	peak
5	7311.000	8.84	36.15	41.41	48.13	51.71	74.00	-22.29	peak
6	9748.000	10.76	37.75	37.52	42.36	53.35	74.00	-20.65	peak




Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1498.781	3.26	25.80	39.95	48.66	37.77	74.00	-36.23	peak
2	4316.859	6.59	33.28	41.71	48.49	46.65	74.00	-27.35	peak
3	4874.000	7.17	34.05	42.20	47.63	46.65	74.00	-27.35	peak
4	6602.265	8.33	35.66	41.97	48.84	50.86	74.00	-23.14	peak
5	7311.000	8.84	36.15	41.41	47.57	51.15	74.00	-22.85	peak
6	9748.000	10.76	37.75	37.52	41.88	52.87	74.00	-21.13	peak

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1374.295	3.07	25.33	39.88	53.58	42.10	74.00 -31.90 peak
2	3992.781	6.27	32.69	41.40	49.38	46.94	74.00 -27.06 peak
3	4924.000	7.22	34.11	42.24	47.61	46.70	74.00 -27.30 peak
4	6507.536	8.28	35.60	42.03	49.26	51.11	74.00 -22.89 peak
5	7386.000	8.91	36.21	41.34	47.47	51.25	74.00 -22.75 peak
6	9848.000	10.73	37.81	37.35	41.38	52.57	74.00 -21.43 peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11n; Bandwidth: 20MHz; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 20011AT/20012AT
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1213.677	2.79	24.65	39.77	50.64	38.31	74.00 -35.69 peak
2	4354.454	6.63	33.35	41.74	48.46	46.70	74.00 -27.30 peak
3	4924.000	7.22	34.11	42.24	48.13	47.22	74.00 -26.78 peak
4	5797.032	8.23	34.90	42.38	50.40	51.15	74.00 -22.85 peak
5	7386.000	8.91	36.21	41.34	46.92	50.70	74.00 -23.30 peak
6	9848.000	10.73	37.81	37.35	41.86	53.05	74.00 -20.95 peak



8 Emission Test Results

8.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement: 47 CFR Part 15, Subpart C 15.247, 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

8.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C

Humidity: 50.3 % RH


Atmospheric Pressure: 1010 mbar

8.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); Only the data of worst case is recorded in the report.



8.1.3 Test Setup Diagram




8.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Model1:KPL-040F-VI;Test Mode: 02; Line: Live line; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : Shielding Room
Condition: Line
Job No. : 20011AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1573	0.03	9.62	12.54	22.19	55.60	-33.41	Average
2	0.1573	0.03	9.62	31.36	41.01	65.60	-24.59	QP
3	0.1945	0.04	9.64	8.05	17.73	53.84	-36.11	Average
4	0.1945	0.04	9.64	25.32	35.00	63.84	-28.84	QP
5	0.2232	0.04	9.64	5.87	15.55	52.70	-37.15	Average
6	0.2232	0.04	9.64	21.19	30.87	62.70	-31.83	QP
7	0.5731	0.08	9.68	22.42	32.18	46.00	-13.82	Average
8	0.5731	0.08	9.68	29.00	38.76	56.00	-17.24	QP
9	3.4538	0.15	9.72	10.01	19.88	46.00	-26.12	Average
10	3.4538	0.15	9.72	14.58	24.45	56.00	-31.55	QP
11	21.9463	0.17	9.94	7.19	17.30	50.00	-32.70	Average
12	21.9463	0.17	9.94	12.63	22.74	60.00	-37.26	QP



Model1:KPL-040F-VI;Test Mode: 02; Line: Neutral Line; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : Shielding Room
Condition: Neutral
Job No. : 20011AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1540	0.03	9.62	15.94	25.59	55.78	-30.19	Average
2	0.1540	0.03	9.62	32.08	41.73	65.78	-24.05	QP
3	0.2197	0.04	9.64	7.05	16.73	52.83	-36.10	Average
4	0.2197	0.04	9.64	22.19	31.87	62.83	-30.96	QP
5	0.2208	0.04	9.64	5.33	15.01	52.79	-37.78	Average
6	0.2208	0.04	9.64	21.97	31.65	62.79	-31.14	QP
7	0.5701	0.08	9.67	21.67	31.42	46.00	-14.58	Average
8	0.5701	0.08	9.67	29.53	39.28	56.00	-16.72	QP
9	3.4538	0.15	9.71	10.12	19.98	46.00	-26.02	Average
10	3.4538	0.15	9.71	14.74	24.60	56.00	-31.40	QP
11	8.7293	0.16	9.92	10.81	20.89	50.00	-29.11	Average
12	8.7293	0.16	9.92	16.43	26.51	60.00	-33.49	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

Model2:WA-36A12R; Test Mode: 02; Line: Live line ; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : Shielding Room
Condition: Line
Job No. : 20011AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1532	0.03	9.62	-1.53	8.12	55.82	-47.70	Average
2	0.1532	0.03	9.62	29.83	39.48	65.82	-26.34	QP
3	0.6899	0.09	9.68	16.59	26.36	46.00	-19.64	Average
4	0.6899	0.09	9.68	28.21	37.98	56.00	-18.02	QP
5	0.8174	0.09	9.68	13.27	23.04	46.00	-22.96	Average
6	0.8174	0.09	9.68	32.26	42.03	56.00	-13.97	QP
7	2.9307	0.14	9.71	18.83	28.68	46.00	-17.32	Average
8	2.9307	0.14	9.71	32.67	42.52	56.00	-13.48	QP
9	3.5466	0.15	9.73	20.94	30.82	46.00	-15.18	Average
10	3.5466	0.15	9.73	33.63	43.51	56.00	-12.49	QP
11	20.1625	0.17	9.92	20.17	30.26	50.00	-19.74	Average
12	20.1625	0.17	9.92	28.35	38.44	60.00	-21.56	QP



Model2:WA-36A12R;Test Mode: 02; Line: Neutral Line; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : Shielding Room
Condition: Neutral
Job No. : 20011AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1557	0.03	9.62	14.12	23.77	55.69	-31.92	Average
2	0.1557	0.03	9.62	29.87	39.52	65.69	-26.17	QP
3	0.6648	0.08	9.67	17.93	27.68	46.00	-18.32	Average
4	0.6648	0.08	9.67	27.34	37.09	56.00	-18.91	QP
5	0.8483	0.09	9.67	17.26	27.02	46.00	-18.98	Average
6	0.8483	0.09	9.67	33.04	42.80	56.00	-13.20	QP
7	2.7648	0.14	9.70	23.74	33.58	46.00	-12.42	Average
8	2.7648	0.14	9.70	31.65	41.49	56.00	-14.51	QP
9	3.5466	0.15	9.72	18.50	28.37	46.00	-17.63	Average
10	3.5466	0.15	9.72	34.11	43.98	56.00	-12.02	QP
11	19.8445	0.17	9.97	19.15	29.29	50.00	-20.71	Average
12	19.8445	0.17	9.97	27.67	37.81	60.00	-22.19	QP



9 Test Setup Photo

Refer to Setup Photos

10 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2103020011AT



11 Appendix



1. Duty Cycle



1.1 Test Result

Test Mode	Channel Frequency (MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
802.11b	2412	SISO	1	8.410	8.450	99.53	0.02
	2437	SISO	1	8.410	8.450	99.53	0.02
	2462	SISO	1	8.410	8.440	99.64	0.02
802.11g	2412	SISO	1	1.364	1.405	97.08	0.13
	2437	SISO	1	1.366	1.406	97.16	0.13
	2462	SISO	1	1.365	1.406	97.08	0.13
802.11n(HT20)	2412	MIMO	1	1.308	1.350	96.89	0.14
	2437	MIMO	1	1.308	1.350	96.89	0.14
	2462	MIMO	1	1.307	1.349	96.89	0.14





1.2 Test Graph








Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com









2. Bandwidth



2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
802.11b	2412	SISO	1	8.619	PASS
	2437	SISO	1	8.603	PASS
	2462	SISO	1	9.056	PASS
802.11g	2412	SISO	1	16.386	PASS
	2437	SISO	1	16.389	PASS
	2462	SISO	1	16.393	PASS
802.11n(HT20)	2412	MIMO	1	17.622	PASS
	2437	MIMO	1	17.605	PASS
	2462	MIMO	1	17.607	PASS



2.2 Test Graph - 6dB Bandwidth










Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com








3. Maximum Conducted Output Power



3.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Measured Average Output Power (dBm)			Directional gain(dBi)	Limits (dBm)	Verdict
			Ant 1	Ant 2	Total			
802.11b	2412	SISO	14.84	14.99	/	4.32	30	PASS
	2437	SISO	15.19	15.36	/	4.32	30	PASS
	2462	SISO	15.56	15.69	/	4.32	30	PASS
802.11g	2412	SISO	15.27	15.71	/	4.32	30	PASS
	2437	SISO	15.69	16.02	/	4.32	30	PASS
	2462	SISO	15.93	16.20	/	4.32	30	PASS
802.11n(HT20)	2412	MIMO	15.20	15.58	18.40	7.33	28.67	PASS
	2437	MIMO	15.50	15.86	18.69	7.33	28.67	PASS
	2462	MIMO	15.66	16.14	18.92	7.33	28.67	PASS



3.2 Test Graph

































4. Maximum Power Spectral Density (PSD)



4.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)			Limits (dBm/3kHz)	Verdict
			Ant 1	Ant 2	Total		
802.11b	2412	SISO	-7.29	-6.88	/	≤8	PASS
	2437	SISO	-6.23	-6.89	/	≤8	PASS
	2462	SISO	-6.63	-5.57	/	≤8	PASS
802.11g	2412	SISO	-10.31	-9.95	/	≤8	PASS
	2437	SISO	-8.87	-8.51	/	≤8	PASS
	2462	SISO	-8.71	-9.35	/	≤8	PASS
802.11n(HT20)	2412	MIMO	-9.73	-8.58	-7.28	≤8	PASS
	2437	MIMO	-9.64	-9.67	-7.08	≤8	PASS
	2462	MIMO	-9.51	-9.31	-7.21	≤8	PASS



4.2 Test Graph



















Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com


















5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
802.11b	2412	SISO	1	Refer to test graph	-22.65	PASS
	2437	SISO	1	Refer to test graph	-22.65	PASS
	2462	SISO	1	Refer to test graph	-22.65	PASS
802.11g	2412	SISO	1	Refer to test graph	-24.81	PASS
	2437	SISO	1	Refer to test graph	-24.81	PASS
	2462	SISO	1	Refer to test graph	-24.81	PASS
802.11n(HT20)	2412	MIMO	MIMO	Refer to test graph	-25.00	PASS
	2437	MIMO	MIMO	Refer to test graph	-25.00	PASS
	2462	MIMO	MIMO	Refer to test graph	-25.00	PASS



5.2 Test Graph






























- End of the Report -

