



FCC PART 15.249 TEST REPORT

For

Shenzhen Jiayz photo industrial ., Ltd

A16 Building, Intelligent Terminal Industrial Park of Silicon Valley Power, Guanlan, Longhua
District, Shenzhen, China

FCC ID: 2ARN3-BLINK500PROTX

Report Type: Original Report	Product Type: 2.4GHz Dual-Channel Wireless Microphone
Report Number: RSZ200813813-00	
Report Date: 2020-09-27 Jacob Kong	<i>Jacob Kong</i>
Reviewed By: RF Engineer	
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC§15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 – AC LINE CONDUCTED EMISSIONS.....	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	10
CORRECTED FACTOR & MARGIN CALCULATION	11
TEST DATA	11
FCC§15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS.....	14
APPLICABLE STANDARD	14
TEST EQUIPMENT SETUP	14
EUT SETUP	15
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST DATA	16
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	2.4GHz Dual-Channel Wireless Microphone
Tested Model	Blink500 Pro TX
Multiple Model	Blink500 Pro TXW
Model Differences	Refer to the DoS letter
Frequency Range	2406-2474MHz
Maximum Field Strength	97.29dBuV/m @3m
Antenna Specification	PCB Antenna: 2dBi
Voltage Range	DC 3.7 V from battery
Date of Test	2020-08-20
Sample serial number	RSZ200813813-RF-S1 (Assigned by BACL, Shenzhen)
Received date	2020-08-13
Sample/EUT Status	Good condition
Adapter information	N/A

Objective

This test report is in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1℃
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing by manufacturer.

18 channels are provided to testing

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2406	10	2442
2	2410	11	2446
3	2414	12	2450
4	2418	13	2454
5	2422	14	2458
6	2426	15	2462
7	2430	16	2466
8	2434	17	2470
9	2438	18	2474

EUT was tested with Channel 1, 9 and 18.

EUT Exercise Software

No exercise software was used.

Equipment Modifications

No modifications were made to the unit tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
MOBIOLA	Mobile Phone	MS55L1	MS55L1
AOHAI	Adapter	A138A-120150U-CN2	A138A-120150U-CN2

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-Shielded Un-Detachable AC Cable	1.0	Socket	Mains
Unshielded Detachable USB Cable	1.0	Adapter	EUT
Unshielded Detachable Audio Cable	0.5	Mobile Phone	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Compliance
15.205, §15.209, §15.249(d)	Radiated Emissions& Outside of Band Emission	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2019/11/29	2020/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2019/11/29	2020/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-02 1304	2017/12/06	2020/12/05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Pass

FCC §15.207 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2020-08-20.

Test Mode: Charging and transmitting

AC 120V/60 Hz, Line




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.467010	39.5	9.000	L1	19.8	17.1	56.6
0.490590	41.2	9.000	L1	19.8	15.0	56.2
0.880830	32.2	9.000	L1	19.8	23.8	56.0
0.995270	33.1	9.000	L1	19.9	22.9	56.0
1.057890	36.7	9.000	L1	19.9	19.3	56.0
1.113110	36.1	9.000	L1	19.8	19.9	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.467010	36.6	9.000	L1	19.8	10.0	46.6
0.490590	37.7	9.000	L1	19.8	8.4	46.2
0.880830	26.2	9.000	L1	19.8	19.8	46.0
0.995270	27.8	9.000	L1	19.9	18.2	46.0
1.057890	28.7	9.000	L1	19.9	17.3	46.0
1.113110	28.9	9.000	L1	19.8	17.1	46.0

AC 120V/60 Hz, Neutral**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.462950	36.2	9.000	N	19.8	20.5	56.6
0.490590	38.2	9.000	N	19.8	18.0	56.2
0.841430	33.5	9.000	N	19.8	22.5	56.0
0.991210	34.1	9.000	N	19.8	21.9	56.0
1.058070	37.4	9.000	N	19.8	18.6	56.0
1.152510	37.1	9.000	N	19.8	18.9	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.218000	35.2	9.000	N	19.8	17.7	52.9
0.470000	32.3	9.000	N	19.8	14.3	46.5
0.494000	31.6	9.000	N	19.8	14.5	46.1
0.962000	30.1	9.000	N	19.8	15.9	46.0
1.038000	30.2	9.000	N	19.8	15.8	46.0
1.142000	28.1	9.000	N	19.8	17.9	46.0

FCC§15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS**Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	Unknown	PK
	1 MHz	10 Hz	Unknown	Average


Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.


All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	25~29 °C
Relative Humidity:	56~64 %
ATM Pressure:	101.0 kPa

The testing was performed by Charlie Cha on 2020-08-20 for below 1GHz and by Leven Gan on 2020-08-20 for above 1GHz.

Test Mode: Transmitting

30MHz – 1 GHz:**Final Result**

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
139.256000	32.43	43.50	11.07	188.0	H	242.0	-14.2
155.651375	28.92	43.50	14.58	223.0	H	166.0	-14.3
188.404000	35.88	43.50	7.62	110.0	H	234.0	-15.2
198.669250	31.10	43.50	12.40	123.0	H	254.0	-14.0
204.797375	35.62	43.50	7.88	164.0	H	258.0	-13.9
253.936750	30.02	46.00	15.98	104.0	H	190.0	-13.8

Above 1 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.249&15.209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2406 MHz)									
2406.00	59.83	PK	259	2.2	H	31.87	91.70	114	22.30
2406.00	55.26	Ave.	259	2.2	H	31.87	87.13	94	6.87
2406.00	65.42	PK	82	2.3	V	31.87	97.29	114	16.71
2406.00	61.21	Ave.	82	2.3	V	31.87	93.08	94	0.92
2400.00	25.32	PK	92	1.5	V	31.72	57.04	74	16.96
2400.00	13.54	Ave.	92	1.5	V	31.72	45.26	54	8.74
2332.87	27.78	PK	98	1.9	V	31.64	59.42	74	14.58
2332.87	14.48	Ave.	98	1.9	V	31.64	46.12	54	7.88
2492.28	29.26	PK	76	1.5	V	32.13	61.39	74	12.61
2492.28	14.49	Ave.	76	1.5	V	32.13	46.62	54	7.38
4812.00	47.13	PK	34	2.4	V	6.28	53.41	74	20.59
4812.00	43.27	Ave.	34	2.4	V	6.28	49.55	54	4.45
Middle Channel (2438 MHz)									
2438.00	59.61	PK	276	1.5	H	31.97	91.58	114	22.42
2438.00	55.09	Ave.	276	1.5	H	31.97	87.06	94	6.94
2438.00	64.68	PK	344	1.3	V	31.97	96.65	114	17.35
2438.00	60.12	Ave.	344	1.3	V	31.97	92.09	94	1.91
4876.00	44.73	PK	58	1.1	V	6.28	51.01	74	22.99
4876.00	40.03	Ave.	58	1.1	V	6.28	46.31	54	7.69
High Channel (2474 MHz)									
2474.00	56.32	PK	261	1.7	H	32.13	88.45	114	25.55
2474.00	51.93	Ave.	261	1.7	H	32.13	84.06	94	9.94
2474.00	63.19	PK	197	1.3	V	32.13	95.32	114	18.68
2474.00	59.05	Ave.	197	1.3	V	32.13	91.18	94	2.82
2324.18	27.68	PK	322	1.3	V	31.64	59.32	74	14.68
2324.18	14.41	Ave.	322	1.3	V	31.64	46.05	54	7.95
2496.12	27.99	PK	241	1.0	V	32.13	60.12	74	13.88
2496.12	14.53	Ave.	241	1.0	V	32.13	46.66	54	7.34
4948.00	48.85	PK	122	1.1	V	6.76	55.61	74	18.39
4948.00	45.47	Ave.	122	1.1	V	6.76	52.23	54	1.77

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor


Margin = Limit- Corr. Amplitude

The emission more than 4dB below the limit was not required to be recorded.

Pre-scan with High channel Peak Horizontal





Date: 20.AUG.2020 16:00:30




Date: 20.AUG.2020 16:41:31


Vertical



Average Horizontal




Date: 20.AUG.2020 16:03:47




Date: 20.AUG.2020 16:44:24

Vertical



Date: 20.AUG.2020 16:11:09



Date: 20.AUG.2020 16:51:51

FCC§15.215(c) - 20DB EMISSION BANDWIDTH**Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

Per ANSI C63.10-2013 §6.9

Test Data**Environmental Conditions**

Temperature:	27 °C
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa


The testing was performed by Leven Gan on 2020-08-20

Test Mode: Transmitting

Please refer to the following table and plots.


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2406	4.370
Middle	2438	4.052
High	2474	4.197

Low Channel




Date: 20.AUG.2020 16:40:48

Middle Channel



Date: 20.AUG.2020 16:09:32

High Channel



Date: 20.AUG.2020 16:23:54

***** END OF REPORT *****