RECEIPT

承认书

APPROVAL SHEET

射频天线

Radio-frequency
mane
antenna

model ANT315M

RF 315M 433M 2.4G

客户 client	审核 examine	制定 formulat	
		C	

东莞市赛硕电子有限公司

Dongguan Saishuo Electronics Co., LTD 厂址:东莞市石碣镇刘屋村新风西路262号二楼

Address: Second floor, No. 262, Xinfeng West Road, Liu Wu Village, Shijie Town, Dongguan

电话: 0769-89616716 Tel: 0769-89616716

营销部: 东莞市石碣镇崇焕东路134号3楼021室 Marketing Department: Room 021, 3rd Floor, No.134 Chonghuan East Road, Shijie Town,

Dongguan City

产品外形结构 Product shape structure


产品 product 射频天线 Radio-frequency antenna 型号 Model number

ANT315M

重量weight

约0.9g Approx. 0.9g

外观图片 Appearance picture



产品、电气规格书 Product, electrical specifications

产品 product	射频天线 Radio-freque antenna	型号 Model number	ANT315M	颜色 colour	Black or white or red			
规范 norm	windi and Cor recei	The straightening length of the antenna is about 25cm, the winding diameter is about 6mm, one end of the tin is about 3mm, and the tail is reserved for welding length is about 8-11mm. Copper wire diameter 0.5mm outer diameter 1.3mm, generally receiving module and transmitting module can be used above, if the distance requirement is high, you can straighten the antenna.						
频率范围 Frequency ra	nge	315MHZ或433MHZ						
驻波比 Stand wave ratio	-	<1.8						
增益 gain		2 — 3 dbi						
输入阻抗 Input impeda	nce	50 (OHM)						
接口方式 Inter mode	face	Solder directly onto the PCB						
测试内容 Test conten	ıt	Experimental results and performance						
额定工作电压 R operating vol		DC3.3-5V						
操作温度测证 Operating temperature t		- 10°C ~ +45°C						
破坏温度测t Failure temperature t		<-30℃ 或>+60℃						
跌落实验测证 Drop test	式	75CM tall monomer falls to the wooden floor surface, functional OK						
接收距离 Recei distance	ving	100-4000 meters, usually 100-2500 meters						
振动实验测证 Vibration te	- н	Function OK after different levels of vibration						
绝缘测试 Insulation to	est	> 50 megohm						

外观尺寸 Apparent dimension	0.5mm*1.3mm*25CM
材料 material	Tinned copper
相容性测试 Compatibility test	Generally applicable to 315 and 433, 2.4G, etc