



## CTC Laboratories, Inc. (FCC Designation Number: CN1208)

Room 101 Building B, No. 7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

### Maximum Permissible Exposure Evaluation

FCC ID: 2AJH3-TV-179K

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

#### EUT Specification

|                            |  |
|----------------------------|--|
| Applicant                  | Dune HD(HK) Limited  |
| Address                    | 10th Floor, Shun On Commercial Building, 112-114 Des Voeux Road Central, Central, Hong Kong  |
| Product Name:              | Kartina EVA  |
| Trade Mark:                | Kartina, Kartina TV, Dune HD   |
| Model/Type Reference:      | TV-179K  |
| Listed Model(s):           | /  |
| Model Differences:         | /  |
| Frequency Band (Operating) | BT: 2402~2480MHz<br>2.4G WiFi: 2412-2462MHz<br>5G WiFi: 5150MHz~5250MHz, 5725MHz~5850MHz   |
| Device Category            | <input type="checkbox"/> Portable (<5mm separation)<br><input type="checkbox"/> Mobile (>20cm separation)<br><input checked="" type="checkbox"/> Fixed (>20cm separation)<br><input type="checkbox"/> Others ____              |
| Exposure Classification    | <input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm <sup>2</sup> )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )                                    |
| Antenna Diversity          | <input type="checkbox"/> Single antenna<br><input checked="" type="checkbox"/> Multiple antennas<br><input type="checkbox"/> TX diversity<br><input type="checkbox"/> RX diversity<br><input type="checkbox"/> TX/RX diversity |
| Antenna Gain (Max)         | BT ANT: 1.88dBi<br>2.4G WiFi: ANT1&ANT2: 3.81dBi, Directional Gain: 6.82dBi<br>5G WiFi: ANT1&ANT2: 5.23dBi, Directional Gain: 8.24dBi  |
| Evaluation Applied         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation  |

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : [yz.cnca.cn](http://yz.cnca.cn)

**Limits for Maximum Permissible Exposure (MPE)**

| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure         |                               |                               |                                     |                          |
| 300-1500  | --                            | --                            | F/300                               | <6                       |
| 1500-100000   | --                            | --                            | 5                                   | <6                       |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 300-1500  | --                            | --                            | F/1500                              | <30                      |
| 1500-100000   | --                            | --                            | 1                                   | <30                      |

**Calculation Method**

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  limit of MPE is 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

**Measurement Result**

| Mode      | Frequency (MHz) | Antenna Gain (dBi) | Maximum Power (dBm) | Tune Up Tolerance (dB) | Max. Tune Up Power (dBm) | Power Density at 20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|-----------|-----------------|--------------------|---------------------|------------------------|--------------------------|---|-----------------------------|--------|
| GFSK(BLE) | 2440            | 1.88               | 6.64                | ± 1                    | 7.50                     | 0.0017                                      | 1                           | Pass   |
| 8-DPSK    | 2402            | 1.88               | 10.24               | ± 1                    | 11.00                    | 0.0039                                      | 1                           | Pass   |
| 802.11g   | 2462            | 3.81               | 16.73               | ± 1                    | 17.50                    | 0.0269                                      | 1                           | Pass   |
| 802.11a   | 5180            | 5.23               | 16.85               | ± 1                    | 17.50                    | 0.0373                                      | 1                           | Pass   |

The BT and WiFi can transmit simultaneously.

| Mode    | Frequency (MHz) | Power Density at 20cm (mW/cm <sup>2</sup> ) | Total Power density at 20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|---------|-----------------|---|---|-----------------------------|--------|
| 8-DPSK  | 2402            | 0.0039                                      | 0.0681  | 1                           | Pass   |
| 802.11g | 2462            | 0.0269                                      |   |                             |        |
| 802.11a | 5180            | 0.0373                                      |   |                             |        |

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

\*\*\*\*\*THE END\*\*\*\*\*