


RF TEST REPORT



Report No.: 16070667-FCC-R1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Smart Phone	
Model No.	SL5008T	
Serial No.	SL5008	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	June 08 to July 12, 2016	
Issue Date	July13, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070667-FCC-R1
Page	3 of 105

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	10
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	11
6.1 RF EXPOSURE (SAR).....	11
6.2 RF OUTPUT POWER	12
6.3 PEAK-AVERAGE RATIO	25
6.4 OCCUPIED BANDWIDTH	30
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	45
6.6 SPURIOUS RADIATED EMISSIONS	61
6.7 BAND EDGE.....	68
6.8 FREQUENCY STABILITY	82
ANNEX A. TEST INSTRUMENT.....	93
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	95
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	101
ANNEX C.II. EUT OPERATING CONKITIONS	103
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	104
ANNEX E. DECLARATION OF SIMILARITY	105

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070667-FCC-R1	NONE	Original	July13, 2016

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	SHENZHEN TOPWELL TECHNOLOGY CO.LTD
Manufacturer Add	T5F, 10Building,Changyuan New Material Port,No.2,Middle Road 1, High Tech Park, Nanshan District ,Shenzhen, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Smart Phone

Main Model: SL5008T

Serial Model: SL5008

Date EUT received: June 07, 2016

Test Date(s): June 08 to July 12, 2016

Equipment Category : PCE

Antenna Gain:

- GSM850: 1.09dBi
- PCS1900: 2.54dBi
- UMTS-FDD Band V: 1.14dBi
- UMTS-FDD Band IV: 2.89dBi
- UMTS-FDD Band II: 2.95dBi
- LTE Band 2: 2.71dBi
- LTE Band 4: 2.92dBi
- LTE Band 5: 1.34dBi
- LTE Band 7: 3.23dBi
- Bluetooth/BLE/WIFI: 2.65dBi
- GPS: 1.42dBi

Antenna Type: PIFA antenna

Type of Modulation:

- GSM / GPRS: GMSK
- EGPRS: GMSK, 8PSK
- UMTS-FDD: QPSK
- LTE Band: QPSK, 16QAM
- 802.11b/g/n: DSSS, OFDM
- Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
- BLE: GFSK
- GPS: BPSK

	Adapter:
	Model: SL5008
	Input: AC 100-240V,50/60Hz;0.2A
	Output: DC 5.0V,1A
Input Power:	Battery:
	Model: SL5008
	Spec: 3.8V,2300mAh(8.74Wh)
	Charge limited voltage: 4.35V

Maximum Conducted
AV Power to Antenna:

GSM Voice:GSM850: 33.11 dBm

PCS1900: 28.75 dBm

GPRS:GSM850: 33.08dBm

PCS1900: 28.66 dBm

MCS1:GSM850: 33.00 dBm

PCS1900: 28.55 dBm

MCS5:GSM850: 26.62 dBm

PCS1900: 24.76 dBm

RMC:UMTS-FDD Band V: 24.29 dBm

UMTS-FDD Band II: 22.83 dBm

UMTS-FDD Band IV: 22.51 dBm

HSDPA:UMTS-FDD Band V: 22.37 dBm

UMTS-FDD Band II: 21.45 dBm

UMTS-FDD Band IV: 22.34 dBm

HSUPA:UMTS-FDD Band V: 22.31dBm

UMTS-FDD Band II: 22.12dBm

UMTS-FDD Band IV: 22.43 dBm

GSM Voice:GSM850: 32.84 dBm / ERP

PCS1900: 30.84 dBm / EIRP

GPRS:GSM850: 32.78 dBm / ERP

PCS1900: 30.67 dBm / EIRP

EGPRS:GSM850: 25.72 dBm / ERP

PCS1900: 26.61 dBm / EIRP

RMC:UMTS-FDD Band V: 23.19 dBm / ERP

UMTS-FDD Band II: 23.54 dBm / ERP

UMTS-FDD Band IV: 24.45 dBm / EIRP

HSDPA:UMTS-FDD Band V: 22.94 dBm / ERP

UMTS-FDD Band II: 23.42 dBm / ERP

UMTS-FDD Band IV: 24.37 dBm / EIRP

HSUPA:UMTS-FDD Band V: 22.82 dBm / ERP

UMTS-FDD Band II: 23.69dBm / ERP

UMTS-FDD Band IV: 24.29 dBm / EIRP

ERP/EIRP:

Test Report	16070667-FCC-R1
Page	9 of 105

Trade Name : N/A

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: WA6SL5008T

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 16070667-FCC-H.

6.2 RF Output Power

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	July 01, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	☒
§24.232 (c)	b)	EIRP:33dBm	☒
§27.50 (c)	c)	EIRP: 30dBm	☒

Test Setup	
------------	--

Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: According with KDB 971168 v02r02 - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

Test Report	16070667-FCC-R1
Page	13 of 105

	frequency was investigated. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.93	33.11	33.10	33±1	28.75	28.55	28.35	28±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.90	32.88	33.08	33±1	28.66	28.42	28.30	28±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	32.10	32.25	32.32	32±1	27.90	27.81	27.73	27±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	28.77	28.80	28.84	28±1	24.79	24.99	25.20	25.3±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.77	32.86	33.00	33±1	28.55	28.26	28.18	28±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	32.09	32.24	32.29	32±1	27.61	27.52	27.48	27±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	28.76	28.8	28.81	28±1	24.45	24.65	24.88	24±1
EGPRS Multi-Slot Class 8 (1 uplink) MCS 5 8PSK	26.51	26.48	26.62	26±1	24.76	24.62	24.53	24±1
EGPRS Multi-Slot Class 10 (2 uplink) MCS 5 8PSK	25.46	25.44	25.54	25±1	23.8	23.70	23.64	23±1
EGPRS Multi-Slot Class 12 (4 uplink) MCS 5 8PSK	22.28	22.25	22.36	22±1	20.03	20.40	20.16	20±1

Test Report	16070667-FCC-R1
Page	15 of 105

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	23.69	24±1
	4175	835	23.93	24±1
	4233	846.6	24.29	24±1
HSDPA Subtest1	4132	826.4	21.42	21.5±1
	4175	835	22.31	21.5±1
	4233	846.6	21.26	21.5±1
HSDPA Subtest2	4132	826.4	21.90	21.5±1
	4175	835	21.56	21.5±1
	4233	846.6	22.37	21.5±1
HSDPA Subtest3	4132	826.4	21.19	21.5±1
	4175	835	21.00	21.5±1
	4233	846.6	21.30	21.5±1
HSDPA Subtest4	4132	826.4	22.16	21.5±1
	4175	835	21.52	21.5±1
	4233	846.6	21.38	21.5±1
HSUPA Subtest1	4132	826.4	21.40	21.5±1
	4175	835	22.11	21.5±1
	4233	846.6	21.25	21.5±1
HSUPA Subtest2	4132	826.4	22.31	21.5±1
	4175	835	21.59	21.5±1
	4233	846.6	21.63	21.5±1
HSUPA Subtest3	4132	826.4	21.69	21.5±1
	4175	835	22.14	21.5±1
	4233	846.6	21.11	21.5±1
HSUPA Subtest4	4132	826.4	21.30	21.5±1
	4175	835	21.63	21.5±1
	4233	846.6	21.58	21.5±1
HSUPA Subtest5	4132	826.4	20.99	21.5±1
	4175	835	21.58	21.5±1
	4233	846.6	21.35	21.5±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.65	22±1
	9400	1880	22.55	22±1
	9538	1907.6	22.83	22±1
HSDPA Subtest1	9262	1852.4	21.45	21.5±1
	9400	1880	21.41	21.5±1
	9538	1907.6	20.96	21.5±1
HSDPA Subtest2	9262	1852.4	21.23	21.5±1
	9400	1880	20.86	21.5±1
	9538	1907.6	20.96	21.5±1
HSDPA Subtest3	9262	1852.4	21.31	21.5±1
	9400	1880	20.77	21.5±1
	9538	1907.6	21.53	21.5±1
HSDPA Subtest4	9262	1852.4	21.03	21.5±1
	9400	1880	20.96	21.5±1
	9538	1907.6	21.00	21.5±1
HSUPA Subtest1	9262	1852.4	20.86	21.5±1
	9400	1880	21.13	21.5±1
	9538	1907.6	22.06	21.5±1
HSUPA Subtest2	9262	1852.4	20.67	21.5±1
	9400	1880	21.05	21.5±1
	9538	1907.6	21.36	21.5±1
HSUPA Subtest3	9262	1852.4	22.12	21.5±1
	9400	1880	21.03	21.5±1
	9538	1907.6	20.58	21.5±1
HSUPA Subtest4	9262	1852.4	20.59	21.5±1
	9400	1880	21.33	21.5±1
	9538	1907.6	21.26	21.5±1
HSUPA Subtest5	9262	1852.4	21.35	21.5±1
	9400	1880	20.93	21.5±1
	9538	1907.6	21.55	21.5±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	22.51	22±1
	4175	835	22.22	22±1
	4233	846.6	22.16	22±1
HSDPA Subtest1	4132	826.4	21.89	21.5±1
	4175	835	21.78	21.5±1
	4233	846.6	21.86	21.5±1
HSDPA Subtest2	4132	826.4	21.35	21.5±1
	4175	835	21.65	21.5±1
	4233	846.6	21.14	21.5±1
HSDPA Subtest3	4132	826.4	22.03	21.5±1
	4175	835	22.27	21.5±1
	4233	846.6	22.34	21.5±1
HSDPA Subtest4	4132	826.4	21.69	21.5±1
	4175	835	21.35	21.5±1
	4233	846.6	21.45	21.5±1
HSUPA Subtest1	4132	826.4	21.33	21.5±1
	4175	835	21.35	21.5±1
	4233	846.6	21.58	21.5±1
HSUPA Subtest2	4132	826.4	21.46	21.5±1
	4175	835	22.43	21.5±1
	4233	846.6	22.28	21.5±1
HSUPA Subtest3	4132	826.4	22.39	21.5±1
	4175	835	22.00	21.5±1
	4233	846.6	22.13	21.5±1
HSUPA Subtest4	4132	826.4	21.98	21.5±1
	4175	835	22.13	21.5±1
	4233	846.6	21.36	21.5±1
HSUPA Subtest5	4132	826.4	22.07	21.5±1
	4175	835	21.36	21.5±1
	4233	846.6	21.46	21.5±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	26.54	V	6.8	0.53	32.81	38.45
824.2	26.01	H	6.8	0.53	32.28	38.45
836.6	26.48	V	6.8	0.53	32.75	38.45
836.6	25.93	H	6.8	0.53	32.20	38.45
848.8	26.47	V	6.9	0.53	32.84	38.45
848.8	25.82	H	6.9	0.53	32.19	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.81	V	7.88	0.85	30.84	33
1850.2	23.27	H	7.88	0.85	30.30	33
1880	23.76	V	7.88	0.85	30.79	33
1880	23.12	H	7.88	0.85	30.15	33
1909.8	23.75	V	7.86	0.85	30.76	33
1909.8	23.28	H	7.86	0.85	30.29	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	26.38	V	6.8	0.53	32.65	38.45
824.2	25.82	H	6.8	0.53	32.09	38.45
836.6	26.35	V	6.8	0.53	32.62	38.45
836.6	25.87	H	6.8	0.53	32.14	38.45
848.8	26.41	V	6.9	0.53	32.78	38.45
848.8	25.95	H	6.9	0.53	32.32	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.64	V	7.88	0.85	30.67	33
1850.2	23.19	H	7.88	0.85	30.22	33
1880	23.52	V	7.88	0.85	30.55	33
1880	22.98	H	7.88	0.85	30.01	33
1909.8	23.57	V	7.86	0.85	30.58	33
1909.8	22.93	H	7.86	0.85	29.94	33

EGPRS (MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	26.25	V	6.8	0.53	25.52	38.45
824.2	25.76	H	6.8	0.53	25.03	38.45
836.6	26.31	V	6.8	0.53	25.58	38.45
836.6	25.84	H	6.8	0.53	25.11	38.45
848.8	26.35	V	6.9	0.53	25.72	38.45
848.8	25.88	H	6.9	0.53	25.25	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.58	V	7.88	0.85	26.61	33
1850.2	23.03	H	7.88	0.85	26.06	33
1880	23.54	V	7.88	0.85	26.57	33
1880	23.01	H	7.88	0.85	26.04	33
1909.8	23.49	V	7.86	0.85	26.50	33
1909.8	22.96	H	7.86	0.85	25.97	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	16.65	V	6.8	0.53	22.92	38.45
826.4	16.11	H	6.8	0.53	22.38	38.45
835	16.78	V	6.8	0.53	23.05	38.45
835	16.15	H	6.8	0.53	22.42	38.45
846.6	16.82	V	6.9	0.53	23.19	38.45
846.6	16.18	H	6.9	0.53	22.55	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.43	V	7.88	0.85	23.46	33
1852.4	15.89	H	7.88	0.85	22.92	33
1880	16.51	V	7.88	0.85	23.54	33
1880	15.96	H	7.88	0.85	22.99	33
1907.6	16.53	V	7.86	0.85	23.54	33
1907.6	16.02	H	7.86	0.85	23.03	33

EIRP for UMTS-FDD Band IV (Part 27E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	17.78	V	7.76	0.82	24.72	30
1712.4	17.23	H	7.76	0.82	24.17	30
1740	17.51	V	7.76	0.82	24.45	30
1740	17.07	H	7.76	0.82	24.01	30
1752.6	17.44	V	7.74	0.82	24.36	30
1752.6	16.95	H	7.74	0.82	23.87	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	16.58	V	6.8	0.53	22.85	38.45
826.4	16.03	H	6.8	0.53	22.30	38.45
835	16.62	V	6.8	0.53	22.89	38.45
835	16.14	H	6.8	0.53	22.41	38.45
846.6	16.57	V	6.9	0.53	22.94	38.45
846.6	16.03	H	6.9	0.53	22.40	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.35	V	7.88	0.85	23.38	33
1852.4	15.71	H	7.88	0.85	22.74	33
1880	16.29	V	7.88	0.85	23.32	33
1880	15.65	H	7.88	0.85	22.68	33
1907.6	16.41	V	7.86	0.85	23.42	33
1907.6	15.83	H	7.86	0.85	22.84	33

EIRP for UMTS-FDD Band IV (Part 27E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	17.43	V	7.76	0.82	24.37	30
1712.4	16.91	H	7.76	0.82	23.85	30
1740	17.35	V	7.76	0.82	24.29	30
1740	16.88	H	7.76	0.82	23.82	30
1752.6	17.24	V	7.74	0.82	24.16	30
1752.6	16.71	H	7.74	0.82	23.63	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	16.47	V	6.8	0.53	22.74	38.45
826.4	15.83	H	6.8	0.53	22.10	38.45
835	16.52	V	6.8	0.53	22.79	38.45
835	15.94	H	6.8	0.53	22.21	38.45
846.6	16.45	V	6.9	0.53	22.82	38.45
846.6	15.88	H	6.9	0.53	22.25	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.24	V	7.88	0.85	23.27	33
1852.4	15.69	H	7.88	0.85	22.72	33
1880	16.16	V	7.88	0.85	23.19	33
1880	15.55	H	7.88	0.85	22.58	33
1907.6	16.23	V	7.86	0.85	23.24	33
1907.6	16.68	H	7.86	0.85	23.69	33

EIRP for UMTS-FDD Band IV (Part 27E)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	17.35	V	7.76	0.82	24.29	30
1712.4	16.81	H	7.76	0.82	23.75	30
1740	17.29	V	7.76	0.82	24.23	30
1740	16.76	H	7.76	0.82	23.70	30
1752.6	17.12	V	7.74	0.82	24.04	30
1752.6	16.55	H	7.74	0.82	23.47	30

6.3 Peak-Average Ratio

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	July 01, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	☒

Test Setup	
------------	---

Test Procedure	According with KDB 971168 v02r02 5.7.2 Alternate procedure for PAPR 5.1.2 Peak power measurements with a peak power meter The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector. 5.2.3 Average power measurement with average power meter As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output
----------------	---

Test Report	16070667-FCC-R1
Page	26 of 105

	power level, then a conventional wide-band RF power meter can be used. If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.65	28.75	0.9
1880	29	28.55	0.45
1909.8	29.48	28.35	1.13

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.6	28.66	0.94
1880	29.65	28.42	1.23
1909.8	29.39	28.3	1.09

EGPRS (MSC 5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	25.69	24.76	0.93
1880	26.47	24.62	1.85
1909.8	28.33	24.53	3.8

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	25.36	22.65	2.71
1880	24.28	22.55	1.73
1907.6	24.19	22.83	1.36

UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	24.66	22.51	2.15
1732.6	25.35	22.22	3.13
1752.4	25.65	22.16	3.49

HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.56	21.45	3.11
1880	24.56	21.41	3.15
1907.6	24.19	20.96	3.23

UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	24.5	21.89	2.61
1732.6	24.36	21.78	2.58
1752.4	24.33	21.86	2.47

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.35	20.86	3.49
1880	24.69	21.13	3.56
1907.6	24.9	22.06	2.84


UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	24.35	21.33	3.02
1732.6	24.58	21.35	3.23
1752.4	24.17	21.58	2.59

6.4 Occupied Bandwidth

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	July 05, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	☒
	b)	26 dB Bandwidth(kHz)	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.2103	316.136
190	836.6	250.6258	318.555
251	848.8	245.9977	320.126

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	251.9545	320.907
661	1880.0	242.4727	314.221
810	1909.8	245.1431	317.872

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	242.8811	311.610
190	836.6	244.6130	322.315
251	848.8	241.8511	312.926

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	244.6309	312.840
661	1880.0	246.7834	320.757
810	1909.8	248.5887	315.323

EGPRS (MCS 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	250.2309	320.039
190	836.6	243.6709	319.436
251	848.8	245.7516	322.949

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.0927	313.388
661	1880.0	247.5553	322.864
810	1909.8	243.1820	320.560

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2046	4.869
4175	835.0	4.2249	4.879
4233	846.6	4.2238	4.847

UMTS-FDD Band IV (Part 27E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2118	4.888
1413	1732.6	4.2055	4.871
1512	1752.4	4.2109	4.897

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2054	4.866
9400	1880.0	4.2028	4.869
9538	1907.6	4.2367	4.892

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2148	4.900
4175	835.0	4.2193	4.883
4233	846.6	4.2217	4.885

UMTS-FDD Band IV (Part 27E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2061	4.880
1413	1732.6	4.2177	4.911
1512	1752.4	4.2080	4.890

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2259	4.905
9400	1880.0	4.2098	4.913
9538	1907.6	4.2140	4.842

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2138	4.864
4175	835.0	4.2224	4.916
4233	846.6	4.2099	4.897

UMTS-FDD Band IV (Part 27E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2085	4.884
1413	1732.6	4.2187	4.870
1512	1752.4	4.2019	4.891

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2140	4.923
9400	1880.0	4.2361	4.886
9538	1907.6	4.2196	4.908

Test Plots


GMS Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1909.8MHz



EGPRS (MCS 5):





RMC:



Band V BW - Low CH 826.6 MHz




Band V BW - High CH 846.4 MHz




Band IV BW - Mid CH 1732.6 MHz


Band IV BW - High CH 1752.4 MHz



Band II BW - Low CH 1852.4MHz




Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz

HSDPA:



Agilent 17:12:50 Jul 5, 2016

R T



Center 1.853 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)


Occupied Bandwidth
4.2259 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -4.251 kHz
x dB Bandwidth 4.905 MHz

Agilent 17:11:10 Jul 5, 2016

R T



Center 1.88 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)

Occupied Bandwidth
4.2098 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -15.451 kHz
x dB Bandwidth 4.913 MHz

Band II BW - Low CH 1852.4MHz

Band II BW - Mid CH 1880MHz

Agilent 17:05:36 Jul 5, 2016

R T



Center 1.907 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)



Occupied Bandwidth
4.2140 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB



Transmit Freq Error -19.189 kHz
x dB Bandwidth 4.842 MHz

Band II BW - High CH 1907.6MHz



HSUPA:



Band V BW - Low CH 826.6 MHz



Band V BW - High CH 846.4 MHz




Band IV BW - Mid CH 1732.6 MHz

Band IV BW - High CH 1752.4 MHz

Agilent 17:13:18 Jul 5, 2016

R T




Center 1.853 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)
Occupied Bandwidth
4.2140 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error 350.880 Hz
x dB Bandwidth 4.923 MHz

Agilent 17:11:31 Jul 5, 2016

R T



Center 1.88 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)
Occupied Bandwidth
4.2361 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -15.644 kHz
x dB Bandwidth 4.886 MHz

Band II BW - Low CH 1852.4MHz

Band II BW - Mid CH 1880MHz

Agilent 17:10:13 Jul 5, 2016

R T



Center 1.907 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10 MHz
Sweep 4 ms (401 pts)
Occupied Bandwidth
4.2196 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -21.223 kHz
x dB Bandwidth 4.908 MHz

Band II BW - High CH 1907.6MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	July 06, 2016
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

PCS Band (Part24E) result




EGPRS (MCS 5):


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSDPA:


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSUPA:


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	July 01, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☒

Test setup	
------------	--

Test Procedure	- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)
----------------	---

Test Report	16070667-FCC-R1
Page	62 of 105

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-44.28	V	7.95	0.78	-37.11	-13	-24.11
1648.4	-43.73	H	7.95	0.78	-36.56	-13	-23.56
342.1	-51.94	V	6.5	0.27	-45.71	-13	-32.71
556.6	-51.87	H	6.7	0.35	-45.52	-13	-32.52

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-44.35	V	7.95	0.78	-37.18	-13	-24.18
1673.2	-43.81	H	7.95	0.78	-36.64	-13	-23.64
341.7	-51.78	V	6.5	0.27	-45.55	-13	-32.55
556.2	-51.94	H	6.7	0.35	-45.59	-13	-32.59

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-44.52	V	7.95	0.78	-37.35	-13	-24.35
1697.6	-43.96	H	7.95	0.78	-36.79	-13	-23.79
342.2	-51.82	V	6.5	0.27	-45.59	-13	-32.59
556.9	-51.97	H	6.7	0.35	-45.62	-13	-32.62

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-47.53	V	10.25	2.73	-40.01	-13	-27.01
3700.4	-48.28	H	10.25	2.73	-40.76	-13	-27.76
341.9	-52.56	V	6.5	0.27	-46.33	-13	-33.33
555.3	-52.41	H	6.7	0.35	-46.06	-13	-33.06

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-47.63	V	10.25	2.73	-40.11	-13	-27.11
3760	-48.17	H	10.25	2.73	-40.65	-13	-27.65
341.5	-52.44	V	6.5	0.27	-46.21	-13	-33.21
555.8	-52.19	H	6.7	0.35	-45.84	-13	-32.84

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-47.56	V	10.36	2.73	-39.93	-13	-26.93
3819.6	-47.32	H	10.36	2.73	-39.69	-13	-26.69
341.6	-52.38	V	6.5	0.27	-46.15	-13	-33.15
555.3	-52.04	H	6.7	0.35	-45.69	-13	-32.69

Note:

- 1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-45.38	V	7.95	0.78	-38.21	-13	-25.21
1652.8	-45.21	H	7.95	0.78	-38.04	-13	-25.04
343.5	-52.39	V	6.5	0.27	-46.16	-13	-33.16
557.1	-52.94	H	6.7	0.35	-46.59	-13	-33.59

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-45.41	V	7.95	0.78	-38.24	-13	-25.24
1670	-45.29	H	7.95	0.78	-38.12	-13	-25.12
343.9	-52.34	V	6.5	0.27	-46.11	-13	-33.11
557.4	-52.86	H	6.7	0.35	-46.51	-13	-33.51

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-45.38	V	7.95	0.78	-38.21	-13	-25.21
1693.2	-45.15	H	7.95	0.78	-37.98	-13	-24.98
343.6	-52.22	V	6.5	0.27	-45.99	-13	-32.99
557.3	-52.47	H	6.7	0.35	-46.12	-13	-33.12

Note:

- 1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-47.65	V	10.25	2.73	-40.13	-13	-27.13
3704.8	-48.11	H	10.25	2.73	-40.59	-13	-27.59
341.5	-52.03	V	6.5	0.27	-45.8	-13	-32.8
556.8	-51.86	H	6.7	0.35	-45.51	-13	-32.51

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-46.95	V	10.25	2.73	-39.43	-13	-26.43
3760	-47.62	H	10.25	2.73	-40.1	-13	-27.1
341.7	-51.86	V	6.5	0.27	-45.63	-13	-32.63
556.2	-51.75	H	6.7	0.35	-45.4	-13	-32.4

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-46.88	V	10.36	2.73	-39.25	-13	-26.25
3815.2	-47.43	H	10.36	2.73	-39.8	-13	-26.8
341.9	-51.69	V	6.5	0.27	-45.46	-13	-32.46
556.3	-51.52	H	6.7	0.35	-45.17	-13	-32.17

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-45.92	V	10.07	2.52	-38.37	-13	-25.37
3424.8	-48.34	H	10.07	2.52	-40.79	-13	-27.79
361.5	-57.04	V	6.1	0.24	-51.18	-13	-38.18
695.1	-52.49	H	6.7	0.38	-46.17	-13	-33.17

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.11	V	10.09	2.52	-38.54	-13	-25.54
3480	-45.83	H	10.09	2.52	-38.26	-13	-25.26
361.8	-56.77	V	6.1	0.24	-50.91	-13	-37.91
695.3	-53.27	H	6.7	0.38	-46.95	-13	-33.95

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-45.88	V	10.09	2.52	-38.31	-13	-25.31
3505.2	-45.27	H	10.09	2.52	-37.7	-13	-24.7
361.4	-57.37	V	6.1	0.24	-51.51	-13	-38.51
695.9	-51.83	H	6.7	0.38	-45.51	-13	-32.51

Note:

1, The testing has been conformed to $10 \times 1712.4 \text{ MHz} = 17,124 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

6.7 Band Edge

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	July 06, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	☒
Test setup			
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-21.02	-13
849.0175	-19.81	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-18.06	-13
1910.0150	-15.16	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9950	-21.78	-13
849.0175	-21.07	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-18.33	-13
1910.0300	-21.74	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9950	-22.73	-13
849.0150	-23.98	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9950	-21.60	-13
1910.0025	-22.03	-13

RMC:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.500	-22.35	-13
849.200	-22.79	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.075	-23.31	-13
1755.950	-28.26	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.850	-22.13	-13
1910.925	-22.38	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.625	-22.42	-13
849.100	-18.21	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.950	-22.43	-13
1755.275	-26.58	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-18.59	-13
1910.050	-21.27	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.700	-22.01	-13
849.250	-21.20	-13

UMTS-FDD Band IV (Part 27)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.825	-23.05	-13
1755.150	-26.83	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.875	-18.44	-13
1910.025	-21.31	-13


GSM Voice:

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.16/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.21/3)=4.5+0.2=4.7dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.18/3)=4.5+0.3=4.8dB


GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(48.69/30)=4.5+2.1=6.6dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.47/30)=4.5+2.1=6.6dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(48.88/30)=4.5+2.1=6.6dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.97/30)=4.5+2.1=6.6dB

Test Report	16070667-FCC-R1
Page	77 of 105



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(48.66/30)4.5+2.1=6.6dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.92/30)=4.5+2.1=6.6dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(49.00/30)=4.5+2.1=6.6dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.85/30)=4.5+2.1=6.6dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(48.88/30)=4.5+2.4=6.6dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.90/30)=4.5+2.4=6.6dB

Test Report	16070667-FCC-R1
Page	79 of 105



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(49.05/30)=4.5+2.2=6.7dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.42/30)=4.5+2.1=6.6dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(48.64/30)=4.5+2.1=6.6dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.97/30)=4.5+2.1=6.6dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(48.84/30)=4.5+2.1=6.6dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.91/30)=4.5+2.1=6.6dB

Test Report	16070667-FCC-R1
Page	81 of 105



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(49.23/30)=4.5+2.1=6.6dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49.08/30)=4.5+2.1=6.6dB

6.8 Frequency Stability

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	July 01, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	☒
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup																																			

Test Report	16070667-FCC-R1
Page	83 of 105

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		16	0.0191	2.5
10		17	0.0203	2.5
20		19	0.0227	2.5
30		12	0.0143	2.5
40		18	0.0215	2.5
50		16	0.0191	2.5
55		20	0.0239	2.5
25	4.2	21	0.0251	2.5
	3.5	16	0.0191	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	14	0.0074	2.5
0		16	0.0085	2.5
10		13	0.0069	2.5
20		14	0.0074	2.5
30		16	0.0085	2.5
40		15	0.0080	2.5
50		13	0.0069	2.5
55		15	0.0080	2.5
25	4.2	15	0.0080	2.5
	3.5	21	0.0112	2.5

GPRS:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0239	2.5
0		21	0.0251	2.5
10		16	0.0191	2.5
20		13	0.0155	2.5
30		12	0.0143	2.5
40		16	0.0191	2.5
50		17	0.0203	2.5
55		22	0.0263	2.5
25	4.2	18	0.0215	2.5
	3.5	21	0.0251	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		16	0.0085	2.5
10		15	0.0080	2.5
20		11	0.0059	2.5
30		15	0.0080	2.5
40		21	0.0112	2.5
50		15	0.0080	2.5
55		16	0.0085	2.5
25	4.2	21	0.0112	2.5
	3.5	20	0.0106	2.5

EGPRS (MCS1):

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0239	2.5
0		16	0.0191	2.5
10		16	0.0191	2.5
20		19	0.0227	2.5
30		15	0.0179	2.5
40		18	0.0215	2.5
50		20	0.0239	2.5
55		19	0.0227	2.5
25	4.2	17	0.0203	2.5
	3.5	16	0.0191	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0106	2.5
0		19	0.0101	2.5
10		16	0.0085	2.5
20		10	0.0053	2.5
30		14	0.0074	2.5
40		12	0.0064	2.5
50		10	0.0053	2.5
55		20	0.0106	2.5
25	4.2	21	0.0112	2.5
	3.5	16	0.0085	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	13	0.0156	2.5
0		15	0.0180	2.5
10		12	0.0144	2.5
20		16	0.0192	2.5
30		13	0.0156	2.5
40		12	0.0144	2.5
50		16	0.0192	2.5
55		19	0.0228	2.5
25	4.2	12	0.0144	2.5
	3.5	17	0.0204	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0085	2.5
0		15	0.0080	2.5
10		14	0.0074	2.5
20		11	0.0059	2.5
30		12	0.0064	2.5
40		13	0.0069	2.5
50		13	0.0069	2.5
55		15	0.0080	2.5
25	4.2	16	0.0085	2.5
	3.5	19	0.0101	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	17	0.0090	2.5
0		14	0.0074	2.5
10		13	0.0069	2.5
20		13	0.0069	2.5
30		11	0.0059	2.5
40		12	0.0064	2.5
50		14	0.0074	2.5
55		15	0.0080	2.5
25	4.2	17	0.0090	2.5
	3.5	20	0.0106	2.5

HSUPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		17	0.0204	2.5
10		12	0.0144	2.5
20		13	0.0156	2.5
30		16	0.0192	2.5
40		16	0.0192	2.5
50		17	0.0204	2.5
55		22	0.0263	2.5
25	4.2	21	0.0251	2.5
	3.5	20	0.0240	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		15	0.0080	2.5
10		14	0.0074	2.5
20		12	0.0064	2.5
30		16	0.0085	2.5
40		12	0.0064	2.5
50		15	0.0080	2.5
55		14	0.0074	2.5
25	4.2	16	0.0085	2.5
	3.5	18	0.0096	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		15	0.0080	2.5
10		14	0.0074	2.5
20		14	0.0074	2.5
30		18	0.0096	2.5
40		15	0.0080	2.5
50		16	0.0085	2.5
55		19	0.0101	2.5
25	4.2	15	0.0080	2.5
	3.5	21	0.0112	2.5

HSDPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		18	0.0216	2.5
10		15	0.0180	2.5
20		12	0.0144	2.5
30		13	0.0156	2.5
40		15	0.0180	2.5
50		15	0.0180	2.5
55		20	0.0240	2.5
25	4.2	17	0.0204	2.5
	3.5	19	0.0228	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0106	2.5
0		16	0.0085	2.5
10		11	0.0059	2.5
20		12	0.0064	2.5
30		11	0.0059	2.5
40		13	0.0069	2.5
50		16	0.0085	2.5
55		20	0.0106	2.5
25	4.2	14	0.0074	2.5
	3.5	15	0.0080	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0106	2.5
0		16	0.0085	2.5
10		11	0.0059	2.5
20		12	0.0064	2.5
30		13	0.0069	2.5
40		15	0.0080	2.5
50		16	0.0085	2.5
55		20	0.0106	2.5
25	4.2	14	0.0074	2.5
	3.5	16	0.0085	2.5

Annex A. TEST INSTRUMENT


Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	☒
Power Splitter	1#	1#	09/01/2015	08/31/2016	☒
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☒
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	☒
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☒
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/17/2015	09/16/2016	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☒
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	☒
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	☒
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	☒
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	☒

Test Report	16070667-FCC-R1
Page	94 of 105

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	09/01/2015	08/31/2016	☒
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo






EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View


Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2



Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard with Shielding - Rear View



Mainboard without Shielding - Rear View



Small Board - Front View



Small Board - Rear View



LCD - Front View



LCD - Rear View



GSM/PCS/UMTS-FDD/LTE Antenna View




WIFI/BT/BLE/GPS - Antenna View




LTE - Antenna View

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	SL5008	SL-005

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	SL-005

Test Report	16070667-FCC-R1
Page	103 of 105

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16070667-FCC-R1
Page	104 of 105

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY



Declaration Letter

For our business issue and marketing requirement, we would like to make some change on the model, details are as below:

Model No.:SL5008T and SL5008

We Verykool USA Inc, hereby declare that our product SL5008T and SL5008 share the same PCB and difference are listed as below:

Main Model No.	Serial Model No.	Difference
SL5008T	SL5008	The LTE bands of SL5008T are band II, IV V, VII, for SL5008, band VII will be shield by software based on SL5008T.

Thank you!

Sincerely

Signature: Sunny Choi

Job Title:

PM Director