

MPE CALCULATION

FCC ID: F5318LT7090E

RF Exposure Requirements:

47 CFR §1.1307(b)

RF Radiation Exposure Limits:

47 CFR §1.1310

RF Radiation Exposure Guidelines:

FCC OST/OET Bulletin Number 65

Limits for General Population/Uncontrolled Exposure in the band of:

Frequency Range (MHz)	Power Density (mW/cm ²)
1,500-100,000	1.0
300-1,500	f/1500

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

MPE Calculations:

Prediction distance 20cm

Radio Mode	Frequency Range (MHz)	Reference Freq. (MHz)	Average Output Power (dBm)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Antenna Gain (dBi)	Measurement Distance (cm)	Power Density (mw/cm2)	MPE Limit (mw/cm2)
LTE Band 2	1850-1910	1880.0	23.41	±1dB	24.41	2.5	20	0.137	1
LTE Band 4	1710-1755	1710.7	23.25	±1dB	24.25	1.5	20	0.0794	1
LTE Band 13	777-787	784.5	23.04	±1dB	24.04	2.2	20	0.111	0.523

The different radios from different bands are not transmitting simultaneously.

The Above Result had shown that the Device complied with MPE requirement.

George Hsu

Completed By: George Hsu

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 11/28/2018

