

## RF EXPOSURE REPORT

Applicant	:	Ruijie Networks Co., Ltd.
Address	:	Building 19, Juyuanzhou Industrial Park, No. 618 Jinshan Road, Cangshan District, Fuzhou, Fujian, China
Equipment under Test	:	Wireless Bridge
Model No.	:	RG-EST450G
Trade Mark	:	<i>Ruijie Ruijie</i>   REYEE REYEE REYEE <small>by Ruijie</small>
FCC ID	:	2AX5J-EST450G
Manufacturer	:	Ruijie Networks Co., Ltd.
Address	:	Building 19, Juyuanzhou Industrial Park, No. 618 Jinshan Road, Cangshan District, Fuzhou, Fujian, China
Report No.	:	DDT-B24111211-2E05
Issue Date	:	Dec. 27, 2024
Issued By	:	Tianjin Dongdian Testing Service Co., Ltd.
Address	:	Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China. Tel: +86-22-58038033, E-mail: ddt@dgddt.com, <a href="http://www.ddttest.com">http://www.ddttest.com</a>



# REPORT

## TABLE OF CONTENTS

	Test report declares.....	3
1.	General information .....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory .....	6
2.	RF Exposure Evaluation .....	7
2.1.	Requirement .....	7
2.2.	Calculation method.....	7
2.3.	Estimation result .....	8

**TEST REPORT DECLARE**

<b>Applicant</b>	:	Ruijie Networks Co., Ltd.
<b>Address</b>	:	Building 19, Juyuanzhou Industrial Park, No. 618 Jinshan Road, Cangshan District, Fuzhou, Fujian, China
<b>Equipment under Test</b>	:	Wireless Bridge
<b>Model No.</b>	:	RG-EST450G
<b>Trade mark</b>	:	<b>Ruijie Ruijie</b>   REYEE REYEE REYEE by Ruijie
<b>Manufacturer</b>	:	Ruijie Networks Co., Ltd.
<b>Address</b>	:	Building 19, Juyuanzhou Industrial Park, No. 618 Jinshan Road, Cangshan District, Fuzhou, Fujian, China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Tianjin Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-B24111211-2E05		
<b>Date of Receipt:</b>	Nov. 25, 2024	<b>Date of Test:</b>	Nov. 25, 2024 ~ Dec. 27, 2024

**Prepared By:**

Sunny Zhang

**Sunny Zhang/Engineer**

**Approved By:**

Aaron Zhang

**Aaron Zhang/Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

## Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 27, 2024	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Wireless Bridge
Model Number	: RG-EST450G
EUT function description	: Please reference user manual of this device
Power supply	: 24 V passive PoE power supply (A passive PoE adapter is delivered with the wireless bridge.) 12 V DC (solar panel)
Radio Technology	: IEEE 802.11a/n/ac
Operation frequency	: 2.4G Band: 2412MHz-2462MHz U-NII-1: 5180MHz-5240MHz U-NII-2A: 5260 MHz-5320 MHz U-NII-2C: 5500 MHz-5700 MHz U-NII-III: 5745MHz-5825MHz
Modulation	: 256QAM, 64QAM, 16QAM, QPSK, BPSK
Transmitter rate	: IEEE 802.11a mode: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n mode: MCS0~MCS15 IEEE 802.11ac mode: MCS0~MCS9
Antenna Type	: Directional Antenna: PCB antenna, maximum PK gain: 1.22dBi for 2.4G U-NII-1: Antenna1:13.36dBi, Antenna2: 13.52dBi U-NII-2A: Antenna1:13.54dBi, Antenna2: 13.76dBi U-NII-2C: Antenna1:13.32dBi, Antenna2: 14.11dBi U-NII-III: Antenna1:12.76dBi, Antenna2: 13.10dBi
Exposure category	: General population/uncontrolled environment
Device Type	: Mobile Device
Target power and tolerance	: 2.4G wifi: $18 \pm 2$ dBm, 5G wifi: $15 \pm 2$ dBm

## 1.2. Assess laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: [ddt@dqddt.com](mailto:ddt@dqddt.com)

**NVLAP** (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

**CNAS** (China National Accreditation Service for Conformity Assessment) CODE: L13402

**FCC** Designation Number: CN5004; FCC Test Firm Registration Number: 368676

**ISED** (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

**VCCI** Facility Registration Number: C-20089, T-20093, R-20125, G-20122

## 2. RF Exposure Evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

### 2.3. Estimation result

Worst Mode	Max. Tune Up power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
2.4G wifi	20.00	100	1.22	1.32	0.0263	1
5G wifi	17.00	50.119	14.11	25.76	0.2659	1

Simultaneous: 2.4G wifi+5G wifi=0.0263/1+0.2659/1=0.2832<1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

**END OF REPORT**