

RF EXPOSURE REPORT

FOR

Applicant	:	JSW(DongGuan)Ltd
Address	:	1/F, No. 38 sanjiang Industrial Zone, Hengli Town, Dongguan, Guangdong, China
Equipment under Test	:	Battery Powered Video Doorbell
Model No.	:	T1
Trade Mark	:	/
FCC ID	:	2AYLFT1
Manufacturer	:	JSW(DongGuan)Ltd
Address	:	1/F, No. 38 sanjiang Industrial Zone, Hengli Town, Dongguan, Guangdong, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory	5
2.	RF Exposure evaluation for FCC	5

Test Report Declare

Applicant	:	JSW(DongGuan)Ltd
Address	:	1/F, No. 38 sanjiang Industrial Zone, Hengli Town, Dongguan, Guangdong, China
Equipment under Test	:	Battery Powered Video Doorbell
Model No.	:	T1
Trade mark	:	/
Manufacturer	:	JSW(DongGuan)Ltd
Address	:	1/F, No. 38 sanjiang Industrial Zone, Hengli Town, Dongguan, Guangdong, China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.


Report No:	DDT-R21010404-1E2		
Date of Receipt:	Jan. 13, 2021	Date of Test:	Jan. 13, 2021 ~ Jan. 29, 2021

Prepared By:

Sam Li

Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jan. 29, 2021	

1. General Information

1.1. Description of equipment

EUT* Name	: Battery Powered Video Doorbell
Model Number	: T1
EUT function description	: Please reference user manual of this device
Power Supply	: DC 5V from external AC Adapter : DC 3.7V Polymer Li-ion built-in battery
Radio Technology	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412 MHz - 2462 MHz : IEEE 802.11g: 2412 MHz - 2462 MHz : IEEE 802.11n HT20: 2412 MHz - 2462 MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) : IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps : IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps : IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: 2 dBi
Serial Number	: N/A

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.4G WIFI Manufacturing Tolerance

802.11b (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	11	11	11
Tolerance ±(dB)	1	1	1
802.11g (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	12	12	12
Tolerance ±(dB)	1	1	1
802.11 n HT20 (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	12	12	12
Tolerance ±(dB)	1	1	1

Estimtion Result

The worst case is as below: [2462 MHz, 13 dBm, 19.95 mW) output power]

$(19.95/5) \cdot [\sqrt{2.462(\text{GHz})}] = 6.26 < 7.5$ for 10-g SAR

Then SAR evaluation is not required

END OF REPORT