

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Hd Smart camera with 2.4G WIFI function operating in 2412-2462MHz and 5G WIFI function operating in 5725MHz~5850MHz. The EUT is powered by AC100~250V, 14W. For more detail information pls. refer to the user manual.

2.4GHz WiFi:

Antenna Type: Integral Antenna.

Antenna1 Gain: 1.79dBi.

Modulation Type: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK and DSSS.

The nominal conducted output power specified: 21.0dBm (Tolerance: +/-3dB).

The maximum conducted output power for the EUT is 23.9dBm in the frequency 2462MHz(IEEE 802.11N20) which is within the production variation.

The minimum conducted output power for the EUT is 18.0dBm in the frequency 2462MHz(IEEE 802.11b) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 24dBm +1.79dBi = 25.79dBm = 379.31mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$\begin{aligned} &= 379.31\text{mW} / 4\pi R^2 \\ &= 0.075 \text{ mW/cm}^2 \\ &< 1\text{mW/cm}^2 \end{aligned}$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

5.8GHz WiFi:

Antenna Type: Integral Antenna.

Antenna1 Gain: 2.64dBi.

Modulation Type: BPSK, QPSK, 16QAM, 64QAM and OFDM.

The nominal conducted output power specified: 10dBm (Tolerance: +/-3dB).

The maximum conducted output power for the EUT is 11.21dBm in the frequency 5785MHz(IEEE 802.11 a) which is within the production variation.

The minimum conducted output power for the EUT is 8.80dBm in the frequency 5745MHz(IEEE 802.11 n-HT20) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting device is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 13dBm +2.64dBi = 15.64dBm =36.64mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 36.64\text{mW} / 4\pi R^2$$

$$= 0.0073 \text{ mW/cm}^2$$

$$<1\text{mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

For Simultaneous transmitting of 2.4GHz WiFi and 5.8GHz WiFi, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.075/1 + 0.0073/1 = 0.07573 < 1$

Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”