

EMF TEST REPORT

Test Report No. : OT-226-RWD-023

Reception No. : 2204001320

Applicant : AIN ELECTRONICS, INC.

Address : RM, 1020, Sicox Tower, 484 Dunchon-daero, Jungwon-gu, Seongnam-si, Gyeonggi-do, 13229, South Korea

Manufacturer : AIN ELECTRONICS, INC.

Address : RM, 1020, Sicox Tower, 484 Dunchon-daero, Jungwon-gu, Seongnam-si, Gyeonggi-do, 13229, South Korea

Type of Equipment : TINGBELL

FCC ID. : 2A6YA-AHP-100

Model Name : AHP-100

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : April 21, 2022

Date of issue : June 09, 2022

SUMMARY

The equipment complies with the regulation; *FCC 47 CFR Part 1, 1.1310*

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Joon-Woo, Kim / Assistant Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / General Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
3. GENERAL INFORMATION	5
3.1 PRODUCT DESCRIPTION.....	5
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
4. EUT MODIFICATIONS.....	5
4. RF EXPOSURE EVALUATION	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED MPE SAFE DISTANCE.....	7
4.3.1 Bluetooth LE	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-226-RWD-023	June 09, 2022	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : AIN ELECTRONICS, INC.

Address : RM, 1020, Sicox Tower, 484 Dunchon-daero, Jungwon-gu, Seongnam-si, Gyeonggi-do, 13229, South Korea

Contact Person : Jae gun, Ma / Team Leader

Telephone No. : +82-31-777-9570

FCC ID : 2A6YA-AHP-100

Model Name : AHP-100

Brand Name : -

Serial Number : N/A

Date : June 09, 2022

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	TINGBELL
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

3. GENERAL INFORMATION

3.1 Product Description

The AIN ELECTRONICS, INC., Model AHP-100 (referred to as the EUT in this report) is a TINGBELL. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	TINGBELL
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
MODULATION TYPE	DSSS Modulation(GFSK)
RF OUTPUT POWER	-5.40 dBm
NUMBER OF CHANNEL	40 Channel
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	1.57 dBi
Electrical Rating	DC 3.70 V
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32 MHz

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

4. RF EXPOSURE EVALUATION

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

Kind of EUT	TINGBELL
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> SAR Test Exclusion Evaluation

4.3 Calculated MPE Safe Distance

4.3.1 Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	-5.40 ± 1.0	-4.40	0.36	1.57	1.44	0.20	0.0001	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(0.36 * 1.44)/1.00} = 0.20 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 0.36 * 1.44 / (4 * \pi * 20^2) = 0.0001$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna