

FCC Part 15B TEST REPORT

Product Name : GPS Locator

Model Name : GL300VC

Prepared for:

Queclink Wireless Solutions Co.,Ltd
Room 501, Building 9, No 99, TianZhou Road, Shanghai, China
TEL: +86 21 51082965
FAX: +86 21 54451990

Prepared by:

Unilab (Shanghai) Co., Ltd.
FCC 2.948 register number is 714465
No. 1350, Lianxi Rd. Pudong New District, Shanghai, China
TEL: +86-21-50275125
FAX: +86-21-50277862

Report Number : UL12620141117 FCC 026-1

Date of Report : 25-11-2014

Date of Test : 17-11-2014~24-11-2014

Notes :

The test results only relate to these samples which have been tested.

Partly using this report will not be admitted unless been allowed by Unilab.

Unilab is only responsible for the complete report with the reported stamp of Unilab.

Applicant: Queclink Wireless Solutions Co.,Ltd.
Room 501, Building 9, No 99, TianZhou Road, Shanghai, China.

Manufacturer: Queclink Wireless Solutions Co.,Ltd.
Room 501, Building 9, No 99, TianZhou Road, Shanghai, China.

Product Name: GPS Locator

Brand Name: Queclink

Model Name: GL300VC

FCC ID: YQD- GL300VC

EUT Voltage: Extreme Low: DC 3.6V
Nominal: DC 3.7V
Extreme High:DC4.2V

Date of Receipt: 17-11-2014

Date of Test 17-11-2014~24-11-2014

Test Standard: FCC CFR Title 47 Part 15 Subpart B

Test Result: PASS

Prepared by : Jingwei Li
(Technical Engineer: Jingwei Li)

Reviewed by : Forest Cao
(Senior Engineer: Forest Cao)

Approved by : Eva Wang
(Supervisor Engineer: Eva Wang)

TABLE OF CONTENTS

1.	1. TECHNIACL SUMMARY	4
1.1	SUMMARY OF STANDARDS AND TEST RESULTS	4
1.2	TEST UNCERTAINTY	4
1.3	TEST EQUIPMENT LIST	4
1.4	SUPPORT EQUIPMENT AND CABLE	4
1.5	CABLE OF TEST	4
1.6	TEST MODE AND DESCRIPTION	5
1.7	TEST FACILITY	5
1.8	TEST SETUP CONFIGURATION	5
2.	CONDUCTED DISTURBANCE	6
2.1	TEST SETUP	6
2.2	LIMITS	6
2.3	TEST PROCEDURE	6
2.4	TEST RESULT	7
3.	RADIATED DISTURBANCE (RE)	11
3.1	TEST SETUP	11
3.2	LIMITS	11
3.3	TEST PROCEDURE	12
3.4	TEST RESULT	13
APPENDIX 1	PHOTOGRAPHS OF TEST SETUP.....	21
APPENDIX 2	PHOTOGRAPHS OF EUT	21

1. 1. TECHNIACL SUMMARY

1.1 SUMMARY OF STANDARDS AND TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below:

Test Item	FCC	Result
Conducted disturbance	FCC 15.107	P*
Radiated disturbance	FCC 15.109	P

Note: P means pass, F means failure, N/A means not applicable

1.2 TEST UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Value (dB)
Conducted disturbance	3.4
Radiated disturbance	4.2

1.3 TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Due Date	Cal interval
Receiver	Agilent	N9038A	MY51210142	27/12/2014	1 year
LISN	R&S	NNBM 8126F	1035	22/08/2015	1 year
3m Chamber & Accessory Equipment	ETS-LINDGREN	FACT-3	CT-0000336	26/11/2017	3 years
Biconilog Antenna	SCHWARZBECK	VULB 9160	3316	19/09/2016	2 years
Horn Antenna	SCHWARZBECK	BBHA9120D	942	19/09/2016	2 years
Microwave Preamplifier	EM Electronics	EM30180	3008A02425	19/02/2015	1 year

1.4 SUPPORT EQUIPMENT AND CABLE

Equipment	Manufacturer	Model	Serial No.	Due Date
PC	DELL	VOSTRO 260	7JXLB3X	/
Displayer	DELL	E1910Hc	CN-0CD1MT-64180-OC7-06TS	/
Mouse	DELL	MS111-P	CN-0MF3JY-71581-2C7-05GB	/
Keyboard	DELL	KB212-B	CN-0Y88XT-65890-22L-01MG-A01	/

1.5 CABLE OF TEST

No.	Cable Type	Quantity	Provider	Length(m)	Specification	Note
1	AC Cable	2	Unilab	1.5	Unshielded	None
2	USB cable	1	Queclink	1.0	Unshielded	None
3	VGA Cable	1	Unilab	1.5	Unshielded	None

1.6 TEST MODE AND DESCRIPTION

Test mode1	Data exchange with USB cable,
Description	The EUT connect to PC with a USB cable, then the command "AT+MCUTEST=80" was sent through the hyperterminal to achieve data exchange between PC and EUT.

Test mode2	Connected With Adapter,
Description	The EUT connect with a adapter, which provided by Manufacturer.

1.7 TEST FACILITY

All test facilities used to collect the test data are located at No. 1350, Lianxi Rd. Pudong New District, Shanghai, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4: 2009, CISPR 16-1-1 and other equivalent standards. The laboratory is compliance with the requirements of the ISO/IEC/EN17025.

1.8 TEST SETUP CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.


Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. All the tests were carried out with the EUT in normal operation. Which was shown in this test report is the worst test mode.

2. CONDUCTED DISTURBANCE

2.1 TEST SETUP

For mains port:



2.2 LIMITS

Limits for Class B digital devices

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

2.3 TEST PROCEDURE


For mains port:

- The EUT and support equipment were placed on a nonconductive table 0.8m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane. The EUT connected to the main through Line Impedance Stability Network (L.I.S.N) to provide a 50 Ω/50uH coupling impedance for the measuring equipment. The support equipment is also connected to the main power through a LISN that provides a 50 Ω/50uH coupling impedance with 50 Ω terminations. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission.
- The RBW of the receiver was set at 9 kHz. The frequency range from 150 kHz to 30 MHz was checked. Run the receiver's pre-scan to record the maximum disturbance generated from EUT in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

2.4 TEST RESULT


For mains port:

Test mode: Data exchange



Site : chamber
Condition : FCC P15 CLASS-B (QP) ENV216(N)-20120730 NEUTRAL
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C / 60 %
Power Rating:
Mode : USB DATA EXCHANGE
Memo :


		Read	LISN	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.19	33.91	10.33	0.23	0.00	44.47	64.02	-19.55	Peak
2	pp 1.69	29.54	10.31	0.15	0.00	40.00	46.00	-6.00	Average
3	pk 1.69	37.10	10.31	0.15	0.00	47.56	56.00	-8.44	Peak
4	1.91	28.18	10.31	0.15	0.00	38.64	46.00	-7.36	Average
5	1.91	36.11	10.31	0.15	0.00	46.57	56.00	-9.43	Peak
6	7.02	36.04	10.33	0.32	0.00	46.69	60.00	-13.31	Peak
7	11.44	32.39	10.42	0.34	0.00	43.15	60.00	-16.85	Peak
8	18.92	33.08	10.42	0.11	0.00	43.61	60.00	-16.39	Peak



Site : chamber
Condition : FCC P15 CLASS-B (QP) ENV216(L)-20120730 LINE
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C /60 %
Power Rating:
Mode : USB DATA EXCHANGE
Memo :


	Freq	Read Level	LISN Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.19	36.82	10.46	0.23	0.00	47.51	63.93	-16.42	Peak
2	0.28	33.06	10.48	0.19	0.00	43.73	60.68	-16.95	Peak
3 av	1.69	27.35	10.52	0.15	0.00	38.02	46.00	-7.98	Average
4 pp	1.69	37.46	10.52	0.15	0.00	48.13	56.00	-7.87	Peak
5	1.86	23.18	10.52	0.15	0.00	33.85	46.00	-12.15	Average
6	1.86	35.89	10.52	0.15	0.00	46.56	56.00	-9.44	Peak
7	7.02	34.28	10.46	0.32	0.00	45.06	60.00	-14.94	Peak
8	19.74	30.29	10.53	0.10	0.00	40.92	60.00	-19.08	Peak

Test mode: Connected With Adapter



Site : chamber
 Condition : FCC P15 CLASS-B (QP) ENV216(N)-20120730 NEUTRAL
 EUT : GPS LOCATOR
 Model Name : GL300VC
 Temp/Humi : 25 °C /60 %
 Power Rating:
 Mode : CONNECTED WITH ADAPTER
 Memo :

		Read	LISN	Cable	Preamp	Limit	Over	
	Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dB	
1	pp	0.52	30.26	10.41	0.10	0.00	40.77	-5.23 Average
2	qp	0.52	34.69	10.41	0.10	0.00	45.20	-10.80 QP
3		0.54	28.74	10.39	0.11	0.00	39.24	-6.76 Average
4		0.54	32.85	10.39	0.11	0.00	43.35	-12.65 QP
5		1.03	19.92	10.31	0.14	0.00	30.37	-15.63 Average
6		1.03	31.79	10.31	0.14	0.00	42.24	-13.76 QP
7		1.08	20.35	10.31	0.14	0.00	30.80	-15.20 Average
8		1.08	34.27	10.31	0.14	0.00	44.72	-11.28 QP
9		2.32	30.27	10.32	0.15	0.00	40.74	-5.26 Average
10		2.32	34.06	10.32	0.15	0.00	44.53	-11.47 QP
11	pk	5.96	36.09	10.33	0.23	0.00	46.65	-13.35 Peak




Site : chamber
 Condition : FCC P15 CLASS-B (QP) ENV216(L)-20120730 LINE
 EUT : GPS LOCATOR
 Model Name : GL300VC
 Temp/Humi : 25 °C / 60 %
 Power Rating:
 Mode : CONNECTED WITH ADAPTER
 Memo :

	Freq	Read Level	LISN Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.52	27.59	10.55	0.10	0.00	38.24	46.00	-7.76	Average
2	0.52	37.65	10.55	0.10	0.00	48.30	56.00	-7.70	Peak
3	1.02	23.68	10.52	0.14	0.00	34.34	46.00	-11.66	Average
4	1.02	37.88	10.52	0.14	0.00	48.54	56.00	-7.46	Peak
5 pp	2.17	33.10	10.52	0.15	0.00	43.77	46.00	-2.23	Average
6 pk	2.22	40.43	10.52	0.15	0.00	51.10	56.00	-4.90	Peak
7	3.66	34.42	10.52	0.14	0.00	45.08	56.00	-10.92	Peak
8	4.90	34.49	10.52	0.14	0.00	45.15	56.00	-10.85	Peak
9	5.77	35.28	10.50	0.21	0.00	45.99	60.00	-14.01	Peak


3. RADIATED DISTURBANCE (RE)

3.1 TEST SETUP

30MHz ~ 1GHz:



Above 1GHz:



3.2 LIMITS

Limits for Class B digital devices

Frequency (MHz)	limits at 3m (QP) dB(μV/m)	
30-88	40.0	
88-216	43.5	
216-960	46.0	
Above 960	54.0	
Above 1000	limits at 3m (PEAK) dB(μV/m)	limits at 3m (AV) dB(μV/m)
	74	54

- NOTE:**
1. The lower limit shall apply at the transition frequency.
 2. The limits shown above are based on measuring equipment employing a CISPR quasi-peak detector function for frequencies below or equal to 1000MHz.
 3. The limits shown above are based on measuring equipment employing an average detector function for frequencies above 1000MHz.

3.3 TEST PROCEDURE

30MHz ~ 1GHz:

- a. The EUT and support equipment were placed on the non-conductive turntable 0.8m above the horizontal metal ground plane at a chamber. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Broadband antenna (Calibrated Bilog Antenna) was used as receiving antenna.
- b. The frequency range from 30MHz to 1GHz was checked. The RBW of the receiver was set at 120kHz. Set the receiver in Peak detector, Max Hold mode. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- c. For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where EUT radiated the maximum emission, then set the test frequency receiver to QP Detector and record the maximum value.


Above 1GHz:

- a. The EUT and support equipment were placed on the non-conductive turntable 0.8m above the ground at a chamber. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Horn antenna was used as receiving antenna.
- b. The frequency range above 1GHz was checked. The RBW of the receiver was set at 1MHz. Set the receiver in Peak detector, Max Hold mode. Record the maximum field strength of all the pre-scan process in the full band when the antenna is 1m and varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- c. For each frequency whose maximum record was higher or close to limit, measure its Average value: rotate the turntable from 0 to 360 degrees to find the degree where EUT radiated the maximum emission, then set the test frequency receiver to EMI Average Detector and record the maximum value.

3.4 TEST RESULT


30MHz ~ 1GHz:

Test mode: Data exchange



Site : chamber
 Condition : FCC PART 15 CLASS-B 3m VULB9160 VERTICAL
 EUT : GPS LOCATOR
 Model Name : GL300VC
 Temp/Humi : 25 °C /60 %
 Power Rating:
 Mode : USB DATE EXCHANGE
 Memo :

	Freq	Read Level	LISN Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1 pp	32.91	18.72	12.22	0.71	0.00	31.65	40.00	-8.35	Peak
2	120.21	12.44	12.03	1.45	0.00	25.92	43.50	-17.58	Peak
3	213.33	16.13	10.61	1.99	0.00	28.73	43.50	-14.77	Peak
4	287.05	11.86	12.96	2.25	0.00	27.07	46.00	-18.93	Peak
5	533.43	8.85	17.54	3.13	0.00	29.52	46.00	-16.48	Peak
6	758.47	10.86	21.37	3.72	0.00	35.95	46.00	-10.05	Peak




Site : chamber
Condition : FCC PART 15 CLASS-B 3m VULB9160 HORIZONTAL
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C /60 %
Power Rating:
Mode : USB DATE EXCHANGE
Memo :

	Freq	Read Level	LISN Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	132.82	14.52	12.92	1.61	0.00	29.05	43.50	-14.45	Peak
2	167.74	11.83	13.44	1.81	0.00	27.08	43.50	-16.42	Peak
3	239.52	11.98	11.71	2.12	0.00	25.81	46.00	-20.19	Peak
4	252.13	13.58	11.96	2.16	0.00	27.70	46.00	-18.30	Peak
5	585.81	6.80	18.78	3.29	0.00	28.87	46.00	-17.13	Peak
6 pp	828.31	6.53	21.95	3.92	0.00	32.40	46.00	-13.60	Peak


Above 1GHz:

Test mode: Data exchange



Site : chamber
 Condition : FCC CLASS-B PK 3m BBHA9120D(942) HORIZONTAL
 EUT : GPS LOCATOR
 Model Name : GL300VC
 Temp/Humi : 25 °C /60 %
 Power Rating:
 Mode : USB DATE EXCHANGE
 Memo :


	Freq	Read Level	LISN Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	1595.00	50.10	24.98	5.71	38.46	42.33	74.00	-31.67	Peak
2	7307.00	38.41	36.48	12.71	37.37	50.23	74.00	-23.77	Peak
3	13529.00	27.58	40.85	17.45	38.56	47.32	54.00	-6.68	Average
4	13529.00	33.69	40.85	17.45	38.56	53.43	74.00	-20.57	Peak
5	14855.00	31.03	41.71	18.61	37.85	53.50	74.00	-20.50	Peak
6	16640.00	28.55	39.94	17.82	38.47	47.84	54.00	-6.16	Average
7	16640.00	35.55	39.94	17.82	38.47	54.84	74.00	-19.16	Peak
8 pp	17966.00	19.62	47.57	18.66	36.76	49.09	54.00	-4.91	Average
9 pk	17966.00	26.62	47.57	18.66	36.76	56.09	74.00	-17.91	Peak



Site : chamber
 Condition : FCC CLASS-B PK 3m BBHA9120D(942) VERTICAL
 EUT : GPS LOCATOR
 Model Name : GL300VC
 Temp/Humi : 25 °C /60 %
 Power Rating:
 Mode : USB DATE EXCHANGE
 Memo :


	Freq	Read Level	LISN Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	1595.00	55.83	24.98	5.71	38.46	48.06	74.00	-25.94	Peak
2	2666.00	51.32	27.92	7.49	38.24	48.49	74.00	-25.51	Peak
3	11693.00	27.54	39.75	16.22	39.25	44.26	54.00	-9.74	Average
4	11693.00	37.74	39.75	16.22	39.25	54.46	74.00	-19.54	Peak
5	14498.00	22.36	42.55	18.96	38.21	45.66	54.00	-8.34	Average
6	14498.00	32.61	42.55	18.96	38.21	55.91	74.00	-18.09	Peak
7	16742.00	27.58	40.38	18.02	38.45	47.53	54.00	-6.47	Average
8	16742.00	37.87	40.38	18.02	38.45	57.82	74.00	-16.18	Peak
9 pp	18000.00	18.01	48.08	18.81	36.70	48.20	54.00	-5.80	Average
10 pk	18000.00	30.23	48.08	18.81	36.70	60.42	74.00	-13.58	Peak

Test mode: Connected With Adapter



Site : chamber
Condition : FCC PART 15 CLASS-B 3m VULB9160 VERTICAL
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C /60 %
Power Rating:
Mode : CONNECTED WITH ADAPTER
Memo :


		Read	LISN	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	pp	38.73	23.16	12.61	0.81	0.00	36.58	40.00	-3.42 QP
2		78.50	25.47	9.14	1.09	0.00	35.70	40.00	-4.30 QP
3	pk	127.00	23.41	12.51	1.56	0.00	37.48	43.50	-6.02 Peak
4		161.92	18.16	13.77	1.70	0.00	33.63	43.50	-9.87 Peak
5		445.16	3.61	16.30	2.87	0.00	22.78	46.00	-23.22 Peak
6		931.13	2.98	23.07	4.11	0.00	30.16	46.00	-15.84 Peak



Site	: chamber							
Condition	: FCC PART 15 CLASS-B 3m VULB9160 HORIZONTAL							
EUT	: GPS LOCATOR							
Model Name	: GL300VC							
Temp/Humi	: 25 °C /60 %							
Power Rating:								
Mode	: CONNECTED WITH ADAPTER							
Memo	:							
	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 pp	77.53	24.02	9.14	1.10	0.00	34.26	40.00	-5.74 Peak
2	110.51	18.51	11.07	1.41	0.00	30.99	43.50	-12.51 Peak
3	160.95	9.63	13.77	1.69	0.00	25.09	43.50	-18.41 Peak
4	294.81	5.16	13.11	2.40	0.00	20.67	46.00	-25.33 Peak
5	360.77	5.10	14.39	2.66	0.00	22.15	46.00	-23.85 Peak
6	938.89	3.93	23.23	4.13	0.00	31.29	46.00	-14.71 Peak


Above 1GHz:

Test mode: Connected With Adapter



Site : chamber
Condition : FCC CLASS-B PK 3m BBHA9120D(942) HORIZONTAL
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C /60 %
Power Rating:
Mode : CONNECTED WITH ADAPTER
Memo :

	Freq	Read Level	LISN Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	5590.00	42.05	32.08	11.14	36.92	48.35	74.00	-25.65	Peak
2	7902.00	42.89	37.00	12.84	39.44	53.29	74.00	-20.71	Peak
3	9738.00	30.48	38.40	14.34	39.87	43.35	54.00	-10.65	Average
4	9738.00	43.79	38.40	14.34	39.87	56.66	74.00	-17.34	Peak
5	12407.00	29.04	38.71	17.32	38.99	46.08	54.00	-7.92	Average
6	12407.00	39.59	38.71	17.32	38.99	56.63	74.00	-17.37	Peak
7	14328.00	25.73	42.37	19.05	38.38	48.77	54.00	-5.23	Average
8	14328.00	34.55	42.37	19.05	38.38	57.59	74.00	-16.41	Peak
9 pp	17320.00	25.48	42.01	19.25	37.85	48.89	54.00	-5.11	Average
10 pk	17320.00	35.85	42.01	19.25	37.85	59.26	74.00	-14.74	Peak



Site : chamber
Condition : FCC CLASS-B PK 3m BBHA9120D(942) VERTICAL
EUT : GPS LOCATOR
Model Name : GL300VC
Temp/Humi : 25 °C /60 %
Power Rating:
Mode : CONNECTED WITH ADAPTER
Memo :

		Read	LISN	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	2445.00	46.05	27.46	7.37	38.32	42.56	74.00	-31.44	Peak
2	6729.00	32.32	34.42	12.53	36.44	42.83	54.00	-11.17	Average
3	6729.00	42.28	34.42	12.53	36.44	52.79	74.00	-21.21	Peak
4	9891.00	31.18	38.68	14.71	39.59	44.98	54.00	-9.02	Average
5	9891.00	40.08	38.68	14.71	39.59	53.88	74.00	-20.12	Peak
6	14311.00	23.18	42.34	18.96	38.39	46.09	54.00	-7.91	Average
7	14311.00	34.11	42.34	18.96	38.39	57.02	74.00	-16.98	Peak
8	16572.00	25.16	39.54	18.00	38.48	44.22	54.00	-9.78	Average
9	16572.00	36.53	39.54	18.00	38.48	55.59	74.00	-18.41	Peak
10 pp	17932.00	19.97	47.05	18.74	36.82	48.94	54.00	-5.06	Average
11 pk	17932.00	30.58	47.05	18.74	36.82	59.55	74.00	-14.45	Peak

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

Please refer to the file named “YQD-GL300VC _Part 15B Setup Photos”.

APPENDIX 2 PHOTOGRAPHS OF EUT

Please refer to the file named “YQD- GL300VC _EUT Photos”.

-----End of the report-----