

Test Laboratory: Compliance Certification Services

File Name: [1_EUT Setup Configuration 1_Aux Antenna.da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 1_EUT Setup Configuration 1_Aux Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 24.0 deg. C

Communication System: 5800MHz band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 6.16$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003

- Sensor-Surface: 3mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn500; Calibrated: 12/23/2003

- Phantom: SAM 2; Type: SAM 2; Serial: 1050

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

L-ch/Area Scan (11x15x1): Measurement grid: dx=10mm, dy=10mm

L-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm

Reference Value = 3.53 V/m; Power Drift = 0.13 dB

Maximum value of SAR (measured) = 0.638 mW/g

Peak SAR (extrapolated) = 1.89 W/kg

SAR(1 g) = 0.492 mW/g; SAR(10 g) = 0.196 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

L-ch/Zoom Scan (7x7x8)/Cube 1: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm


Reference Value = 3.53 V/m; Power Drift = 0.13 dB

Maximum value of SAR (measured) = 0.462 mW/g

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.300 mW/g; SAR(10 g) = 0.128 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [1_EUT Setup Configuration 1_Aux Antenna.da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 1_EUT Setup Configuration 1_Aux Antenna (WNC)

Communication System: 5800MHz band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 6.16$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³


Phantom section: Flat Section

L-ch/Z Scan (1x1x41): Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=2.5$ mm

Reference Value = 3.53 V/m; Power Drift = 0.0 dB

Maximum value of SAR (measured) = 0.316 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [1_EUT Setup Configuration 1_Aux Antenna.da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 1_EUT Setup Configuration 1_Aux Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 24.0 deg. C

Communication System: 5800MHz band; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5785$ MHz; $\sigma = 6.25$ mho/m; $\epsilon_r = 47.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003

- Sensor-Surface: 3mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn500; Calibrated: 12/23/2003

- Phantom: SAM 2; Type: SAM 2; Serial: 1050

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

M-ch/Area Scan (11x15x1): Measurement grid: dx=10mm, dy=10mm

M-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm

Reference Value = 4.29 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.609 mW/g

Peak SAR (extrapolated) = 1.81 W/kg

SAR(1 g) = 0.459 mW/g; SAR(10 g) = 0.184 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

M-ch/Zoom Scan (7x7x8)/Cube 1: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm


Reference Value = 4.29 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.536 mW/g

Peak SAR (extrapolated) = 14.3 W/kg

SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.127 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [1_EUT Setup Configuration 1_Aux Antenna.da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 1_EUT Setup Configuration 1_Aux Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 24.0 deg. C

Communication System: 5800MHz band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5825$ MHz; $\sigma = 6.31$ mho/m; $\epsilon_r = 47.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003

- Sensor-Surface: 3mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn500; Calibrated: 12/23/2003

- Phantom: SAM 2; Type: SAM 2; Serial: 1050

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

H-ch/Area Scan (11x15x1): Measurement grid: dx=10mm, dy=10mm

H-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm

Reference Value = 4.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.475 mW/g

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.356 mW/g; SAR(10 g) = 0.150 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

H-ch/Zoom Scan (7x7x8)/Cube 1: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm


Reference Value = 4.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.521 mW/g

Peak SAR (extrapolated) = 6.11 W/kg

SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.117 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [2_EUT Setup Configuration 2_Main Antenna \(WNC\).da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 2_EUT Setup Configuration 2_Main Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 24.0 deg. C

Communication System: 5800MHz band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 6.16$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003

- Sensor-Surface: 3mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn500; Calibrated: 12/23/2003

- Phantom: SAM 2; Type: SAM 2; Serial: 1050

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

L-ch/Area Scan (11x13x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 3.64 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.357 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

L-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm


Reference Value = 3.64 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.367 mW/g

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.289 mW/g; SAR(10 g) = 0.138 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [2_EUT Setup Configuration 2_Main Antenna \(WNC\).da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 2_EUT Setup Configuration 2_Main Antenna (WNC)

Communication System: 5800MHz band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 6.16$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³


Phantom section: Flat Section

L-ch/Z Scan (1x1x41): Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=2.5$ mm

Reference Value = 3.64 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.171 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [2_EUT Setup Configuration 2_Main Antenna \(WNC\).da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 2_EUT Setup Configuration 2_Main Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 23.0 deg. C

Communication System: 5800MHz band; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5785 \text{ MHz}$; $\sigma = 6.25 \text{ mho/m}$; $\epsilon_r = 47.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003

- Sensor-Surface: 3mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn500; Calibrated: 12/23/2003

- Phantom: SAM 2; Type: SAM 2; Serial: 1050

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

M-ch/Area Scan (11x13x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Reference Value = 3.77 V/m; Power Drift = 0.14 dB

Maximum value of SAR (measured) = 0.430 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

M-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: $dx=4.3\text{mm}$, $dy=4.3\text{mm}$, $dz=3\text{mm}$


Reference Value = 3.77 V/m; Power Drift = 0.14 dB

Maximum value of SAR (measured) = 0.395 mW/g

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.143 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)



Test Laboratory: Compliance Certification Services

File Name: [2_EUT Setup Configuration 2_Main Antenna \(WNC\).da4](#)

DUT: Dell Computer Corporation; Type: WM3A2915ABG; Serial: N/A

Program Name: 2_EUT Setup Configuration 2_Main Antenna (WNC)

Ambient Temp.: 25.0 deg. C; Liquid Temp.: 24.0 deg. C

Communication System: 5800MHz band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5825$ MHz; $\sigma = 6.31$ mho/m; $\epsilon_r = 47.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3021; ConvF(1.1, 1.1, 1.1); Calibrated: 7/29/2003
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 12/23/2003
- Phantom: SAM 2; Type: SAM 2; Serial: 1050
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

H-ch/Area Scan (11x13x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 3.85 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.324 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

H-ch/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm

Reference Value = 3.85 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.329 mW/g

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.253 mW/g; SAR(10 g) = 0.128 mW/g

[Info: Interpolated medium parameters used for SAR evaluation!](#)

