

Mervilla, August 4th, 2021

Subject: Acknowledgment of FCC Modular approval requirements

Applicant: XPLORER
Product: XPMF
FCC ID: XFJMF

To Whom It May Concern:

This application is the XPMF range is the coil part of a wireless metal detector.

All XPMF models are identical except for external enclozure size :

FMF22 : Ø22.5cmFMF28 : Ø28cm

> FMF3428 : Ø34x28cm

Modular Approval Requirement	Yes	No
(i) The radio elements of the modular transmitter must have their own		х
shielding. The physical crystal and tuning capacitors may be located		
external to the shielded radio elements.		
(ii) The modular transmitter must have buffered modulation/data inputs	Х	
(if such inputs are provided) to ensure that the module will comply with		
part 15 requirements under conditions of excessive data rates or over-		
modulation.		
(iii) The modular transmitter must have its own power supply regulation.	Х	
(iv) The modular transmitter must comply with the antenna and	Х	
transmission system requirements of §§ 15.203, 15.204(b) and		
15.204(c). The antenna must either be permanently attached or employ		
a "unique" antenna coupler (at all connections between the module		
and the antenna, including the cable). The "professional installation"		
provision of § 15.203 is not applicable to modules but can apply to		
limited modular approvals under paragraph (b) of this section.		
(v) The modular transmitter must be tested in a stand-alone		х
configuration		
(vi) The modular transmitter must be equipped with either a	Х	
permanently affixed label or must be capable of electronically displaying		
its FCC identification number.		

(vii) The modular transmitter must comply with any specific rules or	х	
operating requirements that ordinarily apply to a complete transmitter		
and the manufacturer must provide adequate instructions along with		
the module to explain any such requirements. A copy of these		
instructions must be included in the application for equipment		
authorization.		
(viii) The modular transmitter must comply with any applicable RF	х	
exposure requirements in its final configuration.		

The module is only integrated in XPLORER equipment. It is systematically tested in the host equipment.

Regards,

Alain Loubet August 4th, 2021