

FCC ID : 2AMEH-ECC-B

1. RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Limits for Maximum Permissible Exposure (MPE).

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm².

P_{out} =output power to antenna in mW.

G = Numeric gain of the antenna relative to isotropic antenna.

π =3.1416.

R = distance between observation point and center of the radiator in 20cm.

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2. EUT TECHNICAL DESCRIPTION

Product Name:	Energy Control Center Basic Version
Model Number:	ECC-B
IEEE 802.11 WLAN Mode Supported:	802.11b 802.11g 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n
Operating Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
Number of Channels:	11 channels for 802.11b/g/n(HT20) 7 Channels for 802.11n(HT40)
Antenna Type:	External Antenna
Antenna Gain:	2.23dBi
Power Supply:	AC 230V/50Hz by Adapter Adapter : Model: DCT30W120200ZZ-A0 Input: 100-240V~50/60Hz, 0.8A Max Output: 12V, 2A, 24W
Temperature Range:	-20°C ~ 60°C

3. Measurement Result

Pass

Mode	Frequency (MHz)	Max Power (dBm)	Antenna gain (dBi)	Antenna Gain Numeric	R (cm)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2.4G WIFI	2412	15.00	2.23	1.67	20	0.011	1.0000

Note: All the modes are tested, only the worst data are described in the table.

----- The End -----