

---

# FCC Test Report

---

Report No.: AGC01284221006FE10

**FCC ID** : T4K-D278U

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Digital DMR and Analog UHF Two Way Radio

**BRAND NAME** : Anytone, RADIOCOM

**MODEL NAME** : AT-D278, T-D278EX, AT-D278U, AT-D278II, AT-D278 PLUS,  
AT-D279, AT-D279EX, AT-D279U, AT-D279II, DT1000

**APPLICANT** : Qixiang Electron Science & Technology Co., Ltd.

**DATE OF ISSUE** : Feb. 08, 2023

**STANDARD(S)** : FCC Part 90 Rules

**REPORT VERSION** : V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



**REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Feb. 08, 2023	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2. PRODUCT INFORMATION .....</b>	<b>6</b>
2.1 PRODUCT TECHNICAL DESCRIPTION .....	6
2.2 TEST FREQUENCY LIST .....	7
2.3 RELATED SUBMITTAL(S) / GRANT (S) .....	8
2.4 TEST METHODOLOGY .....	8
2.5 CALCULATION OF EMISSION INDICATORS .....	8
2.6 SPECIAL ACCESSORIES .....	8
2.7 EQUIPMENT MODIFICATIONS .....	8
<b>3. TEST ENVIRONMENT .....</b>	<b>9</b>
3.1 ADDRESS OF THE TEST LABORATORY .....	9
3.2 TEST FACILITY .....	9
3.3 ENVIRONMENTAL CONDITIONS .....	9
3.4 MEASUREMENT UNCERTAINTY .....	10
3.5 LIST OF EQUIPMENTS USED .....	11
<b>4.SYSTEM TEST CONFIGURATION .....</b>	<b>12</b>
4.1 EUT CONFIGURATION .....	12
4.2 EUT EXERCISE .....	12
4.3 CONFIGURATION OF TESTED SYSTEM .....	12
4.4 EQUIPMENT USED IN TESTED SYSTEM .....	12
4.5 SUMMARY OF TEST RESULTS .....	13
<b>5.DESCRPTION OF TEST MODES .....</b>	<b>14</b>
<b>6.FREQUENCY TOLERANCE .....</b>	<b>15</b>
6.1 PROVISIONS APPLICABLE .....	15
6.2 MEASUREMENT PROCEDURE .....	15
6.3 MEASUREMENT SETUP .....	15
6.4 MEASUREMENT RESULTS .....	16
<b>7. EMISSION BANDWIDTH .....</b>	<b>18</b>
7.1 PROVISIONS APPLICABLE .....	18
7.2 MEASUREMENT PROCEDURE .....	18
7.3 MEASUREMENT SETUP .....	18
7.4 MEASUREMENT RESULTS .....	19
<b>8. SPURIOUS RADIATED EMISSION .....</b>	<b>23</b>
8.1 PROVISIONS APPLICABLE .....	23
8.2 MEASUREMENT PROCEDURE .....	23

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 MEASUREMENT SETUP .....	24
8.4 MEASUREMENT RESULTS.....	24
8.5 EMISSION MASK PLOT .....	34
<b>9.MODULATION CHARACTERISTICS .....</b>	<b>38</b>
9.1 PROVISIONS APPLICABLE.....	38
9.2 MEASUREMENT METHOD .....	38
9.3 MEASUREMENT SETUP .....	38
9.4 MEASUREMENT RESULTS.....	39
<b>10. MAXIMUM TRANSMITTER POWER .....</b>	<b>41</b>
10.1 PROVISIONS APPLICABLE.....	41
10.2 MEASUREMENT METHOD .....	41
10.3 MEASUREMENT METHOD .....	41
10.4 MEASUREMENT RESULTS .....	41
<b>11. SPURIOUS EMISSION ON ANTENNA PORT .....</b>	<b>46</b>
11.1 PROVISIONS APPLICABLE .....	46
11.2 MEASUREMENT METHOD.....	46
11.3 MEASUREMENT SETUP .....	46
11.4 MEASUREMENT RESULTS.....	47
<b>12.TRANSMITTER FREQUENCY BEHAVIOR.....</b>	<b>53</b>
12.1 PROVISIONS APPLICABLE.....	53
13.2 MEASUREMENT SETUP .....	53
12.3 MEASUREMENT METHOD .....	54
12.4 MEASURET RESULTS.....	56
<b>13. AUDIO LOW PASS FILTER RESPONSE .....</b>	<b>57</b>
13.1 PROVISIONS APPLICABLE.....	57
13.2 MEASUREMENT METHOD .....	58
13.3 MEASUREMENT SETUP .....	58
13.4 MEASURET RESULTS.....	59
<b>APPENDIX I: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>60</b>
<b>APPENDIX II: PHOTOGRAPHS OF TEST EUT .....</b>	<b>60</b>

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


## 1. GENERAL INFORMATION

Applicant	Qixiang Electron Science & Technology Co., Ltd.
Address	Qixiang Building, Tangxi Industrial Zone, Luojiang, Quanzhou, Fujian, 362011 China
Manufacturer	Qixiang Electron Science & Technology Co., Ltd.
Address	Qixiang Building, Tangxi Industrial Zone, Luojiang, Quanzhou, Fujian, 362011 China
Factory	Qixiang Electron Science & Technology Co., Ltd.
Address	Qixiang Building, Tangxi Industrial Zone, Luojiang, Quanzhou, Fujian, 362011 China
Product Designation	Digital DMR and Analog UHF Two Way Radio
Brand Name	Anytone, RADIOCOM
Test Model	AT-D278
Series Model(s)	AT-D278EX, AT-D278U, AT-D278II, AT-D278 PLUS, AT-D279, AT-D279EX, AT-D279U, AT-D279II, DT1000
Difference Description	AT-D278 series only model name is different, AT-D279 series only model name is different. AT-D278 series & AT-D279 series both brand name is Anytone, the brand name of D1000 is RADIOCOM. AT-D278 series & D1000 have different cover line design from AT-D279 series.
Deviation from Standard	None
Date of receipt of test item	Oct. 18, 2022
Date of Test	Oct. 18, 2022~Feb. 08, 2023
Test Result	Pass

### WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 90. The test results of this report relate only to the tested sample identified in this report.

Prepared By



Bibo Zhang  
(Project Engineer)

Feb. 08, 2023

Reviewed By



Calvin Liu  
(Reviewer)

Feb. 08, 2023

Approved By



Max Zhang  
Authorized Officer

Feb. 08, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

## 2. PRODUCT INFORMATION

### 2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	V2.2	
Software Version	V1.0	
Power Supply	DC 7.4V 2600mAh	
Communication Type	Voice / Data	
Operation Frequency Range	From 400MHz to 480MHz--UHF	
Modulation Type	Analog Voice:	FM
	Digital (Voice+Data):	4FSK
Digital Type	DMR	
Channel Separation	Analog Voice:	12.5 kHz
	Digital (Voice+Data):	12.5 kHz
Support Data Rate	9600bps	
Emission Designator	Analog Voice:	11K0F3E
	Digital (Voice+Data):	<input checked="" type="checkbox"/> UHF:7K79F1D-5W-12.5kHz <input checked="" type="checkbox"/> UHF:7K79F1D-1W-12.5kHz <input checked="" type="checkbox"/> UHF:7K79F1W-5W-12.5kHz <input checked="" type="checkbox"/> UHF:7K79F1W-1W-12.5kHz
Rated Output Power	5W/1W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	UHF: 36.92dBm(5W-12.5kHz)      UHF: 29.90dBm(1W-12.5kHz)	
Antenna Designation	Detachable Antenna	
Antenna Gain	1.5dBi	
Frequency Tolerance	1.097ppm	

#### Note:

1. The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.
3. The actual working frequency band of the device is UHF: 400-480MHz. According to the frequency division requirements of KDB634817 and the federal frequency allocation requirements, the working frequency band that the device needs to meet is UHF: 406.1-480MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 2.2 TEST FREQUENCY LIST

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 kHz	400-480MHz	Bottom	406.125 MHz
	12.5 kHz	400-480MHz	Middle	453.2125 MHz
	12.5 kHz	400-480MHz	Middle	458.2125 MHz
	12.5 kHz	400-480MHz	Top	479.975 MHz

### Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



## 2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **T4K-D278U**, filing to comply with Part 2, Part 90 of the Federal Communication Commission rules.

## 2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 90	Private Land Mobile Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
4	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
5	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01
6	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
7	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

## 2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

### For FM Mode (Channel Spacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

### For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

## 2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

## 2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>



### 3. TEST ENVIRONMENT

#### 3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L5488**

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

##### **A2LA-Lab Cert. No.: 5054.02**

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

##### **FCC-Registration No.: 975832**

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

##### **IC-Registration No.: 24842**

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

### 3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS
Temperature range (°C)	15 - 35	-20 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 7.4V	LV:DC 6.29V/HV: DC 8.51V

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

### 3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

### 3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9020A	MY53300860	Jun. 08, 2022	Jun. 07, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
preamplifier	ChengYi	EMC184045SE	980508	Oct. 29, 2021	Oct. 28, 2023
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 05, 2022	Jun. 04, 2023
HORN ANTENNA	EM	EM-AH-10180	/	Feb.24, 2022	Feb.23, 2023
SIGNAL GENERATOR	AGILENT	E4421B	MY43351603	Mar. 04 2022	Mar. 03, 2023
SIGNAL GENERATOR	R&S	SMT03	A0304261	Jun. 05, 2022	Jun. 04, 2023
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Apr. 28, 2021	Apr. 27, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2022	May 21, 2024
Modulation Domain Analyzer	HP	53310A	3121A02467	Jun. 08, 2022	Jun. 07, 2024
Small environmental tester	ESPEC	SH-242	93008290	Aug. 03, 2022	Aug. 02, 2024
RF Communication Test Set	HP	8920B	US35010161	Aug. 03, 2022	Aug. 02, 2023
Attenuator	Weinachel Corp	58-30-33	ML030	Oct. 24, 2021	Oct. 23, 2022
RF Cable	R&S	1#	--	Each time	N/A
RF Cable	R&S	2#	--	Each time	N/A
Fliter-UHF	Microwave	N25155M2	498705	May 07, 2022	May 06, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 4.SYSTEM TEST CONFIGURATION

### 4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### 4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

### 4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

### 4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

- ☐ Test Accessories Come From The Laboratory  
☒ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	ID or Specification	Remark
1	Digital DMR and Analog UHF Two Way Radio	AT-D278	T4K-D278U	EUT
2	Charger	QBC-55L	Input: DC 12V 1A Output: DC 8.4V 1A	AE
3	Battery	QB-55HL	DC 7.4V 2600mAh	AE
4	Antenna	N/A	N/A	AE
5	Back clip	N/A	N/A	AE

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

#### 4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	FCC PART 90	Antenna Equipment	Pass
2	§90.205& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 2.1049	Occupied Bandwidth	Pass
6	§90.210& 2.1049	Emission Mask	Pass
7	§90.213& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210& 2.1053	Spurious Radiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 5.DESCRPTION OF TEST MODES

The EUT (**Digital DMR and Analog UHF Two Way Radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

NO.	TEST MODE DESCRIPTION	CHANNEL SEPARATION
1	TX Bottom channel-UHF	12.5 kHz
2	TX Middle channel-UHF	12.5 kHz
3	TX Middle channel-UHF	12.5 kHz
4	TX Top channel-UHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The battery is full-charged during the test.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
5. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 6.FREQUENCY TOLERANCE

### 6.1 PROVISIONS APPLICABLE

- According to FCC §2.1055,§90.213, the frequency stability shall be measured with variation of ambient temperature from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  centigrade.
- According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 kHz channel separation and 0.0001% for 6.25 kHz channel separation.

### 6.2 MEASUREMENT PROCEDURE


#### 6.2.1 Frequency stability versus environmental temperature

- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
- Set the temperature of chamber to  $50^{\circ}\text{C}$ . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- Repeat step 2 with a  $10^{\circ}\text{C}$  decreased per stage until the lowest temperature  $-30^{\circ}\text{C}$  is measured, record all measured frequencies on each temperature step.

#### 6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within  $15^{\circ}\text{C}$  to  $25^{\circ}\text{C}$ . Otherwise, an environment chamber set for a temperature of  $20^{\circ}\text{C}$  shall be used. The EUT shall be powered by DC 7.4V.
- Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

### 6.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).



#### 6.4 MEASUREMENT RESULTS

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	479.975		
7.40	-30	0.775	0.653	0.505	0.641	2.5	Pass
	-20	0.781	0.842	0.961	0.326		
	-10	0.789	0.948	1.092	0.342		
	0	0.795	0.886	0.783	0.349		
	10	0.526	0.603	0.806	0.517		
	20	0.956	0.529	0.658	0.854		
	30	0.983	0.966	0.653	0.687		
	40	0.828	0.571	0.738	0.900		
	50	1.045	0.847	0.681	0.532		
8.51	20	0.565	0.779	0.852	0.889	2.5	Pass
6.29	20	0.622	0.628	0.915	0.475		

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	479.975		
7.40	-30	0.543	0.653	0.772	0.993	2.5	Pass
	-20	0.931	0.932	0.622	0.552		
	-10	0.542	0.808	0.505	0.565		
	0	1.066	0.527	1.066	0.421		
	10	0.889	0.676	0.870	0.928		
	20	1.014	0.965	0.623	0.831		
	30	0.737	1.098	0.500	0.944		
	40	0.759	0.710	0.719	0.450		
	50	0.704	0.713	0.880	0.657		
8.51	20	0.968	1.095	1.085	0.665	2.5	Pass
6.29	20	0.832	0.912	0.949	0.957		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	479.975		
7.40	-30	0.707	0.653	0.763	0.951	2.5	Pass
	-20	1.025	0.586	0.784	0.602		
	-10	0.531	1.029	0.966	0.904		
	0	0.902	0.536	0.967	0.740		
	10	0.612	0.702	0.507	0.383		
	20	0.562	0.671	0.925	0.427		
	30	0.596	1.046	1.059	0.461		
	40	0.899	0.941	0.849	0.828		
	50	0.791	1.023	0.753	0.659		
8.51	20	0.766	0.846	0.978	0.590	2.5	Pass
6.29	20	0.540	0.965	0.764	0.734		

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	479.975		
7.40	-30	0.331	0.653	0.848	0.864	2.5	Pass
	-20	0.722	0.623	0.723	0.739		
	-10	0.955	0.730	0.829	0.616		
	0	0.972	1.071	0.813	0.959		
	10	0.598	0.642	0.605	0.420		
	20	0.823	0.618	0.856	0.678		
	30	0.683	0.791	0.585	0.787		
	40	0.898	1.041	0.829	0.656		
	50	0.927	0.741	0.893	0.991		
8.51	20	0.661	0.937	0.701	0.514	2.5	Pass
6.29	20	0.631	0.583	1.045	0.668		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 7. EMISSION BANDWIDTH

### 7.1 PROVISIONS APPLICABLE

FCC Part 90.209 & FCC Part 2.1049:

The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

### 7.2 MEASUREMENT PROCEDURE

1.The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.

Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).

2.Spectrum set as follow:


Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=100Hz, VBW=300Hz, Sweep = auto,

Detector function = peak, Trace = max hold

3.Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.

4.Measure and record the results in the test report.

### 7.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 7.4 MEASUREMENT RESULTS

Measurement Result of UHF-Analog Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.960 kHz	10.17 kHz	11.25 kHz	Pass
453.2125 MHz	10.006 kHz	10.19 kHz	11.25 kHz	Pass
458.2125 MHz	10.004 kHz	10.18 kHz	11.25 kHz	Pass
479.975 MHz	9.992 kHz	10.19 kHz	11.25 kHz	Pass


Measurement Result of UHF-Analog Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.958 kHz	10.17 kHz	11.25 kHz	Pass
453.2125 MHz	10.005 kHz	10.18 kHz	11.25 kHz	Pass
458.2125 MHz	10.004 kHz	10.18 kHz	11.25 kHz	Pass
479.975 MHz	9.992 kHz	10.18 kHz	11.25 kHz	Pass

Measurement Result of UHF-Digital Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	7.279 kHz	9.924 kHz	11.25 kHz	Pass
453.2125 MHz	7.258 kHz	9.428 kHz	11.25 kHz	Pass
458.2125 MHz	7.579 kHz	9.651 kHz	11.25 kHz	Pass
479.975 MHz	7.445 kHz	9.823 kHz	11.25 kHz	Pass

Measurement Result of UHF- Digital Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	7.279 kHz	9.496 kHz	11.25 kHz	Pass
453.2125 MHz	7.690 kHz	10.250 kHz	11.25 kHz	Pass
458.2125 MHz	7.611 kHz	10.140 kHz	11.25 kHz	Pass
479.975 MHz	7.788 kHz	9.963 kHz	11.25 kHz	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




### 12.5kHz, FM Modulation:458.2125MHz-1W




### 12.5kHz, FM Modulation:479.975MHz-1W




### 12.5kHz, 4FSK Modulation:406.125MHz-5W




### 12.5kHz, 4FSK Modulation:453.2125MHz-5W



### 12.5kHz, 4FSK Modulation:458.2125MHz-5W




### 12.5kHz, 4FSK Modulation:479.975MHz-5W




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


### 12.5kHz, 4FSK Modulation:406.125MHz-1W




### 12.5kHz, 4FSK Modulation:453.2125MHz-1W



### 12.5kHz, 4FSK Modulation:458.2125MHz-1W



### 12.5kHz, 4FSK Modulation:479.975MHz-1W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



## 8. SPURIOUS RADIATED EMISSION

### 8.1 PROVISIONS APPLICABLE

According to FCC §2.1053 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency ( $f_d$  in kHz)  $f_0$  of more than 5.625 kHz but no more than 12.5 kHz: At least  $7.27(f_d - 2.88 \text{ kHz})$  dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency ( $f_d$  in kHz)  $f_0$  of more than 12.5 kHz: At least  $50 + 10 \log(P)$  dB or 70 dB, whichever is lesser attenuation.


### 8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

### 8.3 MEASUREMENT SETUP

#### Radiated Emissions 30MHz to 1GHz Test setup



#### Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 8.4 MEASUREMENT RESULTS

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.


EIRP = "Read Value" + Measured substitution value + 2.15.

Test limit calculation:

Preliminary calculation	Final Result
At least $50 + 10 \log(P) = 50 + 10 \log(5) = 56.99$ (dB)	Limit=P- Preliminary calculation=36.99-56.99=-20 dBm
At least $50 + 10 \log(P) = 50 + 10 \log(1) = 50.00$ (dB)	Limit=P- Preliminary calculation=30.00-50.00=-20 dBm


Note: The report only reflects high-power test data as the worst.

Test Mode:	TX:406.125MHz-FM 5W	Polarity:	Horizontal
------------	---------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-97.73	-54.37	-20.00	34.37	43.36	237	Horizontal
2	1218.5719	-46.32	-50.12	-20.00	30.12	-3.80	160	Horizontal
3	3249.1749	-28.66	-24.93	-20.00	4.93	3.73	358	Horizontal
4	3655.7656	-30.17	-25.81	-20.00	5.81	4.36	332	Horizontal
5	4061.1811	-34.67	-30.08	-20.00	10.08	4.59	28	Horizontal
6	6498.3748	-50.74	-39.18	-20.00	19.18	11.56	360	Horizontal

Test Mode:	TX:406.125MHz-FM 5W	Polarity:	Vertical
------------	---------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	609.09	-91.29	-52.42	-20.00	32.42	38.87	134	Vertical
2	812.79	-90.65	-48.16	-20.00	28.16	42.49	255	Vertical
3	1218.5719	-36.09	-35.80	-20.00	15.80	0.29	76	Vertical
4	3249.1749	-36.53	-33.39	-20.00	13.39	3.14	351	Vertical
5	3655.7656	-30.62	-27.49	-20.00	7.49	3.13	351	Vertical
6	5845.0095	-49.96	-40.53	-20.00	20.53	9.43	225	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:453.2125MHz-FM 5W	Polarity:	Horizontal
------------	----------------------	-----------	------------

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-94.16	-51.07	-20.00	31.07	43.09	319	Horizontal
2	3172.7923	-32.25	-28.65	-20.00	8.65	3.60	9	Horizontal
3	3626.3876	-29.40	-25.08	-20.00	5.08	4.32	339	Horizontal
4	4078.8079	-29.82	-25.27	-20.00	5.27	4.55	49	Horizontal
5	4532.4032	-38.85	-35.35	-20.00	15.35	3.50	9	Horizontal
6	6344.4344	-50.57	-39.25	-20.00	19.25	11.32	356	Horizontal


Test Mode:	TX:453.2125MHz-FM 5W	Polarity:	Vertical
------------	----------------------	-----------	----------

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-92.33	-48.95	-20.00	28.95	43.38	195	Vertical
2	1359.586	-44.62	-43.39	-20.00	23.39	1.23	0	Vertical
3	3172.7923	-41.01	-37.85	-20.00	17.85	3.16	359	Vertical
4	3626.3876	-32.58	-29.46	-20.00	9.46	3.12	332	Vertical
5	4078.8079	-43.00	-39.75	-20.00	19.75	3.25	54	Vertical
6	4985.9986	-39.86	-35.98	-20.00	15.98	3.88	281	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




Test Mode:	TX:458.2125MHz-FM 5W	Polarity:	Horizontal
------------	----------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	916.58	-93.41	-50.11	-20.00	30.11	43.30	1	Horizontal
2	3208.0458	-32.17	-28.51	-20.00	8.51	3.66	10	Horizontal
3	3666.3416	-29.78	-25.41	-20.00	5.41	4.37	338	Horizontal
4	4124.6375	-32.46	-28.03	-20.00	8.03	4.43	38	Horizontal
5	4581.7582	-45.37	-41.85	-20.00	21.85	3.52	288	Horizontal
6	5960.171	-50.64	-39.99	-20.00	19.99	10.65	10	Horizontal


Test Mode:	TX:458.2125MHz-FM 5W	Polarity:	Vertical
------------	----------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	573.2	-91.97	-53.88	-20.00	33.88	38.09	174	Vertical
2	917.55	-95.35	-51.86	-20.00	31.86	43.49	351	Vertical
3	1374.8625	-46.27	-44.94	-20.00	24.94	1.33	214	Vertical
4	3208.0458	-33.92	-30.77	-20.00	10.77	3.15	351	Vertical
5	3666.3416	-30.07	-26.93	-20.00	6.93	3.14	332	Vertical
6	4124.6375	-38.24	-35.01	-20.00	15.01	3.23	304	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:479.975MHz-FM 5W	Polarity:	Horizontal
------------	---------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.23	-89.53	-45.28	-20.00	25.28	44.25	351	Horizontal
2	2410.141	-45.74	-46.83	-20.00	26.83	-1.09	351	Horizontal
3	3359.636	-40.53	-36.60	-20.00	16.60	3.93	351	Horizontal
4	3840.259	-37.30	-32.73	-20.00	12.73	4.57	312	Horizontal
5	5768.6269	-49.09	-39.16	-20.00	19.16	9.93	312	Horizontal
6	8521.9272	-51.33	-38.38	-20.00	18.38	12.95	359	Horizontal

Test Mode:	TX:479.975MHz-FM 5W	Polarity:	Vertical
------------	---------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	600.36	-74.18	-35.46	-20.00	15.46	38.72	35	Vertical
2	960.23	-91.04	-47.12	-20.00	27.12	43.92	351	Vertical
3	1440.6691	-46.82	-45.05	-20.00	25.05	1.77	24	Vertical
4	3359.636	-39.65	-36.55	-20.00	16.55	3.10	351	Vertical
5	6037.7288	-50.90	-39.92	-20.00	19.92	10.98	280	Vertical
6	10587.7838	-54.34	-38.14	-20.00	18.14	16.20	351	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




Test Mode:	TX:406.125MHz-4FSK 5W	Polarity:	Horizontal
------------	-----------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-96.87	-53.51	-20.00	33.51	43.36	237	Horizontal
2	3249.1749	-30.78	-27.05	-20.00	7.05	3.73	342	Horizontal
3	3655.7656	-29.70	-25.34	-20.00	5.34	4.36	317	Horizontal
4	4061.1811	-33.71	-29.12	-20.00	9.12	4.59	33	Horizontal
5	4467.7718	-41.40	-37.84	-20.00	17.84	3.56	15	Horizontal
6	5756.8757	-49.44	-39.55	-20.00	19.55	9.89	282	Horizontal


Test Mode:	TX:406.125MHz-4FSK 5W	Polarity:	Vertical
------------	-----------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	609.09	-88.70	-49.83	-20.00	29.83	38.87	30	Vertical
2	812.79	-89.03	-46.54	-20.00	26.54	42.49	355	Vertical
3	1218.5719	-36.80	-36.51	-20.00	16.51	0.29	102	Vertical
4	3249.1749	-35.93	-32.79	-20.00	12.79	3.14	10	Vertical
5	3655.7656	-27.39	-24.26	-20.00	4.26	3.13	355	Vertical
6	5873.2123	-49.63	-39.93	-20.00	19.93	9.70	256	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:453.2125MHz-4FSK 5W	Polarity:	Horizontal
------------	------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-94.12	-51.03	-20.00	31.03	43.09	275	Horizontal
2	3172.7923	-33.23	-29.63	-20.00	9.63	3.60	2	Horizontal
3	3626.3876	-29.69	-25.37	-20.00	5.37	4.32	312	Horizontal
4	4078.8079	-29.21	-24.66	-20.00	4.66	4.55	29	Horizontal
5	4532.4032	-41.54	-38.04	-20.00	18.04	3.50	0	Horizontal
6	5892.0142	-49.39	-39.00	-20.00	19.00	10.39	72	Horizontal


Test Mode:	TX:453.2125MHz-4FSK 5W	Polarity:	Vertical
------------	------------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-92.27	-48.89	-20.00	28.89	43.38	204	Vertical
2	1359.586	-45.16	-43.93	-20.00	23.93	1.23	360	Vertical
3	3172.7923	-41.49	-38.33	-20.00	18.33	3.16	360	Vertical
4	3626.3876	-32.92	-29.80	-20.00	9.80	3.12	360	Vertical
5	4078.8079	-42.74	-39.49	-20.00	19.49	3.25	170	Vertical
6	4985.9986	-40.85	-36.97	-20.00	16.97	3.88	321	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:458.2125MHz-4FSK 5W	Polarity:	Horizontal
------------	------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	917.55	-92.12	-48.80	-20.00	28.80	43.32	0	Horizontal
2	3208.0458	-28.80	-25.14	-20.00	5.14	3.66	48	Horizontal
3	3666.3416	-29.89	-25.52	-20.00	5.52	4.37	330	Horizontal
4	4124.6375	-30.62	-26.19	-20.00	6.19	4.43	28	Horizontal
5	4581.7582	-42.75	-39.23	-20.00	19.23	3.52	20	Horizontal
6	5857.9358	-49.66	-39.39	-20.00	19.39	10.27	11	Horizontal


Test Mode:	TX:458.2125MHz-4FSK 5W	Polarity:	Vertical
------------	------------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	573.2	-90.63	-52.54	-20.00	32.54	38.09	146	Vertical
2	917.55	-94.28	-50.79	-20.00	30.79	43.49	136	Vertical
3	1374.8625	-46.61	-45.28	-20.00	25.28	1.33	9	Vertical
4	3208.0458	-36.08	-32.93	-20.00	12.93	3.15	9	Vertical
5	3666.3416	-28.52	-25.38	-20.00	5.38	3.14	358	Vertical
6	5040.054	-41.76	-37.69	-20.00	17.69	4.07	313	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:479.975MHz-4FSK 5W	Polarity:	Horizontal
------------	-----------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.23	-88.10	-43.85	-20.00	23.85	44.25	359	Horizontal
2	1440.6691	-44.23	-47.56	-20.00	27.56	-3.33	314	Horizontal
3	3359.636	-33.25	-29.32	-20.00	9.32	3.93	71	Horizontal
4	3839.0839	-31.19	-26.62	-20.00	6.62	4.57	53	Horizontal
5	4319.707	-44.40	-40.46	-20.00	20.46	3.94	7	Horizontal
6	5766.2766	-49.87	-39.95	-20.00	19.95	9.92	0	Horizontal

Test Mode:	TX:479.975MHz-4FSK 5W	Polarity:	Vertical
------------	-----------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	600.36	-74.31	-35.59	-20.00	15.59	38.72	92	Vertical
2	960.23	-91.16	-47.24	-20.00	27.24	43.92	360	Vertical
3	1439.4939	-46.02	-44.26	-20.00	24.26	1.76	46	Vertical
4	3359.636	-40.37	-37.27	-20.00	17.27	3.10	1	Vertical
5	3839.0839	-44.04	-40.82	-20.00	20.82	3.22	326	Vertical
6	6056.5307	-51.21	-40.20	-20.00	20.20	11.01	360	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


## 8.5 EMISSION MASK PLOT

The detailed procedure employed for Emission Mask measurements are specified as following:

-Connect the equipment as illustrated.

-Spectrum set as follow:


1. Centre frequency = fundamental frequency, Span=50kHz for 12.5kHz and 25kHz channel spacing, RBW=100Hz, VBW=300Hz for 12.5kHz, RBW=300Hz, VBW=1000Hz for 25kHz, Sweep = auto, Detector function = peak, Trace = max hold
2. Key the transmitter, and set the level of the unmodulated carrier to a fullscale reference line. This is the 0dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit.
4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Measure and record the results in the test report.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).



Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.