



FCC RADIO TEST REPORT

FCC ID : UZ7MC945A
Equipment : Mobile Computer
Brand Name : ZEBRA
Model Name : MC945A
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart E §15.407

The product was received on Nov. 06, 2023 and testing was performed from Nov. 10, 2023 to Jan. 18, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	9
1.4 Testing Location	9
1.5 Applicable Standards.....	9
2 Test Configuration of Equipment Under Test	10
2.1 Carrier Frequency and Channel	10
2.2 Test Mode.....	11
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	14
3 Test Result	15
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	15
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement	19
3.5 AC Conducted Emission Measurement.....	24
3.6 Antenna Requirements.....	26
4 List of Measuring Equipment.....	27
5 Measurement Uncertainty	28
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR3N2802F	01	Initial issue of report	Jan. 31, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	1.08 dB under the limit at 5925.20 MHz
3.5	15.207	AC Conducted Emission	Pass	17.58 dB under the limit at 0.18 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Michelle Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Computer
Brand Name	ZEBRA
Model Name	MC945A
FCC ID	UZ7MC945A
Sample 1	SE4770 + with Camera
Sample 2	SE5800 + with Camera
Sample 3	SE4770 + without Camera
Sample 4	SE5800 + without Camera
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/NFC/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	DV2
SW Version	13-10-31.00-TN-U00-PRD-NEM-04
FW Version	FUSION_QA_6_1.1.0.004_T
MFD	10NOV23
EUT Stage	Identical Prototype

Specification of Accessories				
Adapter USB Wall Charger	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
Battery 1 Standard Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000370
Battery 2 Standard Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000370B
Earphone USB-C Audio Headset	Brand Name	Zebra	Part Number	HDST-USBC-PTT1-01
USB Cable (Type C to Type A)	Brand Name	Zebra	Part Number	CBL-TC2X-USBC-01
Holster	Brand Name	Zebra	Part Number	SG-MC9X-SHLSTG-01
USB Cable (CUP)	Brand Name	Zebra	Part Number	CBL-MC93-USBCHG-01

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard			
Tx/Rx Frequency Range	5745 MHz ~ 5825 MHz		
Maximum Output Power to Antenna	MIMO <Ant. 6+7> 802.11a: 21.46 dBm / 0.1400 W 802.11n HT20: 21.21 dBm / 0.1321 W 802.11n HT40: 21.41 dBm / 0.1384 W 802.11ac VHT20: 21.31 dBm / 0.1352 W 802.11ac VHT40: 21.41 dBm / 0.1384 W 802.11ac VHT80: 21.36 dBm / 0.1368 W 802.11ax HE20: 21.41 dBm / 0.1384 W 802.11ax HE40: 21.51dBm / 0.1416 W 802.11ax HE80: 21.46 dBm / 0.1400 W		
99% Occupied Bandwidth	MIMO <Ant. 6> 802.11a: 16.38 802.11ac VHT20: 17.48 MHz 802.11ac VHT40: 36.06 MHz 802.11ac VHT80: 75.04 MHz 802.11ax HE20: 18.88 MHz 802.11ax HE40: 37.86 MHz 802.11ax HE80: 76.60 MHz MIMO <Ant. 7> 802.11a: 16.63 MHz 802.11ac VHT20: 17.48 MHz 802.11ac VHT40: 36.06 MHz 802.11ac VHT80: 75.04 MHz 802.11ax HE20: 19.08 MHz 802.11ax HE40: 37.96 MHz 802.11ax HE80: 76.96 MHz		
Antenna Type / Gain	<Ant. 6> : PIFA Antenna with gain 2.59 dBi <Ant. 7> : PIFA Antenna with gain 2.30 dBi		
Type of Modulation	802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax: OFDMA (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)		
Antenna Function Description		Ant. 6	Ant. 7
	802.11a/n/ac/ax MIMO	V	V
	802.11ax TXBF	V	V

Remark:

1. MIMO Ant. 6+7 Directional Gain is a calculated result from MIMO Ant. 6 and MIMO Ant. 7. The formula used in calculation is documented in section 1.2.1.
2. Power of MIMO Ant. 6 + Ant. 7 is a calculated result from sum of the power MIMO Ant. 6 and MIMO Ant. 7.
3. 802.11ax Support Tx Beamforming mode, and the manufacturer declares that Tx Beamforming power/EIRP is less than CDD mode 3dbm, so CDD mode cover Tx Beamforming mode.
4. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for	DG for	Power Limit	PSD Limit
	Ant 6	Ant 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	2.59	2.30	2.59	5.46	0.00	0.00

Calculation example:

If a device has two antenna, $G_{ANT6} = 2.59$ dBi; $G_{ANT7} = 2.30$ dBi

Directional gain of power measurement = $\max(2.59, 2.30) + 0 = 2.59$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(2.59 \text{ dBi} / 20)} + 10^{(2.30 \text{ dBi} / 20)} \right]^2 / 2 \right\}$$

$$= 5.46 \text{ dBi}$$

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)

<For TXBF Modes>

The EUT supports beamforming modes , then

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)e)ii)

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The directional gain “DG” is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 6	Ant 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	2.59	2.30	5.46	5.46	0.00	0.00

Calculation example:

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{\frac{2.59}{20}} + 10^{\frac{2.30}{20}} \right]^2 / 2 \right\}$$

$$= 5.46 \text{ dBi}$$

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH20-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80 and 802.11ax HE80.



2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2018.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by HE20)	MCS0
802.11n HT40 (Covered by HE40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + USB Cable (Type C to Type A) with USB Cable (CUP) (Charging from Adapter USB Wall Charger) + Keypad (53key) + Battery 1 Standard Battery (7000mAh) for Sample 1
Remark: For Radiated Test Cases, the tests were performed with Battery 1.	


MIMO <Ant. 6+7>

Ch. #		Band IV : 5725-5850 MHz	
		802.11a	802.11ax HE20
L	Low	149	149
M	Middle	157	157
H	High	165	165


Ch. #		Band IV : 5725-5850 MHz		
		802.11ac VHT40	802.11ax HE40	802.11ax HE80
L	Low	151	151	-
M	Middle	-	-	155
H	High	-	159	-

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>


<WLAN Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "QRCT 4.0.00206.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.


Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300kHz.
 - Set VBW $\geq$ 1 MHz.
 - Add $10 \log(500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($<500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
 - Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
Method (c): Measure and add $10 \log(N_{\text{ANT}}) \text{ dB}$.
With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}}) \text{ dB}$ is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}}) \text{ dB}$ serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.


6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



**3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 12, 2023	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Dec. 12, 2023	Sep. 19, 2024	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 26, 2023	Dec. 12, 2023	Oct. 25, 2024	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 22, 2023	Dec. 12, 2023	Nov. 21, 2024	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Dec. 12, 2023	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	9kHz-200MHz	Jul. 28, 2023	Dec. 12, 2023	Jul. 27, 2024	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 29, 2022	Dec. 12, 2023	Dec. 28, 2023	Conduction (CO05-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 06, 2023	Dec. 19, 2023~Jan. 18, 2024	Oct. 05, 2024	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 12, 2023	Dec. 19, 2023~Jan. 18, 2024	Sep. 11, 2024	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Sep. 06, 2023	Dec. 19, 2023~Jan. 18, 2024	Sep. 05, 2024	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Dec. 19, 2023~Jan. 18, 2024	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Dec. 19, 2023~Jan. 18, 2024	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Dec. 19, 2023~Jan. 18, 2024	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 12, 2023	Dec. 19, 2023~Jan. 18, 2024	Dec. 11, 2024	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00802N1 D01N-06	55606 & 08	30MHz~1GHz	Oct. 20, 2023	Dec. 19, 2023~Jan. 18, 2024	Oct. 19, 2024	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	02360	1GHz-18GHz	Oct. 30, 2023	Dec. 19, 2023~Jan. 18, 2024	Oct. 29, 2024	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz-40GHz	Jul. 10, 2023	Dec. 19, 2023~Jan. 18, 2024	Jul. 09, 2024	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Jan. 02, 2023	Dec. 19, 2023~Dec. 31, 2023	Jan. 01, 2024	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Jan. 01, 2024	Jan. 01, 2024~Jan. 18, 2024	Dec. 31, 2024	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 13, 2023	Dec. 19, 2023~Jan. 18, 2024	Nov. 12, 2024	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,80401 5/2,804027/2	N/A	Jan. 18, 2023	Dec. 19, 2023~Jan. 16, 2024	Jan. 17, 2024	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,80401 5/2,804027/2	N/A	Jan. 17, 2024	Jan. 17, 2024~Jan. 18, 2024	Jan. 16, 2025	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303B	TP200728	N/A	Mar. 28, 2023	Dec. 19, 2023~Jan. 18, 2024	Mar. 27, 2024	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Dec. 19, 2023~Jan. 18, 2024	N/A	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Nov. 10, 2023~Jan. 17, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO36	10MHz~6GHz	Aug. 23, 2023	Nov. 10, 2023~Jan. 17, 2024	Aug. 22, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101564	10Hz ~ 40GHz	Sep. 12, 2023	Nov. 10, 2023~Jan. 17, 2024	Sep. 11, 2024	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.50 dB
--	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.40 dB
--	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50 dB
--	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
--	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.40 dB
--	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Wei Shun Hung	Temperature:	21~25	°C
Test Date:	2023/11/10~2024/01/17	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	149	5745	16.38	16.63	19.76	22.96	15.20	15.20	0.5	Pass
11a	6Mbps	2	157	5785	16.33	16.38	19.68	19.60	15.20	15.20	0.5	Pass
11a	6Mbps	2	165	5825	16.38	16.33	19.20	19.44	15.20	15.20	0.5	Pass
VHT20	MCS0	2	149	5745	17.43	17.48	20.13	20.42	15.04	15.02	0.5	Pass
VHT20	MCS0	2	157	5785	17.48	17.48	20.39	20.27	15.13	13.80	0.5	Pass
VHT20	MCS0	2	165	5825	17.48	17.48	20.33	20.46	14.99	15.05	0.5	Pass
VHT40	MCS0	2	151	5755	36.06	36.06	40.78	40.85	34.18	35.06	0.5	Pass
VHT40	MCS0	2	159	5795	36.06	36.06	40.43	40.85	35.00	35.00	0.5	Pass
VHT80	MCS0	2	155	5775	75.04	75.04	80.96	81.89	71.26	72.59	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	18.10	18.50	21.31	30.00		2.59		Pass
11a	6Mbps	2	157	5785	18.40	18.50	21.46	30.00		2.59		Pass
11a	6Mbps	2	165	5825	18.30	18.50	21.41	30.00		2.59		Pass
HT20	MCS0	2	149	5745	17.80	18.30	21.07	30.00		2.59		Pass
HT20	MCS0	2	157	5785	18.10	18.30	21.21	30.00		2.59		Pass
HT20	MCS0	2	165	5825	18.00	18.20	21.11	30.00		2.59		Pass
HT40	MCS0	2	151	5755	18.20	18.30	21.26	30.00		2.59		Pass
HT40	MCS0	2	159	5795	18.40	18.40	21.41	30.00		2.59		Pass
VHT20	MCS0	2	149	5745	17.90	18.40	21.17	30.00		2.59		Pass
VHT20	MCS0	2	157	5785	18.20	18.40	21.31	30.00		2.59		Pass
VHT20	MCS0	2	165	5825	18.10	18.30	21.21	30.00		2.59		Pass
VHT40	MCS0	2	151	5755	18.20	18.30	21.26	30.00		2.59		Pass
VHT40	MCS0	2	159	5795	18.40	18.40	21.41	30.00		2.59		Pass
VHT80	MCS0	2	155	5775	18.30	18.40	21.36	30.00		2.59		Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 MIMO																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	0.67	0.66	2.22	4.12	5.54	8.55	30.00	5.46	Pass			
11a	6Mbps	2	157	5785	0.67	0.66	2.22	4.60	5.32	8.33	30.00	5.46	Pass			
11a	6Mbps	2	165	5825	0.67	0.66	2.22	4.55	5.14	8.15	30.00	5.46	Pass			
VHT20	MCS0	2	149	5745	0.66	0.67	2.22	5.72	6.21	9.22	30.00	5.46	Pass			
VHT20	MCS0	2	157	5785	0.66	0.67	2.22	5.64	5.78	8.79	30.00	5.46	Pass			
VHT20	MCS0	2	165	5825	0.66	0.67	2.22	5.66	5.94	8.95	30.00	5.46	Pass			
VHT40	MCS0	2	151	5755	0.66	0.66	2.22	2.84	3.44	6.45	30.00	5.46	Pass			
VHT40	MCS0	2	159	5795	0.66	0.66	2.22	2.77	3.32	6.33	30.00	5.46	Pass			
VHT80	MCS0	2	155	5775	0.67	0.67	2.22	0.60	0.62	3.63	30.00	5.46	Pass			

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
HE20	MCS0	2	149	5745	Full	18.88	19.08	20.80	26.00	15.20	18.55	0.5	Pass
HE20	MCS0	2	157	5785	Full	18.88	18.93	21.36	22.48	16.00	14.75	0.5	Pass
HE20	MCS0	2	165	5825	Full	18.88	18.88	21.20	21.44	15.85	16.00	0.5	Pass
HE40	MCS0	2	151	5755	Full	37.86	37.96	41.60	41.92	35.28	35.28	0.5	Pass
HE40	MCS0	2	159	5795	Full	37.86	37.96	41.76	41.60	35.91	35.28	0.5	Pass
HE80	MCS0	2	155	5775	Full	76.60	76.96	81.60	82.56	69.12	74.24	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	18.00	18.50	21.27	30.00		2.59		Pass
HE20	MCS0	2	149	5745	26/0	9.90	11.50	13.78	30.00		2.59		Pass
HE20	MCS0	2	149	5745	52/37	13.10	14.50	16.87	30.00		2.59		Pass
HE20	MCS0	2	149	5745	106/53	15.00	16.50	18.82	30.00		2.59		Pass
HE20	MCS0	2	157	5785	Full	18.30	18.50	21.41	30.00		2.59		Pass
HE20	MCS0	2	157	5785	26/4	10.10	10.70	13.42	30.00		2.59		Pass
HE20	MCS0	2	157	5785	52/38	13.60	14.10	16.87	30.00		2.59		Pass
HE20	MCS0	2	157	5785	106/53	15.80	16.40	19.12	30.00		2.59		Pass
HE20	MCS0	2	165	5825	Full	18.20	18.40	21.31	30.00		2.59		Pass
HE20	MCS0	2	165	5825	26/8	10.80	10.90	13.86	30.00		2.59		Pass
HE20	MCS0	2	165	5825	52/40	13.80	14.10	16.96	30.00		2.59		Pass
HE20	MCS0	2	165	5825	106/54	16.90	17.00	19.96	30.00		2.59		Pass
HE40	MCS0	2	151	5755	Full	18.30	18.40	21.36	30.00		2.59		Pass
HE40	MCS0	2	151	5755	242/61	16.50	17.10	19.82	30.00		2.59		Pass
HE40	MCS0	2	159	5795	Full	18.50	18.50	21.51	30.00		2.59		Pass
HE40	MCS0	2	159	5795	242/62	17.10	17.60	20.37	30.00		2.59		Pass
HE80	MCS0	2	155	5775	Full	18.40	18.50	21.46	30.00		2.59		Pass
HE80	MCS0	2	155	5775	484/65	16.30	17.30	19.84	30.00		2.59		Pass
HE80	MCS0	2	155	5775	484/66	16.20	17.40	19.85	30.00		2.59		Pass

TEST RESULTS DATA
Power Spectral Density


U-NII-3 MIMO															
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	2.22		3.72	5.04	8.05	30.00		5.46		Pass
HE20	MCS0	2	149	5745	26/0	2.22		3.63	5.03	8.04	30.00		5.46		Pass
HE20	MCS0	2	149	5745	52/37	2.22		3.75	5.00	8.01	30.00		5.46		Pass
HE20	MCS0	2	149	5745	106/53	2.22		3.21	4.70	7.71	30.00		5.46		Pass
HE20	MCS0	2	157	5785	Full	2.22		4.16	4.71	7.72	30.00		5.46		Pass
HE20	MCS0	2	157	5785	26/4	2.22		4.18	4.63	7.64	30.00		5.46		Pass
HE20	MCS0	2	157	5785	52/38	2.22		4.14	4.68	7.69	30.00		5.46		Pass
HE20	MCS0	2	157	5785	106/53	2.22		4.04	4.63	7.64	30.00		5.46		Pass
HE20	MCS0	2	165	5825	Full	2.22		4.73	5.15	8.16	30.00		5.46		Pass
HE20	MCS0	2	165	5825	26/8	2.22		4.55	4.72	7.73	30.00		5.46		Pass
HE20	MCS0	2	165	5825	52/40	2.22		4.79	4.94	7.95	30.00		5.46		Pass
HE20	MCS0	2	165	5825	106/54	2.22		4.97	4.95	7.98	30.00		5.46		Pass
HE40	MCS0	2	151	5755	Full	2.22		1.50	1.80	4.81	30.00		5.46		Pass
HE40	MCS0	2	151	5755	242/61	2.22		0.57	1.40	4.41	30.00		5.46		Pass
HE40	MCS0	2	159	5795	Full	2.22		1.71	1.78	4.79	30.00		5.46		Pass
HE40	MCS0	2	159	5795	242/62	2.22		1.26	1.66	4.67	30.00		5.46		Pass
HE80	MCS0	2	155	5775	Full	2.22		-0.06	-0.42	2.95	30.00		5.46		Pass
HE80	MCS0	2	155	5775	484/65	2.22		-2.64	-1.48	1.53	30.00		5.46		Pass
HE80	MCS0	2	155	5775	484/66	2.22		-2.61	-1.12	1.89	30.00		5.46		Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**


MIMO <Ant. 6+7>

<802.11a>






<802.11ac VHT20>






<802.11ac VHT40>







<802.11ac VHT80>






<802.11ax HE20>




**<802.11ax HE40>**


**<802.11ax HE80>**

Test Result of Power Spectral Density

<802.11a>



<802.11ac VHT20>







<802.11ac VHT40>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6




MIMO Ant. 7




<802.11ac VHT80>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6



MIMO Ant. 7







<802.11ax HE20>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6




MIMO Ant. 7




<802.11ax HE40>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6



MIMO Ant. 7







<802.11ax HE80>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6



MIMO Ant. 7






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

EUT Information

Report NO : 3N2802
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.168000	---	31.90	55.06	23.16	L1	OFF	19.9
0.168000	45.68	---	65.06	19.38	L1	OFF	19.9
0.179250	---	35.35	54.52	19.17	L1	OFF	19.9
0.179250	46.94	---	64.52	17.58	L1	OFF	19.9
0.287250	---	34.06	50.60	16.54	L1	OFF	19.9
0.287250	39.85	---	60.60	20.75	L1	OFF	19.9
0.399750	---	30.11	47.86	17.75	L1	OFF	19.9
0.399750	37.16	---	57.86	20.70	L1	OFF	19.9
1.234500	---	24.41	46.00	21.59	L1	OFF	19.9
1.234500	29.08	---	56.00	26.92	L1	OFF	19.9
8.621250	---	26.11	50.00	23.89	L1	OFF	20.1
8.621250	28.83	---	60.00	31.17	L1	OFF	20.1

EUT Information

Report NO : 3N2802
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.168000	---	33.53	55.06	21.53	N	OFF	19.9
0.168000	45.87	---	65.06	19.19	N	OFF	19.9
0.179250	---	36.46	54.52	18.06	N	OFF	19.9
0.179250	46.48	---	64.52	18.04	N	OFF	19.9
0.287250	---	31.01	50.60	19.59	N	OFF	19.9
0.287250	37.64	---	60.60	22.96	N	OFF	19.9
0.354750	---	30.41	48.85	18.44	N	OFF	19.9
0.354750	36.04	---	58.85	22.81	N	OFF	19.9
3.185250	---	25.15	46.00	20.85	N	OFF	20.0
3.185250	30.12	---	56.00	25.88	N	OFF	20.0
7.010250	---	25.36	50.00	24.64	N	OFF	20.1
7.010250	26.98	---	60.00	33.02	N	OFF	20.1



Appendix C. Radiated Spurious Emission

Test Engineer :	John Chuang, David Dai, and Howard Huang	Temperature :	19.3~23.4°C
		Relative Humidity :	65.9~70.3%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5646.125	50.33	-17.87	68.2	41.71	33.2	13.41	37.99	100	55	P	H
		5698.775	66.42	-37.88	104.3	57.51	33.4	13.49	37.98	100	55	P	H
		5717.225	76.59	-33.43	110.02	67.52	33.54	13.51	37.98	100	55	P	H
		5724.425	80.2	-40.69	120.89	71.06	33.6	13.52	37.98	100	55	P	H
	*	5745	115.11	-	-	105.77	33.76	13.55	37.97	100	55	P	H
	*	5745	110.14	-	-	100.8	33.76	13.55	37.97	100	55	A	H
													H
													H
		5643.875	50.62	-17.58	68.2	42.01	33.2	13.41	38	400	77	P	V
		5696.75	59.55	-43.25	102.8	50.65	33.39	13.49	37.98	400	77	P	V
		5719.7	70.51	-40.21	110.72	61.41	33.56	13.52	37.98	400	77	P	V
		5724.65	74.53	-46.87	121.4	65.39	33.6	13.52	37.98	400	77	P	V
	*	5745	114.04	-	-	104.7	33.76	13.55	37.97	400	77	P	V
	*	5745	107.96	-	-	98.62	33.76	13.55	37.97	400	77	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5607	48.38	-19.82	68.2	39.82	33.2	13.36	38	100	53	P	H
		5693.75	51.71	-48.88	100.59	42.83	33.38	13.48	37.98	100	53	P	H
		5715	54.2	-55.2	109.4	45.15	33.52	13.51	37.98	100	53	P	H
		5723.75	56.4	-62.95	119.35	47.27	33.59	13.52	37.98	100	53	P	H
	*	5785	117.06	-	-	107.47	33.94	13.61	37.96	100	53	P	H
	*	5785	109.92	-	-	100.33	33.94	13.61	37.96	100	53	A	H
		5850.5	54.62	-66.44	121.06	44.57	34.3	13.7	37.95	100	53	P	H
		5857.75	53.31	-56.72	110.03	43.24	34.3	13.71	37.94	100	53	P	H
		5875.5	50.72	-54.11	104.83	40.63	34.3	13.73	37.94	100	53	P	H
		5925	50.68	-17.52	68.2	40.52	34.3	13.79	37.93	100	53	P	H
													H
													H
		5624.75	49.05	-19.15	68.2	40.47	33.2	13.38	38	400	70	P	V
		5700	49.29	-55.91	105.2	40.38	33.4	13.49	37.98	400	70	P	V
		5712.25	50.73	-57.9	108.63	41.7	33.5	13.51	37.98	400	70	P	V
		5724.75	52.12	-69.51	121.63	42.98	33.6	13.52	37.98	400	70	P	V
	*	5785	114.03	-	-	104.44	33.94	13.61	37.96	400	70	P	V
	*	5785	108.14	-	-	98.55	33.94	13.61	37.96	400	70	A	V
		5850	49.61	-72.59	122.2	39.57	34.3	13.69	37.95	400	70	P	V
		5860.25	51.05	-58.28	109.33	40.98	34.3	13.71	37.94	400	70	P	V
		5921	50.19	-20.96	71.15	40.03	34.3	13.79	37.93	400	70	P	V
		5930.25	49.31	-18.89	68.2	39.14	34.3	13.8	37.93	400	70	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	117.86	-	-	108	34.15	13.66	37.95	100	54	P	H
	*	5825	110.53	-	-	100.67	34.15	13.66	37.95	100	54	A	H
		5853.6	68.15	-45.84	113.99	58.1	34.3	13.7	37.95	100	54	P	H
		5857.2	65.92	-44.26	110.18	55.86	34.3	13.7	37.94	100	54	P	H
		5879	58.74	-43.49	102.23	48.65	34.3	13.73	37.94	100	54	P	H
		5925.6	51.09	-17.11	68.2	40.93	34.3	13.79	37.93	100	54	P	H
													H
													H
	*	5825	115	-	-	105.14	34.15	13.66	37.95	290	41	P	V
	*	5825	107.87	-	-	98.01	34.15	13.66	37.95	290	41	A	V
		5850.8	63.2	-57.18	120.38	53.15	34.3	13.7	37.95	290	41	P	V
		5857.4	59.43	-50.7	110.13	49.37	34.3	13.7	37.94	290	41	P	V
		5877	53.51	-50.2	103.71	43.42	34.3	13.73	37.94	290	41	P	V
		5939.2	49.17	-19.03	68.2	38.98	34.3	13.81	37.92	290	41	P	V
													V
													V
													V
Remark 1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													

**Band 4 5725~5850MHz****WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	50.8	-23.2	74	34.25	39.13	20.06	42.64	200	306	P	H
		11490	41.74	-12.26	54	25.19	39.13	20.06	42.64	200	306	A	H
		17235	51.53	-16.67	68.2	33.59	37.97	24.74	44.77	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11490	52.06	-21.94	74	35.51	39.13	20.06	42.64	150	360	P	V
		11490	41.69	-12.31	54	25.14	39.13	20.06	42.64	150	360	A	V
		17235	51.62	-16.58	68.2	33.68	37.97	24.74	44.77	-	-	P	V
													V
													V
													V
													V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		11570	50.16	-23.84	74	33.7	39.03	20.14	42.71	200	316	P	H
		11570	41.71	-12.29	54	25.25	39.03	20.14	42.71	200	316	A	H
		17355	51.82	-16.38	68.2	33.7	38.21	24.79	44.88	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11570	50.15	-23.85	74	33.69	39.03	20.14	42.71	300	352	P	V
		11570	41.73	-12.27	54	25.27	39.03	20.14	42.71	300	352	A	V
		17355	51.88	-16.32	68.2	33.76	38.21	24.79	44.88	-	-	P	V
													V
													V
													V
													V
													V
													V

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5645	62.25	-5.95	68.2	53.64	33.2	13.41	38	100	55	P	H
		5699.25	67.6	-37.05	104.65	58.69	33.4	13.49	37.98	100	55	P	H
		5719.5	75.76	-34.9	110.66	66.66	33.56	13.52	37.98	100	55	P	H
		5721.75	76.66	-38.13	114.79	67.55	33.57	13.52	37.98	100	55	P	H
	*	5755	114.59	-	-	105.17	33.82	13.57	37.97	100	55	P	H
	*	5755	107.88	-	-	98.46	33.82	13.57	37.97	100	55	A	H
		5850.75	62.18	-58.31	120.49	52.13	34.3	13.7	37.95	100	55	P	H
		5859	63.69	-45.99	109.68	53.62	34.3	13.71	37.94	100	55	P	H
		5879.5	60.21	-41.65	101.86	50.12	34.3	13.73	37.94	100	55	P	H
		5926.5	53.21	-14.99	68.2	43.05	34.3	13.79	37.93	100	55	P	H
													H
													H
		5636.25	58.35	-9.85	68.2	49.75	33.2	13.4	38	400	68	P	V
		5699.75	64.11	-40.91	105.02	55.2	33.4	13.49	37.98	400	68	P	V
		5718	71.12	-39.12	110.24	62.04	33.54	13.52	37.98	400	68	P	V
		5724	73.34	-46.58	119.92	64.21	33.59	13.52	37.98	400	68	P	V
	*	5755	113.52	-	-	104.1	33.82	13.57	37.97	400	68	P	V
	*	5755	107.56	-	-	98.14	33.82	13.57	37.97	400	68	A	V
		5850.5	57.12	-63.94	121.06	47.07	34.3	13.7	37.95	400	68	P	V
		5867.75	59.1	-48.13	107.23	49.02	34.3	13.72	37.94	400	68	P	V
		5890.25	58.49	-35.39	93.88	48.38	34.3	13.75	37.94	400	68	P	V
		5926.25	50.92	-17.28	68.2	40.76	34.3	13.79	37.93	400	68	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

[illegible]

**Band 4 5725~5850MHz****WIFI 802.11ax HE20_Full (Band Edge @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 149 5745MHz		5647.025	51.14	-17.06	68.2	42.51	33.2	13.42	37.99	400	7	P	H
		5696.525	64.01	-38.63	102.64	55.11	33.39	13.49	37.98	400	7	P	H
		5717.675	80.38	-29.77	110.15	71.31	33.54	13.51	37.98	400	7	P	H
		5723.75	82.04	-37.31	119.35	72.91	33.59	13.52	37.98	400	7	P	H
	*	5745	116.5	-	-	107.16	33.76	13.55	37.97	400	7	P	H
	*	5745	109.25	-	-	99.91	33.76	13.55	37.97	400	7	A	H
													H
													H
		5647.7	53.37	-14.83	68.2	44.74	33.2	13.42	37.99	400	75	P	V
		5696.525	67.63	-35.01	102.64	58.73	33.39	13.49	37.98	400	75	P	V
		5719.925	77.39	-33.39	110.78	68.29	33.56	13.52	37.98	400	75	P	V
		5724.875	79.86	-42.06	121.92	70.72	33.6	13.52	37.98	400	75	P	V
	*	5745	117.74	-	-	108.4	33.76	13.55	37.97	400	75	P	V
	*	5745	109.42	-	-	100.08	33.76	13.55	37.97	400	75	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 157 5785MHz		5645	48.56	-19.64	68.2	39.95	33.2	13.41	38	242	52	P	H
		5692.25	51.04	-48.45	99.49	42.17	33.37	13.48	37.98	242	52	P	H
		5716	53.43	-56.25	109.68	44.37	33.53	13.51	37.98	242	52	P	H
		5723.25	52.95	-65.26	118.21	43.82	33.59	13.52	37.98	242	52	P	H
	*	5785	117.01	-	-	107.42	33.94	13.61	37.96	242	52	P	H
	*	5785	109.5	-	-	99.91	33.94	13.61	37.96	242	52	A	H
		5851	52.61	-67.31	119.92	42.56	34.3	13.7	37.95	242	52	P	H
		5856.25	52.56	-57.89	110.45	42.5	34.3	13.7	37.94	242	52	P	H
		5875.75	51.12	-53.52	104.64	41.03	34.3	13.73	37.94	242	52	P	H
		5935.25	50.52	-17.68	68.2	40.34	34.3	13.81	37.93	242	52	P	H
													H
													H
		5605.5	48.46	-19.74	68.2	39.9	33.2	13.36	38	395	66	P	V
		5699.25	51.21	-53.44	104.65	42.3	33.4	13.49	37.98	395	66	P	V
		5706	55.43	-51.45	106.88	46.46	33.45	13.5	37.98	395	66	P	V
		5722.25	52.59	-63.34	115.93	43.47	33.58	13.52	37.98	395	66	P	V
	*	5785	116.35	-	-	106.76	33.94	13.61	37.96	395	66	P	V
	*	5785	108.5	-	-	98.91	33.94	13.61	37.96	395	66	A	V
		5851	55.96	-63.96	119.92	45.91	34.3	13.7	37.95	395	66	P	V
		5867.75	53.46	-53.77	107.23	43.38	34.3	13.72	37.94	395	66	P	V
		5889	49.75	-45.06	94.81	39.64	34.3	13.75	37.94	395	66	P	V
		5936.25	49.01	-19.19	68.2	38.83	34.3	13.81	37.93	395	66	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 165 5825MHz	*	5825	115.35	-	-	105.49	34.15	13.66	37.95	230	55	P	H
	*	5825	109.64	-	-	99.78	34.15	13.66	37.95	230	55	A	H
		5850.4	69.93	-51.36	121.29	59.88	34.3	13.7	37.95	230	55	P	H
		5860.4	65.41	-43.88	109.29	55.34	34.3	13.71	37.94	230	55	P	H
		5876.6	60.04	-43.97	104.01	49.95	34.3	13.73	37.94	230	55	P	H
		5926.8	52.04	-16.16	68.2	41.88	34.3	13.79	37.93	230	55	P	H
													H
													H
	*	5825	113.72	-	-	103.86	34.15	13.66	37.95	299	50	P	V
	*	5825	106.78	-	-	96.92	34.15	13.66	37.95	299	50	A	V
		5850.2	67.57	-54.17	121.74	57.52	34.3	13.7	37.95	299	50	P	V
		5856.2	63.33	-47.13	110.46	53.27	34.3	13.7	37.94	299	50	P	V
		5877.6	55.36	-47.91	103.27	45.27	34.3	13.73	37.94	299	50	P	V
		5930.2	49.34	-18.86	68.2	39.17	34.3	13.8	37.93	299	50	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ax HE20 Full (Harmonic @ 3m)

[illegible]



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 157 5785MHz		11570	51.16	-22.84	74	34.7	39.03	20.14	42.71	308	360	P	H
		11570	41.98	-12.02	54	25.52	39.03	20.14	42.71	308	360	A	H
		17355	51.5	-16.7	68.2	33.38	38.21	24.79	44.88	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11570	50.86	-23.14	74	34.4	39.03	20.14	42.71	197	360	P	V
		11570	42.04	-11.96	54	25.58	39.03	20.14	42.71	197	360	A	V
		17355	52.24	-15.96	68.2	34.12	38.21	24.79	44.88	-	-	P	V
													V
													V
													V
													V
													V
													V

[illegible]

**Band 4 5725~5850MHz****WIFI 802.11ax HE20_Partial 106 (Band Edge @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Partial 106/53 CH 149 5745MHz		5649.275	63.2	-5	68.2	54.57	33.2	13.42	37.99	100	55	P	H
		5688.65	76.72	-20.11	96.83	67.88	33.35	13.47	37.98	100	55	P	H
		5717	91.54	-18.42	109.96	82.47	33.54	13.51	37.98	100	55	P	H
		5725.1	86.23	-47.97	134.2	77.08	33.6	13.53	37.98	100	55	P	H
	*	5745	118.97	-	-	109.63	33.76	13.55	37.97	100	55	P	H
	*	5745	111.11	-	-	101.77	33.76	13.55	37.97	100	55	A	H
													H
													H
		5649.5	62.24	-5.96	68.2	53.61	33.2	13.42	37.99	400	68	P	V
		5699	79.24	-25.22	104.46	70.33	33.4	13.49	37.98	400	68	P	V
		5717	86.78	-23.18	109.96	77.71	33.54	13.51	37.98	400	68	P	V
		5720.6	86.67	-25.5	112.17	77.57	33.56	13.52	37.98	400	68	P	V
	*	5745	117.58	-	-	108.24	33.76	13.55	37.97	400	68	P	V
	*	5745	109.28	-	-	99.94	33.76	13.55	37.97	400	68	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Partial 106/54 CH 165 5825MHz	*	5825	117.23	-	-	107.37	34.15	13.66	37.95	100	53	P	H
	*	5825	111.76	-	-	101.9	34.15	13.66	37.95	100	53	A	H
		5850	86.74	-35.46	122.2	76.7	34.3	13.69	37.95	100	53	P	H
		5856.4	89.13	-21.28	110.41	79.07	34.3	13.7	37.94	100	53	P	H
		5895.2	80.22	-9.99	90.21	70.11	34.3	13.75	37.94	100	53	P	H
		5925.2	67.12	-1.08	68.2	56.96	34.3	13.79	37.93	100	53	P	H
													H
													H
	*	5825	115.4	-	-	105.54	34.15	13.66	37.95	350	56	P	V
	*	5825	108.21	-	-	98.35	34.15	13.66	37.95	350	56	A	V
		5853.8	87.37	-26.17	113.54	77.32	34.3	13.7	37.95	350	56	P	V
		5855.6	86.95	-23.68	110.63	76.89	34.3	13.7	37.94	350	56	P	V
		5890.4	71.34	-22.43	93.77	61.23	34.3	13.75	37.94	350	56	P	V
		5927.2	60.17	-8.03	68.2	50	34.3	13.8	37.93	350	56	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 151 5755MHz		5649.75	59.78	-8.42	68.2	51.15	33.2	13.42	37.99	100	53	P	H
		5693.5	69.7	-30.71	100.41	60.83	33.37	13.48	37.98	100	53	P	H
		5719.5	79.56	-31.1	110.66	70.46	33.56	13.52	37.98	100	53	P	H
		5720	78.39	-32.41	110.8	69.29	33.56	13.52	37.98	100	53	P	H
	*	5755	114.14	-	-	104.72	33.82	13.57	37.97	100	53	P	H
	*	5755	107.23	-	-	97.81	33.82	13.57	37.97	100	53	A	H
		5852.5	62.76	-53.74	116.5	52.71	34.3	13.7	37.95	100	53	P	H
		5864	60.59	-47.69	108.28	50.52	34.3	13.71	37.94	100	53	P	H
		5884	59.68	-38.84	98.52	49.58	34.3	13.74	37.94	100	53	P	H
		5927.75	54.27	-13.93	68.2	44.1	34.3	13.8	37.93	100	53	P	H
													H
													H
		5631.75	57.42	-10.78	68.2	48.83	33.2	13.39	38	400	77	P	V
		5697.75	66.73	-36.81	103.54	57.83	33.39	13.49	37.98	400	77	P	V
		5716.5	73.25	-36.57	109.82	64.19	33.53	13.51	37.98	400	77	P	V
		5725	77.45	-44.75	122.2	68.3	33.6	13.53	37.98	400	77	P	V
	*	5755	113.35	-	-	103.93	33.82	13.57	37.97	400	77	P	V
	*	5755	107.09	-	-	97.67	33.82	13.57	37.97	400	77	A	V
		5851	58.61	-61.31	119.92	48.56	34.3	13.7	37.95	400	77	P	V
		5867.75	58.09	-49.14	107.23	48.01	34.3	13.72	37.94	400	77	P	V
		5880.5	56.12	-44.99	101.11	46.03	34.3	13.73	37.94	400	77	P	V
		5928.75	51.38	-16.82	68.2	41.21	34.3	13.8	37.93	400	77	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 159 5795MHz		5650	51.94	-16.26	68.2	43.31	33.2	13.42	37.99	236	51	P	H
		5695.5	57.25	-44.63	101.88	48.37	33.38	13.48	37.98	236	51	P	H
		5712.5	60.96	-47.74	108.7	51.93	33.5	13.51	37.98	236	51	P	H
		5720.75	61.39	-51.12	112.51	52.28	33.57	13.52	37.98	236	51	P	H
	*	5795	115.05	-	-	105.41	33.98	13.62	37.96	236	51	P	H
	*	5795	107.27	-	-	97.63	33.98	13.62	37.96	236	51	A	H
		5853.75	65.77	-47.88	113.65	55.72	34.3	13.7	37.95	236	51	P	H
		5865	64.56	-43.44	108	54.49	34.3	13.71	37.94	236	51	P	H
		5875	57.85	-47.35	105.2	47.76	34.3	13.73	37.94	236	51	P	H
		5936.5	51.94	-16.26	68.2	41.76	34.3	13.81	37.93	236	51	P	H
													H
													H
		5635	52.09	-16.11	68.2	43.49	33.2	13.4	38	400	69	P	V
		5662.25	54.04	-23.26	77.3	45.34	33.25	13.44	37.99	400	69	P	V
		5716.75	59.68	-50.21	109.89	50.62	33.53	13.51	37.98	400	69	P	V
		5724.5	60.29	-60.77	121.06	51.15	33.6	13.52	37.98	400	69	P	V
	*	5795	112.03	-	-	102.39	33.98	13.62	37.96	400	69	P	V
	*	5795	105.03	-	-	95.39	33.98	13.62	37.96	400	69	A	V
		5851.25	62.88	-56.47	119.35	52.83	34.3	13.7	37.95	400	69	P	V
		5855.25	63.58	-47.15	110.73	53.52	34.3	13.7	37.94	400	69	P	V
		5879.5	61.19	-40.67	101.86	51.1	34.3	13.73	37.94	400	69	P	V
		5926.5	54.82	-13.38	68.2	44.66	34.3	13.79	37.93	400	69	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Harmonic @ 3m)

[illegible]

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Partial 242 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Partial 242/61 CH 151 5755MHz		5634	65.9	-2.3	68.2	57.3	33.2	13.4	38	100	56	P	H
		5696.75	74.04	-28.76	102.8	65.14	33.39	13.49	37.98	100	56	P	H
		5717.25	81.84	-28.19	110.03	72.77	33.54	13.51	37.98	100	56	P	H
		5724	81.31	-38.61	119.92	72.18	33.59	13.52	37.98	100	56	P	H
	*	5755	116.46	-	-	107.04	33.82	13.57	37.97	100	56	P	H
	*	5755	107.32	-	-	97.9	33.82	13.57	37.97	100	56	A	H
		5854.75	68.37	-43	111.37	58.31	34.3	13.7	37.94	100	56	P	H
		5858.25	67.01	-42.88	109.89	56.94	34.3	13.71	37.94	100	56	P	H
		5905.5	65.13	-17.46	82.59	54.99	34.3	13.77	37.93	100	56	P	H
		5940.5	57.96	-10.24	68.2	47.77	34.3	13.81	37.92	100	56	P	H
													H
													H
		5633.25	64.5	-3.7	68.2	55.9	33.2	13.4	38	400	77	P	V
		5692	68.42	-30.88	99.3	59.55	33.37	13.48	37.98	400	77	P	V
		5715.75	76.19	-33.42	109.61	67.13	33.53	13.51	37.98	400	77	P	V
		5724.75	78.55	-43.08	121.63	69.41	33.6	13.52	37.98	400	77	P	V
	*	5755	115.54	-	-	106.12	33.82	13.57	37.97	400	77	P	V
	*	5755	105.54	-	-	96.12	33.82	13.57	37.97	400	77	A	V
		5853.25	62.26	-52.53	114.79	52.21	34.3	13.7	37.95	400	77	P	V
		5873.75	64.15	-41.4	105.55	54.06	34.3	13.73	37.94	400	77	P	V
		5875	62.58	-42.62	105.2	52.49	34.3	13.73	37.94	400	77	P	V
		5933	53.4	-14.8	68.2	43.23	34.3	13.8	37.93	400	77	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Partial 242/62 CH 159 5795MHz		5641.5	63.04	-5.16	68.2	54.43	33.2	13.41	38	100	55	P	H
		5679.25	66.51	-23.37	89.88	57.72	33.32	13.46	37.99	100	55	P	H
		5716.75	68.63	-41.26	109.89	59.57	33.53	13.51	37.98	100	55	P	H
		5721	72.82	-40.26	113.08	63.71	33.57	13.52	37.98	100	55	P	H
	*	5795	115.75	-	-	106.11	33.98	13.62	37.96	100	55	P	H
	*	5795	107.83	-	-	98.19	33.98	13.62	37.96	100	55	A	H
		5850.5	80.46	-40.6	121.06	70.41	34.3	13.7	37.95	100	55	P	H
		5856	81.25	-29.27	110.52	71.19	34.3	13.7	37.94	100	55	P	H
		5880.25	74.11	-27.19	101.3	64.02	34.3	13.73	37.94	100	55	P	H
		5945	65.57	-2.63	68.2	55.37	34.3	13.82	37.92	100	55	P	H
													H
													H
		5642.5	60.42	-7.78	68.2	51.81	33.2	13.41	38	350	80	P	V
		5678.25	64.69	-24.46	89.15	55.91	33.31	13.46	37.99	350	80	P	V
		5718.5	67.21	-43.17	110.38	58.12	33.55	13.52	37.98	350	80	P	V
		5725	69.27	-52.93	122.2	60.12	33.6	13.53	37.98	350	80	P	V
	*	5795	113.46	-	-	103.82	33.98	13.62	37.96	350	80	P	V
	*	5795	104.75	-	-	95.11	33.98	13.62	37.96	350	80	A	V
		5852	75.93	-41.71	117.64	65.88	34.3	13.7	37.95	350	80	P	V
		5863.75	74.61	-33.74	108.35	64.54	34.3	13.71	37.94	350	80	P	V
		5889	68.58	-26.23	94.81	58.47	34.3	13.75	37.94	350	80	P	V
		5934	59.71	-8.49	68.2	49.54	34.3	13.8	37.93	350	80	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE80_Full (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Full CH 155 5775MHz		5648	55.96	-12.24	68.2	47.33	33.2	13.42	37.99	240	54	P	H
		5695	64.21	-37.3	101.51	55.33	33.38	13.48	37.98	240	54	P	H
		5718.75	71.22	-39.23	110.45	62.13	33.55	13.52	37.98	240	54	P	H
		5723.5	67.25	-51.53	118.78	58.12	33.59	13.52	37.98	240	54	P	H
	*	5775	110.6	-	-	101.06	33.9	13.6	37.96	240	54	P	H
	*	5775	103.7	-	-	94.16	33.9	13.6	37.96	240	54	A	H
		5854.25	62.08	-50.43	112.51	52.02	34.3	13.7	37.94	240	54	P	H
		5857	63	-47.24	110.24	52.94	34.3	13.7	37.94	240	54	P	H
		5876.5	58.25	-45.84	104.09	48.16	34.3	13.73	37.94	240	54	P	H
		5935.25	53.59	-14.61	68.2	43.41	34.3	13.81	37.93	240	54	P	H
													H
													H
		5634.5	55.87	-12.33	68.2	47.27	33.2	13.4	38	400	75	P	V
		5699.5	64.08	-40.75	104.83	55.17	33.4	13.49	37.98	400	75	P	V
		5719.5	66.5	-44.16	110.66	57.4	33.56	13.52	37.98	400	75	P	V
		5725	61.14	-61.06	122.2	51.99	33.6	13.53	37.98	400	75	P	V
	*	5775	110	-	-	100.46	33.9	13.6	37.96	400	75	P	V
	*	5775	103.22	-	-	93.68	33.9	13.6	37.96	400	75	A	V
		5852.75	59.18	-56.75	115.93	49.13	34.3	13.7	37.95	400	75	P	V
		5862.5	59.85	-48.85	108.7	49.78	34.3	13.71	37.94	400	75	P	V
		5891	58.34	-34.99	93.33	48.23	34.3	13.75	37.94	400	75	P	V
		5933.25	52.47	-15.73	68.2	42.3	34.3	13.8	37.93	400	75	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ax HE80_Full (Harmonic @ 3m)

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE80_Partial 484 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Partial 484/65 CH 155 5775MHz		5622.75	64.29	-3.91	68.2	55.71	33.2	13.38	38	100	112	P	H
		5700	75.62	-29.58	105.2	66.71	33.4	13.49	37.98	100	112	P	H
		5718.5	79.53	-30.85	110.38	70.44	33.55	13.52	37.98	100	112	P	H
		5721.5	81.61	-32.61	114.22	72.5	33.57	13.52	37.98	100	112	P	H
	*	5775	107.43	-	-	97.89	33.9	13.6	37.96	100	112	P	H
	*	5775	100.26	-	-	90.72	33.9	13.6	37.96	100	112	A	H
		5850.5	82.83	-38.23	121.06	72.78	34.3	13.7	37.95	100	112	P	H
		5855.75	82.46	-28.13	110.59	72.4	34.3	13.7	37.94	100	112	P	H
		5875.25	74.05	-30.96	105.01	63.96	34.3	13.73	37.94	100	112	P	H
		5941	66.7	-1.5	68.2	56.51	34.3	13.81	37.92	100	112	P	H
													H
													H
		5646	64.23	-3.97	68.2	55.61	33.2	13.41	37.99	100	10	P	V
		5697.25	74.06	-29.11	103.17	65.16	33.39	13.49	37.98	100	10	P	V
		5712	79.7	-28.86	108.56	70.67	33.5	13.51	37.98	100	10	P	V
		5721.75	79.43	-35.36	114.79	70.32	33.57	13.52	37.98	100	10	P	V
	*	5775	105.98	-	-	96.44	33.9	13.6	37.96	100	10	P	V
	*	5775	98.51	-	-	88.97	33.9	13.6	37.96	100	10	A	V
		5853.5	78.74	-35.48	114.22	68.69	34.3	13.7	37.95	100	10	P	V
		5857.5	78.8	-31.3	110.1	68.74	34.3	13.7	37.94	100	10	P	V
		5875	68.72	-36.48	105.2	58.63	34.3	13.73	37.94	100	10	P	V
		5927.75	62.63	-5.57	68.2	52.46	34.3	13.8	37.93	100	10	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Partial 484/66 CH 155 5775MHz		5649.5	66.88	-1.32	68.2	58.25	33.2	13.42	37.99	100	56	P	H
		5694	76.3	-24.48	100.78	67.42	33.38	13.48	37.98	100	56	P	H
		5718.75	84.37	-26.08	110.45	75.28	33.55	13.52	37.98	100	56	P	H
		5720.75	82.01	-30.5	112.51	72.9	33.57	13.52	37.98	100	56	P	H
	*	5775	110.89	-	-	101.35	33.9	13.6	37.96	100	56	P	H
	*	5775	103.72	-	-	94.18	33.9	13.6	37.96	100	56	A	H
		5853	82.46	-32.9	115.36	72.41	34.3	13.7	37.95	100	56	P	H
		5867.75	80.12	-27.11	107.23	70.04	34.3	13.72	37.94	100	56	P	H
		5880.5	76.03	-25.08	101.11	65.94	34.3	13.73	37.94	100	56	P	H
		5934	65.65	-2.55	68.2	55.48	34.3	13.8	37.93	100	56	P	H
													H
													H
		5624.25	64.9	-3.3	68.2	56.32	33.2	13.38	38	100	5	P	V
		5692.5	74.68	-24.99	99.67	65.81	33.37	13.48	37.98	100	5	P	V
		5719.5	82.46	-28.2	110.66	73.36	33.56	13.52	37.98	100	5	P	V
		5722.75	84.57	-32.5	117.07	75.45	33.58	13.52	37.98	100	5	P	V
	*	5775	106.56	-	-	97.02	33.9	13.6	37.96	100	5	P	V
	*	5775	99.68	-	-	90.14	33.9	13.6	37.96	100	5	A	V
		5853.25	78.39	-36.4	114.79	68.34	34.3	13.7	37.95	100	5	P	V
		5868	77.38	-29.78	107.16	67.3	34.3	13.72	37.94	100	5	P	V
		5888	74.27	-21.28	95.55	64.17	34.3	13.74	37.94	100	5	P	V
		5941.25	65.66	-2.54	68.2	55.47	34.3	13.81	37.92	100	5	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

Emission above 18GHz

5GHz WIFI 802.11ax HE40 Full (SHF @ 1m)

[illegible]

Emission below 1GHz

5GHz WIFI 802.11ax HE40 Full (LF @ 3m)

WIFI	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ax HE40 Full LF		31.87	24.89	-15.11	40	35.06	24.13	1.29	35.59	-	-	P	H
		108.03	19.91	-23.59	43.5	36.25	17.15	2	35.49	-	-	P	H
		152.4	23.1	-20.4	43.5	38.97	17.21	2.34	35.42	-	-	P	H
		744	31.93	-14.07	46	32.38	28.23	5.02	33.7	-	-	P	H
		918.4	34.94	-11.06	46	33.16	29.3	5.58	33.1	-	-	P	H
		956.8	35.47	-10.53	46	31.72	30.98	5.72	32.95	-	-	P	H
													H
													H
													H
													H
													H
													H
		35.44	29.48	-10.52	40	41.56	22.25	1.25	35.58	-	-	P	V
		40.54	24.69	-15.31	40	39.57	19.42	1.29	35.59	-	-	P	V
		124.69	27.97	-15.53	43.5	43.64	17.66	2.14	35.47	-	-	P	V
		564.8	29.66	-16.34	46	33.28	26.32	4.41	34.35	-	-	P	V
		759.2	32.51	-13.49	46	32.76	28.31	5.07	33.63	-	-	P	V
		956	36.67	-9.33	46	32.92	30.98	5.72	32.95	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												
	3. The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Margin line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5650	55.45	-12.75	68.2	54.51	32.22	4.58	35.86	103	308	P	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin (dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 5650MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Margin(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 68.2(dBμV/m)
 = -12.75 (dB)

Peak measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots




Test Engineer :	John Chuang, David Dai, and Howard Huang	Temperature :	19.3~23.4°C
		Relative Humidity :	65.9~70.3%

Note symbol




-L	Low channel location
-R	High channel location






Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE[84]_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK[UNIT] 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE[94]_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE1) 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.620KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_RE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK_LIN(B) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto







WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HV Condition : PEAK_IN(16)_16-24 3m 91200_02360_231030-HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE[94]_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE1) 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.620KHz SWT:Auto



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HV Condition : PEAK_IN(16-24) 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_80[94]_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	Site : 03CH20-HY Condition : PEAK_80211a_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site : 03CH20-HY Condition : PEAK(FUND) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto






Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNB) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:0.430KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HV Condition : PEAK_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_8C[04]_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK[LINE] 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.430KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_16(16)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank




Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(84)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNI) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.270KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_RE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	Avg Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak		Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LNB) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HV Condition : PEAK_IN(16)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_8C[94]_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK[LINE1] 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(FUND) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_F4 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto




Band 4 5725~5850MHz
WIFI 802.11ax HE20 Partial 106 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(84)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:0.270KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.270KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_8C[94]_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK[LINE1] 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_B4_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UMB) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.270KHz SWT:Auto






Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNII) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:0.470KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HV Condition : : PEAK_BC[94]_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE[94]_16-24 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK[LINE1] 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL : RBW:1000.000KHz VBW:0.470KHz SWT:Auto







WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HV Condition : PEAK_IN(04)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(FUND) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.470KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HV Condition : PEAK_IN[04]_16-24 3m 91200_02360_231030-HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE[94]_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE1) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	Left blank	 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.470KHz SWT:Auto
Avg		




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_IN[04]_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank




Band 4 5725~5850MHz
WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNII) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HV Condition : :PEAK_BC[94]_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LNB) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HV Condition : PEAK_IN(04)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_RE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HV Condition : PEARL_BC[94]_16-24 3m 91200_02360_231030-HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:0.620KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNI) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:1000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HV Condition : : PEAK_BC[94]_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_RE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK_LIN(B) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:11000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_IN(04)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank




Band 4 5725~5850MHz
WIFI 802.11ax HE80 Partial 484 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(84)_16-24 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(UNII) 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL : RBW:1000.000KHz VBW:1000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_8C(94)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(64)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:11000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_24(04)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 HORIZONTAL RBW:1000.000KHz VBW:11000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_2M(15)_16-24 3m 91200_02360_231030-HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH20-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH20-HY Condition : PEAK(LINE) 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Avg	Left blank	 Site : 03CH20-HY Condition : AVG_54 3m 91200_02360_231030 VERTICAL RBW:1000.000KHz VBW:11000KHz SWT:Auto



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 09CH20-HY Condition : PEAK_8C(94)_16-24 3m 91200_02360_231030 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :-	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :-



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 50 dBuV/m. The plot date is 2023-12-20. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 50 dBuV/m. The plot date is 2023-12-20. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 50 dBuV/m. The plot date is 2023-12-20. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 50 dBuV/m. The plot date is 2023-12-20. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :-	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :-



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is at approximately 55 dBuV/m. The plot shows a flat spectrum with minor noise. Date: 2023-12-31 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL :	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is at approximately 55 dBuV/m. The plot shows a flat spectrum with minor noise. Date: 2023-12-31 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL :
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is at approximately 55 dBuV/m. The plot shows a flat spectrum with minor noise. Date: 2023-12-31 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL :	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is at approximately 55 dBuV/m. The plot shows a flat spectrum with minor noise. Date: 2023-12-31 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL :



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2024-01-06. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2024-01-06. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2024-01-06. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2024-01-06. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-31. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :-	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :-



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :-	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :-



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for 14.47G. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for 14.47G. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for 17.7G. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for 17.7G. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot shows a flat baseline with minor noise. Date: 2023-12-26 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL :	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 14470 to 14500 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot shows a flat baseline with minor noise. Date: 2023-12-26 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL :
	Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot shows a flat baseline with minor noise. Date: 2023-12-26 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL :	Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The y-axis ranges from 10.0 to 140.0 dBuV/m, and the x-axis ranges from 17700 to 18000 MHz. A red line labeled 'AVG_54' is visible at approximately 55 dBuV/m. The plot shows a flat baseline with minor noise. Date: 2023-12-26 Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL :
17.7G ~18G Avg		



Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 3m 91200_02360_231030 VERTICAL :



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) vs Frequency (MHz) for Horizontal polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 14470 to 14500 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL
	Level (dBuV/m) vs Frequency (MHz) for Horizontal polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 HORIZONTAL	Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The plot shows a flat line at approximately 50 dBuV/m across the frequency range 17700 to 18000 MHz. The date is 2023-12-26. Site : 03CH20-HY Condition : AV6_54 3m 91200_02360_231030 VERTICAL



Emission above 18GHz
5GHz WIFI 802.11ax HE40 Full (SHF @ 1m)

WIFI	5GHz WIFI	
ANT	802.11ax HE40 Full SHF	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH20-HY Condition : PEAK(UNIT) 1m SHF_1224_230710 HORIZONTAL :	 Site : 03CH20-HY Condition : PEAK(UNIT) 1m SHF_1224_230710 VERTICAL :



Emission below 1GHz
5GHz WIFI 802.11ax HE40 Full (LF @ 3m)


WIFI	5GHz WIFI	
ANT	802.11ax HE40 Full LF	
6+7	Horizontal	Vertical
QP / Peak	Site : 03CH20-4HY Condition : QP 3m LF_55606_231020_200 HORIZONTAL	Site : 03CH20-4HY Condition : QP 3m LF_55606_231020_200 VERTICAL



Appendix E. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
6+7	802.11a	85.79	1720	0.58	620Hz
6+7	5GHz 802.11ac VHT20	85.92	4880	0.20	220Hz
6+7	5GHz 802.11ac VHT40	85.87	2370	0.42	430Hz
6+7	5GHz 802.11ax HE20 Full RU	85.68	3710	0.27	270Hz
6+7	5GHz 802.11ax HE20 106 RU	85.90	3900	0.26	270Hz
6+7	5GHz 802.11ax HE40 Full RU	85.72	2215	0.45	470Hz
6+7	5GHz 802.11ax HE40 242 RU	88.10	1740	0.57	620Hz
6+7	5GHz 802.11ax HE80 Full RU	85.71	930	1.08	1.1kHz
6+7	5GHz 802.11ax HE80 484 RU	85.85	910	1.10	1.1kHz

MIMO <Ant.6+7>







5GHz 802.11ac VHT40




5GHz 802.11ax HE20 Full RU




5GHz 802.11ax HE20 106 RU



5GHz 802.11ax HE40 Full RU



5GHz 802.11ax HE40 242 RU



5GHz 802.11ax HE80 Full RU

