



FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

ATEN Technology Inc.

2.4GHz Wireless Receiver

Model Number:GKM602R(R)

FCC ID: QLERXGKM602R

Prepared for : ATEN Technology Inc.  
19641 Da Vinci Foothill Ranch, CA 92610 USA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14389  
Date of Test : Aug.03, 2011~Jan.20, 2015  
Date of Report : Feb.06, 2015

## TABLE OF CONTENTS

| Description                                                        | Page        |
|--------------------------------------------------------------------|-------------|
| <b>1. SUMMARY OF STANDARDS AND RESULTS.....</b>                    | <b>1-1</b>  |
| 1.1. Description of Standards and Results .....                    | 1-1         |
| <b>2. GENERAL INFORMATION .....</b>                                | <b>2-1</b>  |
| 2.1. Description of Device (EUT).....                              | 2-1         |
| 2.2. Tested Supporting System Details .....                        | 2-2         |
| 2.3. EUT Configuration and operation conditions for test.....      | 2-2         |
| 2.4. Test Facility .....                                           | 2-3         |
| 2.5. Measurement Uncertainty (95% confidence levels, k=2) .....    | 2-3         |
| <b>3. POWER LINE CONDUCTED EMISSION TEST .....</b>                 | <b>3-1</b>  |
| 3.1. Test Equipment .....                                          | 3-1         |
| 3.2. Block Diagram of Test Setup.....                              | 3-1         |
| 3.3. Power Line Conducted Emission Test Limits.....                | 3-1         |
| 3.4. Configuration of EUT on Test .....                            | 3-1         |
| 3.5. Operating Condition of EUT.....                               | 3-2         |
| 3.6. Test Procedure.....                                           | 3-2         |
| 3.7. Conducted Disturbance at Mains Terminals Test Results.....    | 3-2         |
| <b>4. RADIATED EMISSION TEST .....</b>                             | <b>4-1</b>  |
| 4.1. Test Equipment .....                                          | 4-1         |
| 4.2. Block Diagram of Test Setup.....                              | 4-2         |
| 4.3. Radiated Emission Limit Standard: FCC 15.209 and 15.249 ..... | 4-3         |
| 4.4. EUT Configuration on Test.....                                | 4-3         |
| 4.5. Operating Condition of EUT.....                               | 4-3         |
| 4.6. Test Procedure.....                                           | 4-3         |
| 4.7. Radiated Emission Test Results .....                          | 4-4         |
| <b>5. 20 DB BANDWIDTH TEST .....</b>                               | <b>5-1</b>  |
| 5.1. Test Equipment .....                                          | 5-1         |
| 5.2. Limit.....                                                    | 5-1         |
| 5.3. Test Results .....                                            | 5-1         |
| <b>6. BAND EDGE COMPLIANCE TEST .....</b>                          | <b>6-1</b>  |
| 6.1. Test Equipment .....                                          | 6-1         |
| 6.2. Limit.....                                                    | 6-1         |
| 6.3. Test Produce .....                                            | 6-1         |
| 6.4. Test Results .....                                            | 6-1         |
| <b>7. ANTENNA REQUIREMENT .....</b>                                | <b>7-1</b>  |
| <b>8. RADIO FRREQUENCY EXPOSURE COMPLIANCE.....</b>                | <b>8-1</b>  |
| <b>9. TEST SOFTWARE.....</b>                                       | <b>9-1</b>  |
| <b>10. DEVIATION TO TEST SPECIFICATIONS.....</b>                   | <b>10-1</b> |
| <b>11. PHOTOGRAPH OF TEST .....</b>                                | <b>11-1</b> |
| 11.1. Photos of Power Line Conducted Emission Test.....            | 11-1        |
| 11.2. Photos of Radiated Emission Test.....                        | 11-2        |
| <b>12. PHOTOGRAPH OF EUT .....</b>                                 | <b>12-1</b> |

**TEST REPORT CERTIFICATION**

Applicant : ATEN Technology Inc.  
Manufacturer : G.tech Technology Ltd.  
EUT Description : 2.4GHz Wireless Receiver  
FCC ID : QLERXGKM602R  
(A) MODEL NO. : GKM602R(R)  
(B) SERIAL NO. : N/A  
(C) POWER SUPPLY : DC 5V  
(D) TEST VOLTAGE : DC 5V From PC Input AC120/60Hz

Tested for comply with:  
FCC Rules and Regulations Part 15 Subpart C: 2013

Test procedure used:  
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. This report contains data that are not covered by the NVLAP accreditation. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Aug.03, 2011~Jan.20, 2015 Report of date: Feb.06, 2015

Prepared by : Cindy Zhu Reviewed by : Sunny Lu  
Cindy Zhu / Assistant Sunny Lu / Assistant Manager



信華科技(深圳)有限公司

Audix Technology (Shenzhen) Co., Ltd.

EMC 部門報告專用章

Stamp only for EMC Dept. Report

Signature: David Jin 2.6

Approved &amp; Authorized Signer :

David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

| EMISSION                                   |                                                                  |         |
|--------------------------------------------|------------------------------------------------------------------|---------|
| Description of Test Item                   | Standard                                                         | Results |
| Power Line Conducted Emission Test         | FCC Part 15C: 15.207<br>ANSI C63.10-2009                         | PASS    |
| Radiated Emission Test                     | FCC Part 15C: 15.209<br>FCC Part 15C: 15.249<br>ANSI C63.10-2009 | PASS    |
| Band Edge Compliance Test                  | FCC Part 15: 15.249<br>ANSI C63.10-2009                          | PASS    |
| 20dB Bandwidth Test                        | FCC Part 15: 15.215<br>ANSI C63.10-2009                          | PASS    |
| N/A is an abbreviation for Not Applicable. |                                                                  |         |

## 2. GENERAL INFORMATION


### 2.1. Description of Device (EUT)

|                     |                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name        | : 2.4GHz Wireless Receiver                                                                                                                       |
| Model Number        | : GKM602R(R)                                                                                                                                     |
| FCC ID              | : QLERXGKM602R                                                                                                                                   |
| Operation frequency | : 2402MHz-2479MHz                                                                                                                                |
| Antenna             | : Integrated PCB antenna, 0dBi gain                                                                                                              |
| Modulation          | : GFSK                                                                                                                                           |
| Applicant           | : ATEN Technology Inc.<br>19641 Da Vinci Foothill Ranch, CA 92610 USA                                                                            |
| Manufacturer        | : G. tech Technology Ltd.<br>No.21, Jinding Industrial Park, West Jinfeng Road,<br>Tangjiawan Town, Xiangzhou District Zhuhai<br>Guangdong China |
| Date of Test        | : Aug.03, 2011~Jan.20, 2015                                                                                                                      |
| Date of Receipt     | : Aug.02, 2011                                                                                                                                   |
| Sample Type         | : Prototype production                                                                                                                           |

## 2.2. Tested Supporting System Details

| No. | Description | ACS No.                                                                                                                                                      | Manufacturer | Model | Serial Number | Approved type                                                                                      |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|---------------|----------------------------------------------------------------------------------------------------|
| 1.  | Notebook    | N/A                                                                                                                                                          | DELL         | PP09S | N/A           | <input checked="" type="checkbox"/> FCC DoC<br><input checked="" type="checkbox"/> BSMI ID: R41108 |
|     |             | Power Cord: Unshielded, Detachable, 1.8m<br>Power Adapter: Manufacturer: DELL, M/N: LA65NS1-00<br>Cable: Unshielded, Detachable, 4.0m(Bond one ferrite core) |              |       |               |                                                                                                    |

## 2.3. EUT Configuration and operation conditions for test.



Notebook run test software to control EUT work in test mode

## 2.4. Test Facility

### Site Description

|                           |   |                                                                                                                                                     |
|---------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Name of Firm              | : | Audix Technology (Shenzhen) Co., Ltd.<br>No. 6, Ke Feng Rd., 52 Block, Shenzhen<br>Science & Industrial Park, Nantou, Shenzhen,<br>Guangdong, China |
| 3m Anechoic Chamber       | : | Certificated by FCC, USA<br>Registration Number: 90454<br>Valid Date: Feb.22, 2015                                                                  |
| 3m & 10m Anechoic Chamber | : | Certificated by FCC, USA<br>Registration Number: 794232<br>Valid Date: Oct.31, 2015                                                                 |
| EMC Lab.                  | : | Certificated by Industry Canada<br>Registration Number: IC 5183A-1<br>Valid Date: May.14, 2017                                                      |
|                           | : | Certificated by DAkkS, Germany<br>Registration No: D-PL-12151-01-00<br>Valid Date: Dec.15, 2016                                                     |
|                           | : | Accredited by NVLAP, USA<br>NVLAP Code: 200372-0<br>Valid Date: Mar.31, 2015                                                                        |

## 2.5. Measurement Uncertainty (95% confidence levels, k=2)


| Test Item                                                          | Uncertainty                     |
|--------------------------------------------------------------------|---------------------------------|
| Uncertainty for Conduction emission test in No. 1 Conduction       | 3.10dB(150kHz to 30MHz)         |
| Uncertainty for Radiation Emission test in 3m chamber              | 3.22 dB(30~200MHz, Polarize: H) |
|                                                                    | 3.23 dB(30~200MHz, Polarize: V) |
|                                                                    | 3.49 dB(200M~1GHz, Polarize: H) |
|                                                                    | 3.39 dB(200M~1GHz, Polarize: V) |
| Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz) | 4.97 dB (1~6GHz, Distance: 3m)  |
|                                                                    | 4.99 dB (6~18GHz, Distance: 3m) |
| Uncertainty for Radiated Spurious Emission test in RF chamber      | 3.57 dB                         |
| Uncertainty for Conduction Spurious emission test                  | 2.00 dB                         |
| Uncertainty for Output power test                                  | 0.73 dB                         |
| Uncertainty for Bandwidth test                                     | 83 kHz                          |
| Uncertainty for DC power test                                      | 0.038 %                         |
| Uncertainty for test site temperature and humidity                 | 0.6                             |
|                                                                    | 3%                              |

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipment

| Item | Equipment      | Manufacturer    | Model No. | Serial No.    | Last Cal.  | Cal. Interval |
|------|----------------|-----------------|-----------|---------------|------------|---------------|
| 1.   | Test Receiver  | Rohde & Schwarz | ESHS10    | 838693/001    | Nov.05, 10 | 1 Year        |
| 2.   | L.I.S.N.#1     | Rohde & Schwarz | ESH2-Z5   | 834066/011    | Nov.05, 11 | 1 Year        |
| 3.   | L.I.S.N.#3     | Kyoritsu        | KNW-242C  | 8-1920-1      | May.08, 11 | 1 Year        |
| 4.   | Terminator     | Hubersuhner     | 50Ω       | No. 1         | May.08, 11 | 1 Year        |
| 5.   | RF Cable       | Fujikura        | 3D-2W     | LISN Cable 1# | May.08, 11 | 1Year         |
| 6.   | Coaxial Switch | Anritsu         | MP59B     | M55367        | May.08, 11 | 1 Year        |
| 7.   | Passive Probe  | Rohde & Schwarz | ESH2-Z3   | 299.7810.52   | May.08, 11 | 1 Year        |
| 8.   | Pulse Limiter  | Rohde & Schwarz | ESH3-Z2   | 100341        | May.08, 11 | 1 Year        |

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

| Frequency range<br>MHz | Limits dB(μV)    |               |
|------------------------|------------------|---------------|
|                        | Quasi-peak Level | Average Level |
| 0,15 to 0,5            | 79               | 66            |
| 0,5 to 30              | 73               | 60            |

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. 2.4GHz Wireless Receiver (EUT)

Model Number : GKM602R(R)  
Serial Number : N/A  
Manufacturer : ATEN Technology Inc.

### 3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 2.2.
- 3.5.2. Turn on the power of all equipment.
- 3.5.3. Let the EUT work in test mode (Notebook LINK) and measure it.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#3). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

### 3.7. Conducted Disturbance at Mains Terminals Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)




# Trace: (Discrete)

Site no :1#conduction Data No :6  
Dis./Ant. :\*\* 2011 ESH2-Z5 LINE  
Limit :FCC PART 15 C  
Env./Ins. :29.5°C/55% Engineer :Leo-Li  
EUT :Long Range 2.4GHz Wireless Receiver  
Power Rating :DC 5V From PC Input AC 120V/60Hz  
Test Mode :Tx Mode  
M/N: GKM602R(R)

| No | Freq<br>(MHz) | LISN<br>Factor<br>(dB) | Cable<br>Loss<br>(dB) | Reading<br>(dBUV) | Emission<br>Level<br>(dBUV) | Limits<br>(dBUV) | Margin<br>(dB) | Remark |
|----|---------------|------------------------|-----------------------|-------------------|-----------------------------|------------------|----------------|--------|
| 1  | 0.15000       | 0.17                   | 9.98                  | 37.21             | 47.36                       | 66.00            | 18.64          | QP     |
| 2  | 0.20970       | 0.17                   | 9.98                  | 33.82             | 43.97                       | 63.22            | 19.25          | QP     |
| 3  | 2.090         | 0.31                   | 9.96                  | 24.70             | 34.97                       | 56.00            | 21.03          | QP     |
| 4  | 4.210         | 0.35                   | 9.94                  | 29.55             | 39.84                       | 56.00            | 16.16          | QP     |
| 5  | 5.493         | 0.40                   | 9.93                  | 22.56             | 32.89                       | 60.00            | 27.11          | QP     |
| 6  | 17.373        | 0.98                   | 9.97                  | 19.42             | 30.37                       | 60.00            | 29.63          | QP     |

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)  
+Reading.  
2.If the average limit is met when using a quasi-peak detector.  
the EUT shall be deemed to meet both limits and measurement  
with average detector is unnecessary.



# Trace: (Discrete)

Site no :1#conduction Data No :5  
Dis./Ant. :\*\* 2011 ESH2-Z5 NEUTRAL  
Limit :FCC PART 15 C  
Env./Ins. :29.5°C/55% Engineer :Leo-Li  
EUT :Long Range 2.4GHz Wireless Receiver  
Power Rating :DC 5V From PC Input AC 120V/60Hz  
Test Mode :Tx Mode  
M/N:GKM602R(R)

| No | Freq<br>(MHz) | LISN<br>Factor<br>(dB) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV) | Limits<br>(dBuV) | Margin<br>(dB) | Remark |
|----|---------------|------------------------|-----------------------|-------------------|-----------------------------|------------------|----------------|--------|
| 1  | 0.15000       | 0.21                   | 9.98                  | 36.50             | 46.69                       | 66.00            | 19.31          | QP     |
| 2  | 0.20970       | 0.21                   | 9.98                  | 32.11             | 42.30                       | 63.22            | 20.92          | QP     |
| 3  | 0.26940       | 0.21                   | 9.98                  | 27.51             | 37.70                       | 61.14            | 23.44          | QP     |
| 4  | 2.090         | 0.27                   | 9.96                  | 24.98             | 35.21                       | 56.00            | 20.79          | QP     |
| 5  | 4.090         | 0.31                   | 9.94                  | 27.87             | 38.12                       | 56.00            | 17.88          | QP     |
| 6  | 5.613         | 0.35                   | 9.93                  | 23.85             | 34.13                       | 60.00            | 25.87          | QP     |

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)  
+Reading.  
2.If the average limit is met when using a quasi-peak detector.  
the EUT shall be deemed to meet both limits and measurement  
with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipment

Frequency rang: 30~1000MHz


| Item | Equipment      | Manufacturer    | Model No. | Serial No.      | Last Cal.   | Cal. Interval |
|------|----------------|-----------------|-----------|-----------------|-------------|---------------|
| 1.   | 3#Chamber      | AUDIX           | N/A       | N/A             | Nov.23, 14  | 1 Year        |
| 2.   | EMI Spectrum   | Agilent         | E4407B    | MY41440292      | Apr. 28,14  | 1 Year        |
| 3.   | Test Receiver  | Rohde & Schwarz | ESVS10    | 834468/011      | Apr. 28,14  | 1 Year        |
| 4.   | Amplifier      | HP              | 8447D     | 2648A04738      | Apr. 28,14  | 1 Year        |
| 5.   | Bilog Antenna  | TESEQ           | CBL6112D  | 35375           | Jun. 18, 14 | 1 Year        |
| 6.   | RF Cable       | MIYAZAKI        | CFD400-NL | 3# Chamber No.1 | Apr. 28,14  | 1 Year        |
| 7.   | Coaxial Switch | Anritsu         | MP59B     | 6200313662      | Apr. 28,14  | 1 Year        |

Frequency rang: above 1000MHz


| Item | Equipment         | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-------------|------------|------------|---------------|
| 1    | Spectrum Analyzer | Agilent      | E4407B      | MY41440292 | May 08, 11 | 1 Year        |
| 2    | Horn Antenna      | EMCO         | 3115        | 9607-4877  | May 08, 11 | 1.5 Year      |
| 3    | Amplifier         | Agilent      | 8449B       | 3008A00863 | May 08, 11 | 1 Year        |
| 4    | RF Cable          | Hubersuhner  | SUCOFLEX102 | 28622/2    | May 08, 11 | 1 Year        |
| 5    | RF Cable          | Hubersuhner  | SUCOFLEX102 | 29091/2    | May 08, 11 | 1 Year        |
| 6    | Horn Antenna      | ETS          | 3116        | 00060089   | May 08, 11 | 1 Year        |

## 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range above 1GHz



### 4.3. Radiated Emission Limit Standard: FCC 15.209 and 15.249

| FREQUENCY<br>MHz                                                   | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT                                                                              |                                   |
|--------------------------------------------------------------------|--------------------|----------------------------------------------------------------------------------------------------|-----------------------------------|
|                                                                    |                    | $\mu\text{V/m}$                                                                                    | $\text{dB}(\mu\text{V})/\text{m}$ |
| 30 ~ 88                                                            | 3                  | 100                                                                                                | 40.0                              |
| 88 ~ 216                                                           | 3                  | 150                                                                                                | 43.5                              |
| 216 ~ 960                                                          | 3                  | 200                                                                                                | 46.0                              |
| 960 ~ 1000                                                         | 3                  | 500                                                                                                | 54.0                              |
| Above 1000MHz                                                      | 3                  | 74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak)<br>54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)  |                                   |
| Field Strength of<br>fundamental emissions for<br>2.4GHz-2.4835GHz | 3                  | 114.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak)<br>94.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average) |                                   |

- Remark :
- (1) Emission level  $\text{dB}\mu\text{V} = 20 \log$  Emission level  $\mu\text{V/m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
  - (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

### 4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 4.5.Operating Condition of EUT

- 4.5.1.Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2.Turned on the power of all equipment.
- 4.5.3.Let EUT work in Tx mode.

### 4.6.Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions.

After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation show in the test setup photos.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse modulated, a duty cycle factor was used to calculate average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

#### 4.7.Radiated Emission Test Results



**PASS.**


All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is 28.73 dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.

Duty cycle:  $280\mu s / 7.65\text{ms} \times 100\% = 3.66\%$

Duty cycle factor =  $20\log ( 1/\text{duty cycle} ) = 28.73\text{dB}$






# Frequency: 30MHz~1GHz

Data: 2

File: E:\2014 Report Data\A\ATEN\ACS14Q2041.EM6 (6)


Date: 2015-01-20



Site no. : 3m Chamber Data no. : 2  
Dis. / Ant. : 3m 2011 CBL6112D 35375 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15 C (3M)  
Env. / Ins. : 26.9°C/50% Engineer : Kobe  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx Mode  
M/N: GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 34.850         | 16.93                    | 0.65                  | 4.98              | 22.56                         | 40.00              | 17.44          | QP     |
| 2   | 119.240        | 12.70                    | 1.30                  | 7.92              | 21.92                         | 43.50              | 21.58          | QP     |
| 3   | 301.600        | 14.03                    | 2.28                  | 9.37              | 25.68                         | 46.00              | 20.32          | QP     |
| 4   | 439.340        | 17.19                    | 2.98                  | 5.77              | 25.94                         | 46.00              | 20.06          | QP     |
| 5   | 500.450        | 18.30                    | 3.22                  | 7.08              | 28.60                         | 46.00              | 17.40          | QP     |
| 6   | 575.140        | 19.30                    | 3.60                  | 2.94              | 25.84                         | 46.00              | 20.16          | QP     |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2011 CBL6112D 35375 Ant. pol. : VERTICAL  
Limit : FCC PART 15 C (3M)  
Env. / Ins. : 26.9°C/50% Engineer : Kobe  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx Mode  
M/N:GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 192.960        | 9.85                     | 1.80                  | 13.30             | 24.95                         | 43.50              | 18.55          | QP     |
| 2   | 264.740        | 13.93                    | 2.14                  | 13.36             | 29.43                         | 46.00              | 16.57          | QP     |
| 3   | 335.550        | 14.81                    | 2.48                  | 9.53              | 26.82                         | 46.00              | 19.18          | QP     |
| 4   | 432.550        | 17.10                    | 2.95                  | 6.42              | 26.47                         | 46.00              | 19.53          | QP     |
| 5   | 500.450        | 18.30                    | 3.22                  | 5.83              | 27.35                         | 46.00              | 18.65          | QP     |
| 6   | 623.640        | 19.70                    | 3.81                  | 4.05              | 27.56                         | 46.00              | 18.44          | QP     |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
2. The emission levels that are 20dB below the official limit are not reported.

# Frequency: 1GHz~18GHz


Data: 1

File: F:\2014 Report\A\ATEN\ACS11Q2041-FCC.EM6 (16)

Date: 2011-01-19



Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2402MHz  
M/N : GKM602R(R)




Site no. : 3m Chamber Data no. : 2  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2402MHz  
M/N : GKM602R(R)


| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2402.000       | 27.96                    | 6.75                  | 34.44                 | 82.11             | 82.38                         | 114.00             | 31.62          | Peak   |
| 2   | 4804.000       | 32.86                    | 9.55                  | 34.60                 | 44.37             | 52.18                         | 74.00              | 21.82          | Peak   |
| 3   | 7206.000       | 35.74                    | 11.82                 | 34.72                 | 45.25             | 58.09                         | 74.00              | 15.91          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7206                 | 58.09                    | 28.73                     | 29.36                | 54            | Pass       |



|              |                                    |           |              |
|--------------|------------------------------------|-----------|--------------|
| Site no.     | : 3m Chamber                       | Data no.  | : 3          |
| Dis. / Ant.  | : 3m 2011 3115 4580                | Ant. pol. | : HORIZONTAL |
| Limit        | : FCC PART 15 PEAK 2.4             |           |              |
| Env. / Ins.  | : 23°C/54%                         |           |              |
| Engineer     | : Black Yan                        |           |              |
| EUT          | : 2.4GHz Wireless Receiver         |           |              |
| Power rating | : DC 5V From PC Input AC 120V/60Hz |           |              |
| Test Mode    | : Tx 2402MHz                       |           |              |
| M/N          | : GKM602R(R)                       |           |              |




Site no. : 3m Chamber Data no. : 4  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2402MHz  
M/N : GKM602R(R)


| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2402.000       | 27.96                    | 6.75                  | 34.44                 | 90.78             | 91.05                         | 114.00             | 22.95          | Peak   |
| 2   | 4804.000       | 32.86                    | 9.55                  | 34.60                 | 45.68             | 53.49                         | 74.00              | 20.51          | Peak   |
| 3   | 7206.000       | 35.74                    | 11.82                 | 34.72                 | 46.50             | 59.34                         | 74.00              | 14.66          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7206                 | 59.34                    | 28.73                     | 30.61                | 54            | Pass       |



|              |                                    |           |            |
|--------------|------------------------------------|-----------|------------|
| Site no.     | : 3m Chamber                       | Data no.  | : 7        |
| Dis. / Ant.  | : 3m 2011 3115 4580                | Ant. pol. | : VERTICAL |
| Limit        | : FCC PART 15 PEAK 2.4             |           |            |
| Env. / Ins.  | : 23°C/54%                         |           |            |
| Engineer     | : Black Yan                        |           |            |
| EUT          | : 2.4GHz Wireless Receiver         |           |            |
| Power rating | : DC 5V From PC Input AC 120V/60Hz |           |            |
| Test Mode    | : Tx 2440MHz                       |           |            |
| M/N          | : GKM602R(R)                       |           |            |




Site no. : 3m Chamber Data no. : 8  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2440MHz  
M/N : GKM602R(R)


| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2440.000       | 28.03                    | 6.81                  | 34.44                 | 83.02             | 83.42                         | 114.00             | 30.58          | Peak   |
| 2   | 4880.000       | 32.98                    | 9.62                  | 34.60                 | 44.13             | 52.13                         | 74.00              | 21.87          | Peak   |
| 3   | 7320.000       | 36.05                    | 11.89                 | 34.73                 | 45.79             | 59.00                         | 74.00              | 15.00          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7320                 | 59                       | 28.73                     | 30.27                | 54            | Pass       |



|              |                                    |           |              |
|--------------|------------------------------------|-----------|--------------|
| Site no.     | : 3m Chamber                       | Data no.  | : 9          |
| Dis. / Ant.  | : 3m 2011 3115 4580                | Ant. pol. | : HORIZONTAL |
| Limit        | : FCC PART 15 PEAK 2.4             |           |              |
| Env. / Ins.  | : 23°C/54%                         |           |              |
| Engineer     | : Black Yan                        |           |              |
| EUT          | : 2.4GHz Wireless Receiver         |           |              |
| Power rating | : DC 5V From PC Input AC 120V/60Hz |           |              |
| Test Mode    | : Tx 2440MHz                       |           |              |
| M/N          | : GKM602R(R)                       |           |              |




Site no. : 3m Chamber Data no. : 10  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2440MHz  
M/N : GKM602R(R)


| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2440.000       | 28.03                    | 6.81                  | 34.44                 | 90.06             | 90.46                         | 114.00             | 23.54          | Peak   |
| 2   | 4880.000       | 32.98                    | 9.62                  | 34.60                 | 45.73             | 53.73                         | 74.00              | 20.27          | Peak   |
| 3   | 7320.000       | 36.05                    | 11.89                 | 34.73                 | 46.92             | 60.13                         | 74.00              | 13.87          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7320                 | 60.13                    | 28.73                     | 31.40                | 54            | Pass       |



|              |                                    |           |              |
|--------------|------------------------------------|-----------|--------------|
| Site no.     | : 3m Chamber                       | Data no.  | : 11         |
| Dis. / Ant.  | : 3m 2011 3115 4580                | Ant. pol. | : HORIZONTAL |
| Limit        | : FCC PART 15 PEAK 2.4             |           |              |
| Env. / Ins.  | : 23°C/54%                         |           |              |
| Engineer     | : Black Yan                        |           |              |
| EUT          | : 2.4GHz Wireless Receiver         |           |              |
| Power rating | : DC 5V From PC Input AC 120V/60Hz |           |              |
| Test Mode    | : Tx 2479MHz                       |           |              |
| M/N          | : GKM602R(R)                       |           |              |




Site no. : 3m Chamber Data no. : 12  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2479MHz  
M/N : GKM602R(R)


| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2479.000       | 28.08                    | 6.87                  | 34.45                 | 87.77             | 88.27                         | 114.00             | 25.73          | Peak   |
| 2   | 4958.000       | 33.14                    | 9.69                  | 34.60                 | 45.22             | 53.45                         | 74.00              | 20.55          | Peak   |
| 3   | 7437.000       | 36.37                    | 11.95                 | 34.74                 | 46.18             | 59.76                         | 74.00              | 14.24          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7437                 | 59.76                    | 28.73                     | 31.03                | 54            | Pass       |



|              |                                    |           |            |
|--------------|------------------------------------|-----------|------------|
| Site no.     | : 3m Chamber                       | Data no.  | : 13       |
| Dis. / Ant.  | : 3m 2011 3115 4580                | Ant. pol. | : VERTICAL |
| Limit        | : FCC PART 15 PEAK 2.4             |           |            |
| Env. / Ins.  | : 23°C/54%                         |           |            |
| Engineer     | : Black Yan                        |           |            |
| EUT          | : 2.4GHz Wireless Receiver         |           |            |
| Power rating | : DC 5V From PC Input AC 120V/60Hz |           |            |
| Test Mode    | : Tx 2479MHz                       |           |            |
| M/N          | : GKM602R(R)                       |           |            |



Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 PEAK 2.4  
 Env. / Ins. : 23°C/54%  
 Engineer : Black Yan  
 EUT : 2.4GHz Wireless Receiver  
 Power rating : DC 5V From PC Input AC 120V/60Hz  
 Test Mode : Tx 2479MHz  
 M/N : GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2479.000       | 28.08                    | 6.87                  | 34.45                 | 83.19             | 83.69                         | 114.00             | 30.31          | Peak   |
| 2   | 4958.000       | 33.14                    | 9.69                  | 34.60                 | 45.02             | 53.25                         | 74.00              | 20.75          | Peak   |
| 3   | 7437.000       | 36.37                    | 11.95                 | 34.74                 | 46.44             | 60.02                         | 74.00              | 13.98          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.

| Frequency<br>( MHz ) | Peak level<br>( dBuV/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuV/m) | Limit(dBuV/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 7437                 | 60.02                    | 28.73                     | 31.29                | 54            | Pass       |

## 5. 20 DB BANDWIDTH TEST

### 5.1. Test Equipment

| Item | Equipment         | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|-------------------|--------------|-----------|------------|-----------|---------------|
| 1.   | Spectrum Analyzer | Agilent      | E4446A    | US44300459 | May.08,11 | 1 Year        |

### 5.2. Limit


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 5.3. Test Results


|                               |                     |                    |
|-------------------------------|---------------------|--------------------|
| EUT: 2.4GHz Wireless Receiver |                     |                    |
| M/N: GKM602R(R)               |                     |                    |
| Test date:2011-08-05          | Pressure: 101.7 kpa | Humidity: 52 %     |
| Tested by: Leo-Li             | Test site: RF site  | Temperature : 25.6 |

| Frequency         | 20dB bandwidth<br>( KHz ) | Limit<br>(KHz) |
|-------------------|---------------------------|----------------|
| 2402MHz           | 1956                      | N/A            |
| 2440MHz           | 1456                      | N/A            |
| 2479MHz           | 2309                      | N/A            |
| Conclusion : PASS |                           |                |


Test Frequency: 2402MHz



Test Frequency: 2440MHz



Test Frequency: 2479MHz



## 6. BAND EDGE COMPLIANCE TEST

### 6.1. Test Equipment

| Item | Equipment         | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-------------|------------|------------|---------------|
| 1.   | Spectrum Analyzer | Agilent      | E4446A      | US44300459 | May.08,11  | 1 Year        |
| 2.   | Horn Antenna      | EMCO         | 3115        | 9607-4877  | May.25, 11 | 1.5 Year      |
| 3.   | Amplifier         | Agilent      | 8449B       | 3008A02495 | May.08, 11 | 1 Year        |
| 4.   | RF Cable          | Hubersuhner  | SUCOFLEX102 | 28620/2    | May.08,11  | 1 Year        |
| 5.   | RF Cable          | Hubersuhner  | SUCOFLEX102 | 28618/2    | May.08,11  | 1 Year        |
| 6.   | RF Cable          | Hubersuhner  | SUCOFLEX102 | 28610/2    | May.08,11  | 1 Year        |

### 6.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 6.3. Test Produce


1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
  - (b)This device is pulse modulated, a duty cycle factor was used to calculate average level based measured peak level

### 6.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

Note: The duty cycle factor for calculate average level is 28.73 dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.




Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 PEAK 2.4  
 Env. / Ins. : 23°C/54%  
 Engineer : Black Yan  
 EUT : 2.4GHz Wireless Receiver  
 Power rating : DC 5V From PC Input AC 120V/60Hz  
 Test Mode : Tx 2402MHz  
 M/N : GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2390.000       | 27.96                    | 6.72                  | 34.44                 | 56.33             | 56.57                         | 74.00              | 17.43          | Peak   |
| 2   | 2400.000       | 27.96                    | 6.75                  | 34.44                 | 73.20             | 73.47                         | 74.00              | 0.53           | Peak   |
| 3   | 2402.352       | 27.96                    | 6.75                  | 34.44                 | 89.90             | 90.17                         | 114.00             | 23.83          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.


| Frequency<br>( MHz ) | Peak level<br>( dBuv/m ) | Duty cycle factor<br>(dB) | AV level<br>(dBuv/m) | Limit(dBuv/m) | Conclusion |
|----------------------|--------------------------|---------------------------|----------------------|---------------|------------|
| 2400.000             | 73.47                    | 28.73                     | 44.74                | 54            | Pass       |



Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 PEAK 2.4  
 Env. / Ins. : 23°C/54%  
 Engineer : Black Yan  
 EUT : 2.4GHz Wireless Receiver  
 Power rating : DC 5V From PC Input AC 120V/60Hz  
 Test Mode : Tx 2402MHz  
 M/N : GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission          |                    |                |        |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                |                          |                       |                       |                   | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
| 1   | 2390.000       | 27.96                    | 6.72                  | 34.44                 | 49.74             | 49.98             | 74.00              | 24.02          | Peak   |
| 2   | 2400.000       | 27.96                    | 6.75                  | 34.44                 | 63.96             | 64.23             | 74.00              | 9.77           | Peak   |
| 3   | 2402.352       | 27.96                    | 6.75                  | 34.44                 | 82.30             | 82.57             | 114.00             | 31.43          | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 15  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15 PEAK 2.4  
Env. / Ins. : 23°C/54%  
Engineer : Black Yan  
EUT : 2.4GHz Wireless Receiver  
Power rating : DC 5V From PC Input AC 120V/60Hz  
Test Mode : Tx 2479MHz  
M/N : GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2478.745       | 28.08                    | 6.87                  | 34.45                 | 82.71             | 83.21                         | 114.00             | 30.79          | Peak   |
| 2   | 2483.500       | 28.08                    | 6.90                  | 34.45                 | 57.59             | 58.12                         | 74.00              | 15.88          | Peak   |
| 3   | 2483.680       | 28.08                    | 6.90                  | 34.45                 | 57.93             | 58.46                         | 74.00              | 15.54          | Peak   |
| 4   | 2500.000       | 28.10                    | 6.90                  | 34.45                 | 46.15             | 46.70                         | 74.00              | 27.30          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
- Amp Factor  
2. The emission levels that are 20dB below the official  
limit are not measured



Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 PEAK 2.4  
 Env. / Ins. : 23°C/54%  
 Engineer : Black Yan  
 EUT : 2.4GHz Wireless Receiver  
 Power rating : DC 5V From PC Input AC 120V/60Hz  
 Test Mode : Tx 2479MHz  
 M/N : GKM602R(R)

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | AMP<br>factor<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 2478.920       | 28.08                    | 6.87                  | 34.45                 | 87.36             | 87.86                         | 114.00             | 26.14          | Peak   |
| 2   | 2483.500       | 28.08                    | 6.90                  | 34.45                 | 61.42             | 61.95                         | 74.00              | 12.05          | Peak   |
| 3   | 2500.000       | 28.10                    | 6.90                  | 34.45                 | 49.44             | 49.99                         | 74.00              | 24.01          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.

## 7. ANTENNA REQUIREMENT

**RESULT : PASS**

Test Date : Aug.03~07, 2011

Test standard : FCC Part 15.203

Limit : the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply the provision.

## 8. RADIO FRREQUENCY EXPOSURE COMPLIANCE

**RESULT : PASS**

Test standard : FCC KDB Publication 447498 D01 V05

Since maximum peak output power of the transmitter is  $<10\text{mW}$ , i.e.  $0.009346\text{mW} < 10\text{mW}$ , hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01:General RF Exposure Guidance V05.

## 9. TEST SOFTWARE

Manufacturer : G. tech Technology Ltd.

Version : Fuhlen Bind V1.1

The test software is used to control EUT work in TX mode and to change the test channel.

## 10.DEVIATION TO TEST SPECIFICATIONS

[NONE]