

Eimssion of Restricted bands

Operation Mode : Transmitting / Receiving

Test Date : Mar. 18, 2003

Temperature : 25 °C

Humidity : 68 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.		
1135.000	47.1	***	43.1	***	-9.1	38.0	***	74.0	54.0	109	1.4
1208.000	---	***	40.2	***	-8.8	---	***	74.0	54.0	---	---
1527.000	---	***	42.1	***	-7.3	---	***	74.0	54.0	---	---
1618.000	40.1	***	40.1	***	-6.8	33.3	***	74.0	54.0	313	1.5
1689.000	42.1	***	40.1	***	-6.4	35.7	***	74.0	54.0	185	1.4
1720.000	---	---	---	---	-6.2	---	---	74.0	54.0	---	---
2273.000	---	---	---	---	-3.6	---	---	74.0	54.0	---	---
2355.000	40.1	***	---	***	-3.3	36.8	***	74.0	54.0	350	1.1
2495.000	40.1	***	---	***	-2.7	37.4	***	74.0	54.0	238	1.1
2788.000	45.2	***	40.1	***	-1.8	43.4	***	74.0	54.0	118	1.1
2814.000	40.8	***	41.2	***	-1.8	39.4	***	74.0	54.0	178	1.5
3265.000	41.1	***	---	***	-0.6	40.5	***	74.0	54.0	235	1.1
3337.000	---	---	---	---	-0.4	---	---	74.0	54.0	---	---
3352.000	---	***	40.3	***	-0.4	39.9	***	74.0	54.0	178	1.4
3849.000	42.4	***	---	***	1.4	43.8	***	74.0	54.0	198	1.2
3952.000	43.4	***	---	***	1.8	45.2	***	74.0	54.0	234	1.1
4132.000	44.5	***	40.8	***	2.0	46.5	***	74.0	54.0	109	1.4
4351.000	41.5	***	---	***	2.0	43.5	***	74.0	54.0	182	1.1
4577.000	---	---	---	---	2.1	---	---	74.0	54.0	---	---
5015.000	43.1	***	---	***	2.9	46.0	***	74.0	54.0	223	1.4
5384.000	45.2	***	40.8	***	4.1	49.3	***	74.0	54.0	235	1.1
5433.000	---	---	---	---	4.2	---	---	74.0	54.0	---	---
7567.000	43.1	***	41.0	***	6.2	49.3	***	74.0	54.0	321	1.2
8234.000	45.1	***	---	***	6.6	51.7	***	74.0	54.0	112	1.5
8411.000	41.1	***	---	***	6.7	47.8	***	74.0	54.0	198	1.5
9072.000	42.3	***	---	***	7.0	49.3	***	74.0	54.0	85	1.3
9189.000	46.0	***	43.7	***	7.1	53.1	***	74.0	54.0	35	1.4
9383.000	45.1	***	41.0	***	7.2	52.3	***	74.0	54.0	128	1.3

Eimssion of Restricted bands

Operation Mode : Transmitting / Receiving

Test Date : Mar. 18, 2003

Temperature : 25 °C

Humidity : 68 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave	Peak	Ave.		
9478.000	44.0	***	40.0	***	7.2	51.2	***	74.0	54.0	98	1.3
10732.000	43.0	***	---	***	8.2	51.2	***	74.0	54.0	90	1.4
11523.000	42.1	***	40.7	***	9.1	51.2	***	74.0	54.0	185	1.1
12566.000	43.4	***	40.7	***	9.5	52.9	***	74.0	54.0	198	1.2
13388.000	48.1	***	42.3	***	10.8	52.9	***	74.0	54.0	109	1.5
14489.000	40.2	***	---	***	11.6	51.8	***	74.0	54.0	238	1.1
15788.000	---	---	---	---	8.3	---	---	74.0	54.0	---	---
16109.000	41.1	***	---	***	8.3	49.4	***	74.0	54.0	221	1.1
17989.000	42.8	***	---	***	8.4	51.2	***	74.0	54.0	189	1.1
19832.000	44.2	***	41.7	***	8.6	52.8	***	74.0	54.0	177	1.5
21341.000	43.1	***	42.0	***	9.7	52.8	***	74.0	54.0	108	1.5
22773.000	---	---	---	---	10.5	---	---	74.0	54.0	---	---
23845.000	41.2	***	---	***	10.4	51.6	***	74.0	54.0	125	1.4
31451.000	---	---	---	---	13.5	---	---	74.0	54.0	---	---
31781.000	---	---	---	---	13.7	---	---	74.0	54.0	---	---
36498.000	---	---	---	---	13.8	---	---	74.0	54.0	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

Tested by

: Imout Chaw

Checked by

: Charles

