



## Maximum Permissible Exposure (MPE) & Exposure evaluation

**Report identification number: 1-9218/19-01-15-A MPE (FCC\_ISED)**

Certification numbers and labeling requirements	
FCC ID	Y82-DA14AVD
ISED number	9576A-DA14AVD
HVIN (Hardware Version Identification Number)	DA14AVDDECT SF01
PMN (Product Marketing Name)	DA14AVDDECT
FVIN (Firmware Version Identification Number)	Fixed Part Radio Module, Portable Part Radio Module
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorised:



Thomas Vogler  
Lab Manager  
Radio Communications & EMC



Marco Scigliano  
Testing Manager  
Radio Communications & EMC

### Document History:

Version	Applied Changes	Date of Release
	Initial Release	2020-08-26
-A	Added FVIN.	2020-09-10

**EUT technologies:**

Technologies:	Max. peak power [dBm]		Antenna gain max.: [dBi] *	Declared by customer
	Conducted *	EIRP *		
UPCS 1925	decl. 19.0 meas. 18.0	decl. 19.0 meas. 18.0	0.0	18.0 dBm +/-1 dB

)\* worst case result see CTC advanced test report 1-9218/19-01-07 (FP) and 1-9218/19-01-13 (PP)

### Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density  
 P = Power input to the antenna  
 G = Antenna gain  
 R = Distance to the center of radiation of the antenna  
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

#### Prediction: worst case

Technologies:		UPCS	
	Frequency (MHz)	1925	
PG	Declared max power (EIRP)	19	dBm
R	Distance	20	cm
S	MPE limit for uncontrolled exposure	1	mW/cm <sup>2</sup>
	<b>Calculated Power density:</b>	0.0158	mW/cm <sup>2</sup>
	<b>Calculated percentage of Limit:</b>	1.58%	

#### **This prediction demonstrates the following:**

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

### Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5} \text{ W}$  (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834} \text{ W}$  (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		0.3 - 6 GHz	
	Frequency	1925	MHz
R	Distance	20	cm
P	Max power input to the antenna	19	dBm
G	Antenna gain	0	dBi
PG	Maximum EIRP	19	dBm
PG	<b>Maximum EIRP</b>	79.4	mW
	<b>Exclusion Limit from above:</b>	2.30	W
	<b>Calculated percentage of Limit:</b>	3.45%	

**Conclusion:** RF exposure evaluation is not required.