


# Radio test report 99529334

based on:

FCC part 15; subpart C; section 15.227 (10-1-03 edition)

Cordless Keyboard Logitech Cordless Keyboard Y-RR54





Report number:

99529334

#### **Contents**

MA	AIN MODULE	3
1	1 Introduction	3
2		
3	3 TEST SCHEDULE	4
4		
5	5 OBSERVATIONS AND COMMENTS	
6		
7	7 SUMMARY	6
8	8 CONCLUSIONS	7
TES	ST RESULTS MODULE	8
1	1 General information	8
•	1.1 Equipment information	
2	1 1	
	2.1 Field strength of intentional signal	
	2.2 Field strength of unwanted emissions	
TICT	ED TEST EQUIDMENT MODULE	11

This report comprises of three modules. The total number of pages is: 11





Main module Page: 3 of 11
Report number: 99529334

#### Main module

#### 1 Introduction

This report contains the result of tests performed by:

Telefication by Edisonstraat 12a 6902 PK Zevenaar The Netherlands

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:1999. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie). The contents of this test report, if reproduced, shall be copied in full, unless special consent in writing for reproduction in part is granted by Telefication. Copyright of this test report is reserved to Telefication.

#### Ordering party:

Company name : Logitech Europe S.A. Address : Z.I. Moulin du Choc D

Zipcode : CH-1122

City/town : Romanel sur Morges

Country : Switzerland Date of order : 3 March 2004



TESTING
RVA L 021

Main module Page: 4 of 11
Report number: 99529334

#### 2 Product

A sample of the following product was submitted for testing:

Product description : Cordless Keyboard Manufacturer : Logitech Europe S.A.

Trade mark : Logitech Cordless Keyboard

Type designation : Y-RR54 FCC ID : DZL131836M

Hardware version : -

Serial number : 0406100016

Software release : --

#### 3 Test schedule

Tests were carried out in accordance with the specification detailed in chapter 7 "Summary" of this report.

Tests were carried out at the following location:

TNO Electronic Products & Services (EPS) B.V

Smidshornerweg 18 9822 TL Niekerk The Netherlands

FCC listed : 90828 Industry Canada : IC3501

The samples of the product were received on:

• 28 June 2004

Tests were carried out on:

• 30 June 2004



TESTING
RVA L 021
4

Main module Page: 5 of 11 Report number: 99529334

## 4 Product documentation

For production of this report the following product documentation was used:

<b>Description:</b>	Date:	Identification:
Testing indications	June 2004	Cordless Keyboard Y-RR54
Product Description	June 2004	Y-RR54
Block diagram		Midas Lite (Y-RR54)
PCB lay out	8 May 2004	P/No 131836 PAS, 10 pages
Circuit diagram vDial module	26 January 2004	MidasLite: vDial module
Circuit diagram RF	3 June 2004	Y-RR54 MIDAS LITE - RF

The above-mentioned documentation will be filed at Telefication for a period of 10 years following the issue of this test report.



## Logitech AGY-734664-0000.A0 Main module



Page: 6 of 11 Report number: 99529334

#### **5** Observations and comments

During the tests the product was set in continuous transmit mode (CH1 & CH2 selectable), by means of a test mode.

### **6** Modifications to the sample

No modifications were made to the sample.

#### 7 Summary

The product is intended for use in the following application area(s):

INDUCTIVE DATA TRANSMISSION APPLICATION IN THE 27 MHz BAND

The samples were tested according to the following specification(s):

FCC part 15; subpart C; section 15.227 (10-1-03 edition)



TESTING
RVA L 021

Main module Page: 7 of 11
Report number: 99529334

#### 8 Conclusions

The samples of the product showed **NO NON-COMPLIANCES** to the specification stated in chapter 7 of this report.

The results of the tests as stated in this report, are exclusively applicable to the product items as identified in this test report. Telefication does not accept any responsibility for the results stated in this test report, with respect to the properties of product items not involved in these tests.

All tests are performed by:

name : ing. P.A. Suringa

function : Senior Engineer Radio/EMC

signature

Review of test report by:

name : J.P. van de Poll

function : Co-ordinator Test Group

signature :

The above conclusions have been verified by the following signatory:

Date : 9 July 2004

name : drs. ir. W.B.A. Blom

function : Managing Director

signature :



Test results module Page: 8 of 11
Report number: 99529334

## **Test results module**

#### 1 General information

## 1.1 Equipment information

Rated RF output power	n.a., integral antenna	
Rated radiated RF power	400 nW	
Operating frequencies	27.095 MHz; 27.145 MHz	
Modulation	FSK	
Modulation bit rate	2400 bit/s	
ITU emission class	7K00F2D	
FCC ID	DZL131836M	



Test results module Page: 9 of 11
Report number: 99529334

#### 2 Emission tests

#### 2.1 Field strength of intentional signal

Compliance standard : FCC part 15, subpart C, section 15.227 (a). Method of test : ANSI C63.4-2001, sections 5.3 & 8.2.1

Test results

Radiated emissions (dBµV/m) (AV)			
	27.095 MHz channel		
Orthogonal plane	Test result @ 3 m distance	Limit @ 3 m distance	
X	43.4	80.0	
Y	55.2	80.0	
Z	55.2	80.0	

Measurement uncertainty: -2.4 dB / +1.6 dB



Test results module Page: 10 of 11
Report number: 99529334

#### 2.2 Field strength of unwanted emissions

Compliance standard : FCC part 15, subpart C, section 15.227 (b).

Method of test : ANSI C63.4-2001, sections 5.4, 8.2.3 & 8.3.1.2; FCC part 15,

subpart A, section 15.31(m), 15.33, 15.35.

EUT condition : 27.095 MHz channel

Test results :

#### < 30 MHz

Frequency	Test result	EUT	Limit
	@ 3 m distance	orthogonal	
(MHz)	$(dB\mu V/m) (QP)$	plane	$(dB\mu V/m)$
13.548	29.0	Z	29.5

#### > 30 MHz

Frequency	Test result	Polarisation	Limit
(MHz)	@ 3 m distance (dBµV/m) (QP)		$dB\mu V/m$
54.180	16.3	Н	40.0
81.270	25.9	H	40.0
108.360	36.2	Н	43.5
135.450	39.5	Н	43.5
162.540	41.5	Н	43.5
189.650	28.7	Н	43.5
216.750	29.4	Н	46.0
243.850	44.9	Н	46.0
244.300	28.0	Н	46.0
270.940	32.5	Н	46.0
298.040	35.5	Н	46.0

Measurement uncertainty: -2.4 dB / +1.6 dB



Photographs module Page: 11 of 11 Report number: 99529334

## Used test equipment module

The following measurement equipment was used:

Description	ID / SN	Manufacturer	Model
Plastic measurement room	12636	Polyforce	-
Open Area Test Site	13886	Comtest	_
Antenna mast 4m	14277	Heinrich Deisel	MA240
Controller OATS	14278	Heinrich Deisel	HD100
Loop Antenna	1107	Chase	HLA6120
Biconilog antenna 30MHz – 1000MHz	15633	Chase	CBL6111B
EMI test receiver	15667	Rohde & Schwarz	ESCS 30
Turntable OATS	99108	Heinrich Deisel	HD050