




MEASUREMENT REPORT

FCC PART 15.407 / RSS-247 WLAN 802.11a/n/ac

FCC ID: 2AD8UFZCWI2A1
IC: 109D-FZCWI2A01
APPLICANT: Nokia Solutions and Networks

Application Type: Certification
Product: Wireless Access Point
Model No.: WI2A-AC200i
Brand Name: Nokia
FCC Classification: Unlicensed National Information Infrastructure (UNII)
FCC Rule Part(s): Part 15.407
IC Rule(s): RSS-247 Issue 1
Test Procedure(s): ANSI C63.10-2013, KDB 789033 D02v01,
KDB 662911 D01v02r01, KDB 644545 D03v01
Test Date: June 16 ~ August 18, 2015

Reviewed By : 
(Robin Wu)

Approved By : 
(Marlin Chen)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1506RSU00612	Rev. 01	Initial report	10-01-2015

CONTENTS

Description	Page
§2.1033 General Information	6
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Equipment Description.....	8
2.2. Working Frequencies for this report	10
2.3. Description of Available Antennas.....	11
2.4. Description of Antenna RF Port	12
2.5. Test Mode	12
2.6. Test Software	12
2.7. Device Capabilities	13
2.8. Test Configuration	15
2.9. EMI Suppression Device(s)/Modifications.....	15
2.10. Labeling Requirements.....	15
3. DESCRIPTION OF TEST	16
3.1. Evaluation Procedure	16
3.2. AC Line Conducted Emissions	16
3.3. Radiated Emissions	17
4. ANTENNA REQUIREMENTS.....	18
5. TEST EQUIPMENT CALIBRATION DATE	19
6. MEASUREMENT UNCERTAINTY	20
7. TEST RESULT	21
7.1. Summary	21
7.2. 26dB Bandwidth Measurement.....	24
7.2.1. Test Limit	24
7.2.2. Test Procedure used.....	24
7.2.3. Test Setting.....	24
7.2.4. Test Setup	24
7.2.5. Test Result.....	25
7.3. 6dB Bandwidth Measurement.....	39
7.3.1. Test Limit	39
7.3.2. Test Procedure used.....	39

7.3.3. Test Setting.....	39
7.3.4. Test Setup	39
7.3.5. Test Result.....	40
7.4. Operation Frequency Range of 26dBc Bandwidth Measurement.....	49
7.4.1. Test Limit	49
7.4.2. Test Procedure used.....	49
7.4.3. Test Setting.....	49
7.4.4. Test Setup	49
7.4.5. Test Result.....	50
7.5. Output Power Measurement.....	53
7.5.1. Test Limit	53
7.5.2. Test Procedure Used	53
7.5.3. Test Setting.....	53
7.5.4. Test Setup	54
7.5.5. Test Result.....	55
7.6. Transmit Power Control	68
7.6.1. Test Limit	68
7.6.2. Test Procedure Used	68
7.6.3. Test Setting.....	68
7.6.4. Test Setup	68
7.6.5. Test Result.....	68
7.7. Power Spectral Density Measurement	69
7.7.1. Test Limit	69
7.7.2. Test Procedure Used	69
7.7.3. Test Setting.....	69
7.7.4. Test Setup	70
7.7.5. Test Result.....	71
7.8. Frequency Stability Measurement.....	119
7.8.1. Test Limit	119
7.8.2. Test Procedure Used	119
7.8.3. Test Setup	119
7.8.4. Test Result.....	120
7.9. Radiated Spurious Emission Measurement	121
7.9.1. Test Limit	121
7.9.2. Test Procedure Used	121
7.9.3. Test Setting.....	121
7.9.4. Test Setup	122
7.9.5. Test Result.....	124
7.10. Radiated Restricted Band Edge Measurement	214

7.10.1. Test Limit	214
7.10.2. Test Result of Radiated Restricted Band Edge	218
7.11. AC Conducted Emissions Measurement.....	422
7.11.1. Test Limit	422
7.11.2. Test Procedure	422
7.11.3. Test Setup	423
7.11.4. Test Result.....	424
8. CONCLUSION.....	426

§2.1033 General Information

Applicant:	Nokia Solutions and Networks
Applicant Address:	Karaportti 3, P.O. Box 226, FI-00045 Nokia Group, Finland
Manufacturer:	Nokia Solutions and Networks
Manufacturer Address:	Karaportti 3, P.O. Box 226, FI-00045 Nokia Group, Finland
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
FCC Registration No.:	809388
IC Registration No.:	11384A
FCC Rule Part(s):	Part 15.247
IC Rule(s):	RSS-247
Model No.:	WI2A-AC200i
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering
FCC Classification:	Unlicensed National Information Infrastructure (UNII)

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



2. PRODUCT INFORMATION

2.1. Equipment Description


Product Name	Wireless Access Point
Model No.	WI2A-AC200i
Brand Name	Nokia
Hardware Version	v2.0
Frequency Range	<u>2.4GHz:</u> For 802.11b/g/n-HT20: 2412 ~ 2462 MHz For 802.11n-HT40: 2422 ~ 2452 MHz <u>5GHz:</u> For 802.11a/n-HT20/ac-VHT20:: 5180~5240MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40: 5190~5230MHz, 5755~5795MHz For 802.11ac-VHT80: 5210MHz, 5775MHz
Maximum Output Power	802.11a: 26.29dBm 802.11n-HT20: 26.09dBm 802.11n-HT40: 25.98dBm 802.11ac-VHT20: 26.18dBm 802.11ac-VHT40: 26.00dBm 802.11ac-VHT80: 21.15dBm
Type of Modulation	802.11a/n/ac: OFDM
Components	
Adapter	M/N: DSA-12CA-12 120100 Input: 100-240V ~ 50/60Hz, 0.3A OUTPUT: 12Vdc, 1A
POE	M/N: PoE35-54A Input: 100-240V ~ 50/60Hz, 1A OUTPUT: 54Vdc, 0.65A

Note 1: For all of the test mode, two power supplies have been assessed in the spurious emission test, and showed the worst test data for AC Adpter (DSA-12CA-12 120100) in the test report.

Note 2: The change of the measured voltage at the radio part of the EUT is below $\pm 1\%$, when input voltage from external power supply (AC Adapter & POE Adapter) to the equipment under test, thus

the RF test is tested with AC Adapter only.

AC Adapter Voltage	3.30V
POE Adapter Voltage	3.31V



2.2. Working Frequencies for this report

802.11a/n-HT20/ ac-VHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	149	5745 MHz	153	5765 MHz
157	5785 MHz	161	5805 MHz	165	5825 MHz

802.11n-HT40/ ac-VHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	151	5755 MHz
159	5795 MHz	--	--	--	--

802.11ac-VHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	155	5775 MHz	--	--


2.3. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Per Chain Max Antenna Gain (dBi)		Beam Forming Directional Gain (dBi)	CDD Directional Gain (dBi)
			Ant 1	Ant 2		
PCB Antenna	2412 ~ 2462	2	3.23	2.38	5.83	5.83
	5150 ~ 5250	2	5.40	4.53	7.99	7.99
	5725 ~ 5850	2	6.00	5.86	8.94	8.94

- The EUT supports Cyclic Delay Diversity (CDD) technology for 802.11a/b/g mode, and CDD signals are correlated.
- The EUT supports Beam Forming technology for 802.11n/ac mode, and exclude 802.11b/g mode.
Correlated signals include, but are not limited to, signals transmitted in any of the following modes:
 - Unequal Antenna gains, with equal transmit powers. For Antenna gains given by $G_1, G_2, \dots, G_N$ dBi transmit signals are correlated, then
 - Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]
For example: 5150 ~ 5250MHz Directional Gain = $10 \cdot \log[(10^{5.40/20} + 10^{4.53/20})^2 / 2] = 7.99$ dBi

2.4. Description of Antenna RF Port

Antenna RF Port				
--	2.4GHz RF Port		5GHz RF Port	
	2.4GHz-1	2.4GHz-2	5GHz-1	5GHz-2
Software Control Port	Ant 1	Ant 2	Ant 1	Ant 2



The photograph shows a blue antenna module with two ports. Red arrows point to the ports, which are labeled '2.4GHz & 5GHz Ant Port #1' and '2.4GHz & 5GHz Ant Port #2'.

2.5. Test Mode

Test Mode	Mode 1: Transmit by 802.11a
	Mode 2: Transmit by 802.11n-HT20
	Mode 3: Transmit by 802.11n-HT40
	Mode 4: Transmit by 802.11ac-VHT20
	Mode 5: Transmit by 802.11ac-VHT40
	Mode 6: Transmit by 802.11ac-VHT80

2.6. Test Software

The test utility software used during testing was “ART2-GUI Version: 2.3”.


2.7. Device Capabilities

This device contains the following capabilities:


2.4GHz WLAN (DTS) and 5GHz WLAN (NII).

Note: 5GHz (NII) operation is possible in 20MHz, 40MHz and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = average per the guidance of Section B)2)b) of KDB 789033 D02v01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:


Test Mode	Duty Cycle
802.11a	96.04 %
802.11n-HT20	93.72 %
802.11n-HT40	91.16 %
802.11ac-VHT20	95.63 %
802.11ac-VHT40	90.35 %
802.11ac-VHT80	82.45 %




802.11n-HT40




802.11ac-VHT20



802.11ac-VHT40



802.11ac-VHT80



2.8. Test Configuration

The **Wireless Access Point FCC ID: 2AD8UFZCWI2A1, Model Number: WI2A-AC200i** was tested per the guidance of KDB 789033 D02v01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.9. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.10. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v01 were used in the measurement of the **Wireless Access Point FCC ID: 2AD8UFZCW12A1, Model Number: W12A-AC200i.**

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.10.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of **Wireless Access Point** is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **Wireless Access Point FCC ID: 2AD8UFZCWI2A1, Model Number: WI2A-AC200i** unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2015/11/07
Temperature/Humidity Meter	Ouleinuo	N/A	MRTSUE06114	1 year	2015/11/20

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	E4447A	MRTSUE06028	1 year	2015/12/09
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2015/11/07
Preamplifier	Agilent	83017A	MRTSUE06020	1 year	2016/03/29
Preamplifier	Schwarzbeck	BBV9721	MRTSUE06121	1 year	2016/04/16
Loop Antenna	Schwarzbeck	FMZB1519	MRTSUE06025	1 year	2015/12/09
TRILOG Antenna	Schwarzbeck	VULB9162	MRTSUE06022	1 year	2015/11/08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2015/11/08
Broadband Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06024	1 year	2016/01/06
Temperature/Humidity Meter	Ouleinuo	N/A	MRTSUE06115	1 year	2015/11/20

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2016/05/08
USB Wideband Power Sensor	Boonton	55006	MRTSUE06109	1 year	2016/05/08
Temperature/Humidity Meter	Ouleinuo	N/A	MRTSUE06112	1 year	2015/11/20

Software	Version	Function
e3	V 8.3.5	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 40GHz: 4.76dB

7. TEST RESULT

7.1. Summary

Company Name: Nokia Solutions and Networks
FCC ID: 2AD8UFZCWI2A1
IC: 109D-FZCWI2A01
Model No.: WI2A-AC200i
Data Rate(s) Tested: 6Mbps ~ 54Mbps (a);
6.5/7.2Mbps ~ 130/144.4Mbps (n-HT20MHz BW);
13.5/15.0Mbps ~ 270/300Mbps (n-HT40MHz BW);
6.5/7.2Mbps ~ 156/173.4Mbps (ac-VHT20MHz BW);
13.5/15.0Mbps ~ 360/400Mbps (ac-VHT40MHz BW);
29.3/32.5Mbps ~ 780/866.6Mbps (ac-VHT80MHz BW)

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	$\geq 500\text{kHz}$		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	$\leq 30\text{ dBm U-NII-1}$ $\leq 30\text{ dBm U-NII-3}$		Pass	Section 7.5
15.407(h)(1)	Transmit Power Control	$\leq 24\text{ dBm}$		Pass	Section 7.6
15.407(a)(1)(ii), (2), (3), (5)	Peak Power Spectral Density	$\leq 17\text{ dBm/MHz U-NII-1}$ $\leq 30\text{ dBm/500kHz U-NII-3}$		Pass	Section 7.7
15.407(g)	Frequency Stability	N/A		Pass	Section 7.8
15.407(b)(1), (2), (3), (4)	Undesirable Emissions	$\leq -27\text{dBm/MHz EIRP}$ $\leq -17\text{dBm/MHz EIRP}$	Radiated	Pass	Section 7.9 & 7.10
15.205, 15.209 15.407(b)(5), (6), (7)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.11

RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
RSS-247 §6.2	99% Bandwidth	N/A	Conducted	Pass	Section 7.2
RSS-247 §6.2.4	6dB Bandwidth	>500kHz		Pass	Section 7.3
RSS-247 §6.2.1	Operation Frequency Range of 26dB BW	26dBc frequency range above 5250MHz		Pass	Section 7.4
RSS-247 §6.2.1, §6.2.2, §6.2.3, §6.2.4	Max Conducted Output Power	5725~5850MHz, ≤ 30 dBm		Pass	Section 7.5
	Maximum E.I.R.P	5150~5250MHz ≤ 23 dBm or 10 + 10 log10(99% B)			
RSS-247 §6.2.2, §6.2.3	Transmit Power Control	≤ 24 dBm		Pass	Section 7.6
RSS-247 §6.2.1, §6.2.2, §6.2.3, §6.2.4	Peak Power Spectral Density	5150~5250MHz ≤ 10 dBm/MHz 5725~5850MHz ≤ 30 dBm/500kHz		Pass	Section 7.7
RSS-Gen [8.11]	Frequency Stability	N/A		Pass	Section 7.8
RSS-247 §6.2.1, §6.2.2, §6.2.3, §6.2.4	Out-of-Band Emissions	≤ -27dBm/MHz EIRP ≤ -17dBm/MHz EIRP	Radiated	Pass	Section 7.9 & 7.10
RSS-247 §6.2.1, §6.2.2, §6.2.3, §6.2.4	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in RSS-Gen [8.9]		Pass	
RSS-Gen [8.8]	AC Conducted Emissions 150kHz - 30MHz	< RSS-Gen [8.8] limits	Line Conducted	Pass	Section 7.11

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) Test Items “26dB Bandwidth”, “99% Bandwidth”, “6dB Bandwidth” & “Operation Frequency Range of 26dB BW” have been assessed single and MIMO transmission, and showed the worst test data in this report.

7.2. 26dB Bandwidth Measurement

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

KDB 789033 D02v01 – Section C.1

7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4. Test Setup




7.2.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 1					
802.11a	6	36	5180	22.11	16.67
802.11a	6	44	5220	21.11	16.72
802.11a	6	48	5240	21.44	16.65
802.11a	6	149	5745	22.19	16.66
802.11a	6	157	5785	21.39	16.67
802.11a	6	165	5825	22.19	16.67
802.11n-HT20	6.5	36	5180	22.03	17.78
802.11n-HT20	6.5	44	5220	22.66	17.80
802.11n-HT20	6.5	48	5240	22.80	17.82
802.11n-HT20	6.5	149	5745	22.41	17.85
802.11n-HT20	6.5	157	5785	23.11	17.80
802.11n-HT20	6.5	165	5825	22.53	17.80
802.11n-HT40	13.5	38	5190	44.73	36.47
802.11n-HT40	13.5	46	5230	43.40	36.33
802.11n-HT40	13.5	151	5755	43.99	36.37
802.11n-HT40	13.5	159	5795	45.22	36.39
802.11ac-VHT20	6.5	36	5180	21.95	17.79
802.11ac-VHT20	6.5	44	5220	22.03	17.79
802.11ac-VHT20	6.5	48	5240	22.43	17.83
802.11ac-VHT20	6.5	149	5745	22.63	17.82
802.11ac-VHT20	6.5	157	5785	23.15	17.80
802.11ac-VHT20	6.5	165	5825	23.55	17.85
802.11ac-VHT40	13.5	38	5190	44.11	36.38
802.11ac-VHT40	13.5	46	5230	42.66	36.35
802.11ac-VHT40	13.5	151	5755	43.10	36.38
802.11ac-VHT40	13.5	159	5795	43.60	36.40
802.11ac-VHT80	29.3	42	5210	85.94	75.81
802.11ac-VHT80	29.3	155	5775	86.65	75.79


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 2					
802.11a	6	36	5180	21.27	16.63
802.11a	6	44	5220	21.71	16.63
802.11a	6	48	5240	21.00	16.64
802.11a	6	149	5745	21.09	16.66
802.11a	6	157	5785	21.01	16.66
802.11a	6	165	5825	21.44	16.68
802.11n-HT20	6.5	36	5180	23.69	17.89
802.11n-HT20	6.5	44	5220	22.32	17.81
802.11n-HT20	6.5	48	5240	22.48	17.77
802.11n-HT20	6.5	149	5745	22.06	17.80
802.11n-HT20	6.5	157	5785	22.62	17.83
802.11n-HT20	6.5	165	5825	22.37	17.81
802.11n-HT40	13.5	38	5190	44.95	36.43
802.11n-HT40	13.5	46	5230	44.26	36.41
802.11n-HT40	13.5	151	5755	44.51	36.39
802.11n-HT40	13.5	159	5795	45.34	36.41
802.11ac-VHT20	6.5	36	5180	22.48	17.78
802.11ac-VHT20	6.5	44	5220	22.37	17.80
802.11ac-VHT20	6.5	48	5240	22.57	17.80
802.11ac-VHT20	6.5	149	5745	22.08	17.82
802.11ac-VHT20	6.5	157	5785	22.31	17.84
802.11ac-VHT20	6.5	165	5825	22.08	17.82
802.11ac-VHT40	13.5	38	5190	44.07	36.39
802.11ac-VHT40	13.5	46	5230	43.18	36.36
802.11ac-VHT40	13.5	151	5755	43.50	36.38
802.11ac-VHT40	13.5	159	5795	44.25	36.44
802.11ac-VHT80	29.3	42	5210	86.04	75.79
802.11ac-VHT80	29.3	155	5775	85.04	75.71

802.11a 26dB Bandwidth & 99% Bandwidth - Ant 1


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT20 26dB Bandwidth & 99% Bandwidth - Ant 1


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT40 26dB Bandwidth & 99% Bandwidth - Ant 1


Channel 38 (5190MHz)




Channel 46 (5230MHz)



Channel 151 (5755MHz)




Channel 159 (5795MHz)




802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Ant 1


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth - Ant 1


Channel 38 (5190MHz)




Channel 46 (5230MHz)



Channel 151 (5755MHz)




Channel 159 (5795MHz)




802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth - Ant 1

Channel 42 (5210MHz)




Channel 155 (5755MHz)




802.11a 26dB Bandwidth & 99% Bandwidth - Ant 2


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT20 26dB Bandwidth & 99% Bandwidth - Ant 2


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT40 26dB Bandwidth & 99% Bandwidth - Ant 2


Channel 38 (5190MHz)



Channel 46 (5230MHz)



Channel 151 (5755 MHz)



Channel 159 (5795 MHz)

