

# FIH CO., LTD.

No.4, Minsheng St., Tu-Cheng Dist., New Taipei City 23679, Taiwan  
Tel: 886-2-2268-5511 / FAX: 886-2-2269-2922

Date: 2023-12-01

FCC ID: RYQGP3

## MIF for HAC RF Interference Evaluation

To Whom It May Concern,

We, [FIH CO., LTD.](#) declare that this device, Hearing Aid Compatibility Requirement is going to be certified under **ANSI C63.19-2011 version per Part 20.19**.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in the HAC report and adding the MIF value in dB (V/m) using pre-determined values provided by Speag under the below table:

UID	Reversion	Communication System Name	MIF (dB)
10021	DAC	GSM-FDD (TDMA, GMSK)	3.63
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	3.75
10460	AAA	UMTS-FDD (WCDMA, AMR)	-25.43
10225	CAB	UMTS-FDD (HSPA+)	-20.39
10170	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-9.76
10172	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	-1.62
10173	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-1.44
10174	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	-1.54
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	0.12
10427	AAC	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	-13.44
10069	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	-3.15
10616	AAC	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	-5.57

The Speag-reference documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, UID SUMMARY (Communication Systems for Calibration, Issued Date 2020/09/05).

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely yours,

*Barry Tsai*

Barry Tsai / Manager

FIH CO., LTD.

Tel: 886-2-2268-5511 / FAX: 886-2-2269-2922

E-mail: Certification@fih-foxconn.com