

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Udfine Watch Starry
Model Name	Udfine Starry
FCC ID	2BACS-UDFINE

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR/EDR:

$P_t = -1.316\text{dBm} = 0.739\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (2.270\text{mW} / 5\text{mm}) \cdot [\sqrt{2.402\text{GHz}}] = 0.229 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE 1M:

$P_t = -0.555\text{dBm} = 0.880\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (1.752\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480\text{GHz}}] = 0.277 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE 2M:

$P_t = -0.555\text{dBm} = 0.880\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (1.752\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480\text{GHz}}] = 0.277 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.