



*Evaluation of Compliance with FCC-Specified Guidelines for  
Human Exposure to Radio Frequency Electromagnetic Fields*

on the

**4 Watts ERP RF CDPD Amplifier  
Model: AirBooster 350  
for  
Sierra Wireless, Inc.**

Date of Test: October 25, 1999

Job # J99027747

Total No. of Pages Contained in this Report: 8 + data pages


All services undertaken are subject to the following general policy: Reports are submitted for exclusive use of the client to whom they are addressed. Their significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations or surveys made. No quotations from reports or use of Intertek Testing Services' name is permitted except as expressly authorized by Intertek Testing Services in writing.



FCC 2.1091 & ANSI 95.1-1992

**Intertek Testing Services NA Inc.**

1365 Adams Court, Menlo Park, CA 94025  
Telephone 650-463-2900 Fax 650-463-2910 Home Page [www.worldlab.com](http://www.worldlab.com)



**VERIFICATION OF COMPLIANCE**

**No. J99027747**

Verification is hereby issued to the named APPLICANT and is VALID ONLY for the equipment identified hereon for use under the rules and regulations listed below.

Equipment Under Test:	4 Watts ERP RF CDPD Amplifier
Trade Name:	Sierra Wireless
Model No.:	AirBooster 350
Serial No.:	Not Labeled
Applicant:	Sierra Wireless, Inc.
Contact:	Mr. Dominique Kwan
Address:	13575 Commerce Parkway, Suite 150 Richmond, BC V6V 2L1
Tel. number:	(604) 231-1181
Fax number:	(604) 231-1109
Applicable Regulation:	FCC 2.1091 & ANSI C95.1:1992
Equipment Class:	Uncontrolled Environments
Date of Test:	October 25, 1999

*We attest to the accuracy of this report:*



*Xi-Ming Yang*  
Xi-Ming Yang  
Test Engineer

*C.K. Li*  
C.K. Li  
Telco Manager

**Intertek Testing Services NA Inc.**

1365 Adams Court, Menlo Park, CA 94025

Telephone 650-463-2900 Fax 650-463-2910 Home Page [www.worldlab.com](http://www.worldlab.com)

## Table of Contents

1.0	<b>Introduction.....</b>	1
2.0	<b>Description of Equipment.....</b>	1
3.0	<b>Test Summary .....</b>	1
4.0	<b>System Test Configuration.....</b>	2
4.1	Support Equipment .....	2
4.2	Block Diagram of Test Setup .....	2
4.3	Justification .....	3
4.4	Software Exercise Program .....	3
4.5	Mode of Operation During Test .....	3
4.6	Modifications Required for Compliance .....	3
5.0	<b>Radiated Emissions .....</b>	4
5.1	Radiated Emission Limits .....	4
5.2	Site Description and List of Test Equipment. ....	5
5.3	Test Procedure .....	5
5.4	Field Strength Calculation.....	5
5.5	Configuration Photographs.....	6
5.6	Test Data.....	7
6.0	<b>Miscellaneous Information or Other Comments .....</b>	8



## 1.0 Introduction

This report is designed to show compliance with the FCC Part 2.1091 Radio Frequency Radiation Exposure Evaluation for mobile and unlicensed devices. The test procedures and limits, as described in American National Standards Institute C95.1-1992, were employed. A description of the product and operating configuration, the various provisions of the rules, the methods for determining compliance, and a detailed summary of the results are included within this test report.

## 2.0 Description of Equipment

The Sierra Wireless, Inc. Model AirBooster is a 4 watts ERP RF CDPD amplifier with frequency range from 824 - 849 MHz.

The amplifier is used with the following antennas:

1. Larsen Model MM3 800 FME - magnetic mount 3.4 dBd gain
2. Antenna World Model CLR-877 magnetic mount 3 dBd gain

## 3.0 Test Summary

The CDPD Amplifier was tested by Intertek Testing Services as documented herein, and the energy emitted by the EUT was found to be below the recommended levels of Maximum Permissible Exposure for Uncontrolled Environments in FCC 1.1310 (ANSI C95.1: 1992).

Therefore, in reference to the limits set forth in FCC 1.1310 use of the equipment is deemed to be safe with respect to human exposure to Radio Frequency Electromagnetic Fields, when used in a normal fashion.

Sierra Wireless, Inc., CDPD Amplifier


Date of Test: October 25, 1999

#### 4.0 System Test Configuration

#### 4.1 Support Equipment

Item #	Description	Model No.	Serial No.	FCC ID
1	IBM Computer	ThinkPad	2600-50UAS00DVC	MLZ315
2	GW DC Power Supply	GPR-6030	N/A	N/A
3	Sierra Modem	SB300	206-00065973	N7N0EM2
4	Sierra Interface Test Band	M1E	N/A	N/A
5	AC Adaptor	NDIE1000L00	N/A	N/A

#### 4.2 Block Diagram of Test Setup



\* = EUT

\*\* = No ferrites on video cable

S = Shielded;

U = Unshielded

F = With Ferrite

Sierra Wireless, Inc., CDPD Amplifier

Date of Test: October 25, 1999

#### 4.3 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it).

#### 4.4 Software Exercise Program

No special software was used during the tests.

#### 4.5 Mode of Operation During Test

Transmitting full power (4W).

#### 4.6 Modifications Required for Compliance

The following modifications were installed during compliance testing in order to bring the product into compliance (Please note that this list does not include changes made specifically by Teledex Corporation prior to compliance testing):

No modifications were installed by Intertek Testing Services.

Sierra Wireless, Inc., CDPD Amplifier

Date of Test: October 25, 1999

**5.0 Radiated Emissions****5.1 Radiated Emission Limits, FCC 1.1310**

The following exposure limits apply to equipment use in Uncontrolled Environments:

**Maximum Permissible Exposure for Uncontrolled Environments**

Frequency Range (MHZ)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) E-field, H-field (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3 - 1.34	614	1.63	*100	30
1.34 - 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

\* = Plane-wave equivalent power density.

Dashes "-" are used to indicate that there is no limit under the guideline.



Sierra Wireless, Inc., CDPD Amplifier

Date of Test: October 25, 1999

## 5.2 Site Description and List of Test Equipment.

All tests were performed on Open Area Test Site.

Measurement equipment used for radiated emission compliance testing utilized some of the equipment on the following list:

Manufacturer	Equipment	Model Number	Calibration Due
Holaday	Field Strength Meter	HI-3004EX	5/17/00

## 5.3 Test Procedure

The test was performed at 836 MHz. The antenna was placed on a 0.8m wooden table on open site. The antenna was connected to the EUT. EUT output power was measured at RF output connector. EUT has 36.5 dBm power output.

The sensor of the field strength meter was moved around the antenna to obtain the maximum reading of the field strength meter. The measurements were performed at the distance 0.2m and 0.3m from the antenna.

## 5.4 Field Strength Calculation


The field strength was measured directly from the meter. The power density (PD in  $W.m^2$ ) was calculated using the following formula:

$$Pd = E^2/120\pi$$

Where E is Field Strength in V/m

5.5 Configuration Photographs

**Radiated Emission**



## 5.6 Test Data

The results on the following page(s) were obtained when the device was tested in the condition described in section 4.

Amplifier Used with Larsen Antenna			
Test Distance m	Maximum Field Strength Reading V/m	Calculated Power Density mW/cm <sup>2</sup>	FCC Limit for Time- Averaging Interval of 30 min. mW/cm <sup>2</sup>
0.1	55	0.80	0.54
0.2	30	0.23	0.54
0.3	25	0.17	0.54
0.5	15	0.06	0.54
1.0	10	0.027	0.54
1.5	5.5	0.008	0.54

Amplifier Used with Antenna World Antenna			
Test Distance m	Maximum Field Strength Reading V/m	Calculated Power Density mW/cm <sup>2</sup>	FCC Limit for Time- Averaging Interval of 30 min. mW/cm <sup>2</sup>
0.1	55	0.80	0.54
0.2	30	0.23	0.54
0.3	25	0.17	0.54
0.5	15	0.06	0.54
1.0	10	0.027	0.54
1.5	5.5	0.008	0.54

Judgment: The EUT will pass FCC limit at a distance 0.2m or longer from EUT.

Sierra Wireless, Inc., CDPD Amplifier

Date of Test: October 25, 1999

**6.0 Miscellaneous Information or Other Comments**

None.