

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.

WIRELESS SOUND SYSTEM

Model Number: TY-ASC20

FCC ID: ESX-ASC20

Prepared for : Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.
Vtrek Dewei Industrial Garden, Shibe Industrial Road, Dashi
Town, Panyu Borough, Guangzhou, Guangdong, China

Prepared By : EST Technology Co., Ltd.
San Tun Management Zone, Houjie Town, Dongguan,
Guangdong, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1704021
Date of Test : March 06, 2017 ~ June 23, 2017
Date of Report : June 27, 2017

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	4
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram	8
2.6. Test mode	9
2.7. Channel List for Bluetooth.....	9
2.8. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Result.....	11
3.4. Test Data	12
4. 20 DB BANDWIDTH.....	16
4.1. Limit	16
4.2. Test Procedure	16
4.3. Test Result.....	16
4.4. Test Data	17
5. CARRIER FREQUENCY SEPARATION	21
5.1. Limit	21
5.2. Test Procedure	21
5.3. Test Result.....	21
5.4. Test Data	22
6. NUMBER OF HOPPING CHANNEL	26
6.1. Limit	26
6.2. Test Procedure	26
6.3. Test Result.....	26
6.4. Test Data	27
7. DWELL TIME	29
7.1. Limit	29
7.2. Test Procedure	29
7.3. Test Result.....	29
7.4. Test Data	30
8. RADIATED EMISSIONS.....	36
8.1. Limit	36
8.2. Block Diagram of Test setup	37
8.3. Test Procedure	38
8.4. Test Result.....	38
8.5. Test Data	39
9. BAND EDGE COMPLIANCE	65

9.1.	Limit	65
9.2.	Block Diagram of Test setup	65
9.3.	Test Procedure	65
9.4.	Test Result	65
9.5.	Test Data	66
10.	POWER LINE CONDUCTED EMISSIONS	82
10.1.	Limit	82
10.2.	Test Procedure	82
11.	ANTENNA REQUIREMENTS	87
11.1.	Limit	87
11.2.	Result	87
12.	TEST SETUP PHOTO	88
13.	PHOTOS OF EUT	90

Test Report Verification

Applicant:	Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.		
Address:	Vtrek Dewei Industrial Garden, Shibe Industrial Road, Dashi Town, Panyu Borough, Guangzhou, Guangdong, China		
Manufacturer	Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.		
Address:	Vtrek Dewei Industrial Garden, Shibe Industrial Road, Dashi Town, Panyu Borough, Guangzhou, Guangdong, China		
E.U.T:	WIRELESS SOUND SYSTEM		
Model Number:	TY-ASC20 Note:TY-ASC20 may come in color variations but are electrically and mechanically the same. The only difference is the color.		
Power Supply:	DC 11.1V From Internal Battery DC 5V From Adapter Input AC 100-240V~50-60Hz		
Test Voltage:	DC 5V From Adapter Input AC 120V/60Hz DC 5V From Adapter Input AC 240V/60Hz		
Trade Name:	TOSHIBA	Serial No.:	-----
Date of Receipt:	March 06, 2017	Date of Test:	March 06, 2017 ~ June 23, 2017
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2016 ANSI C63.10:2013		
Test Result:	The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: June 27, 2017		
Prepared by:	Tested by:	Approved by:	
 _____ Ada / Assistant	 _____ Tony.Tang / Engineer	 _____ Iceman.Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	WIRELESS SOUND SYSTEM
FCC ID	:	ESX-ASC20
Model Number	:	TY-ASC20
Operation frequency	:	2402MHz~2480MHz
Number of channel	:	79
Antenna	:	Internal antenna, 0dBi gain
Modulation	:	BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK
Sample Type	:	Prototype production

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) DA 00-705	PASS
20dB Bandwidth	FCC Part 15: 15.247a1 DA 00-705	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) DA 00-705	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 DA 00-705	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) DA 00-705	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:201 DA 00-705	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Test Facilities

EMC Lab	:	Certificated by CNAL, CHINA Registration No.: L5288 Date of registration: December 07, 2015 Certificated by FCC, USA Registration No.: 989591 Date of registration: November 15, 2016 Certificated by Industry Canada Registration No.: 9405A-1 Date of registration: December 30, 2015 Certificated by VCCI, Japan Registration No.: R-3663 & C-4103 Date of registration: July 25, 2011 Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: January 07, 2011 Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011 Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L1-18 Date of registration: April 28, 2011 Certificated by Siemic, Inc. Registration No.: SLCN021 Date of registration: November 8, 2011 Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62dB
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86dB
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.4. Assistant equipment used for test

2.4.1. Adapter

M/N : PGAE0500200U1UL
 Input : 100-240V~50-60Hz 0.3A
 Output : 5.0V/2.0A

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was be set into BT test mode by software before test.



(EUT: WIRELESS SOUND SYSTEM)

2.6. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
8-DPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

2.7. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

2.8. Test Equipment

2.8.1. For conducted emissions test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June,25,16	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June,25,16	1 Year
Pulse Limiter	Rohde & Schwarz	ESDS6-Z2	101100	June,25,16	1 Year

2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	100435	June,25,16	1 Year
Loop Antenna	ETS-LINDGREN	6502	00071730	June,25,16	1 Year

2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,25,16	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June,25,16	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,15	3 Year
Signal Amplifier	Agilent	310N	187037	June,25,16	1 Year

2.8.4. For radio & radiated emissions test (above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1002	June,28,15	3 Year
Board-Band Horn Antenna	SCHWARZB ECK	BBHA 9170	9170-497	June,28,15	3 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June,25,16	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,25,16	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	June,25,16	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June,25,16	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer

3.3. Test Result


EUT: WIRELESS SOUND SYSTEM					
M/N: TY-ASC20					
Test date: 2017-04-12		Test site: RF site		Tested by: Tony Tang	
Mode	Freq (MHz)	Result (dBm)	Limit		Margin (dB)
			dBm	W	
GFSK	2402	0.183	21.00	0.125	20.817
	2441	-0.011	21.00	0.125	21.011
	2480	-0.184	21.00	0.125	21.184
8-DPSK	2402	0.184	21.00	0.125	20.816
	2441	-0.020	21.00	0.125	21.020
	2480	-0.169	21.00	0.125	21.169
Conclusion: PASS					

3.4. Test Data


GFSK 2402 MHz




GFSK 2441 MHz




GFSK 2480 MHz




8-DPSK 2402 MHz



8-DPSK 2441 MHz



8-DPSK 2480 MHz



4. 20 DB BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: WIRELESS SOUND SYSTEM				
M/N: TY-ASC20				
Test date: 2017-04-12		Test site: RF site		Tested by: Tony Tang
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	1.050	/	PASS
	2441	1.090	/	PASS
	2480	1.038	/	PASS
8-DPSK	2402	1.356	/	PASS
	2441	1.359	/	PASS
	2480	1.361	/	PASS

4.4. Test Data


GFSK 2402MHz




GFSK 2441MHz




GFSK 2480MHz




8-DPSK 2402MHz



8-DPSK 2441MHz



8-DPSK 2480MHz



5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.

5.3. Test Result


EUT: WIRELESS SOUND SYSTEM				
M/N: TY-ASC20				
Test date: 2017-04-12			Test site: RF site	Tested by: Tony Tang
Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.000	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS
8-DPSK	Low CH	1.000		PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS


5.4. Test Data

GFSK
Low Channel




Mid Channel







8-DPSK
Low Channel



Mid Channel





6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure




The transmitter output (antenna port) was connected to the spectrum analyzer. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

6.3. Test Result




EUT: WIRELESS SOUND SYSTEM			
M/N: TY-ASC20			
Test date: 2017-04-12		Test site: RF site	Tested by: Tony.Tang
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
8-DPSK	79	>15	PASS

6.4. Test Data

GFSK



8-DPSK



7. DWELL TIME

7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



7.2. Test Procedure

1. Connect the antenna port of the EUT to the spectrum analyzer by a low loss cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW= 1MHz, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.



7.3. Test Result

EUT: WIRELESS SOUND SYSTEM			
M/N: TY-ASC20			
Test date: 2017-04-12		Test site: RF site	Tested by: Tony Tang
Mode	Dwell time (ms)	Limit	Conclusion
GFSK DH1	127.42	<400ms	PASS
GFSK DH3	245.72	<400ms	PASS
GFSK DH5	319.10	<400ms	PASS
8-DPSK 3DH1	127.42	<400ms	PASS
8-DPSK 3DH3	239.65	<400ms	PASS
8-DPSK 3DH5	284.15	<400ms	PASS



7.4. Test Data





GFSK DH3 : 24hop/5s * 0.4 * 79 * 1.62ms= 245.72





$$\text{GSFK DH5 : } 17\text{hop}/5\text{s} * 0.4 * 79 * 2.97\text{ms} = 319.10$$





$8\text{-DPSK } 3\text{DH1} : 48\text{hop}/5\text{s} * 0.4 * 79 * 0.42\text{ms} = 127.42$



$8\text{-DPSK } 3\text{DH3} : 24\text{hop}/5\text{s} * 0.4 * 79 * 1.58\text{ms} = 239.65$



$8\text{-DPSK } 3\text{DH5} : 16\text{hop}/5\text{s} * 0.4 * 79 * 2.81\text{ms} = 284.15$



8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system

8.2. Block Diagram of Test setup



8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

8.4. Test Result

Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz 、 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

8.5. Test Data


9 kHz – 30 MHz

Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


30 MHz – 1000 MHz

Date: 2017-06-23




Site no. : site Data no. : 387
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	71.710	6.03	1.08	14.29	21.40	40.00	18.60	QP
2	91.110	8.41	1.29	11.37	21.07	43.50	22.43	QP
3	117.300	11.02	1.47	12.56	25.05	43.50	18.45	QP
4	172.590	9.07	1.68	24.22	34.97	43.50	8.53	QP
5	219.150	9.10	1.94	18.00	29.04	46.00	16.96	QP
6	866.140	22.87	3.79	4.14	30.80	46.00	15.20	QP




Site no. : 1# 966 Chamber Data no. : 388
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	116.330	10.98	1.50	13.36	25.84	43.50	17.66	QP
2	130.880	11.33	1.47	7.71	20.51	43.50	22.99	QP
3	172.590	9.07	1.68	12.75	23.50	43.50	20.00	QP
4	224.000	9.42	2.01	15.22	26.65	46.00	19.35	QP
5	229.820	9.44	2.07	15.35	26.86	46.00	19.14	QP
6	865.170	22.89	3.78	4.62	31.29	46.00	14.71	QP




Site no. : 1# 966 Chamber Data no. : 389
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	116.330	10.98	1.50	12.68	25.16	43.50	18.34	QP
2	166.770	9.54	1.69	14.05	25.28	43.50	18.22	QP
3	220.120	9.20	1.97	14.09	25.26	46.00	20.74	QP
4	234.670	9.69	2.09	12.48	24.26	46.00	21.74	QP
5	353.980	14.46	2.57	6.12	23.15	46.00	22.85	QP
6	864.200	22.90	3.78	3.76	30.44	46.00	15.56	QP




Site no. : 1# 966 Chamber Data no. : 390
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	66.860	5.28	1.06	15.57	21.91	40.00	18.09	QP
2	97.900	9.13	1.33	10.85	21.31	43.50	22.19	QP
3	110.510	10.52	1.42	9.59	21.53	43.50	21.97	QP
4	168.710	9.31	1.70	22.34	33.35	43.50	10.15	QP
5	215.270	8.70	1.96	17.97	28.63	43.50	14.87	QP
6	865.170	22.89	3.78	2.74	29.41	46.00	16.59	QP




Site no. : 1# 966 Chamber Data no. : 391
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.710	6.03	1.08	12.28	19.39	40.00	20.61	QP
2	115.360	10.93	1.46	9.29	21.68	43.50	21.82	QP
3	169.680	9.20	1.69	23.14	34.03	43.50	9.47	QP
4	201.690	7.79	1.77	16.31	25.87	43.50	17.63	QP
5	217.210	8.90	1.93	17.48	28.31	46.00	17.69	QP
6	864.200	22.90	3.78	4.87	31.55	46.00	14.45	QP




Site no. : 1# 966 Chamber Data no. : 392
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	114.390	10.85	1.42	13.35	25.62	43.50	17.88	QP
2	167.740	9.43	1.71	12.59	23.73	43.50	19.77	QP
3	223.030	9.37	2.01	15.05	26.43	46.00	19.57	QP
4	353.980	14.46	2.57	6.15	23.18	46.00	22.82	QP
5	672.140	20.23	3.62	7.62	31.47	46.00	14.53	QP
6	864.200	22.90	3.78	5.96	32.64	46.00	13.36	QP




Site no. : 1# 966 Chamber Data no. : 393
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	117.300	11.02	1.47	12.96	25.45	43.50	18.05	QP
2	171.620	9.12	1.68	14.94	25.74	43.50	17.76	QP
3	222.060	9.31	2.01	15.95	27.27	46.00	18.73	QP
4	353.980	14.46	2.57	6.29	23.32	46.00	22.68	QP
5	673.110	20.24	3.63	4.10	27.97	46.00	18.03	QP
6	864.200	22.90	3.78	4.58	31.26	46.00	14.74	QP




Site no. : 1# 966 Chamber Data no. : 394
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	68.800	5.51	1.10	16.69	23.30	40.00	16.70	QP
2	111.480	10.60	1.44	11.92	23.96	43.50	19.54	QP
3	171.620	9.12	1.68	21.28	32.08	43.50	11.42	QP
4	220.120	9.20	1.97	16.61	27.78	46.00	18.22	QP
5	672.140	20.23	3.62	5.23	29.08	46.00	16.92	QP
6	865.170	22.89	3.78	5.55	32.22	46.00	13.78	QP




Site no. : 1# 966 Chamber Data no. : 395
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	69.770	5.62	1.07	13.30	19.99	40.00	20.01	QP
2	115.360	10.93	1.46	10.72	23.11	43.50	20.39	QP
3	169.680	9.20	1.69	21.28	32.17	43.50	11.33	QP
4	214.300	8.65	1.96	18.28	28.89	43.50	14.61	QP
5	672.140	20.23	3.62	5.74	29.59	46.00	16.41	QP
6	865.170	22.89	3.78	4.34	31.01	46.00	14.99	QP




Site no. : 1# 966 Chamber Data no. : 396
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	114.390	10.85	1.42	11.68	23.95	43.50	19.55	QP
2	169.680	9.20	1.69	12.42	23.31	43.50	20.19	QP
3	224.000	9.42	2.01	15.16	26.59	46.00	19.41	QP
4	365.620	14.68	2.67	5.95	23.30	46.00	22.70	QP
5	672.140	20.23	3.62	4.55	28.40	46.00	17.60	QP
6	863.230	22.91	3.77	5.17	31.85	46.00	14.15	QP



Site no. : 1# 966 Chamber Data no. : 397
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	115.360	10.93	1.46	13.25	25.64	43.50	17.86	QP
2	167.740	9.43	1.71	13.09	24.23	43.50	19.27	QP
3	226.910	9.46	2.04	15.64	27.14	46.00	18.86	QP
4	364.650	14.65	2.63	7.55	24.83	46.00	21.17	QP
5	672.140	20.23	3.62	5.42	29.27	46.00	16.73	QP
6	866.140	22.87	3.79	7.01	33.67	46.00	12.33	QP



Site no. : 1# 966 Chamber Data no. : 398
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	68.800	5.51	1.10	16.07	22.68	40.00	17.32	QP
2	97.900	9.13	1.33	14.06	24.52	43.50	18.98	QP
3	116.330	10.98	1.50	13.51	25.99	43.50	17.51	QP
4	167.740	9.43	1.71	19.76	30.90	43.50	12.60	QP
5	216.240	8.80	1.95	19.15	29.90	46.00	16.10	QP
6	863.230	22.91	3.77	5.18	31.86	46.00	14.14	QP

1000 MHz – 18000MHz

Site no. : 1# 966 Chamber Data no. : 405
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	89.45	89.04	74.00	-15.04	Peak
2	4804.00	31.25	11.77	35.64	32.23	39.61	74.00	34.39	Peak
3	7206.00	36.52	11.54	33.95	29.28	43.39	74.00	30.61	Peak
4	8684.00	37.32	11.45	33.66	28.24	43.35	74.00	30.65	Peak
5	11285.00	39.33	11.08	33.32	26.95	44.04	74.00	29.96	Peak
6	13886.00	41.16	11.04	33.03	25.46	44.63	74.00	29.37	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official
 limit are not reported.

Site no. : 1# 966 Chamber Data no. : 406
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	91.28	90.87	74.00	-16.87	Peak
2	4804.00	31.25	11.77	35.64	31.26	38.64	74.00	35.36	Peak
3	7206.00	36.52	11.54	33.95	28.17	42.28	74.00	31.72	Peak
4	8565.00	37.10	11.45	33.92	28.24	42.87	74.00	31.13	Peak
5	11166.00	39.41	11.17	33.31	26.15	43.42	74.00	30.58	Peak
6	13393.00	39.83	11.49	32.88	25.55	43.99	74.00	30.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 407
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	91.15	90.57	74.00	-16.57	Peak
2	4882.00	31.37	12.07	35.76	31.57	39.25	74.00	34.75	Peak
3	7323.00	36.55	11.57	34.14	29.18	43.16	74.00	30.84	Peak
4	9075.00	37.53	11.49	34.20	28.20	43.02	74.00	30.98	Peak
5	11166.00	39.41	11.17	33.31	25.19	42.46	74.00	31.54	Peak
6	13274.00	39.54	11.47	32.92	25.51	43.60	74.00	30.40	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 408
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	89.55	88.97	74.00	-14.97	Peak
2	4882.00	31.37	12.07	35.76	30.84	38.52	74.00	35.48	Peak
3	7323.00	36.55	11.57	34.14	27.68	41.66	74.00	32.34	Peak
4	8514.00	36.96	11.45	34.07	28.67	43.01	74.00	30.99	Peak
5	10996.00	39.52	11.29	34.11	24.40	41.10	74.00	32.90	Peak
6	14260.00	41.68	10.92	33.42	24.96	44.14	74.00	29.86	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 409
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	90.13	89.31	74.00	-15.31	Peak
2	4960.00	31.49	12.44	36.01	32.64	40.56	74.00	33.44	Peak
3	7440.00	36.54	11.61	34.22	28.94	42.87	74.00	31.13	Peak
4	8684.00	37.32	11.45	33.66	28.25	43.36	74.00	30.64	Peak
5	11200.00	39.39	11.14	33.24	25.80	43.09	74.00	30.91	Peak
6	13546.00	40.21	11.44	32.61	25.29	44.33	74.00	29.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 410
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	92.51	91.69	74.00	-17.69	Peak
2	4960.00	31.49	12.44	36.01	31.31	39.23	74.00	34.77	Peak
3	7440.00	36.54	11.61	34.22	28.70	42.63	74.00	31.37	Peak
4	8684.00	37.32	11.45	33.66	27.94	43.05	74.00	30.95	Peak
5	11166.00	39.41	11.17	33.31	24.68	41.95	74.00	32.05	Peak
6	13665.00	40.55	11.30	32.75	24.17	43.27	74.00	30.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official
 limit are not reported.

Site no. : 1# 966 Chamber Data no. : 411
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	90.97	90.56	74.00	-16.56	Peak
2	4804.00	31.25	11.77	35.64	31.36	38.74	74.00	35.26	Peak
3	7206.00	36.52	11.54	33.95	27.55	41.66	74.00	32.34	Peak
4	8684.00	37.32	11.45	33.66	27.58	42.69	74.00	31.31	Peak
5	10656.00	39.15	11.30	34.31	27.16	43.30	74.00	30.70	Peak
6	14090.00	41.54	10.91	33.13	23.95	43.27	74.00	30.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 412
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	89.25	88.84	74.00	-14.84	Peak
2	4804.00	31.25	11.77	35.64	32.86	40.24	74.00	33.76	Peak
3	7206.00	36.52	11.54	33.95	29.86	43.97	74.00	30.03	Peak
4	8667.00	37.30	11.45	33.67	29.44	44.52	74.00	29.48	Peak
5	11064.00	39.48	11.24	33.83	26.96	43.85	74.00	30.15	Peak
6	13376.00	39.78	11.48	32.91	25.57	43.92	74.00	30.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 413
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	89.92	89.34	74.00	-15.34	Peak
2	4882.00	31.37	12.07	35.76	31.34	39.02	74.00	34.98	Peak
3	7323.00	36.55	11.57	34.14	27.35	41.33	74.00	32.67	Peak
4	8684.00	37.32	11.45	33.66	27.11	42.22	74.00	31.78	Peak
5	11285.00	39.33	11.08	33.32	23.74	40.83	74.00	33.17	Peak
6	14090.00	41.54	10.91	33.13	23.72	43.04	74.00	30.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 414
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	91.83	91.25	74.00	-17.25	Peak
2	4882.00	31.37	12.07	35.76	31.28	38.96	74.00	35.04	Peak
3	7323.00	36.55	11.57	34.14	27.56	41.54	74.00	32.46	Peak
4	9160.00	37.69	11.54	34.07	27.43	42.59	74.00	31.41	Peak
5	11166.00	39.41	11.17	33.31	25.57	42.84	74.00	31.16	Peak
6	13665.00	40.55	11.30	32.75	24.40	43.50	74.00	30.50	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : site Data no. : 415
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	92.37	91.55	74.00	-17.55	Peak
2	4960.00	31.49	12.44	36.01	31.24	39.16	74.00	34.84	Peak
3	7440.00	36.54	11.61	34.22	29.10	43.03	74.00	30.97	Peak
4	9126.00	37.62	11.52	34.09	28.11	43.16	74.00	30.84	Peak
5	11013.00	39.51	11.28	34.05	26.92	43.66	74.00	30.34	Peak
6	13920.00	41.26	11.00	33.00	25.72	44.98	74.00	29.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 416
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	90.69	89.87	74.00	-15.87	Peak
2	4960.00	31.49	12.44	36.01	31.44	39.36	74.00	34.64	Peak
3	7440.00	36.54	11.61	34.22	28.50	42.43	74.00	31.57	Peak
4	8718.00	37.38	11.45	33.71	28.05	43.17	74.00	30.83	Peak
5	11200.00	39.39	11.14	33.24	25.86	43.15	74.00	30.85	Peak
6	13665.00	40.55	11.30	32.75	24.59	43.69	74.00	30.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

18000MHz – 25000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

9. BAND EDGE COMPLIANCE

9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.2. Block Diagram of Test setup



9.3. Test Procedure

EUT was placed on a turn table, which is 1.5 m high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.


9.4. Test Result

Pass (The testing data was attached in the next pages.)

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


9.5. Test Data



Site no. : 1# 966 Chamber Data no. : 397
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2369.30	27.67	6.60	34.59	39.34	39.02	74.00	34.98	Peak
2	2390.00	27.64	6.62	34.62	36.44	36.08	74.00	37.92	Peak
3	2400.00	27.61	6.62	34.64	51.17	50.76	74.00	23.24	Peak
4	2402.08	27.61	6.62	34.64	89.00	88.59	74.00	-14.59	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 398
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2383.60	27.64	6.60	34.62	41.52	41.14	74.00	32.86	Peak
2	2390.00	27.64	6.62	34.62	40.21	39.85	74.00	34.15	Peak
3	2400.00	27.61	6.62	34.64	54.37	53.96	74.00	20.04	Peak
4	2401.75	27.61	6.62	34.64	91.43	91.02	74.00	-17.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 399
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	92.23	91.41	74.00	-17.41	Peak
2	2483.50	27.58	6.71	35.11	50.91	50.09	74.00	23.91	Peak
3	2483.78	27.58	6.71	35.11	52.25	51.43	74.00	22.57	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 400
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.05	27.58	6.71	35.11	90.32	89.50	74.00	-15.50	Peak
2	2483.50	27.58	6.71	35.11	46.24	45.42	74.00	28.58	Peak
3	2483.80	27.58	6.71	35.11	45.86	45.04	74.00	28.96	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 401
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6°;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.65	27.64	6.62	34.62	38.59	38.23	74.00	35.77	Peak
2	2390.00	27.64	6.62	34.62	37.51	37.15	74.00	36.85	Peak
3	2400.00	27.61	6.62	34.64	40.64	40.23	54.00	13.77	Average
4	2400.00	27.61	6.62	34.64	57.58	57.17	74.00	16.83	Peak
5	2401.75	27.61	6.62	34.64	89.40	88.99	74.00	-14.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 1# 966 Chamber Data no. : 402
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2388.88	27.64	6.62	34.62	41.46	41.10	74.00	32.90	Peak
2	2390.00	27.64	6.62	34.62	39.21	38.85	74.00	35.15	Peak
3	2400.00	27.61	6.62	34.64	45.30	44.89	54.00	9.11	Average
4	2400.00	27.61	6.62	34.64	61.00	60.59	74.00	13.41	Peak
5	2401.75	27.61	6.62	34.64	91.44	91.03	74.00	-17.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.


2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 403
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.80	27.58	6.71	35.11	92.37	91.55	74.00	-17.55	Peak
2	2483.50	27.58	6.71	35.11	38.93	38.11	54.00	15.89	Average
3	2483.50	27.58	6.71	35.11	55.08	54.26	74.00	19.74	Peak
4	2484.13	27.58	6.71	35.11	54.04	53.22	74.00	20.78	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 404
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.80	27.58	6.71	35.11	90.23	89.41	74.00	-15.41	Peak
2	2483.50	27.58	6.71	35.11	51.36	50.54	74.00	23.46	Peak
3	2483.80	27.58	6.71	35.11	50.35	49.53	74.00	24.47	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 389
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2377.00	27.64	6.60	34.59	40.67	40.32	74.00	33.68	Peak
2	2390.00	27.64	6.62	34.62	38.28	37.92	74.00	36.08	Peak
3	2400.00	27.61	6.62	34.64	49.96	49.55	74.00	24.45	Peak
4	2408.02	27.61	6.64	34.64	88.50	88.11	74.00	-14.11	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 390
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2386.90	27.64	6.62	34.62	41.85	41.49	74.00	32.51	Peak
2	2390.00	27.64	6.62	34.62	40.88	40.52	74.00	33.48	Peak
3	2400.00	27.61	6.62	34.64	53.52	53.11	74.00	20.89	Peak
4	2406.92	27.61	6.64	34.64	91.13	90.74	74.00	-16.74	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 391
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.05	27.58	6.71	35.11	92.49	91.67	74.00	-17.67	Peak
2	2483.50	27.58	6.71	35.11	52.44	51.62	74.00	22.38	Peak
3	2483.70	27.58	6.71	35.11	52.13	51.31	74.00	22.69	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 392
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : GFSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	2479.00	27.58	6.71	35.11	89.61	88.79	74.00	-14.79	Peak
2	2483.50	27.58	6.71	35.11	44.14	43.32	74.00	30.68	Peak
3	2483.75	27.58	6.71	35.11	44.87	44.05	74.00	29.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 393
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2342.90	27.70	6.56	34.59	38.68	38.35	74.00	35.65	Peak
2	2390.00	27.64	6.62	34.62	35.08	34.72	74.00	39.28	Peak
3	2400.00	27.61	6.62	34.64	39.59	39.18	54.00	14.82	Average
4	2400.00	27.61	6.62	34.64	56.40	55.99	74.00	18.01	Peak
5	2409.78	27.60	6.64	34.64	88.84	88.44	74.00	-14.44	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 394
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2359.18	27.67	6.58	34.57	43.66	43.34	74.00	30.66	Peak
2	2390.00	27.64	6.62	34.62	41.93	41.57	74.00	32.43	Peak
3	2400.00	27.61	6.62	34.64	43.97	43.56	54.00	10.44	Average
4	2400.00	27.61	6.62	34.64	60.24	59.83	74.00	14.17	Peak
5	2409.78	27.60	6.64	34.64	90.75	90.35	74.00	-16.35	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 395
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2478.80	27.58	6.71	35.11	92.19	91.37	74.00	-17.37	Peak
2	2483.50	27.58	6.71	35.11	54.20	53.38	74.00	20.62	Peak
3	2483.88	27.58	6.71	35.11	54.24	53.42	74.00	20.58	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 396
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2477.80	27.58	6.71	35.11	89.80	88.98	74.00	-14.98	Peak
2	2483.50	27.58	6.71	35.11	51.57	50.75	74.00	23.25	Peak
3	2483.70	27.58	6.71	35.11	51.06	50.24	74.00	23.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

10. POWER LINE CONDUCTED EMISSIONS

10.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.2. Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane. The EUT was charged from Adapter which connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#).. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

10.3. Test Result


PASS. (All emissions not reported below are too low against the prescribed limits.)

10.4. Test data




Site no : 844 Shield Room Data no. : 61
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.40	9.59	9.82	12.02	31.43	47.95	16.52	Average
2	0.40	9.59	9.82	26.42	45.83	57.95	12.12	QP
3	0.45	9.59	9.81	11.48	30.88	46.93	16.05	Average
4	0.45	9.59	9.81	25.89	45.29	56.93	11.64	QP
5	0.47	9.59	9.81	17.98	37.38	46.49	9.11	Average
6	0.47	9.59	9.81	31.01	50.41	56.49	6.08	QP
7	0.66	9.62	9.81	10.10	29.53	46.00	16.47	Average
8	0.66	9.62	9.81	21.97	41.40	56.00	14.60	QP
9	0.78	9.62	9.81	10.46	29.89	46.00	16.11	Average
10	0.78	9.62	9.81	23.04	42.47	56.00	13.53	QP
11	12.92	9.73	9.90	11.39	31.02	50.00	18.98	Average
12	12.92	9.73	9.90	23.10	42.73	60.00	17.27	QP




Site no : 844 Shield Room Data no. : 63
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : TY-ASC20
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.39	9.61	9.82	16.69	36.12	48.03	11.91	Average
2	0.39	9.61	9.82	24.55	43.98	58.03	14.05	QP
3	0.45	9.61	9.81	13.86	33.28	46.93	13.65	Average
4	0.45	9.61	9.81	24.43	43.85	56.93	13.08	QP
5	0.48	9.61	9.81	18.85	38.27	46.41	8.14	Average
6	0.48	9.61	9.81	28.58	48.00	56.41	8.41	QP
7	0.78	9.60	9.81	11.91	31.32	46.00	14.68	Average
8	0.78	9.60	9.81	21.75	41.16	56.00	14.84	QP
9	0.99	9.64	9.83	7.66	27.13	46.00	18.87	Average
10	0.99	9.64	9.83	19.70	39.17	56.00	16.83	QP
11	12.72	9.67	9.92	9.22	28.81	50.00	21.19	Average
12	12.72	9.67	9.92	23.53	43.12	60.00	16.88	QP



Site no : 844 Shield Room Data no. : 65
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : TY-ASC20
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.37	9.61	9.82	13.56	32.99	48.61	15.62	Average
2	0.37	9.61	9.82	22.80	42.23	58.61	16.38	QP
3	0.46	9.61	9.81	17.05	36.47	46.71	10.24	Average
4	0.46	9.61	9.81	29.45	48.87	56.71	7.84	QP
5	0.73	9.60	9.81	12.68	32.09	46.00	13.91	Average
6	0.73	9.60	9.81	23.16	42.57	56.00	13.43	QP
7	0.84	9.62	9.82	13.54	32.98	46.00	13.02	Average
8	0.84	9.62	9.82	23.13	42.57	56.00	13.43	QP
9	1.30	9.63	9.82	12.93	32.38	46.00	13.62	Average
10	1.30	9.63	9.82	20.67	40.12	56.00	15.88	QP
11	1.74	9.62	9.82	11.57	31.01	46.00	14.99	Average
12	1.74	9.62	9.82	20.29	39.73	56.00	16.27	QP



Site no : 844 Shield Room Data no. : 67
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : WIRELESS SOUND SYSTEM
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : TY-ASC20
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.37	9.59	9.82	11.85	31.26	48.52	17.26	Average
2	0.37	9.59	9.82	25.11	44.52	58.52	14.00	QP
3	0.46	9.59	9.81	17.05	36.45	46.71	10.26	Average
4	0.46	9.59	9.81	30.73	50.13	56.71	6.58	QP
5	0.48	9.59	9.81	16.00	35.40	46.41	11.01	Average
6	0.48	9.59	9.81	28.91	48.31	56.41	8.10	QP
7	0.61	9.61	9.82	10.57	30.00	46.00	16.00	Average
8	0.61	9.61	9.82	24.09	43.52	56.00	12.48	QP
9	0.75	9.63	9.81	10.67	30.11	46.00	15.89	Average
10	0.75	9.63	9.81	25.85	45.29	56.00	10.71	QP
11	1.28	9.61	9.83	8.49	27.93	46.00	18.07	Average
12	1.28	9.61	9.83	23.01	42.45	56.00	13.55	QP

11. ANTENNA REQUIREMENTS

11.1. Limit



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are internal Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

12. TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)





Radiated Test (Above 1GHz)



13. PHOTOS OF EUT

External Photos


M/N: TY-ASC20



External Photos
M/N: TY-ASC20



External Photos
M/N: TY-ASC20



External Photos
M/N: TY-ASC20




External Photos


M/N: TY-ASC20




Internal Photos
M/N: TY-ASC20





Internal Photos
M/N: TY-ASC20



Internal Photos
M/N: TY-ASC20




Internal Photos
M/N: TY-ASC20





Bluetooth
Antenna

This antenna
don't work
for this device



Internal Photos
M/N: TY-ASC20




Internal Photos
M/N: TY-ASC20



Internal Photos
M/N: TY-ASC20



Internal Photos
M/N: TY-ASC20



Compared to the original PCB board, These two ports are on the back.

