

FCC Test Report

(PART 27)

Report No.: RF171115C32-2

FCC ID: YY3-1127824

Test Model: Algiz 8X

Received Date: Nov. 15, 2017

Test Date: Dec. 02, 2017 ~ Jan. 20, 2018

Issued Date: Jan. 22, 2018

Applicant: Handheld Group AB

Address: Kinnegatan 17 A 531 33 Lidköping Sweden

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C

**FCC Registration /
Designation Number:** 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	6
2.2 Test Site and Instruments	6
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units.....	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	13
3.5 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Output Power Measurement.....	14
4.1.1 Limits of Output Power Measurement	14
4.1.2 Test Procedures.....	14
4.1.3 Test Setup.....	15
4.1.4 Test Results	16
4.2 Frequency Stability Measurement	22
4.2.1 Limits of Frequency Stability Measurement.....	22
4.2.2 Test Procedure	22
4.2.3 Test Setup.....	22
4.2.4 Test Results	23
4.3 Occupied Bandwidth Measurement.....	31
4.3.1 Limits of Occupied Bandwidth Measurement	31
4.3.2 Test Procedure	31
4.3.3 Test Setup.....	31
4.3.4 Test Result	32
4.4 Band Edge Measurement	36
4.4.1 Limits of Band Edge Measurement	36
4.4.2 Test Setup.....	36
4.4.3 Test Procedures.....	36
4.4.4 Test Results	37
4.5 Peak to Average Ratio	47
4.5.1 Limits of Peak to Average Ratio Measurement	47
4.5.2 Test Setup.....	47
4.5.3 Test Procedures.....	47
4.5.4 Test Results	48
4.6 Conducted Spurious Emissions	52
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	52
4.6.2 Test Setup.....	52
4.6.3 Test Procedure	52
4.6.4 Test Results	53
4.7 Radiated Emission Measurement.....	73
4.7.1 Limits of Radiated Emission Measurement	73
4.7.2 Test Procedure	73
4.7.3 Deviation from Test Standard	73
4.7.4 Test Setup.....	74
4.7.5 Test Results	75
5 Pictures of Test Arrangements.....	85
Appendix – Information on the Testing Laboratories	86

Release Control Record

Issue No.	Description	Date Issued
RF171115C32-2	Original Release	Jan. 22, 2018

1 Certificate of Conformity

Product: Rugged Tablet PC

Brand: Handheld

Test Model: Algiz 8X

Sample Status: Identical Prototype


Applicant: Handheld Group AB

Test Date: Dec. 02, 2017 ~ Jan. 20, 2018

Standards: FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , Date: Jan. 22, 2018
Vera Huang / Specialist

Approved by :   , Date: Jan. 22, 2018
Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -18.44 dB at 3465.00 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 13)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(b)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(g)(f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -7.91 dB at 1564.00 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
			Jan. 11, 2018	Jan. 10, 2019
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 13, 2016	Dec. 12, 2017
			Dec. 06, 2017	Dec. 05, 2018
HORN Antenna ETS-Lindgren	3117	00143293	Jun. 26, 2017	Jun. 25, 2018
Double Ridge Guide Horn Antenna EMCO	3115	5619	Dec. 15, 2016	Dec. 14, 2017
			Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 13, 2016	Dec. 12, 2017
			Dec. 06, 2017	Dec. 05, 2018
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
			Dec. 01, 2017	Nov. 30, 2018
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 07, 2017	Jul. 06, 2018
Bluetooth Tester	CBT	100980	Jun. 28, 2017	Jun. 27, 2019
Loop Antenna	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Preamplifier Agilent	310N	187226	Jun. 23, 2017	Jun. 22, 2018
Preamplifier Agilent	83017A	MY39501357	Jun. 23, 2017	Jun. 22, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 26, 2017	Jun. 25, 2018
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 26, 2017	Jun. 25, 2018
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2017	Jul. 07, 2018

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Rugged Tablet PC	
Brand	Handheld	
Test Model	Algiz 8X	
Status of EUT	Identical Prototype	
Power Supply Rating	19 Vdc (adapter) 7.6 Vdc (Li-ion battery)	
Modulation Type	LTE	QPSK, 16QAM
Frequency Range	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1754.3 MHz
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1753.5 MHz
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1752.5 MHz
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1750.0 MHz
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1747.5 MHz
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1745.0 MHz
	LTE Band 13 (Channel Bandwidth: 5 MHz)	779.5 ~ 784.5 MHz
	LTE Band 13 (Channel Bandwidth: 10 MHz)	782.0 MHz
Emission Designator	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1M09W7D
	LTE Band 4 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE Band 4 (Channel Bandwidth: 5 MHz)	4M49W7D
	LTE Band 4 (Channel Bandwidth: 10 MHz)	8M97G7D
	LTE Band 4 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 4 (Channel Bandwidth: 20 MHz)	18M0W7D
	LTE Band 13 (Channel Bandwidth: 5 MHz)	4M50W7D
	LTE Band 13 (Channel Bandwidth: 10 MHz)	8M95W7D
Max. ERP Power	LTE Band 13 (Channel Bandwidth: 5 MHz)	181.30 mW
	LTE Band 13 (Channel Bandwidth: 10 MHz)	185.23 mW
Max. EIRP Power	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	357.03 mW
	LTE Band 4 (Channel Bandwidth: 3 MHz)	361.83 mW
	LTE Band 4 (Channel Bandwidth: 5 MHz)	359.50 mW
	LTE Band 4 (Channel Bandwidth: 10 MHz)	362.66 mW
	LTE Band 4 (Channel Bandwidth: 15 MHz)	361.99 mW
	LTE Band 4 (Channel Bandwidth: 20 MHz)	368.55 mW
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	EDAC	EA10633B-190	I/P: 100-240 Vac, 50-60 Hz, 2 A O/P: 19 Vdc, 3.42 A
Battery 1	Handheld Group AB	ALG8X-08A	7.6 Vdc, 5200 mAh
Battery 2	Handheld Group AB	BH340	7.4 Vdc, 400 mAh


2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP / EIRP	Radiated Emission
LTE Band 4	Y-plane	Y-axis
LTE Band 13	Y-plane	X-axis

LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	19957 to 20393	19957, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20385	3 MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20375	5 MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20350	10 MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20300	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	19957 to 20393	19957	1.4 MHz	QPSK	1 RB / 0 RB Offset
			20393	1.4 MHz	QPSK	6 RB / 0 RB Offset
		19965 to 20385	19965	3 MHz	QPSK	1 RB / 5 RB Offset
			20385	3 MHz	QPSK	6 RB / 0 RB Offset
		19975 to 20375	19975	5 MHz	QPSK	1 RB / 0 RB Offset
			20375	5 MHz	QPSK	15 RB / 0 RB Offset
		20000 to 20350	20000	10 MHz	QPSK	1 RB / 14 RB Offset
			20350	10 MHz	QPSK	15 RB / 0 RB Offset
		20025 to 20325	20025	15 MHz	QPSK	1 RB / 0 RB Offset
			20325	15 MHz	QPSK	25 RB / 0 RB Offset
		20050 to 20300	20050	20 MHz	QPSK	1 RB / 24 RB Offset
			20300	20 MHz	QPSK	25 RB / 0 RB Offset
		19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
			19965, 20175, 20385	3 MHz	QPSK	50 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK	1 RB / 49 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	75 RB / 0 RB Offset
-	Radiated Emission	20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 74 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 13

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	23205 to 23255	23205, 23255	5 MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	23205 to 23255	23205	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
		23230	23255	5 MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
			23230	10 MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
-	Conducted Emission	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset
						1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25 deg. C, 65 % RH	7.6 Vdc	Karl Lee
Frequency Stability	25 deg. C, 65 % RH	7.6 Vdc	Carlos Chen
Occupied Bandwidth	25 deg. C, 65 % RH	7.6 Vdc	Carlos Chen
Band Edge	25 deg. C, 65 % RH	7.6 Vdc	Carlos Chen
Peak to Average Ratio	25 deg. C, 65 % RH	7.6 Vdc	Carlos Chen
Conducted Emission	25 deg. C, 65 % RH	7.6 Vdc	Carlos Chen
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee / Harry Hsueh

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 776-787 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.


Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

LTE Band 4										
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 20050	Mid CH 20175	High CH 20300	3GPP MPR (dB)	Low CH 20050	Mid CH 20175	High CH 20300	3GPP MPR (dB)
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
20	1	0	23.22	23.17	23.15	0	22.17	22.12	22.10	1
	1	50	23.18	23.13	23.11	0	22.13	22.08	22.06	1
	1	99	23.01	22.96	22.94	0	21.96	21.91	21.89	1
	50	0	22.37	22.32	22.30	1	21.32	21.27	21.25	2
	50	25	22.26	22.21	22.19	1	21.21	21.16	21.14	2
	50	50	22.12	22.07	22.05	1	21.07	21.02	21.00	2
	100	0	22.10	22.05	22.03	1	21.05	21.00	20.98	2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 20025	Mid CH 20175	High CH 20325	3GPP MPR (dB)	Low CH 20025	Mid CH 20175	High CH 20325	3GPP MPR (dB)
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
15	1	0	23.09	23.04	23.02	0	22.04	21.99	21.97	1
	1	37	23.05	23.00	22.98	0	22.00	21.95	21.93	1
	1	74	22.88	22.83	22.81	0	21.83	21.78	21.76	1
	36	0	22.24	22.19	22.17	1	21.19	21.14	21.12	2
	36	19	22.13	22.08	22.06	1	21.08	21.03	21.01	2
	36	39	21.99	21.94	21.92	1	20.94	20.89	20.87	2
	75	0	21.97	21.92	21.90	1	20.92	20.87	20.85	2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 20000	Mid CH 20175	High CH 20350	3GPP MPR (dB)	Low CH 20000	Mid CH 20175	High CH 20350	3GPP MPR (dB)
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
10	1	0	22.98	22.93	22.91	0	21.93	21.88	21.86	1
	1	24	22.94	22.89	22.87	0	21.89	21.84	21.82	1
	1	49	22.77	22.72	22.70	0	21.72	21.67	21.65	1
	25	0	22.13	22.08	22.06	1	21.08	21.03	21.01	2
	25	12	22.02	21.97	21.95	1	20.97	20.92	20.90	2
	25	25	21.88	21.83	21.81	1	20.83	20.78	20.76	2
	50	0	21.86	21.81	21.79	1	20.81	20.76	20.74	2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 19975	Mid CH 20175	High CH 20375	3GPP MPR (dB)	Low CH 19975	Mid CH 20175	High CH 20375	3GPP MPR (dB)
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
5	1	0	22.89	22.84	22.82	0	21.84	21.79	21.77	1
	1	12	22.85	22.80	22.78	0	21.80	21.75	21.73	1
	1	24	22.68	22.63	22.61	0	21.63	21.58	21.56	1
	12	0	22.04	21.99	21.97	1	20.99	20.94	20.92	2
	12	6	21.93	21.88	21.86	1	20.88	20.83	20.81	2
	12	13	21.79	21.74	21.72	1	20.74	20.69	20.67	2
	25	0	21.77	21.72	21.70	1	20.72	20.67	20.65	2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 19965	Mid CH 20175	High CH 20385	3GPP MPR (dB)	Low CH 19965	Mid CH 20175	High CH 20385	3GPP MPR (dB)
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
3	1	0	22.77	22.72	22.70	0	21.72	21.67	21.65	1
	1	7	22.73	22.68	22.66	0	21.68	21.63	21.61	1
	1	14	22.56	22.51	22.49	0	21.51	21.46	21.44	1
	8	0	21.92	21.87	21.85	1	20.87	20.82	20.80	2
	8	3	21.81	21.76	21.74	1	20.76	20.71	20.69	2
	8	7	21.67	21.62	21.60	1	20.62	20.57	20.55	2
	15	0	21.65	21.60	21.58	1	20.60	20.55	20.53	2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 19957	Mid CH 20175	High CH 20393	3GPP MPR (dB)	Low CH 19957	Mid CH 20175	High CH 20393	3GPP MPR (dB)
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
1.4	1	0	22.69	22.64	22.62	0	21.64	21.59	21.57	1
	1	2	22.65	22.60	22.58	0	21.60	21.55	21.53	1
	1	5	22.48	22.43	22.41	0	21.43	21.38	21.36	1
	3	0	22.57	22.52	22.50	0	21.51	21.46	21.44	1
	3	1	22.46	22.41	22.39	0	21.40	21.35	21.33	1
	3	3	22.32	22.27	22.25	0	21.26	21.21	21.19	1
	6	0	21.57	21.52	21.50	1	20.52	20.47	20.45	2

LTE Band 13										
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
				Mid CH 23230		3GPP MPR (dB)		Mid CH 23230		3GPP MPR (dB)
				782.0 MHz				782.0 MHz		
10	1	0		21.88		0		20.98		1
	1	24		21.44		0		20.91		1
	1	49		21.47		0		20.53		1
	25	0		20.50		1		19.61		2
	25	12		20.49		1		19.54		2
	25	25		20.47		1		19.59		2
	50	0		20.4		1		19.61		2
BW (MHz)	RB Size	RB Offset	QPSK				16QAM			
			Low CH 23205	Mid CH 23230	High CH 23255	3GPP MPR (dB)	Low CH 23205	Mid CH 23230	High CH 23255	3GPP MPR (dB)
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
5	1	0	21.43	21.76	21.53	0	20.64	20.93	20.60	1
	1	12	21.36	21.56	21.61	0	20.47	20.86	20.95	1
	1	24	21.38	21.47	21.46	0	20.74	20.60	20.79	1
	12	0	20.51	20.53	20.46	1	19.32	19.53	19.51	2
	12	6	20.46	20.64	20.50	1	19.46	19.53	19.46	2
	12	13	20.39	20.42	20.51	1	19.53	19.51	19.52	2
	25	0	20.55	20.40	20.47	1	19.68	19.42	19.49	2

ERP Power (dBm)

LTE Band 13							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23205	779.5	-8.09	32.771	22.53	179.10	H
	23230	782.0	-8.12	32.741	22.47	176.64	
	23255	784.5	-8.12	32.854	22.58	181.30	
	23205	779.5	-13.80	32.5	16.55	45.19	V
	23230	782.0	-13.87	32.52	16.50	44.67	
	23255	784.5	-13.86	32.62	16.61	45.81	
Channel Bandwidth: 5 MHz / 16QAM							
Y	23205	779.5	-9.14	32.771	21.48	140.64	H
	23230	782.0	-9.11	32.741	21.48	140.64	
	23255	784.5	-9.15	32.854	21.55	143.02	
	23205	779.5	-14.92	32.5	15.43	34.91	V
	23230	782.0	-14.82	32.52	15.55	35.89	
	23255	784.5	-14.90	32.62	15.57	36.06	

LTE Band 13							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23230	782.0	-7.91	32.737	22.68	185.23	H
	23230	782.0	-13.72	32.52	16.65	46.24	V
Channel Bandwidth: 10 MHz / 16QAM							
Y	23230	782.0	-8.95	32.737	21.64	145.78	H
	23230	782.0	-14.71	32.52	15.66	36.81	V

EIRP Power (dBm)

LTE Band 4							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	19957	1710.7	-16.97	42.49	25.52	356.04	H
	20175	1732.5	-16.80	42.33	25.53	357.03	
	20393	1754.3	-16.59	42.10	25.51	355.63	
	19957	1710.7	-21.42	42.99	21.57	143.55	V
	20175	1732.5	-21.25	42.74	21.49	140.93	
	20393	1754.3	-21.73	42.21	20.48	111.69	
Channel Bandwidth: 1.4 MHz / 16QAM							
Y	19957	1710.7	-18.06	42.49	24.43	277.01	H
	20175	1732.5	-17.75	42.33	24.58	286.88	
	20393	1754.3	-17.59	42.10	24.51	282.49	
	19957	1710.7	-22.54	42.99	20.45	110.92	V
	20175	1732.5	-22.26	42.74	20.48	111.69	
	20393	1754.3	-21.72	42.21	20.49	111.94	

LTE Band 4							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	19965	1711.5	-16.90	42.49	25.59	361.83	H
	20175	1732.5	-16.84	42.33	25.49	353.75	
	20385	1753.5	-16.55	42.10	25.55	358.92	
	19965	1711.5	-21.43	42.99	21.56	143.22	V
	20175	1732.5	-21.25	42.74	21.49	140.93	
	20385	1753.5	-20.69	42.21	21.52	141.91	
Channel Bandwidth: 3 MHz / 16QAM							
Y	19965	1711.5	-17.99	42.49	24.50	281.51	H
	20175	1732.5	-17.82	42.33	24.51	282.29	
	20385	1753.5	-17.52	42.10	24.58	287.08	
	19965	1711.5	-22.47	42.99	20.52	112.72	V
	20175	1732.5	-22.34	42.74	20.40	109.65	
	20385	1753.5	-21.78	42.21	20.43	110.41	

LTE Band 4							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	19975	1712.5	-16.95	42.49	25.54	357.68	H
	20175	1732.5	-16.77	42.33	25.56	359.50	
	20375	1752.5	-16.58	42.10	25.52	356.45	
	19975	1712.5	-21.46	42.99	21.53	142.23	V
	20175	1732.5	-21.26	42.74	21.48	140.60	
	20375	1752.5	-20.67	42.21	21.54	142.56	
Channel Bandwidth: 5 MHz / 16QAM							
Y	19975	1712.5	-18.04	42.49	24.45	278.29	H
	20175	1732.5	-17.74	42.33	24.59	287.54	
	20375	1752.5	-17.56	42.10	24.54	284.45	
	19975	1712.5	-22.43	42.99	20.56	113.76	V
	20175	1732.5	-22.24	42.74	20.50	112.20	
	20375	1752.5	-21.68	42.21	20.53	112.98	

LTE Band 4							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	20000	1715.0	-16.89	42.49	25.60	362.66	H
	20175	1732.5	-16.74	42.33	25.59	361.99	
	20350	1750.0	-16.51	42.10	25.59	362.24	
	20000	1715.0	-21.43	42.99	21.56	143.22	V
	20175	1732.5	-21.21	42.74	21.53	142.23	
	20350	1750.0	-20.68	42.21	21.53	142.23	
Channel Bandwidth: 10 MHz / 16QAM							
Y	20000	1715.0	-17.98	42.49	24.51	282.16	H
	20175	1732.5	-17.80	42.33	24.53	283.60	
	20350	1750.0	-17.54	42.10	24.56	285.76	
	20000	1715.0	-22.44	42.99	20.55	113.50	V
	20175	1732.5	-22.21	42.74	20.53	112.98	
	20350	1750.0	-21.68	42.21	20.53	112.98	

LTE Band 4							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	20025	1717.5	-16.92	42.49	25.57	360.16	H
	20175	1732.5	-16.74	42.33	25.59	361.99	
	20325	1747.5	-16.54	42.10	25.56	359.75	
	20025	1717.5	-21.43	42.99	21.56	143.22	V
	20175	1732.5	-21.25	42.74	21.49	140.93	
	20325	1747.5	-20.57	42.21	21.64	145.88	
Channel Bandwidth: 15 MHz / 16QAM							
Y	20025	1717.5	-17.90	42.49	24.59	287.41	H
	20175	1732.5	-17.82	42.33	24.51	282.29	
	20325	1747.5	-17.59	42.10	24.51	282.49	
	20025	1717.5	-22.46	42.99	20.53	112.98	V
	20175	1732.5	-22.17	42.74	20.57	114.02	
	20325	1747.5	-21.68	42.21	20.53	112.98	

LTE Band 4							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Y	20050	1720.0	-16.82	42.49	25.67	368.55	H
	20175	1732.5	-16.74	42.33	25.59	361.99	
	20300	1745.0	-16.49	42.10	25.61	363.92	
	20050	1720.0	-21.42	42.99	21.57	143.55	V
	20175	1732.5	-21.28	42.74	21.46	139.96	
	20300	1745.0	-20.53	42.21	21.68	147.23	
Channel Bandwidth: 20 MHz / 16QAM							
Y	20050	1720.0	-17.86	42.49	24.63	290.07	H
	20175	1732.5	-17.72	42.33	24.61	288.87	
	20300	1745.0	-17.53	42.10	24.57	286.42	
	20050	1720.0	-22.47	42.99	20.52	112.72	V
	20175	1732.5	-22.12	42.74	20.62	115.35	
	20300	1745.0	-21.60	42.21	20.61	115.08	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1710.700002	0.001	1754.300001	0.001	2.5
6.8	1710.700001	0.001	1754.300003	0.001	2.5
8.7	1710.700003	0.002	1754.300001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1710.700003	0.002	1754.300004	0.002	2.5
-20	1710.700001	0.001	1754.300002	0.001	2.5
-10	1710.700003	0.002	1754.300002	0.001	2.5
0	1710.700002	0.001	1754.300002	0.001	2.5
10	1710.699999	-0.001	1754.299998	-0.001	2.5
20	1710.699999	-0.001	1754.299999	-0.001	2.5
30	1710.699996	-0.002	1754.299997	-0.002	2.5
40	1710.699997	-0.002	1754.299998	-0.001	2.5
50	1710.699996	-0.002	1754.299998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1711.500001	0.001	1753.500003	0.002	2.5
6.8	1711.500002	0.001	1753.500004	0.002	2.5
8.7	1711.500001	0.001	1753.500001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1711.500004	0.002	1753.500003	0.002	2.5
-20	1711.500003	0.002	1753.500003	0.002	2.5
-10	1711.500003	0.002	1753.500001	0.001	2.5
0	1711.500002	0.001	1753.500002	0.001	2.5
10	1711.499997	-0.002	1753.499997	-0.002	2.5
20	1711.499996	-0.002	1753.499996	-0.002	2.5
30	1711.499998	-0.001	1753.499998	-0.001	2.5
40	1711.499997	-0.002	1753.499997	-0.002	2.5
50	1711.499997	-0.002	1753.499999	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1712.500001	0.001	1752.500003	0.002	2.5
6.8	1712.500003	0.002	1752.500003	0.001	2.5
8.7	1712.500003	0.002	1752.500002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1712.500001	0.001	1752.500003	0.002	2.5
-20	1712.500004	0.002	1752.500002	0.001	2.5
-10	1712.500001	0.001	1752.500003	0.002	2.5
0	1712.500003	0.002	1752.500004	0.002	2.5
10	1712.499998	-0.001	1752.499997	-0.002	2.5
20	1712.499997	-0.002	1752.499998	-0.001	2.5
30	1712.499997	-0.002	1752.499996	-0.002	2.5
40	1712.499996	-0.002	1752.499996	-0.002	2.5
50	1712.499997	-0.002	1752.499999	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1715.000004	0.002	1750.000001	0.001	2.5
6.8	1715.000001	0.001	1750.000003	0.002	2.5
8.7	1715.000001	0.001	1750.000003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1715.000003	0.002	1750.000002	0.001	2.5
-20	1715.000003	0.002	1750.000001	0.001	2.5
-10	1715.000003	0.002	1750.000004	0.002	2.5
0	1715.000003	0.002	1750.000001	0.001	2.5
10	1714.999997	-0.002	1749.999999	-0.001	2.5
20	1714.999998	-0.001	1749.999999	-0.001	2.5
30	1714.999998	-0.001	1749.999997	-0.002	2.5
40	1714.999997	-0.002	1749.999997	-0.002	2.5
50	1714.999999	-0.001	1749.999999	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1717.500002	0.001	1747.500004	0.002	2.5
6.8	1717.500002	0.001	1747.500004	0.002	2.5
8.7	1717.500004	0.002	1747.500001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1717.500004	0.002	1747.500001	0.001	2.5
-20	1717.500003	0.002	1747.500001	0.001	2.5
-10	1717.500003	0.002	1747.500001	0.001	2.5
0	1717.500001	0.001	1747.500002	0.001	2.5
10	1717.499998	-0.001	1747.499996	-0.002	2.5
20	1717.499996	-0.002	1747.499996	-0.002	2.5
30	1717.499996	-0.002	1747.499999	-0.001	2.5
40	1717.499998	-0.001	1747.499998	-0.001	2.5
50	1717.499997	-0.002	1747.499996	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	1720.000003	0.002	1745.000001	0.001	2.5
6.8	1720.000004	0.002	1745.000002	0.001	2.5
8.7	1720.000002	0.001	1745.000002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1720.000003	0.002	1745.000002	0.001	2.5
-20	1720.000004	0.002	1745.000004	0.002	2.5
-10	1720.000003	0.002	1745.000003	0.002	2.5
0	1720.000004	0.002	1745.000004	0.002	2.5
10	1719.999997	-0.002	1744.999997	-0.002	2.5
20	1719.999997	-0.002	1744.999996	-0.002	2.5
30	1719.999998	-0.001	1744.999997	-0.002	2.5
40	1719.999997	-0.002	1744.999997	-0.002	2.5
50	1719.999996	-0.002	1744.999998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 13				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.6	779.500002	0.003	784.500003	0.003	2.5
6.8	779.500004	0.005	784.500004	0.005	2.5
8.7	779.500003	0.004	784.500004	0.005	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 13				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	779.500002	0.003	784.500002	0.002	2.5
-20	779.500002	0.002	784.500002	0.002	2.5
-10	779.500003	0.003	784.500002	0.002	2.5
0	779.500003	0.004	784.500004	0.005	2.5
10	779.499997	-0.003	784.499998	-0.003	2.5
20	779.499999	-0.001	784.499996	-0.005	2.5
30	779.499997	-0.004	784.499998	-0.002	2.5
40	779.499996	-0.005	784.499998	-0.002	2.5
50	779.499997	-0.004	784.499996	-0.005	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 13		Limit (ppm)
	Channel Bandwidth: 10 MHz		
	Frequency (MHz)	Frequency Error (ppm)	
7.6	782.000003	0.004	2.5
6.8	782.000003	0.004	2.5
8.7	782.000003	0.004	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.8 Vdc to 8.7 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 13		Limit (ppm)
	Channel Bandwidth: 10 MHz		
	Frequency (MHz)	Frequency Error (ppm)	
-30	782.000004	0.005	2.5
-20	782.000003	0.004	2.5
-10	782.000003	0.003	2.5
0	782.000003	0.004	2.5
10	781.999997	-0.004	2.5
20	781.999997	-0.003	2.5
30	781.999998	-0.002	2.5
40	781.999998	-0.002	2.5
50	781.999996	-0.005	2.5

4.3 Occupied Bandwidth Measurement


4.3.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result


LTE Band 4							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.0880	1.0895	19965	1711.5	2.7019	2.6972
20175	1732.5	1.0874	1.0894	20175	1732.5	2.7019	2.6963
20393	1754.3	1.0881	1.0883	20385	1753.5	2.7018	2.6982



LTE Band 4

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.4885	4.4891	20000	1715.0	8.9735	8.9726
20175	1732.5	4.4892	4.4921	20175	1732.5	8.9638	8.9695
20375	1752.5	4.4835	4.4865	20350	1750.0	8.9615	8.9651


Spectrum Plot of Worst Value



LTE Band 4

Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.472	13.465	20050	1720.0	17.958	17.995
20175	1732.5	13.460	13.453	20175	1732.5	17.937	17.972
20325	1747.5	13.478	13.461	20300	1745.0	17.960	18.018


Spectrum Plot of Worst Value



LTE Band 13

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	4.4804	4.4816	23230	782.0	8.9436	8.9517
23230	782.0	4.4889	4.4903				
23255	784.5	4.4929	4.4962				

Spectrum Plot of Worst Value



4.4 Band Edge Measurement


4.4.1 Limits of Band Edge Measurement

For operations in the 776-787 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.


4.4.2 Test Setup





4.4.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 180 kHz and VB of the spectrum is 560 kHz (LTE Bandwidth 20 MHz).
- Record the max. trace plot into the test report.


4.4.4 Test Results






















Emission Mask



For the 763 - 775 MHz and 793 - 805 MHz band, the FCC limit is $65 + 10\log(P[\text{watt}])$ in a 6.25 kHz bandwidth. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10\log(10\text{kHz}/6.25\text{kHz}) = 2.04 \text{ dB}$$

$$\text{Limit line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$



For the 763 - 775 MHz and 793 - 805 MHz band, the FCC limit is $65 + 10\log(P[\text{watt}])$ in a 6.25 kHz bandwidth. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10\log(10\text{kHz}/6.25\text{kHz}) = 2.04 \text{ dB}$$


$$\text{Limit line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$

4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results


LTE Band 4							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.61	5.24	19965	1711.5	5.49	5.35
20175	1732.5	4.41	5.06	20175	1732.5	4.06	5.09
20393	1754.3	3.52	4.28	20385	1753.5	3.44	4.39



LTE Band 4

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.51	5.39	20000	1715.0	4.58	5.11
20175	1732.5	4.47	5.43	20175	1732.5	4.38	5.32
20375	1752.5	4.10	4.43	20350	1750.0	3.83	4.63


Spectrum Plot of Worst Value




LTE Band 4

Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	4.69	5.53	20050	1720.0	4.85	5.58
20175	1732.5	4.62	5.31	20175	1732.5	4.68	4.81
20325	1747.5	4.02	4.57	20300	1745.0	4.14	4.62

Spectrum Plot of Worst Value



LTE Band 13							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	3.79	4.52	23230	782.0	4.11	5.05
23230	782.0	4.69	5.46				
23255	784.5	4.70	5.46				




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.

4.6.2 Test Setup




4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30MHz to 1 GHz and 1 GHz to 10GHz for LTE Band 13 and from 30MHz to 1 GHz, 1 GHz to 10GHz, and 10 GHz to 26.5GHz for LTE Band 4. 10 dB attenuation pad is connected with spectrum. RBW = 100 kHz and VBW = 300 kHz are used for conducted emission measurement.

4.6.4 Test Results

LTE Band 4


30MHz ~ 1GHz




LTE Band 4

Channel Bandwidth: 3 MHz


Channel 19965



Channel 17075




Channel 20385




LTE Band 4 Channel Bandwidth: 5 MHz


Channel 19975



Channel 17175




Channel 20375




LTE Band 4

Channel Bandwidth: 10 MHz


Channel 20000



Channel 10175




Channel 20350




LTE Band 4

Channel Bandwidth: 15 MHz


Channel 20025



Channel 17175




Channel 20325




LTE Band 4

Channel Bandwidth: 20 MHz


Channel 20050



Channel 17175



Channel 20300




1GHz ~ 10GHz


LTE Band 4

Channel Bandwidth: 1.4 MHz


Channel 19957



Channel 17175




Channel 20393




LTE Band 4

Channel Bandwidth: 3 MHz


Channel 19965



Channel 20175




Channel 20385




LTE Band 4

Channel Bandwidth: 5 MHz


Channel 19975



Channel 17175




Channel 20375




LTE Band 4

Channel Bandwidth: 10 MHz


Channel 20000



Channel 17175




Channel 20350




LTE Band 4

Channel Bandwidth: 15 MHz


Channel 20025



Channel 17175




Channel 20325




LTE Band 4

Channel Bandwidth: 20 MHz


Channel 20050




Channel 20175



Channel 20300




10GHz ~ 26.5GHz




LTE Band 4

Channel Bandwidth: 3 MHz


Channel 19965



Channel 17075




Channel 20385




LTE Band 4

Channel Bandwidth: 5 MHz


Channel 19975



Channel 17175




Channel 20375




LTE Band 4

Channel Bandwidth: 10 MHz


Channel 20000



Channel 10175




Channel 20350




LTE Band 4

Channel Bandwidth: 15 MHz


Channel 20025



Channel 17175




Channel 20325




LTE Band 4

Channel Bandwidth: 20 MHz


Channel 20050






Channel 20175






Channel 20300



LTE Band 13
30MHz ~ 1GHz



1GHz ~ 10GHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

- a. The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.
- b. For operations in the 775-788 MHz, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz. The limit of emissions is equal to -40 dBm.

4.7.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.


Note: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard


No deviation.

4.7.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

LTE Band 4

Channel Bandwidth: 20 MHz / QPSK

Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3

Date: 2017-12-02



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : LTE_Band 4_Link_CH20050

Tested by: Karl Lee

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1 pp	3440.00	-36.91	-51.26	-13.00	-23.91	14.35 Peak
2	5160.00	-37.20	-57.12	-13.00	-24.20	19.92 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2017-12-02



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 4_Link_CH20050
Tested by: Karl Lee

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3440.00	-39.67	-54.02	-13.00	-26.67	14.35	Peak
2	5160.00	-37.32	-57.24	-13.00	-24.32	19.92	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 7

Date: 2017-12-02



Site : 966 chamber 1
Condition: PART 27(B4/B17) Horizontal
Remark : LTE_Band 4_Link_CH20175
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	37.56	-76.93	-66.96	-13.00	-63.93	-9.97	Peak
2	184.44	-60.86	-55.22	-13.00	-47.86	-5.64	Peak
3	258.96	-58.09	-52.50	-13.00	-45.09	-5.59	Peak
4	419.00	-57.95	-54.78	-13.00	-44.95	-3.17	Peak
5	602.40	-60.87	-61.27	-13.00	-47.87	0.40	Peak
6	814.50	-59.25	-61.10	-13.00	-46.25	1.85	Peak
7 pp	3465.00	-31.44	-45.78	-13.00	-18.44	14.34	Peak
8	5197.50	-36.11	-56.23	-13.00	-23.11	20.12	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 8

Date: 2017-12-02



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 4_Link_CH20175
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	82.65	-70.73	-59.18	-13.00	-57.73	-11.55	Peak
2	201.72	-60.70	-54.54	-13.00	-47.70	-6.16	Peak
3	250.59	-63.28	-57.77	-13.00	-50.28	-5.51	Peak
4	486.20	-63.38	-58.51	-13.00	-50.38	-4.87	Peak
5	733.30	-61.85	-60.85	-13.00	-48.85	-1.00	Peak
6	843.90	-66.93	-68.44	-13.00	-53.93	1.51	Peak
7	3465.00	-40.62	-54.96	-13.00	-27.62	14.34	Peak
8 pp	5197.50	-36.06	-56.18	-13.00	-23.06	20.12	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 3

Date: 2017-12-02



Site : 966 chamber 1
Condition: PART 27(B4/B17) Horizontal
Remark : LTE_Band 4_Link_CH20300
Tested by: Karl Lee

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1 pp	3490.00	-33.86	-48.17	-13.00	-20.86	14.31 Peak
2	5235.00	-35.82	-55.98	-13.00	-22.82	20.16 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2017-12-02



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 4_Link_CH20300
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3490.00	-40.75	-55.06	-13.00	-27.75	14.31	Peak
2 pp	5235.00	-34.45	-54.61	-13.00	-21.45	20.16	Peak

LTE Band 13
Channel Bandwidth: 10 MHz / QPSK
1 RB / 0 RB Offset




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-12-07



Site : 966 chamber 1
Condition: PART 27(B13) Horizontal
Remark : LTE_Band 13_Link_CH23230
Tested by: Harry Hsueh

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	122.34	-69.15	-61.02	-13.00	-56.15	-8.13 Peak
2	229.53	-59.23	-53.45	-13.00	-46.23	-5.78 Peak
3	273.81	-55.84	-50.12	-13.00	-42.84	-5.72 Peak
4	441.40	-60.23	-56.58	-13.00	-47.23	-3.65 Peak
5	517.00	-63.40	-59.32	-13.00	-50.40	-4.08 Peak
6	656.30	-55.90	-55.73	-13.00	-42.90	-0.17 Peak
7 pp	1564.00	-47.91	-54.77	-40.00	-7.91	6.86 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-12-07



Site : 966 chamber 1

Condition: PART 27(B13) Vertical

Remark : LTE_Band 13_Link_CH23230

Tested by: Harry Hsueh

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	90.21	-70.89	-60.22	-13.00	-57.89	-10.67	Peak
2	155.01	-66.90	-59.09	-13.00	-53.90	-7.81	Peak
3	237.90	-61.75	-56.07	-13.00	-48.75	-5.68	Peak
4	357.40	-63.29	-58.33	-13.00	-50.29	-4.96	Peak
5	561.10	-55.15	-53.97	-13.00	-42.15	-1.18	Peak
6	591.90	-57.32	-57.39	-13.00	-44.32	0.07	Peak
7 pp	1564.00	-52.17	-59.03	-40.00	-12.17	6.86	Peak

LTE Band 13
Channel Bandwidth: 10 MHz / QPSK
50 RB / 0 RB Offset




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-12-07



Site : 966 chamber 1
Condition: PART 27(B13) Horizontal
Remark : LTE_Band 13_Link_CH23230
Tested by: Harry Hsueh

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	99.93	-62.04	-51.92	-13.00	-49.04	-10.12 Peak
2	160.68	-62.36	-54.79	-13.00	-49.36	-7.57 Peak
3	244.38	-60.53	-54.94	-13.00	-47.53	-5.59 Peak
4	394.50	-56.74	-53.74	-13.00	-43.74	-3.00 Peak
5	626.20	-59.82	-59.95	-13.00	-46.82	0.13 Peak
6	703.90	-54.65	-54.20	-13.00	-41.65	-0.45 Peak
7 pp	1564.00	-53.61	-60.47	-40.00	-13.61	6.86 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-12-07



Site : 966 chamber 1

Condition: PART 27(B13) Vertical

Remark : LTE_Band 13_Link_CH23230

Tested by: Harry Hsueh

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	36.48	-58.52	-48.18	-13.00	-45.52	-10.34	Peak
2	103.71	-63.61	-53.96	-13.00	-50.61	-9.65	Peak
3	189.57	-60.68	-54.95	-13.00	-47.68	-5.73	Peak
4	430.20	-60.11	-56.69	-13.00	-47.11	-3.42	Peak
5	610.10	-55.87	-56.19	-13.00	-42.87	0.32	Peak
6	698.30	-59.84	-59.47	-13.00	-46.84	-0.37	Peak
7 pp	1564.00	-53.57	-60.43	-40.00	-13.57	6.86	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---