

FCC TEST REPORT	
FCC 47 CFR Part 15C Industry Canada RSS-210 Frequency hopping systems operating within the 2400 – 2483.5 MHz band	
Report Reference No.....:	G0M-1406-3920-TFC247BT-V01
Testing Laboratory	Eurofins Product Service GmbH
Address.....:	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	  A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A
Applicant's name	GN Netcom A/S
Address.....:	Lautrupbjerg 7 2750 Ballerup DENMARK
Test specification: Standard: 47 CFR Part 15C RSS-210, Issue 8, 2010-12 RSS-Gen, Issue 3, 2010-12 ANSI C63.4:2009	
Equipment under test (EUT): Product description Bluetooth headset Model No. OTE20 Additional Model(s) None Brand Name(s) Jabra Hardware version 28-03918 Firmware / Software version 2-10 FCC-ID: BCE-OTE20 IC: 2386C-OTE20 Test result Passed	

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2014-06-23

Date (s) of performance of tests: 2014-06-23 – 2014-06-25

Compiled by: Matthias Handrik

Tested by (+ signature).....: Matthias Handrik 

(Responsible for Test)

Approved by (+ signature): Christian Weber 

Date of issue: 2014-07-02

Total number of pages: 129

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
01	2014-07-02	Initial Release	



REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment External	6
1.2	Photos – Equipment internal	8
1.3	Photos – Test setup	9
1.4	Supporting Equipment Used During Testing	10
1.5	Test Modes	11
1.6	Test Equipment Used During Testing	13
1.7	Sample emission level calculation	15
2	RESULT SUMMARY	16
3	TEST CONDITIONS AND RESULTS	17
3.1	Test Conditions and Results – Occupied Bandwidth	17
3.2	Test Conditions and Results – 20 dB Bandwidth	24
3.3	Test Conditions and Results – Number of hopping frequencies	34
3.4	Test Conditions and Results – Frequency hopping channel separation	38
3.5	Test Conditions and Results – Time of occupancy (Dwell Time)	40
3.6	Test Conditions and Results – Maximum peak conducted power	42
3.7	Test Conditions and Results – AC power line conducted emissions	44
3.8	Test Conditions and Results – Band edge compliance	47
3.9	Test Conditions and Results – Conducted spurious emissions	61
3.10	Test Conditions and Results – Transmitter radiated emissions	68
3.11	Test Conditions and Results – Receiver radiated emissions	71
ANNEX A	Transmitter radiated spurious emissions	73
ANNEX B	Receiver radiated spurious emissions	122

1 Equipment (Test item) Description

Description	Bluetooth headset	
Model	OTE20	
Additional Model(s)	None	
Brand Name(s)	Jabra	
Serial number	None	
Hardware version	28-03918	
Software / Firmware version	2-10	
FCC-ID	BCE-OTE20	
IC	2386C-OTE20	
Equipment type	End product	
Radio type	Transceiver	
Radio technology	Bluetooth	
Operating frequency range	2402 - 2480 MHz	
Assigned frequency band	2400 - 2483.5 MHz	
Main test frequencies	F _{LOW}	2402 MHz
	F _{MID}	2441 MHz
	F _{HIGH}	2480 MHz
Spreading	FHSS	
Modulations	GFSK, PI/4-DQPSK, 8-DPSK	
Number of channels	79 hopping channels at all	
Channel spacing	1 MHz	
Number of antennas	1	
Antenna	Type	integrated
	Model	-
	Manufacturer	GN Netcom
	Gain	3.1 dBi
Manufacturer	GN Netcom A/S Lautrupbjerg 7 2750 Ballerup DENMARK	
Power supply	V _{NOM}	3.7 VDC
	V _{MIN}	3.2 VDC
	V _{MIN}	4.2 VDC
AC/DC-Adaptor	Model	SSA-5W-05 EU 050060F
	Vendor	SIL Switching Adapter
	Input	100-240V ~ 50/60Hz 0.2A
	Output	5.0V DC 800mA

1.1 Photos – Equipment External



Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany



EUT Headset




EUT Multi-function button



1.2 Photos – Equipment internal



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
SIM	Bluetooth tester	Rhode & Schwarz	CBT	
AE	Laptop	Samsung	NP-X20I	
AE : Auxiliary/Associated Equipment SIM : Simulator (Not Subjected to Test)				

1.5 Test Modes

Mode #	Description	
DH5-Sngl	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = GFSK Packet type = DH5 Data rate = 1 Mbps Duty cycle = 49 % Power level = Maximum
2DH5-Sngl	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = $\pi/4$ -DQPSK Packet type = 2DH5 Data rate = 2 Mbps Duty cycle = 49 % Power level = Maximum
3DH5-Sngl	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = 8-DPSK Packet type = 3DH5 Data rate = 3 Mbps Duty cycle = 49 % Power level = Maximum
DH5-Hop	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = GFSK Packet type = DH5 Data rate = 1 Mbps Duty cycle = 49 % Power level = Maximum

2DH5-Hop	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = $\pi/4$ -DQPSK Packet type = 2DH5 Data rate = 2 Mbps Duty cycle = 49 % Power level = Maximum
3DH5-Hop	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = 8-DPSK Packet type = 3DH5 Data rate = 3 Mbps Duty cycle = 49 % Power level = Maximum
Receive	General conditions:	EUT powered by internal battery.
	Radio conditions:	Mode = standalone receive Spreading = Hopping
AC-Powerline	General conditions:	EUT powered by commercial AC/DC-Adapter
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Power level = Maximum

1.6 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2014.1.15

20dB Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Number of hopping frequencies					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02
Time of occupancy					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Maximum peak conducted power					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Band edge compliance					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Conducted spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2014-02	2015-02

Radiated spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-Anechoic chamber	Frankonia GmbH	AC 1	EF00062	-	-
Spectrum Analyzer	R&S	FSEK30	EF00168	2014-01	2015-01
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00187	2014-03	2017-03
LPD Antenna	R&S	HL 025	EF00327	2013-02	2016-02

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2012-10	2014-10
EMI Test Receiver	R&S	ESCS 30	EF00295	2013-10	2014-10

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dBμV. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dBμV/m). The FCC limits are given in units of μV/m. The following formula is used to convert the units of μV/m to dBμV/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 4.6.1	Occupied Bandwidth	RSS-Gen 4.6.1	N/R	Informational only
FCC § 15.247(a)(1) IC RSS-210 § A8.1	20 dB Bandwidth	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1)(iii) IC RSS-210 § A8.1	Number of hopping frequencies	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1) IC RSS-210 § A8.1	Frequency hopping channel separation	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1)(iii) IC RSS-210 § A8.1	Time of occupancy (Dwell time)	Public notice DA 00-705	PASS	
FCC § 15.247(b)(1) IC RSS-210 § A8.4	Maximum peak conducted power	Public notice DA 00-705	PASS	
47 CFR 15.207 RSS-Gen 7.2.4	AC power line conducted emissions	ANSI C63.4	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Band edge compliance	Public notice DA 00-705	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Conducted spurious emissions	Public notice DA 00-705	PASS	
FCC § 15.247(d) FCC § 15.209 IC RSS-210 A8.5 IC RSS-Gen 4.9 IC RSS-Gen 7.2.5	Transmitter radiated spurious emissions	Public notice DA 00-705 / ANSI C 63.4	PASS	
IC RSS-Gen 4.10 IC RSS-Gen 6.1	Receiver radiated spurious emissions	ANSI C 63.4	PASS	
Remarks:				

3 Test Conditions and Results

3.1 Test Conditions and Results – Occupied Bandwidth


Occupied Bandwidth acc. IC RSS-Gen			Verdict: PASS
Test according to measurement reference	Reference Method		
	RSS-Gen 4.6.1		
Test frequency range	Tested frequencies		
	F _{LOW} / F _{MID} / F _{HIGH}		
Limits			
None (Informational only)			
Test setup			
Spectrum Analyzer EUT			
Test procedure			
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to at least twice the emission spectrum 3. Resolution bandwidth set to 1 % of span 4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function			
Test results			
Channel	Frequency [MHz]	Mode	Occupied Bandwidth [kHz]
F _{LOW}	2402	DH5-Sngl	963.5
F _{MID}	2441	DH5-Sngl	974.8
F _{HIGH}	2480	DH5-Sngl	963.5
F _{LOW}	2402	3DH5-Sngl	1222.2
F _{MID}	2441	3DH5-Sngl	1222.2
F _{HIGH}	2480	3DH5-Sngl	1218.4
Comments:			

Occupied Bandwidth – DH5-Sngl F_{Low}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2402 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW = 963.5 kHz




Occupied Bandwidth – DH5-Sngl F_{MID}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2441 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW = 974.8 kHz



Occupied Bandwidth – DH5-Sngl F_{HIGH}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2480 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW = 963.5 kHz



Occupied bandwidth: 963.5 kHz

Date: 23 JUN 2014 14:37:57

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Occupied Bandwidth – 3-DH5-Sngl F_{LOW}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2402 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW = 1222.2 kHz




Occupied Bandwidth – 3-DH5-Sngl F_{MID}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2441 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW = 1222.2 kHz




Occupied Bandwidth – 3-DH5-Sngl F_{HIGH}

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2480 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used
Note 2: OBW= 1218.4 kHz



3.2 Test Conditions and Results – 20 dB Bandwidth

20 dB Bandwidth acc. FCC 15.247 / IC RSS-210				Verdict: PASS	
EUT requirement rule parts and clause	Reference				
	FCC 15.247(a)(1) / IC RSS-210 A8.1				
Test according to measurement reference	Reference Method				
	FCC Public Notice DA 00-705				
Test frequency range	Tested frequencies				
	F _{LOW} / F _{MID} / F _{HIGH}				
Limits					
Limit		Condition			
1.5 · Carrier spacing		Output power ≤ 125 mW / 21 dBm			
1.0 · Carrier spacing		125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm			
Test setup					
Spectrum Analyzer EUT					
Test procedure					
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to at least twice the emission spectrum 3. Detector set to peak and max hold 4. Envelope peak value of emission spectrum is selected 5. Marker on envelope of spectrum is set to level of -20 dB to the left of the peak 6. Marker on envelope of spectrum is set to level of -20 dB to the right of the peak 7. 20dB Bandwidth is determined by marker frequency separation					
Test results					
Channel	Frequency [MHz]	Mode	20 dB Bandwidth [MHz]	Limit [MHz]	Result
F _{LOW}	2402	DH5-Sngl	0.923	1.5	PASS
F _{MID}	2441	DH5-Sngl	0.923	1.5	PASS
F _{HIGH}	2480	DH5-Sngl	0.923	1.5	PASS
F _{LOW}	2402	2DH5-Sngl	1.3077	1.5	PASS
F _{MID}	2441	2DH5-Sngl	1.3099	1.5	PASS
F _{HIGH}	2480	2DH5-Sngl	1.3077	1.5	PASS
F _{LOW}	2402	3DH5-Sngl	1.2638	1.5	PASS
F _{MID}	2441	3DH5-Sngl	1.2638	1.5	PASS
F _{HIGH}	2480	3DH5-Sngl	1.2638	1.5	PASS
Comments:					

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – DH5-Sngl F_{LOW}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, 2402MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:




20 dB Bandwidth – DH5-Sngl F_{MID}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, 2441MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:




20 dB bandwidth: 923 KHz
 Date: 23 JUN 2014 13:15:35

20 dB Bandwidth – DH5-Sngl F_{HIGH}

20 dB Bandwidth acc. to FCC 15.247

Project Number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, 2480MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:




20 dB bandwidth: 923 KHz
 Date: 23 JUN 2014 13:14:16

20 dB Bandwidth – 2-DH5-Sngl F_{Low}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT $\pi/4$ -DQPSK, 2402MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:



20 dB bandwidth: 1307.7 KHz


Date: 23 JUN 2014 13:08:28

20 dB Bandwidth – 2-DH5-Sngl F_{MID}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT $\pi/4$ -DQPSK, 2441MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:




20 dB Bandwidth – 2-DH5-Sngl F_{HIGH}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT $\pi/4$ -DQPSK, 2480MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:



20 dB bandwidth: 1307.7 KHz


Date: 23 JUN 2014 13:12:29

20 dB Bandwidth – 3-DH5-Sngl F_{Low}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT 8DPSK, 2402MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:



20 dB bandwidth: 1263.8 kHz


Date: 23 JUN 2014 13:06:20

20 dB Bandwidth – 3-DH5-Sngl F_{MID}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT 8DPSK, 2441MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:



20 dB bandwidth: 1263.8 kHz


Date: 23 JUN 2014 13:04:56

20 dB Bandwidth – 3-DH5-Sngl F_{HIGH}

20 dB Bandwidth acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT 8DPSK, 2480MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2:



20 dB bandwidth: 1263.8 kHz

Date: 23 JUN 2014 13:01:32

3.3 Test Conditions and Results – Number of hopping frequencies


Number of hopping frequencies acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(a)(1)(iii) / IC RSS-210 A8.1	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	F _{LOW} - F _{HIGH}	
EUT test mode	DH5-Hop	
Limits		
Limit	Condition	
Number of hopping channels ≥ 15	Output power ≤ 125 mW / 21 dBm	
Number of hopping channels ≥ 75	125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm	
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to measurement frequency range 3. Detector set to peak and max hold 4. Resolution bandwidth is set small enough to resolve hopping channel emission spectra 5. The number of peaks is counted to determine number of hopping frequencies		
Test results		
Number of hopping frequencies	Limit	Result
78	≥ 15	PASS
Comments:		

Number of hopping frequencies - Range A

Number of hopping frequencies acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2: Hopping mode




Number of hopping frequencies
 Date: 23.JUN.2014 14:27:10

Number of hopping frequencies - Range B

Number of hopping frequencies acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2: Hopping mode




Number of hopping frequencies
 Date: 23.JUN.2014 14:29:12

Number of hopping frequencies - Range C

Number of hopping frequencies acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)
 Note 2: Hopping mode



Number of hopping frequencies
 Date: 23 JUN 2014 14:30:48

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

3.4 Test Conditions and Results – Frequency hopping channel separation


Frequency hopping channel separation acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(a)(1) / IC RSS-210 A8.1	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	2441 & 2442 MHz	
EUT test mode	DH5-Hop	
Limits		
Limit	Condition	
≥ 25 kHz or ⅔ of 20 dB bandwidth	Output power ≤ 125 mW / 21 dBm	
≥ 25 kHz or 20 dB bandwidth	125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm	
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to measurement frequency range 3. Detector set to peak and max hold 4. Resolution bandwidth is set small enough to resolve hopping channel emission spectra 5. The two adjacent channel peaks are marked 6. Channel separation is determined from frequency separation of markers		
Test results		
Channel separation [kHz]	Limit [kHz]	Result
1000	≥ ⅔ · 923 = 615.3	PASS
Comments:		

Frequency hopping channel separation

Carrier frequency separation acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Jabra
 Model: OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Matthias Handrik
 Test Conditions: Tnom / Vnom
 Mode: Tx, BT GFSK, 2441/2442 MHz, modulated
 Test Date: 2014-06-23
 Verdict: PASS
 Note 1: FCC part 15 section 247 (a)(1)
 Note 2: Hopping mode



Limit: > two-thirds of the 20 dB bandwidth ; Result: Pass
 Date: 23 JUN 2014 14:19:00

3.5 Test Conditions and Results – Time of occupancy (Dwell Time)


Time of occupancy (Dwell time) acc. FCC 15.247 / IC RSS-210				Verdict: PASS	
EUT requirement rule parts and clause		Reference			
		FCC 15.247(a)(1)(iii) / IC RSS-210 A8.1			
Test according to measurement reference		Reference Method			
		FCC Public Notice DA 00-705			
Test frequency range		Tested frequencies			
		2441 MHz			
EUT test mode		DH5-Hop			
Limits					
Limit					
Time of occupancy ≤ 0.4 s within 0.4 s · Number of hopping channels					
Test setup					
Spectrum Analyzer EUT					
Test procedure					
1. EUT set to test mode (Communication tester is used if needed) 2. Center frequency set to test channel center frequency 3. Span set to zero span and detector to peak and max hold 4. Resolution bandwidth is set to 100kHz and sweep time to observation period 5. Time of occupancy determined from number of peaks multiplied by single hop dwell time					
Test results					
Observation period [s]	No. of hops	Dwell time/hop [s]	Time of occupancy [s]	Limit [s]	Result
31.2	95	0.02872	0.27284	≤ 0.4	PASS
Comments:					

Time of occupancy

Time of occupancy acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2441 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (a)
Note 2: 95 events * 2.872 ms result: 272.84 ms



Comment: Burst length=2.872 ms
Date: 23.JUN.2014 14:47:17

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

3.6 Test Conditions and Results – Maximum peak conducted power

Maximum peak conducted power acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(b)(1) / IC RSS-210 A8.4	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	F _{LOW} / F _{MID} / F _{HIGH}	
Measurement mode	Peak	
Maximum antenna gain	5 dBi ⇒ Limit correction = 0 dB	
Limits		
Limit	Condition	
1 W (30 dBm)	Number of hopping channels ≥ 75	
0.125 W (21 dBm)	75 > Number of hopping channels ≥ 15	
The conducted output power limit specified above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in the table, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.		
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Center frequency set to test channel center frequency 3. Span set to twice the 20 dB bandwidth and detector to peak and max hold 4. Resolution bandwidth is set to 3 MHz 5. Peak conducted power is determined from peak of spectrum envelope		

Test results								
Channel	Frequency [MHz]	Voltage	Mode	Peak power [dbm]	Peak power [W]	Limit [dBm]	Margin [dB]	Result
F _{LOW}	2402	3.7 VDC	DH5-Sngl	4.73	0.003	30	-25.27	PASS
F _{MID}	2441	3.7 VDC	DH5-Sngl	6.73	0.005	30	-23.27	PASS
F _{HIGH}	2480	3.7 VDC	DH5-Sngl	6.6	0.005	30	-23.40	PASS
F _{LOW}	2402	3.7 VDC	2DH5-Sngl	2.53	0.002	30	-27.47	PASS
F _{MID}	2441	3.7 VDC	2DH5-Sngl	4.81	0.003	30	-25.19	PASS
F _{HIGH}	2480	3.7 VDC	2DH5-Sngl	4.76	0.003	30	-25.24	PASS
F _{LOW}	2402	3.7 VDC	3DH5-Sngl	2.95	0.002	30	-27.05	PASS
F _{MID}	2441	3.7 VDC	3DH5-Sngl	5.23	0.003	30	-24.77	PASS
F _{HIGH}	2480	3.7 VDC	3DH5-Sngl	5.28	0.003	30	-24.72	PASS
Comments:								

3.7 Test Conditions and Results – AC power line conducted emissions

Power line conducted emissions acc. FCC 47 CFR 15.207 / IC RSS-Gen				Verdict: PASS	
Test according referenced standards		Reference Method			
		ANSI C63.4			
Fully configured sample scanned over the following frequency range		Frequency range			
		0.15 MHz to 30 MHz			
Points of Application		Application Interface			
AC Mains		LISN			
EUT test mode		AC-Powerline			
Limits and results					
Frequency [MHz]	Quasi-Peak [dBμV]	Result	Average [dBμV]	Result	
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS	
0.5 to 5	56	PASS	46	PASS	
5 to 30	60	PASS	50	PASS	
Comments:					
* Limit decreases linearly with the logarithm of the frequency.					


Conducted Emissions

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1406-3920

Manufacturer: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Unom: 120 V AC (AC/DC adaptor)
 LISN: ESH2-Z5 N
 Mode: charging
 Test Date: 2014-06-25
 Note:

Index 56




Conducted Emissions

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1406-3920

Manufacturer: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Unom: 120 V AC (AC/DC adaptor)
 LISN: ESH2-Z5 L
 Mode: charging
 Test Date: 2014-06-25
 Note:

Index 57



3.8 Test Conditions and Results – Band edge compliance

Band-edge compliance acc. FCC 15.247 / IC RSS-210					Verdict: PASS	
EUT requirement rule parts and clause		Reference				
		FCC 15.247(d) / IC RSS-210 A8.5				
Test according to measurement reference		Reference Method				
		FCC Public Notice DA 00-705				
Test frequency range		Tested frequencies				
		F _{LOW} / F _{HIGH}				
Measurement mode		Peak				
Limits						
Limit			Condition			
≤ -20 dB/100 kHz			Peak power measurement detector = Peak			
≤ -30 dB/100 kHz			Peak power measurement detector = RMS			
Test setup						
Spectrum Analyzer EUT						
Test procedure						
1. EUT set to test mode (Communication tester is used if needed) 2. Span set around lower band edge and detector is set to peak and max hold 3. Resolution bandwidth is set to 100 kHz 4. Markers are set to peak emission levels within frequency band and outside frequency band 5. Band edge attenuation is determined from level difference						
Test results						
Channel	Frequency [MHz]	Mode	Level [dBc]	Limit [dBc]	Margin [dB]	Result
F _{LOW}	2402	DH5-Sngl	-49.62	-20	-29.62	PASS
F _{HIGH}	2480	DH5-Sngl	-66.65	-20	-46.65	PASS
F _{LOW}	2402	DH5-Hop	-49.2	-20	-29.20	PASS
F _{HIGH}	2480	DH5-Hop	-65.05	-20	-45.05	PASS
F _{LOW}	2402	2DH5-Sngl	-42.84	-20	-22.84	PASS
F _{HIGH}	2480	2DH5-Sngl	-62.93	-20	-42.93	PASS
F _{LOW}	2402	2DH5-Hop	-44.96	-20	-24.96	PASS
F _{HIGH}	2480	2DH5-Hop	-63.60	-20	-43.60	PASS


F _{LOW}	2402	3DH5-Sngl	-40.87	-20	-20.87	PASS
F _{HIGH}	2480	3DH5-Sngl	-63.03	-20	-43.03	PASS
F _{LOW}	2402	3DH5-Hop	-44.63	-20	-24.63	PASS
F _{HIGH}	2480	3DH5-Hop	-62.66	-20	-42.66	PASS
Comments:						

Band-edge compliance – DH5-Sngl F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:23:23

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – DH5-Sngl F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode




Band-edge compliance – DH5-Hop F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode




Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:57:31

Band-edge compliance – DH5-Hop F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:54:32

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – 2-DH5-Sngl F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT $\pi/4$ -DQPSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode




Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:28:44

Band-edge compliance – 2-DH5-Sngl F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT $\pi/4$ -DQPSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:27:30

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – 2-DH5-Hop F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT $\pi/4$ -DQPSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:47:57

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – 2-DH5-Hop F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT $\pi/4$ -DQPSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode




Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:49:25

Band-edge compliance – 3-DH5-Sngl F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:31:15

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – 3-DH5-Sngl F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Single frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:34:18

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany


Page 58 of 129

Band-edge compliance – 3-DH5-Hop F_{LOW}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2402MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:43:45

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – 3-DH5-Hop F_{HIGH}

Band-edge compliance of RF conducted emission acc. to FCC 15.247

Project Number: GOM-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2480MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (c)
Note 2: Hopping frequency mode



Limit: Marker Delta value >20 dB; Result: PASS
Date: 23 JUN 2014 13:40:53

Test Report No.: GOM-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

3.9 Test Conditions and Results – Conducted spurious emissions


Conducted spurious emissions acc. FCC 15.247 / IC RSS-210							Verdict: PASS	
EUT requirement rule parts and clause			Reference					
			FCC 15.247(d) / IC RSS-210 A8.5					
Test according to measurement reference			Reference Method					
			FCC Public Notice DA 00-705					
Test frequency range			Tested frequencies					
			10 MHz – 10 th Harmonic					
Measurement mode			Peak					
Limits								
Limit				Condition				
≤ -20 dB/100 kHz				Peak power measurement detector = Peak				
≤ -30 dB/100 kHz				Peak power measurement detector = RMS				
Test setup								
Spectrum Analyzer EUT								
Test procedure								
1. EUT set to test mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth is set to 100 kHz and detector to peak and max hold 4. Markers are set to peak emission levels within frequency band 5. Emission level is determined by second marker on emission peak 6. Attenuation is determined from level difference								
Test results								
Channel	Frequency [MHz]	Mode	Emission [MHz]	Emission Level [dBm]	Peak power [dBm]	Limit [dBm]	Margin [dB]	Result
F _{LOW}	2402	DH5-Sngl	No significant spurious emissions					PASS
F _{MID}	2441	DH5-Sngl	No significant spurious emissions					PASS
F _{HIGH}	2480	DH5-Sngl	No significant spurious emissions					PASS
F _{LOW}	2402	3DH5-Sngl	3043.66	-47.40	0.65	-19.4	-28.00	PASS
F _{MID}	2441	3DH5-Sngl	No significant spurious emissions					PASS
F _{HIGH}	2480	3DH5-Sngl	No significant spurious emissions					PASS
Comments:								

Conducted spurious emissions – DH5-Sngl F_{Low}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2402 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (d)
Note 2:



Date: 23.JUN.2014 14:54:24

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Conducted spurious emissions – DH5-Sngl F_{MID}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT GFSK, 2441 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (d)
Note 2:



Date: 23.JUN.2014 14:57:36

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Conducted spurious emissions – DH5-Sngl F_{HIGH}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Jabra
Model:	OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Matthias Handrik
Test Conditions:	Tnom / Vnom
Mode:	Tx, BT GFSK, 2480 MHz, modulated
Test Date:	2014-06-23
Verdict:	PASS
Note 1:	FCC part 15 section 247 (d)
Note 2:	



Date: 23.JUN.2014 15:01:22

Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Conducted spurious emissions – 3-DH5-Sngl F_{LOW}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2402 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (d)
Note 2:




Date: 23.JUN.2014 15:10:53

Conducted spurious emissions – 3-DH5-Sngl F_{MID}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Jabra
Model:	OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Matthias Handrik
Test Conditions:	Tnom / Vnom
Mode:	Tx, BT 8DPSK, 2441 MHz, modulated
Test Date:	2014-06-23
Verdict:	PASS
Note 1:	FCC part 15 section 247 (d)
Note 2:	




Date: 23.JUN.2014 15:08:10

Conducted spurious emissions – 3-DH5-Sngl F_{HIGH}

Conducted spurious emission acc. to FCC part 15.247

Project Number: G0M-1406-3920

Applicant: GN Netcom A/S
EUT Name: Jabra
Model: OTE20
Test Site: Eurofins Product Service GmbH
Operator: Matthias Handrik
Test Conditions: Tnom / Vnom
Mode: Tx, BT 8DPSK, 2480 MHz, modulated
Test Date: 2014-06-23
Verdict: PASS
Note 1: FCC part 15 section 247 (d)
Note 2:




Date: 23.JUN.2014 15:04:32

3.10 Test Conditions and Results – Transmitter radiated emissions

Transmitter radiated emissions acc. FCC 47 CFR 15.247 / IC RSS-210				Verdict: PASS	
Test according referenced standards		Reference Method			
		FCC 15.247(d) / IC RSS-210 A8.5			
Test according to measurement reference		Reference Method			
		FCC Public Notice DA 00-705 / ANSI C63.4			
Test frequency range		Tested frequencies			
		30 MHz – 10 th Harmonic			
Limits					
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]	
30 – 88	Quasi-Peak	100	40	3	
88 – 216	Quasi-Peak	150	43.5	3	
216 – 960	Quasi-Peak	200	46	3	
960 – 1000	Quasi-Peak	500	54	3	
> 1000	Average	500	54	3	

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

When average radiated emission measurements are specified, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Test setup



Test procedure									
1. EUT set to test mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to peak emission levels within restricted bands									
Test results									
Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dBμV/m]	Det.	Pol.	Limit [dBμV/m]	Limit dist. [m]*	Margin [dB]
F _{HIGH}	2480	3DH5-Sngl	2483.5	54.70	pk	ver	74.00	3	-19.30
F _{HIGH}	2480	3DH5-Sngl	2483.5	43.79	RMS	ver	54.00	3	-10.21
F _{HIGH}	2480	3DH5-Sngl	2483.5	61.47	pk	hor	74.00	3	-12.53
F _{HIGH}	2480	3DH5-Sngl	2483.5	51.21	RMS	hor	54.00	3	-02.79
F _{HIGH}	2480	3DH5-Sngl	4960	52.93	pk	ver	74.00	3	-21.07
F _{HIGH}	2480	3DH5-Sngl	4960	45.06	avg	ver	54.00	3	-08.94
F _{HIGH}	2480	3DH5-Sngl	4960	56.67	pk	hor	74.00	3	-17.33
F _{HIGH}	2480	3DH5-Sngl	4960	49.05	avg	hor	54.00	3	-04.95
F _{MID}	2441	3DH5-Sngl	4882	52.68	pk	ver	74.00	3	-21.32
F _{MID}	2441	3DH5-Sngl	4882	44.08	avg	ver	54.00	3	-09.92
F _{MID}	2441	3DH5-Sngl	4882	56.48	pk	hor	74.00	3	-17.52
F _{MID}	2441	3DH5-Sngl	4882	48.27	avg	hor	54.00	3	-05.73
F _{LOW}	2402	3DH5-Sngl	4800	50.58	pk	ver	74.00	3	-23.42
F _{HIGH}	2480	DH5-Sngl	2483.5	53.57	pk	ver	74.00	3	-20.43
F _{HIGH}	2480	DH5-Sngl	2483.5	45.50	RMS	ver	54.00	3	-08.50
F _{HIGH}	2480	DH5-Sngl	2483.5	60.79	pk	hor	74.00	3	-13.21
F _{HIGH}	2480	DH5-Sngl	2483.5	53.26	RMS	hor	54.00	3	-00.74
F _{HIGH}	2480	DH5-Sngl	4960	56.03	pk	ver	74.00	3	-17.97
F _{HIGH}	2480	DH5-Sngl	4960	51.37	avg	ver	54.00	3	-02.63
F _{HIGH}	2480	DH5-Sngl	4960	57.45	pk	hor	74.00	3	-16.55
F _{HIGH}	2480	DH5-Sngl	4960	52.96	avg	hor	54.00	3	-01.04
F _{HIGH}	2480	DH5-Sngl	12390	49.88	pk	ver	74.00	3	-24.12
F _{MID}	2441	DH5-Sngl	4882	58.14	pk	ver	74.00	3	-15.86
F _{MID}	2441	DH5-Sngl	4882	53.18	avg	ver	54.00	3	-00.82
F _{MID}	2441	DH5-Sngl	4882	54.88	pk	hor	74.00	3	-19.12
F _{MID}	2441	DH5-Sngl	4882	49.25	avg	hor	54.00	3	-04.75
F _{MID}	2441	DH5-Sngl	12200	48.12	pk	ver	74.00	3	-25.88
F _{LOW}	2402	DH5-Sngl	4804	53.73	pk	ver	74.00	3	-20.27

Test Report No.: G0M-1406-3920-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

F _{LOW}	2402	DH5-Sngl	4804	47.93	avg	ver	54.00	3	-06.07
F _{LOW}	2402	DH5-Sngl	4804	55.99	pk	hor	74.00	3	-18.01
F _{LOW}	2402	DH5-Sngl	4804	51.28	avg	hor	54.00	3	-02.72
Comments: * Physical distance between EUT and measurement antenna.									

3.11 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 3 th Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

Test procedure							
1. EUT set to receive mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to peak emission levels							
Test results							
Channel	Frequency [MHz]	Emission [MHz]	Emission Level [db μ V/m]	Emission Level [μ V/m]	Det.	Limit [μ V/m]	Margin [μ V/m]
F _{MID}	2441	884.8	36.27	65.1	pk	200	-134.90
Comments: * Physical distance between EUT and measurement antenna. ** Emission level corresponds to ambient noise floor							


ANNEX A Transmitter radiated spurious emissions

Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 21




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note: lower bandedge

Index 22




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-24
 Note:

Index 5




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3 m
Mode:	TX; GFSK; Ch.: 0
Test Date:	2014-06-24
Note:	lower bandedge

Index 6



Test Report No.: G0M-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 23




Frequency 4.804 GHz	Peak 53.73 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -20.27 dB	Peak Status Pass
Frequency 4.804 GHz	Average 47.93 dBµV/m	Average Limit 54 dBµV/m	Average Difference -6.07 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-24
 Note:

Index 7




Frequency 4.804 GHz	Peak 55.99 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -18.01 dB	Peak Status Pass
Frequency 4.804 GHz	Average 51.28 dBµV/m	Average Limit 54 dBµV/m	Average Difference -2.72 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 40




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 51




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 41




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 50




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 26




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 38




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 24




Frequency 4.882 GHz	Peak 58.14 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -15.86 dB	Peak Status Pass
Frequency 4.882 GHz	Average 53.18 dBµV/m	Average Limit 54 dBµV/m	Average Difference -0.82 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-24
 Note:

Index 8



Frequency 4.882 GHz	Peak 54.88 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -19.12 dB	Peak Status Pass
Frequency 4.882 GHz	Average 49.25 dBµV/m	Average Limit 54 dBµV/m	Average Difference -4.75 dB	Average Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 43



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
12.2 GHz	48.12 dBµV/m	74 dBµV/m	-25.88 dB	Pass


Frequency
12.2 GHz

Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 48




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 42




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 49




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; GFSK; Ch.: 78
Test Date:	2014-06-25
Note:	worst case

Index 54




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; GFSK; Ch.: 78
Test Date:	2014-06-25
Note:	worst case

Index 55




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; GFSK; Ch.: 78
Test Date:	2014-06-25
Note:	worst case

Index 52




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; GFSK; Ch.: 78
Test Date:	2014-06-25
Note:	worst case

Index 53




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 27




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note: upper bandedge

Index 28




Frequency 2.4835 GHz	Peak 53.57 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -20.43 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 45.5 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -8.5 dB	RMS Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-24
 Note:

Index 10




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-24
 Note: upper bandedge

Index 11



Frequency 2.4835 GHz	Peak 60.79 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -13.21 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 53.26 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -0.74 dB	RMS Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 29




Frequency 4.96 GHz	Peak 56.03 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -17.97 dB	Peak Status Pass
Frequency 4.96 GHz	Average 51.37 dBµV/m	Average Limit 54 dBµV/m	Average Difference -2.63 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-24
 Note:

Index 12




Frequency 4.96 GHz	Peak 57.45 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -16.55 dB	Peak Status Pass
Frequency 4.96 GHz	Average 52.96 dBµV/m	Average Limit 54 dBµV/m	Average Difference -1.04 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 44



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
12.39 GHz	49.88 dBµV/m	74 dBµV/m	-24.12 dB	Pass


Frequency
12.39 GHz

Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 47




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 45




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 1 m
 Mode: TX; GFSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 46




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 36




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3 m
Mode:	TX; 8DPSK; Ch.: 0
Test Date:	2014-06-25
Note:	lower bandedge

Index 37




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 0
 Test Date: 2014-06-24
 Note:

Index 20




Spurious emissions according to FCC 15.247

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 0
 Test Date: 2014-06-24
 Note: lower bandedge

Index 19




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 0
 Test Date: 2014-06-25
 Note:

Index 35



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.8 GHz	50.58 dBµV/m	74 dBµV/m	-23.42 dB	Pass


Frequency
4.8 GHz

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 0
 Test Date: 2014-06-24
 Note:

Index 18




Frequency 4.804 GHz	Peak 51.39 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -22.61 dB	Peak Status Pass
Frequency 4.804 GHz	Average 42.76 dBµV/m	Average Limit 54 dBµV/m	Average Difference -11.24 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 34



Frequency 4.882 GHz	Peak 52.68 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -21.32 dB	Peak Status Pass
Frequency 4.882 GHz	Average 44.08 dBµV/m	Average Limit 54 dBµV/m	Average Difference -9.92 dB	Average Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 33




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 39
 Test Date: 2014-06-24
 Note:

Index 16




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 39
 Test Date: 2014-06-25
 Note:

Index 39




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 39
 Test Date: 2014-06-24
 Note:

Index 17



Frequency 4.882 GHz	Peak 56.48 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -17.52 dB	Peak Status Pass
Frequency 4.882 GHz	Average 48.27 dBµV/m	Average Limit 54 dBµV/m	Average Difference -5.73 dB	Average Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 31




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-25
 Note: upper bandedge

Index 32



Frequency 2.4835 GHz	Peak 54.7 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -19.3 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 43.79 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -10.21 dB	RMS Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-24
 Note:

Index 15




Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-24
 Note: upper bandedge

Index 14



Frequency 2.4835 GHz	Peak 61.47 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -12.53 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 51.21 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -2.79 dB	RMS Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-25
 Note:

Index 30



Frequency 4.96 GHz	Peak 52.93 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -21.07 dB	Peak Status Pass
Frequency 4.96 GHz	Average 45.06 dBµV/m	Average Limit 54 dBµV/m	Average Difference -8.94 dB	Average Status Pass

Test Report No.: GOM-1406-3920-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: GOM-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 8DPSK; Ch.: 78
 Test Date: 2014-06-24
 Note:

Index 13



Frequency 4.96 GHz	Peak 56.67 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -17.33 dB	Peak Status Pass
Frequency 4.96 GHz	Average 49.05 dBµV/m	Average Limit 54 dBµV/m	Average Difference -4.95 dB	Average Status Pass


ANNEX B Receiver radiated spurious emissions

Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	RX; Bluetooth; CH.: 39
Test Date:	2014-06-24
Note:	

Index 14




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	RX; Bluetooth; CH.: 39
Test Date:	2014-06-24
Note:	

Index 15




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 223, Vertical
 Measurement distance: 3 m
 Mode: RX; Bluetooth; CH.: 39
 Test Date: 2014-06-24
 Note:

Index 17




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Rohde & Schwarz HL 223, Horizontal
 Measurement distance: 3 m
 Mode: RX; Bluetooth; CH.: 39
 Test Date: 2014-06-24
 Note:

Index 16




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: RX; Bluetooth; CH.: 39
 Test Date: 2014-06-24
 Note:

Index 18




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: Jabra / OTE20
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 22°C, Vnom: 3.7V DC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: RX; Bluetooth; CH.: 39
 Test Date: 2014-06-24
 Note:

Index 20




Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3 m
Mode:	RX; Bluetooth; CH.: 39
Test Date:	2014-06-24
Note:	

Index 19



Spurious emissions according to RSS-GEN

Project number: G0M-1406-3920

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	Jabra / OTE20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 22°C, Vnom: 3.7V DC (battery)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3 m
Mode:	RX; Bluetooth; CH.: 39
Test Date:	2014-06-24
Note:	

Index 21

