


Product Name: K610w Wireless Mechanical Keyboard	Report No: FCC022022-5383RF1
Product Model: K610w	Security Classification: Open
Version: V1.0	Total Page:46

TIRT Testing Report



Prepared By:	Checked By:	Approved By:	
Stone Tang	Randy Lv	Daniel Chen	
Stone Tang	Randy Lv	Daniel chen	

FCC Radio Test Report

FCC ID: 2AXCA-K610W

This report concerns: Original Grant

Project No. : 022022-5383
Equipment : K610w Wireless Mechanical Keyboard
Brand Name : DURGOD
Test Model : K610w
Series Model : N/A
Applicant : Zhuhai Hoksi Technology CO.,LTD
Address : Room803, No.3 BLDG, No.6, Pingbei 1 Rd., Nanping Technology & Industry Park, Xiangzhou St., ZhuHai,China
Manufacturer : Zhuhai Hoksi Technology CO.,LTD
Address : Room803, No.3 BLDG, No.6, Pingbei 1 Rd., Nanping Technology & Industry Park, Xiangzhou St., ZhuHai,China
Factory : Zhuhai Hengchang Electronic Technology Co.,Ltd
Address : 3rd floor, A building, No. 7 of 3rd pingxi Road, Nanping Technical industry park, Zhuhai, China
Date of Test : 2022.09.05-2022.10.21
Issued Date : 2022.10.20
Report Version : V1.0
Test Sample : Engineering Sample No.: 20220713018147
Standard(s) : FCC CFR Title 47, Part 15, Subpart C
FCC KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc. the test report shall not reproduced except in full.

Add: Plant 3,Gongjindianzi,Shatian, Kengzi Street, Pingshan District, Shenzhen,
Guangdong, China

TEL: +86-0755-27087573

Table of Contents	Page
REPORT ISSUED HISTORY	6
1 . SUMMARY OF TEST RESULTS	7
1.1 TEST LOCATION	8
1.2 MEASUREMENT UNCERTAINTY	8
1.3 TEST ENVIRONMENT CONDITIONS	9
2 . GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 PARAMETERS OF TEST SOFTWARE	12
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.5 SUPPORT UNITS	12
3 . AC POWER LINE CONDUCTED EMISSIONS	13
3.1 LIMIT	13
3.2 TEST PROCEDURE	13
3.3 DEVIATION FROM TEST STANDARD	13
3.4 TEST SETUP	14
3.5 EUT OPERATION CONDITIONS	14
3.6 TEST RESULTS	14
4 . RADIATED EMISSIONS	15
4.1 LIMIT	15
4.2 TEST PROCEDURE	16
4.3 DEVIATION FROM TEST STANDARD	17
4.4 TEST SETUP	17
4.5 EUT OPERATION CONDITIONS	18
4.6 TEST RESULTS - 9 KHZ TO 30 MHZ	18
4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ	18
4.8 TEST RESULTS - ABOVE 1000 MHZ	18
5 . BANDWIDTH	19
5.1 LIMIT	19
5.2 TEST PROCEDURE	19
5.3 DEVIATION FROM STANDARD	19
5.4 TEST SETUP	19
5.5 EUT OPERATION CONDITIONS	19

Table of Contents	Page
5.6 TEST RESULTS	19
6 . MAXIMUM OUTPUT POWER	20
6.1 LIMIT	20
6.2 TEST PROCEDURE	20
6.3 DEVIATION FROM STANDARD	20
6.4 TEST SETUP	20
6.5 EUT OPERATION CONDITIONS	20
6.6 TEST RESULTS	20
7 . CONDUCTED SPURIOUS EMISSIONS	21
7.1 LIMIT	21
7.2 TEST PROCEDURE	21
7.3 DEVIATION FROM STANDARD	21
7.4 TEST SETUP	21
7.5 EUT OPERATION CONDITIONS	21
7.6 TEST RESULTS	21
8 . POWER SPECTRAL DENSITY	22
8.1 LIMIT	22
8.2 TEST PROCEDURE	22
8.3 DEVIATION FROM STANDARD	22
8.4 TEST SETUP	22
8.5 EUT OPERATION CONDITIONS	22
8.6 TEST RESULTS	22
9 . MEASUREMENT INSTRUMENTS LIST	23
10 . EUT TEST PHOTO	24
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS	26
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ	29
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ	30
APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ	33
APPENDIX E - BANDWIDTH	39
APPENDIX F - MAXIMUM AVERAGE OUTPUT POWER	41
APPENDIX G - CONDUCTED SPURIOUS EMISSIONS	43
APPENDIX H - POWER SPECTRAL DENSITY	45

Table of Contents

Page

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
FCC022022-5383RF1	V1.0	Original Report.	2022.10.20	Valid

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	Test Item	Test Result	Judgment	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	-----
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	-----
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	-----
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	-----
15.247(d)	Conducted Spurious Emissions	APPENDIX G	PASS	-----
15.247(e)	Power Spectral Density	APPENDIX H	PASS	-----
15.203	Antenna Requirement	-----	PASS	Note(2)

Note:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1 TEST LOCATION

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan District, Shenzhen, China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number:	6049.01
FCC Accredited Lab. Designation Number:	CN1309
FCC Test Firm Registration Number:	825524
Telephone:	+86-0755-27087573

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

The TIRT measurement uncertainty as below table:

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 142.12\text{kHz}$
RF power conducted	$\pm 0.74\text{dB}$
RF power radiated	$\pm 3.25\text{dB}$
Spurious emissions, conducted	$\pm 1.78\text{dB}$
Spurious emissions, radiated (30MHz~1GHz)	$\pm 4.6\text{dB}$
Spurious emissions, radiated (1GHz ~ 18GHz)	$\pm 4.9\text{dB}$
Conduction Emissions(150kHz~30MHz)	$\pm 3.1\text{dB}$
Humidity	$\pm 4.6\%$
Temperature	$\pm 0.7^\circ\text{C}$
Time	$\pm 1.25\%$

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	26°C	56%	AC 120V/60Hz	Stone Tang
Radiated Emissions-9kHz to 30 MHz	25°C	55%	DC 5V	Stone Tang
Radiated Emissions-30MHz to 1000MHz	23°C	53%	DC 5V	Stone Tang
Radiated Emissions-Above 1000MHz	23°C	53%	DC 5V	Stone Tang
Bandwidth	23°C	54%	DC 5V	Stone Tang
Maximum Output Power	23°C	54%	DC 5V	Stone Tang
Conducted Spurious Emissions	23°C	54%	DC 5V	Stone Tang
Power Spectral Density	23°C	54%	DC 5V	Stone Tang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	K610w Wireless Mechanical Keyboard
Brand Name	DURGOD
Test Model	K610w
Series Model	N/A
Model Difference(s)	N/A
Software Version	N/A
Hardware Version	N/A
Power Source	1# Supplied from PC USB port. 2# Supplied from battery. Model: 5830132-3600mAh-1S1P
Power Rating	1# 5V 1.5A 2# DC 3.8V, 3600mAh, 13.68Wh
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK
Bit Rate of Transmitter	1 Mbps
Maximum Output Power	1Mbps: -6.72 dBm (0.0002 W)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3. Antenna Specification:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	PSA	RFPCA430816IMAB301	PCB	IPEX Compatible (Gold)	3.12

Note:

- 1) The antenna gain is provided by the manufacturer.

2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39
Mode 2	TX Mode_1Mbps Channel 00

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 2	TX Mode_1Mbps Channel 00

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 2	TX Mode_1Mbps Channel 00

Radiated emissions test - Above 1GHz (Bandedge)	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39

Radiated emissions test - Above 1GHz (Harmonic)	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39

NOTE:


- (1) All the bit rate of transmitter have been tested and found the lowest rate is found to be the worst case and recorded.
- (2) For AC power line conducted emissions and radiated emission below 1 GHz test, the IEEE 802.11b channel 11 is found to be the worst case and recorded.
- (3) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

- (4) For radiated emission above 1 GHz test, the polarization of Vertical and Horizontal are evaluated, the worst case is Vertical and recorded.

2.3 PARAMETERS OF TEST SOFTWARE

Test Software Version	sscom5.13.1		
Frequency (MHz)	2402	40	2480
1Mbps	N/A	N/A	N/A

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	ThinkPad	L450	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	NO	NO	1m

3. AC POWER LINE CONDUCTED EMISSIONS

3.1 LIMIT

Frequency of Emission (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.


The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.3 DEVIATION FROM TEST STANDARD

No deviation.

3.4 TEST SETUP



3.5 EUT OPERATION CONDITIONS

EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULTS

Please refer to the APPENDIX A.

4. RADIATED EMISSIONS

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a) , then the 15.209(a) and limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

NOTE:

- (1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2 TEST PROCEDURE

- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
(below 1 GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- For the actual test configuration, please refer to the related Item -EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value


Receiver Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector

4.3 DEVIATION FROM TEST STANDARD


No deviation.


4.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz





4.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ

Please refer to the APPENDIX B.

Remark:

- (1) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ

Please refer to the APPENDIX C.

4.8 TEST RESULTS - ABOVE 1000 MHZ

Please refer to the APPENDIX D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH

5.1 LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz
	99% Emission Bandwidth	-

5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span Frequency	> Measurement Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span Frequency	Between 1.5 times and 5.0 times the OBW
RBW	300 kHz
VBW	1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULTS

Please refer to the APPENDIX E.

6. MAXIMUM OUTPUT POWER

6.1 LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 Watt or 30.00 dBm

6.2 TEST PROCEDURE


- The EUT was directly connected to the peak power analyzer and antenna output port as show in the block diagram below.
- The maximum conducted output power was performed in accordance with method 11.9.2.3.1 (for AVG power) of ANSI C63.10-2013 and FCC KDB 662911 D01 v02r01 Multiple Transmitter Output.

Spectrum Parameters	Setting
Span Frequency	$\geq 3 \times \text{RBW}$
RBW	3 MHz
VBW	3 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX F.

7. CONDUCTED SPURIOUS EMISSIONS

7.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:


For Emission Level:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX G.

8. POWER SPECTRAL DENSITY

8.1 LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	2 MHz
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX H.

9. MEASUREMENT INSTRUMENTS LIST


No.	Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Receiver	Rohde&Schwarz	ESCI	1166.5950.03	2022/11/09
2	AMN	Rohde&Schwarz	ENV216	3560.6550.05	2022/11/09
3	AMN	Schwarzbeck	NSLK8127	#829	2022/11/09
4	ECSI RF IN RF Cable	Rohde&Schwarz	RP-X1	N/A	2022/11/09
5	ECSI RF IN RF Cable	Rohde&Schwarz	Sapre sm	N/A	2022/11/09
6	EMI Receiver	Rohde&Schwarz	ESR7	102013	2022/11/09
7	Spectrum analyzer	Rohde&Schwarz	FSV30	103741	2022/11/09
8	Spectrum analyzer	KEYSIGHT	N9010A-44	MY51440158	2022/11/09
9	Integral Antenna	Schwarzbeck	VULB 9163	VULB 9163-361	2022/11/20
10	Integral Antenna	Schwarzbeck	BBHA 9120D	BBHA 9120D 1201	2022/11/20
11	Integral Antenna	Schwarzbeck	BBHA 9170	9170#685	2022/11/20
12	Preamplifier	Schwarzbeck	BBV9745	#78	2022/11/09
13	Preamplifier	Schwarzbeck	BBV9721	9721-019	2022/11/09
14	Preamplifier	RF System/UK	TRLA-0101 80G50B	22062101	2023/07/20
15	ECSI RF IN RF Cable	Rohde&Schwarz	AP-X1	N/A	2022/11/09
16	ECSI RF IN RF Cable	HAOXUN	Z-108	N/A	2022/11/09
17	RF Cable	ZDECL	ZT40-2.92J -2.92J-6M	18124358	2023/07/20
18	Spectrum Analyzer	Agilent	N9010A	MY51440158	2022/11/09
19	Spectrum Analyzer	Agilent	N9010A	MY52221119	2022/11/09
20	EMI Receiver	Rohde&Schwarz	ESU	100184	2023/07/20
21	Temp&Humidity Recorder	Anymetre	JR900	N/A	2022/11/03
22	Temp&Humidity Chamber	ETOMA	NTH1100-3 0A	16080628	2022/11/03
23	Filter	STI	STI15-9845	N/A	N/A
24	Filter	STI	5.1G	N/A	N/A
25	Filter	STI	STI15-9845	N/A	N/A
26	Testing Software	EZ-EMC	TW-03A2	N/A	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.

"**" calibration period of equipment list is three year.


Except * item, all calibration period of equipment list is one year.

10. EUT TEST PHOTO**AC Power Line Conducted Emissions Test Photos****Radiated Emissions Test Photos****30 MHz to 1 GHz**

Radiated Emissions Test Photos**Above 1 GHz**

APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode	TX G Mode Channel 00	Phase	Line
-----------	----------------------	-------	------




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1545	37.70	19.28	56.98	65.75	-8.77	QP	
2	0.1545	30.18	19.28	49.46	55.75	-6.29	AVG	
3	4.6635	26.96	20.60	47.56	56.00	-8.44	QP	
4	4.6635	18.00	20.60	38.60	46.00	-7.40	AVG	
5	5.2575	27.25	20.64	47.89	60.00	-12.11	QP	
6	5.2575	19.00	20.64	39.64	50.00	-10.36	AVG	
7	8.4480	32.53	20.81	53.34	60.00	-6.66	QP	
8 *	8.4480	23.07	20.81	43.88	50.00	-6.12	AVG	
9	10.4505	27.34	20.79	48.13	60.00	-11.87	QP	
10	10.4505	18.10	20.79	38.89	50.00	-11.11	AVG	
11	12.3810	22.55	20.94	43.49	60.00	-16.51	QP	
12	12.3810	14.19	20.94	35.13	50.00	-14.87	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.
- (3) The test result has included the cable loss.

Test Mode	TX G Mode Channel 00	Phase	Neutral
-----------	----------------------	-------	---------



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1500	39.44	19.48	58.92	66.00	-7.08	QP	
2 *	0.1500	30.43	19.48	49.91	56.00	-6.09	AVG	
3	0.1815	35.22	19.48	54.70	64.42	-9.72	QP	
4	0.1815	26.03	19.48	45.51	54.42	-8.91	AVG	
5	0.2495	28.25	19.48	47.73	61.77	-14.04	QP	
6	0.2495	20.96	19.48	40.44	51.77	-11.33	AVG	
7	5.3340	27.78	20.70	48.48	60.00	-11.52	QP	
8	5.3340	19.58	20.70	40.28	50.00	-9.72	AVG	
9	8.0834	31.34	20.82	52.16	60.00	-7.84	QP	
10	8.0834	21.76	20.82	42.58	50.00	-7.42	AVG	
11	10.8825	26.74	20.82	47.56	60.00	-12.44	QP	
12	10.8825	19.18	20.82	40.00	50.00	-10.00	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

(3) The test result has included the cable loss.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ


Radiated emission: 9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode	TX G Mode Channel 06	Polarization	Vertical
-----------	----------------------	--------------	----------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		52.310	7.67	14.61	22.28	40.00	-17.72	peak	
2	*	75.590	10.05	14.72	24.77	40.00	-15.23	peak	
3		159.980	9.30	15.23	24.53	43.50	-18.97	peak	
4		239.520	9.18	16.36	25.54	46.00	-20.46	peak	
5		399.570	10.86	19.23	30.09	46.00	-15.91	peak	
6		666.320	5.29	23.92	29.21	46.00	-16.79	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Polarization	Horizontal
-----------	----------------------	--------------	------------



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	56.190	10.35	11.83	22.18	40.00	-17.82	peak	
2	159.980	11.81	13.37	25.18	43.50	-18.32	peak	
3	239.520	10.50	16.36	26.86	46.00	-19.14	peak	
4 *	599.390	12.55	23.16	35.71	46.00	-10.29	peak	
5	761.380	8.54	25.16	33.70	46.00	-12.30	peak	
6	948.590	5.03	30.13	35.16	46.00	-10.84	peak	


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ

Test Mode	TX 2402 MHz _CH00_1Mbps	Polarization	Horizontal
-----------	-------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		2390.000	21.23	32.63	53.86	74.00	-20.14	peak	
2		2390.000	6.89	32.63	39.52	54.00	-14.48	AVG	
3	*	2402.050	59.19	32.67	91.86	54.00	37.86	AVG	No Limit
4	X	2402.550	65.38	32.68	98.06	74.00	24.06	peak	No Limit

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2480 MHz _CH39_1Mbps	Polarization	Horizontal
-----------	-------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1	X	2479.550	54.50	32.96	87.46	74.00	13.46	peak	No Limit
2	*	2480.050	48.32	32.96	81.28	54.00	27.28	AVG	No Limit
3		2483.500	27.48	32.97	60.45	74.00	-13.55	peak	
4		2483.500	6.15	32.97	39.12	54.00	-14.88	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2402 MHz _CH00_1Mbps	Polarization	Vertical
-----------	-------------------------	--------------	----------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	4802.980	49.69	-14.49	35.20	54.00	-18.80	AVG	
2		4804.995	60.52	-14.49	46.03	74.00	-27.97	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.


(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2440MHz _CH19_1Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1	*	4878.980	48.64	-14.23	34.41	54.00	-19.59	AVG	
2		4880.080	60.32	-14.23	46.09	74.00	-27.91	peak	

Test Mode	TX 2480 MHz _CH39_1Mbps	Polarization	Vertical
-----------	-------------------------	--------------	----------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	4958.960	47.33	-13.95	33.38	54.00	-20.62	AVG	
2		4959.395	58.50	-13.95	44.55	74.00	-29.45	peak	

APPENDIX E - BANDWIDTH


Test Mode	TX Mode _1Mbps
-----------	----------------

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6 dB Bandwidth Min. Limit (MHz)	Result
00	2402	0.659	1.020	0.5	Complies
19	2440	0.659	1.024	0.5	Complies
39	2480	0.664	1.020	0.5	Complies

CH00




Data: 27/06/2022 04:02:00

CH19
6 dB Bandwidth



Data: 27/06/2022 04:02:00

CH39




Data: 27/06/2022 04:02:00


99 % Occupied Bandwidth



Data: 27/06/2022 04:02:00



Data: 27/06/2022 04:02:00




Data: 27/06/2022 04:02:00

APPENDIX F - MAXIMUM AVERAGE OUTPUT POWER

Test Mode	TX B Mode
-----------	-----------


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
00	2402	-6.72	0.0004	30.00	1.0000	Complies
19	2440	-7.46	0.0003	30.00	1.0000	Complies
39	2480	-7.96	0.0003	30.00	1.0000	Complies

CH00




Data: 27/06/2022 04:09:49

CH19



Data: 27/06/2022 04:10:09

CH39




Data: 27/06/2022 04:11:22

APPENDIX G - CONDUCTED SPURIOUS EMISSIONS


Test Mode	TX Mode _1Mbps
-----------	----------------

Bandedge-CH00 (Lower)




地址: 深圳市福田区福安路100号 邮编: 518040

Bandedge-CH39 (Upper)




地址: 上海 100000 电话: 021-62420242 邮编: 200001


CH00 – 10th Harmonic of the fundamental frequency



地址: 深圳市福田区福安路100号 邮编: 518040




收稿日期: 2007-01-10; 修回日期: 2007-03-10




资料来源: 根据《中国统计年鉴》、《中国人口统计年鉴》、《中国农村统计年鉴》、《中国城市统计年鉴》、《中国固定资产投资统计年鉴》、《中国财政统计年鉴》、《中国金融统计年鉴》、《中国贸易统计年鉴》、《中国工业统计年鉴》、《中国商业统计年鉴》、《中国交通统计年鉴》、《中国能源统计年鉴》、《中国农业统计年鉴》、《中国林业统计年鉴》、《中国渔业统计年鉴》、《中国畜牧业统计年鉴》、《中国轻工业统计年鉴》、《中国重工业统计年鉴》、《中国建筑业统计年鉴》、《中国房地产业统计年鉴》、《中国旅游业统计年鉴》、《中国邮电统计年鉴》、《中国广播统计年鉴》、《中国电视统计年鉴》、《中国电影统计年鉴》、《中国图书统计年鉴》、《中国报纸统计年鉴》、《中国杂志统计年鉴》、《中国期刊统计年鉴》、《中国音像统计年鉴》、《中国出版统计年鉴》、《中国印刷统计年鉴》、《中国造纸统计年鉴》、《中国纺织统计年鉴》、《中国服装统计年鉴》、《中国鞋帽统计年鉴》、《中国皮革统计年鉴》、《中国橡胶统计年鉴》、《中国塑料统计年鉴》、《中国玻璃统计年鉴》、《中国陶瓷统计年鉴》、《中国金属统计年鉴》、《中国非金属统计年鉴》、《中国化工统计年鉴》、《中国医药统计年鉴》、《中国食品统计年鉴》、《中国饮料统计年鉴》、《中国烟草统计年鉴》、《中国酒类统计年鉴》、《中国茶叶统计年鉴》、《中国香料统计年鉴》、《中国调味品统计年鉴》、《中国粮油统计年鉴》、《中国蔬菜统计年鉴》、《中国水果统计年鉴》、《中国坚果统计年鉴》、《中国种子统计年鉴》、《中国苗木统计年鉴》、《中国花卉统计年鉴》、《中国盆景统计年鉴》、《中国园林统计年鉴》、《中国旅游统计年鉴》、《中国交通统计年鉴》、《中国能源统计年鉴》、《中国农业统计年鉴》、《中国林业统计年鉴》、《中国渔业统计年鉴》、《中国畜牧业统计年鉴》、《中国轻工业统计年鉴》、《中国重工业统计年鉴》、《中国建筑业统计年鉴》、《中国房地产业统计年鉴》、《中国旅游业统计年鉴》、《中国邮电统计年鉴》、《中国广播统计年鉴》、《中国电视统计年鉴》、《中国电影统计年鉴》、《中国图书统计年鉴》、《中国报纸统计年鉴》、《中国杂志统计年鉴》、《中国期刊统计年鉴》、《中国音像统计年鉴》、《中国出版统计年鉴》、《中国印刷统计年鉴》、《中国造纸统计年鉴》、《中国纺织统计年鉴》、《中国服装统计年鉴》、《中国鞋帽统计年鉴》、《中国皮革统计年鉴》、《中国橡胶统计年鉴》、《中国塑料统计年鉴》、《中国玻璃统计年鉴》、《中国陶瓷统计年鉴》、《中国金属统计年鉴》、《中国非金属统计年鉴》、《中国化工统计年鉴》、《中国医药统计年鉴》、《中国食品统计年鉴》、《中国饮料统计年鉴》、《中国烟草统计年鉴》、《中国酒类统计年鉴》、《中国茶叶统计年鉴》、《中国香料统计年鉴》、《中国调味品统计年鉴》、《中国粮油统计年鉴》、《中国蔬菜统计年鉴》、《中国水果统计年鉴》、《中国坚果统计年鉴》、《中国种子统计年鉴》、《中国苗木统计年鉴》、《中国花卉统计年鉴》、《中国盆景统计年鉴》、《中国园林统计年鉴》。


CH19 – 10th Harmonic of the fundamental frequency



资料来源:根据《宁夏回族自治区统计年鉴》、《宁夏回族自治区年鉴》整理。




地址: 广州市天河区珠江新城花城大道100号 邮编: 510623




地址: 温州市鹿城区南汇街道 电话: 0577-86666666


CH39 – 10th Harmonic of the fundamental frequency



资料来源：根据《2015—2016年度中国公路交通行业发展报告》整理。



资料来源:《中国统计年鉴》,《中国统计出版社》,《中国统计出版社》。



作者地址：南京（210000）；南京（210000）；南京（210000）

APPENDIX H - POWER SPECTRAL DENSITY

Test Mode	TX Mode _1Mbps
-----------	----------------

Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
00	2402	-17.29	8.00	Complies
19	2440	-19.12	8.00	Complies
39	2480	-19.12	8.00	Complies



End of Test Report