



RF Exposure Evaluation Report

Page: 1 / 6

Application No.: DNT230875R1022-1507
Applicant: Shenzhen Jooan Technology Co., Ltd
Address of Applicant: Building 101-3,5 and 6, No.8 , Guixiang Community Square Road, Guanlan Street, Longhua District, Shenzhen, China
EUT Description: Smart DoorBell
Model No.: L2-U
FCC ID: 2BBQ4-L2U
Power supply: DC 3.7V From Battery;DC 5V From Adapter Input AC 100-240V, 50/60Hz
Trade Mark: Jooan
47 CFR Part 2.1091
Standards: FCC KDB 447498 D01 v06
Date of Receipt: 2023/12/1
Date of Test: 2023/12/3 to 2023/12/18
Date of Issue: 2023/12/18
Test Result : **PASS ***

Prepared By: Wayne Lin (Testing Engineer)

Reviewed By: Pencils Chen (Project Engineer)

Approved By: Wick Peng (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

Dongguan DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com

**Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V2.0	/	Dec.18, 2023	Valid	Original Report



Contents

1	GENERAL INFORMATION	4
1.1	TEST LOCATION	4
1.2	GENERAL DESCRIPTION OF EUT	4
2	RF EXPOSURE EVALUATION	5
2.1	RF EXPOSURE COMPLIANCE REQUIREMENT	5
2.1.1	Limits	5
2.1.2	Test Procedure	6
2.1.3	EUT RF Exposure Evaluation	6



1 General Information

1.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang ' an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin

1.2 General Description of EUT

EUT Description::	Smart DoorBell
Manufacturer:	Shenzhen Jooan Technology Co., Ltd
Address of Manufacturer:	Building 101-3,5 and 6, No.8 , Guixiang Community Square Road, Guanlan Street, Longhua District, Shenzhen, China
Model No.:	L2-U
Additional Model(s):	L1-U,L2-U,L3-U,L4-U,L5-U,L6-U,L7-U,L8-U,L9-U,L10-U
Chip Type:	ATBM6441
Serial Number	SP2301211015
Power Supply	DC 3.7V From Battery;DC 5V From Adapter Input AC 100-240V, 50/60Hz
Trade Mark:	Jooan
Hardware Version:	V1.0
Software Version:	V1.0
Sample Type:	<input type="checkbox"/> Portable Device, <input type="checkbox"/> Module, <input checked="" type="checkbox"/> Mobile Device
Antenna Type:	<input type="checkbox"/> External, <input checked="" type="checkbox"/> Integrated
Antenna Gain:	<input checked="" type="checkbox"/> Provided by applicant
	0.95dBi

Remark:

*Since the above data and/or information is provided by the applicant relevant results or conclusions of this report are only made for these data and/or information , DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.



2 RF Exposure Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

2.1.3 EUT RF Exposure Evaluation

This confirmed that the device comply with MPE limit.

For 433 SRD:

$$EIRP = E - 104.8 + 20 \log D = 84.11 - 104.8 + 20 \log 3 = -11.118 \text{ dBm}$$

For 2.4GWifi

Test Mode	Antenna	Freq(MHz)	Power [dBm]
11B	Ant1	2412	11.03
		2437	12.19
		2462	13.42
11G	Ant1	2412	13.12
		2437	14.00
		2462	15.34
11N20SISO	Ant1	2412	12.51
		2437	13.45
		2462	14.76

The Worst Mode	Antenna	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
					(dBi)	(Linear)			
ASK	Ant1	-11.12	-11±1	-10	3	1.995	0.00004	1	Complies
11G	Ant1	15.34	15±1	16	0.95	1.245	0.0099	1	Complies

433 Max Power Density (S) (mW/cm ²)	WIFI Max Power Density (S) (mW/cm ²)	Total Ratio	Limit Ratio	Test Result
0.00004	0.0099	0.00994	1	Complies

The End Report